

**COSEL**

**TEST DATA OF RMC15A-1  
(100V INPUT)**

Regulated DC Power Supply

Sep. 24, 1999

Approved by : Motoji Takehara  
Design Manager

Prepared by : Yuichi Takahashi  
Design Engineer

**コーセル株式会社  
COSEL CO., LTD.**



## CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Efficiency (by Input Voltage) . . . . .	3
効率 (入力電圧特性)	
3. Power Factor (by Input Voltage) . . . . .	4
力率 (入力電圧特性)	
4. Hold-Up Time . . . . .	5
出力保持時間	
5. Instantaneous Interruption Compensation . . . . .	8
瞬時停電保障	
6. Load Regulation . . . . .	11
静的負荷変動	
7. Ripple Voltage (by Load Current) . . . . .	13
リップル電圧 (負荷特性)	
8. Ripple-Noise . . . . .	16
リップルノイズ	
9. Overcurrent Protection . . . . .	19
過電流保護	
10. Inrush Current . . . . .	21
突入電流	
11. Dynamic Load Responce . . . . .	22
動的負荷変動	
12. Rise and Fall Time . . . . .	25
立ち上り、立下り時間	
13. Ambient Temperature Drift . . . . .	28
周囲温度変動	
14. Minimum Input Voltage for Regulated Output Voltage . . . . .	30
最低レギュレーション電圧	
15. Ripple Voltage (by Ambient Temperature) . . . . .	32
リップル電圧 (周囲温度特性)	
16. Time Lapse Drift . . . . .	34
経時ドリフト	
17. Output Voltage Accuracy . . . . .	36
定電圧精度	
18. Condensation . . . . .	37
結露特性	
19. Leakage Current . . . . .	38
漏洩電流	
20. Conducted Emission . . . . .	39
雑音端子電圧	
21. Figure of Testing Circuitry . . . . .	40
測定回路図	

(Final Page 41 )

**COSEL**


Model	RMC15A-1	Temperature	25°C																																
Item	Line Regulation 静的入力変動	Testing Circuitry	Figure A																																
Object	+5.0V 2A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.068</td><td>5.066</td></tr> <tr><td>80</td><td>5.068</td><td>5.066</td></tr> <tr><td>85</td><td>5.068</td><td>5.066</td></tr> <tr><td>90</td><td>5.068</td><td>5.066</td></tr> <tr><td>100</td><td>5.068</td><td>5.066</td></tr> <tr><td>110</td><td>5.068</td><td>5.066</td></tr> <tr><td>120</td><td>5.068</td><td>5.066</td></tr> <tr><td>132</td><td>5.068</td><td>5.066</td></tr> <tr><td>140</td><td>5.068</td><td>5.066</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.068	5.066	80	5.068	5.066	85	5.068	5.066	90	5.068	5.066	100	5.068	5.066	110	5.068	5.066	120	5.068	5.066	132	5.068	5.066	140	5.068	5.066
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	5.068	5.066																																	
80	5.068	5.066																																	
85	5.068	5.066																																	
90	5.068	5.066																																	
100	5.068	5.066																																	
110	5.068	5.066																																	
120	5.068	5.066																																	
132	5.068	5.066																																	
140	5.068	5.066																																	
Object	+12.0V 0.3A	2. Values																																	
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.094</td><td>12.084</td></tr> <tr><td>80</td><td>12.096</td><td>12.081</td></tr> <tr><td>85</td><td>12.097</td><td>12.080</td></tr> <tr><td>90</td><td>12.097</td><td>12.080</td></tr> <tr><td>100</td><td>12.098</td><td>12.079</td></tr> <tr><td>110</td><td>12.099</td><td>12.079</td></tr> <tr><td>120</td><td>12.099</td><td>12.079</td></tr> <tr><td>132</td><td>12.099</td><td>12.079</td></tr> <tr><td>140</td><td>12.099</td><td>12.079</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	12.094	12.084	80	12.096	12.081	85	12.097	12.080	90	12.097	12.080	100	12.098	12.079	110	12.099	12.079	120	12.099	12.079	132	12.099	12.079	140	12.099	12.079
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	12.094	12.084																																	
80	12.096	12.081																																	
85	12.097	12.080																																	
90	12.097	12.080																																	
100	12.098	12.079																																	
110	12.099	12.079																																	
120	12.099	12.079																																	
132	12.099	12.079																																	
140	12.099	12.079																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	RMC15A-1
Item	Line Regulation 静的入力変動
Object	-12.0V 0.2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	-12.189	-12.185
80	-12.190	-12.183
85	-12.190	-12.182
90	-12.191	-12.182
100	-12.192	-12.182
110	-12.192	-12.181
120	-12.192	-12.182
132	-12.192	-12.182
140	-12.192	-12.182

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

**COSEL**

Model	RMC15A-1
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)
Object	—

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	62.3	62.8
80	62.4	63.4
85	62.3	64.0
90	62.4	64.3
100	61.6	65.1
110	60.8	65.2
120	60.2	65.3
132	58.9	65.1
140	58.3	65.1

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

**COSEL**

Model	RMC15A-1	
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)	Temperature 25°C Testing Circuitry Figure A
Object		
1. Graph		
	□ Load 50%	Load 100%
	△	
Power Factor	0.90	1.00
	0.80	
	0.70	
	0.60	
	0.50	
	0	
Input Voltage [V]	0	150
	70	
	80	
	90	
	100	
	110	
	120	
	130	
	140	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.58	0.63
80	0.58	0.61
85	0.57	0.60
90	0.56	0.59
100	0.55	0.57
110	0.53	0.56
120	0.52	0.55
132	0.51	0.53
140	0.50	0.53

**COSEL**

Model	RMC15A-1	Temperature	25°C																																	
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																	
Object	+5.0V 2A																																			
1. Graph		2. Values																																		
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>19</td><td>11</td></tr> <tr><td>80</td><td>23</td><td>14</td></tr> <tr><td>85</td><td>27</td><td>17</td></tr> <tr><td>90</td><td>31</td><td>20</td></tr> <tr><td>100</td><td>40</td><td>26</td></tr> <tr><td>110</td><td>50</td><td>33</td></tr> <tr><td>120</td><td>61</td><td>41</td></tr> <tr><td>132</td><td>75</td><td>52</td></tr> <tr><td>140</td><td>85</td><td>59</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	19	11	80	23	14	85	27	17	90	31	20	100	40	26	110	50	33	120	61	41	132	75	52	140	85	59
Input Voltage [V]	Hold-Up Time [mS]																																			
	Load 50%	Load 100%																																		
75	19	11																																		
80	23	14																																		
85	27	17																																		
90	31	20																																		
100	40	26																																		
110	50	33																																		
120	61	41																																		
132	75	52																																		
140	85	59																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																				


COSEL

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+12.0V 0.3A																																		
1. Graph			2. Values																																
<p>The graph plots Hold-Up Time [mS] on a logarithmic y-axis (1 to 1000) against Input Voltage [V] on the x-axis (0 to 150). Two data series are shown: Load 50% (squares) and Load 100% (triangles). Both series show an increase in hold-up time as input voltage increases. A slanted line indicates the range of rated input voltage.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% [mS]</th> <th>Load 100% [mS]</th> </tr> </thead> <tbody> <tr><td>80</td><td>~20</td><td>~15</td></tr> <tr><td>90</td><td>~30</td><td>~25</td></tr> <tr><td>100</td><td>~40</td><td>~35</td></tr> <tr><td>110</td><td>~50</td><td>~45</td></tr> <tr><td>120</td><td>~60</td><td>~55</td></tr> <tr><td>130</td><td>~70</td><td>~65</td></tr> <tr><td>140</td><td>~80</td><td>~75</td></tr> </tbody> </table>				Input Voltage [V]	Load 50% [mS]	Load 100% [mS]	80	~20	~15	90	~30	~25	100	~40	~35	110	~50	~45	120	~60	~55	130	~70	~65	140	~80	~75								
Input Voltage [V]	Load 50% [mS]	Load 100% [mS]																																	
80	~20	~15																																	
90	~30	~25																																	
100	~40	~35																																	
110	~50	~45																																	
120	~60	~55																																	
130	~70	~65																																	
140	~80	~75																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>19</td><td>15</td></tr> <tr><td>80</td><td>22</td><td>17</td></tr> <tr><td>85</td><td>25</td><td>20</td></tr> <tr><td>90</td><td>29</td><td>23</td></tr> <tr><td>100</td><td>36</td><td>30</td></tr> <tr><td>110</td><td>44</td><td>37</td></tr> <tr><td>120</td><td>53</td><td>45</td></tr> <tr><td>132</td><td>65</td><td>55</td></tr> <tr><td>140</td><td>74</td><td>63</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	19	15	80	22	17	85	25	20	90	29	23	100	36	30	110	44	37	120	53	45	132	65	55	140	74	63
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	19	15																																	
80	22	17																																	
85	25	20																																	
90	29	23																																	
100	36	30																																	
110	44	37																																	
120	53	45																																	
132	65	55																																	
140	74	63																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	RMC15A-1	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	-12.0V 0.2A																																		
1. Graph		2. Values																																	
<p>The graph plots Hold-Up Time in milliseconds against Input Voltage in volts. The Y-axis is logarithmic, ranging from 1 to 1000 mS. The X-axis ranges from 0 to 150 V. Two sets of data points are shown: one for Load 50% (squares) and one for Load 100% (triangles). Both sets show an increase in hold-up time as input voltage increases. A slanted line on the graph represents the input voltage range of 75V to 140V.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>19</td> <td>15</td> </tr> <tr> <td>80</td> <td>22</td> <td>18</td> </tr> <tr> <td>85</td> <td>25</td> <td>21</td> </tr> <tr> <td>90</td> <td>28</td> <td>24</td> </tr> <tr> <td>100</td> <td>35</td> <td>30</td> </tr> <tr> <td>110</td> <td>43</td> <td>37</td> </tr> <tr> <td>120</td> <td>52</td> <td>45</td> </tr> <tr> <td>132</td> <td>63</td> <td>56</td> </tr> <tr> <td>140</td> <td>71</td> <td>63</td> </tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	19	15	80	22	18	85	25	21	90	28	24	100	35	30	110	43	37	120	52	45	132	63	56	140	71	63
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	19	15																																	
80	22	18																																	
85	25	21																																	
90	28	24																																	
100	35	30																																	
110	43	37																																	
120	52	45																																	
132	63	56																																	
140	71	63																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

# COSEL



Temperature 25°C  
Testing Circuitry Figure A

**COSEL**


Model	RMC15A-1	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																				
Object	+12.0V 0.3A																																																				
1. Graph	<p style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 10px; background-color: black; border: 1px solid black;"></span> Input Volt. 85 V  <span style="display: inline-block; width: 15px; height: 10px; border: 1px solid black;"></span> Input Volt. 100 V  <span style="display: inline-block; width: 15px; height: 10px; border: 1px solid black; border-radius: 50%;"></span> Input Volt. 132 V         </p> <p>Instantaneous Compensation Time [mS]</p> <p>Load Current [A]</p>	2. Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.06</td><td>28</td><td>40</td><td>72</td></tr> <tr><td>0.12</td><td>23</td><td>35</td><td>65</td></tr> <tr><td>0.18</td><td>21</td><td>31</td><td>60</td></tr> <tr><td>0.24</td><td>20</td><td>30</td><td>57</td></tr> <tr><td>0.30</td><td>18</td><td>28</td><td>53</td></tr> <tr><td>0.33</td><td>15</td><td>27</td><td>53</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	—	—	—	0.06	28	40	72	0.12	23	35	65	0.18	21	31	60	0.24	20	30	57	0.30	18	28	53	0.33	15	27	53	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																				
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																		
0.00	—	—	—																																																		
0.06	28	40	72																																																		
0.12	23	35	65																																																		
0.18	21	31	60																																																		
0.24	20	30	57																																																		
0.30	18	28	53																																																		
0.33	15	27	53																																																		
—	—	—	—																																																		
—	—	—	—																																																		
—	—	—	—																																																		
—	—	—	—																																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																					

COSEL

Model	RMC15A-1
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	-12.0V 0.2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

## 2. Values

Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.00	—	—	—
0.04	25	37	65
0.08	22	31	61
0.12	20	31	57
0.16	19	29	55
0.20	18	27	53
0.22	18	27	53
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

**COSEL**

Model RMC15A-1		Temperature 25°C Testing Circuitry Figure A																																																	
Item Load Regulation 靜的負荷變動																																																			
Object +5.0V 2A																																																			
1. Graph																																																			
		2. Values																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.070</td><td>5.070</td><td>5.070</td></tr> <tr><td>0.4</td><td>5.070</td><td>5.070</td><td>5.070</td></tr> <tr><td>0.8</td><td>5.069</td><td>5.069</td><td>5.069</td></tr> <tr><td>1.2</td><td>5.068</td><td>5.068</td><td>5.068</td></tr> <tr><td>1.6</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>2.0</td><td>5.066</td><td>5.066</td><td>5.066</td></tr> <tr><td>2.2</td><td>5.065</td><td>5.065</td><td>5.065</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	5.070	5.070	5.070	0.4	5.070	5.070	5.070	0.8	5.069	5.069	5.069	1.2	5.068	5.068	5.068	1.6	5.067	5.067	5.067	2.0	5.066	5.066	5.066	2.2	5.065	5.065	5.065	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.0	5.070	5.070	5.070																																																
0.4	5.070	5.070	5.070																																																
0.8	5.069	5.069	5.069																																																
1.2	5.068	5.068	5.068																																																
1.6	5.067	5.067	5.067																																																
2.0	5.066	5.066	5.066																																																
2.2	5.065	5.065	5.065																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
Object +12.0V 0.3A		2. Values																																																	
1. Graph																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.100</td><td>12.102</td><td>12.103</td></tr> <tr><td>0.06</td><td>12.099</td><td>12.100</td><td>12.101</td></tr> <tr><td>0.12</td><td>12.096</td><td>12.097</td><td>12.098</td></tr> <tr><td>0.18</td><td>12.092</td><td>12.093</td><td>12.094</td></tr> <tr><td>0.24</td><td>12.088</td><td>12.089</td><td>12.090</td></tr> <tr><td>0.30</td><td>12.083</td><td>12.084</td><td>12.085</td></tr> <tr><td>0.33</td><td>12.080</td><td>12.081</td><td>12.082</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	12.100	12.102	12.103	0.06	12.099	12.100	12.101	0.12	12.096	12.097	12.098	0.18	12.092	12.093	12.094	0.24	12.088	12.089	12.090	0.30	12.083	12.084	12.085	0.33	12.080	12.081	12.082	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0.00	12.100	12.102	12.103																																																
0.06	12.099	12.100	12.101																																																
0.12	12.096	12.097	12.098																																																
0.18	12.092	12.093	12.094																																																
0.24	12.088	12.089	12.090																																																
0.30	12.083	12.084	12.085																																																
0.33	12.080	12.081	12.082																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
Note: Slanted line shows the range of the rated load current.																																																			
(注) 斜線は定格負荷電流範囲を示す。																																																			

**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 靜的負荷変動																																																	
Object	-12.0V 0.2A																																																	
1. Graph	<p>—▲— Input Volt. 85 V        —□— Input Volt. 100 V        —○— Input Volt. 132 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-12.190</td><td>-12.190</td><td>-12.191</td></tr> <tr> <td>0.04</td><td>-12.191</td><td>-12.192</td><td>-12.192</td></tr> <tr> <td>0.08</td><td>-12.190</td><td>-12.191</td><td>-12.191</td></tr> <tr> <td>0.12</td><td>-12.189</td><td>-12.190</td><td>-12.189</td></tr> <tr> <td>0.16</td><td>-12.187</td><td>-12.188</td><td>-12.188</td></tr> <tr> <td>0.20</td><td>-12.185</td><td>-12.186</td><td>-12.186</td></tr> <tr> <td>0.22</td><td>-12.184</td><td>-12.184</td><td>-12.184</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.00	-12.190	-12.190	-12.191	0.04	-12.191	-12.192	-12.192	0.08	-12.190	-12.191	-12.191	0.12	-12.189	-12.190	-12.189	0.16	-12.187	-12.188	-12.188	0.20	-12.185	-12.186	-12.186	0.22	-12.184	-12.184	-12.184	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.00	-12.190	-12.190	-12.191																																															
0.04	-12.191	-12.192	-12.192																																															
0.08	-12.190	-12.191	-12.191																																															
0.12	-12.189	-12.190	-12.189																																															
0.16	-12.187	-12.188	-12.188																																															
0.20	-12.185	-12.186	-12.186																																															
0.22	-12.184	-12.184	-12.184																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	RMC15A-1	Temperature Testing Circuitry Figure A	25°C Figure A																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																								
Object	+5.0V 2A																																								
1. Graph	<p>—▲— Input Volt. 85V [mV]</p> <p>—○— Input Volt. 132V [mV]</p>	2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.5</td><td>5</td><td>5</td></tr> <tr><td>1.0</td><td>10</td><td>5</td></tr> <tr><td>1.5</td><td>15</td><td>10</td></tr> <tr><td>2.0</td><td>15</td><td>10</td></tr> <tr><td>2.5</td><td>25</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	5	5	0.5	5	5	1.0	10	5	1.5	15	10	2.0	15	10	2.5	25	15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	5	5																																							
0.5	5	5																																							
1.0	10	5																																							
1.5	15	10																																							
2.0	15	10																																							
2.5	25	15																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
入力商用周期

T2: Due to Switching  
スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL





Temperature 25°C  
Testing Circuitry Figure A

**COSSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																								
Object	-12.0V 0.2A																																								
1. Graph	<p>1. Graph</p> <p>— ▲ — Input Volt. 85V [mV]</p> <p>— ○ — Input Volt. 132V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.05</td><td>5</td><td>5</td></tr> <tr><td>0.10</td><td>5</td><td>5</td></tr> <tr><td>0.15</td><td>5</td><td>5</td></tr> <tr><td>0.20</td><td>5</td><td>5</td></tr> <tr><td>0.25</td><td>5</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	5	5	0.05	5	5	0.10	5	5	0.15	5	5	0.20	5	5	0.25	5	5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.00	5	5																																							
0.05	5	5																																							
0.10	5	5																																							
0.15	5	5																																							
0.20	5	5																																							
0.25	5	5																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																									

COSEL

Model	RMC15A-1	Temperature	25°C																																						
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																						
Object	+5.0V2A																																								
1. Graph		2. Values																																							
 <p>The graph plots Ripple-Noise [mV] on the y-axis (0 to 200) against Load Current [A] on the x-axis (0 to 3). Two data series are shown: Input Volt. 85V (represented by squares) and Input Volt. 132V (represented by triangles). Both series show a sharp increase in noise at higher load currents, particularly between 1.5A and 2.5A. A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>15</td></tr> <tr><td>0.5</td><td>15</td><td>15</td></tr> <tr><td>1.0</td><td>15</td><td>15</td></tr> <tr><td>1.5</td><td>15</td><td>15</td></tr> <tr><td>2.0</td><td>20</td><td>20</td></tr> <tr><td>2.5</td><td>30</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	15	15	0.5	15	15	1.0	15	15	1.5	15	15	2.0	20	20	2.5	30	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	15	15																																							
0.5	15	15																																							
1.0	15	15																																							
1.5	15	15																																							
2.0	20	20																																							
2.5	30	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.  Note: Slanted line shows the range of the rated load current.</p>																																									
<p>リップルノイズは、下図 p - p 値で示される。  (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line  T2: Due to Switching</p>																																									
 <p>A detailed view of a complex ripple wave form. The vertical axis is labeled "Ripple-Noise [mVp-p]". The horizontal axis is divided into two segments: T1 and T2. T1 represents the period due to AC input line noise, and T2 represents the period due to switching noise. The wave form shows high-frequency noise superimposed on a lower-frequency switching pattern.</p>																																									
<p>Fig. Complex Ripple Wave Form  図 リップル波形詳細図</p>																																									

**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																																			
Item	Ripple-Noise リップルノイズ																																					
Object	+12.0V 0.3A																																					
1. Graph		2. Values																																				
<p style="text-align: center;">—□— Input Volt. 85V [mV]      —△— Input Volt. 132V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 85V)</th> <th>Ripple-Noise [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.05</td><td>15</td><td>15</td></tr> <tr><td>0.10</td><td>15</td><td>15</td></tr> <tr><td>0.20</td><td>15</td><td>15</td></tr> <tr><td>0.30</td><td>15</td><td>15</td></tr> <tr><td>0.35</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)	0.00	10	10	0.05	15	15	0.10	15	15	0.20	15	15	0.30	15	15	0.35	20	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—		
Load Current [A]	Ripple-Noise [mV] (Input Volt. 85V)	Ripple-Noise [mV] (Input Volt. 132V)																																				
0.00	10	10																																				
0.05	15	15																																				
0.10	15	15																																				
0.20	15	15																																				
0.30	15	15																																				
0.35	20	20																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
—	—	—																																				
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																						
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																						

**COSEL**


Model	RMC15A-1	Temperature	25°C																																							
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																							
Object	-12.0V 0.2A																																									
1. Graph		2. Values																																								
<p style="text-align: center;">□ Input Volt. 85V [mV]      △ Input Volt. 132V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.05</td><td>20</td><td>20</td></tr> <tr><td>0.10</td><td>20</td><td>20</td></tr> <tr><td>0.15</td><td>20</td><td>20</td></tr> <tr><td>0.20</td><td>20</td><td>20</td></tr> <tr><td>0.25</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.00	15	15	0.05	20	20	0.10	20	20	0.15	20	20	0.20	20	20	0.25	20	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																									
	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
0.00	15	15																																								
0.05	20	20																																								
0.10	20	20																																								
0.15	20	20																																								
0.20	20	20																																								
0.25	20	20																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																										
<p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																										
<p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング 周期</p>																																										
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																										

**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection 過電流保護																																																									
Object	+5.0V2A																																																									
1. Graph	<p>[V]</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2. Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>2.69</td><td>2.70</td><td>2.59</td></tr> <tr><td>4.75</td><td>2.69</td><td>2.68</td><td>2.55</td></tr> <tr><td>4.50</td><td>2.67</td><td>2.65</td><td>2.50</td></tr> <tr><td>4.00</td><td>2.65</td><td>2.60</td><td>2.43</td></tr> <tr><td>3.50</td><td>2.75</td><td>2.67</td><td>2.49</td></tr> <tr><td>3.00</td><td>2.82</td><td>2.72</td><td>2.51</td></tr> <tr><td>2.50</td><td>2.85</td><td>2.73</td><td>2.52</td></tr> <tr><td>2.00</td><td>2.83</td><td>2.70</td><td>2.51</td></tr> <tr><td>1.50</td><td>2.75</td><td>2.62</td><td>2.47</td></tr> <tr><td>1.00</td><td>2.60</td><td>2.50</td><td>2.38</td></tr> <tr><td>0.50</td><td>2.42</td><td>2.33</td><td>2.21</td></tr> <tr><td>0.00</td><td>2.18</td><td>2.11</td><td>2.02</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	5.00	2.69	2.70	2.59	4.75	2.69	2.68	2.55	4.50	2.67	2.65	2.50	4.00	2.65	2.60	2.43	3.50	2.75	2.67	2.49	3.00	2.82	2.72	2.51	2.50	2.85	2.73	2.52	2.00	2.83	2.70	2.51	1.50	2.75	2.62	2.47	1.00	2.60	2.50	2.38	0.50	2.42	2.33	2.21	0.00	2.18	2.11	2.02	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
5.00	2.69	2.70	2.59																																																							
4.75	2.69	2.68	2.55																																																							
4.50	2.67	2.65	2.50																																																							
4.00	2.65	2.60	2.43																																																							
3.50	2.75	2.67	2.49																																																							
3.00	2.82	2.72	2.51																																																							
2.50	2.85	2.73	2.52																																																							
2.00	2.83	2.70	2.51																																																							
1.50	2.75	2.62	2.47																																																							
1.00	2.60	2.50	2.38																																																							
0.50	2.42	2.33	2.21																																																							
0.00	2.18	2.11	2.02																																																							
Object	+12.0V0.3A	2. Values																																																								
1. Graph	<p>[V]</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>0.622</td><td>0.608</td><td>0.555</td></tr> <tr><td>11.40</td><td>0.637</td><td>0.623</td><td>0.565</td></tr> <tr><td>10.80</td><td>0.660</td><td>0.642</td><td>0.581</td></tr> <tr><td>9.60</td><td>0.709</td><td>0.684</td><td>0.618</td></tr> <tr><td>8.40</td><td>0.750</td><td>0.717</td><td>0.650</td></tr> <tr><td>7.20</td><td>0.783</td><td>0.745</td><td>0.671</td></tr> <tr><td>6.00</td><td>0.808</td><td>0.766</td><td>0.694</td></tr> <tr><td>4.80</td><td>0.825</td><td>0.780</td><td>0.714</td></tr> <tr><td>3.60</td><td>0.830</td><td>0.785</td><td>0.729</td></tr> <tr><td>2.40</td><td>0.827</td><td>0.784</td><td>0.734</td></tr> <tr><td>1.20</td><td>0.827</td><td>0.784</td><td>0.736</td></tr> <tr><td>0.00</td><td>0.827</td><td>0.786</td><td>0.737</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	12.00	0.622	0.608	0.555	11.40	0.637	0.623	0.565	10.80	0.660	0.642	0.581	9.60	0.709	0.684	0.618	8.40	0.750	0.717	0.650	7.20	0.783	0.745	0.671	6.00	0.808	0.766	0.694	4.80	0.825	0.780	0.714	3.60	0.830	0.785	0.729	2.40	0.827	0.784	0.734	1.20	0.827	0.784	0.736	0.00	0.827	0.786	0.737	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
12.00	0.622	0.608	0.555																																																							
11.40	0.637	0.623	0.565																																																							
10.80	0.660	0.642	0.581																																																							
9.60	0.709	0.684	0.618																																																							
8.40	0.750	0.717	0.650																																																							
7.20	0.783	0.745	0.671																																																							
6.00	0.808	0.766	0.694																																																							
4.80	0.825	0.780	0.714																																																							
3.60	0.830	0.785	0.729																																																							
2.40	0.827	0.784	0.734																																																							
1.20	0.827	0.784	0.736																																																							
0.00	0.827	0.786	0.737																																																							
Note:	Slanted line shows the range of the rated load current.																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

**COSSEL**

Model	RMC15A-1
Item	Overcurrent Protection 過電流保護
Object	-12.0V 0.2A



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-12.00	0.000	0.000	0.000
-11.40	0.586	0.568	0.508
-10.80	0.623	0.601	0.537
-9.60	0.690	0.661	0.589
-8.40	0.745	0.709	0.634
-7.20	0.790	0.752	0.675
-6.00	0.830	0.785	0.710
-4.80	0.858	0.809	0.743
-3.60	0.869	0.822	0.767
-2.40	0.866	0.828	0.787
-1.20	0.884	0.850	0.804
0.00	0.881	0.848	0.802

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current 突入電流		
Object	—		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 13.48 [A]

② 2.15 [A]



**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response 動的負荷変動		
Object	+5.0V2A		


Input Volt. 100 V

Cycle 1000 mS

Load Current

Load 0% ↔


Load 100 %



Load 0% ↔

Load 50 %

100 mV/div




10 mS/div


**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response 動的負荷変動		
Object	+12.0V 0.3A		

Input Volt. 100 V

Cycle 1000 mS





**COSEL**

**COSEL**

Model	RMC15A-1
Item	Rise and Fall Time 立上り、立下り時間
Object	+5.0V2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		2.0	8.2	10.2	26.6	47.6	
100 %		2.2	10.0	12.2	16.4	41.2	





**COSSEL**

Model	RMC15A-1
Item	Rise and Fall Time 立ち上り、立下り時間
Object	+12.0V 0.3A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		3.4	5.6	9.0	25.0	161.6	
100 %		3.6	6.2	9.8	19.6	31.8	





**COSEL**

Model	RMC15A-1
Item	Rise and Fall Time 立上り、立下り時間
Object	-12.0V 0.2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		3.0	6.4	9.4	24.4	78.2	
100 %		3.0	7.0	10.0	20.2	36.4	




**COSEL**

Model RMC15A-1

Item Ambient Temperature Drift  
周囲温度変動

Object +5.0V2A

## 1. Graph




Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	5.075	5.075	5.075
-10	5.074	5.074	5.074
0	5.072	5.072	5.072
10	5.070	5.070	5.070
20	5.067	5.067	5.067
25	5.066	5.066	5.066
30	5.064	5.064	5.064
40	5.061	5.061	5.061
50	5.056	5.056	5.056
60	5.052	5.052	5.052
—	—	—	—

Object +12.0V0.3A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	12.166	12.166	12.166
-10	12.150	12.150	12.150
0	12.134	12.133	12.133
10	12.115	12.115	12.115
20	12.097	12.097	12.096
25	12.087	12.086	12.086
30	12.075	12.075	12.074
40	12.054	12.053	12.053
50	12.032	12.031	12.031
60	12.008	12.007	12.007
—	—	—	—



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

**COSEL**


Model	RMC15A-1	Testing Circuitry      Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	-12.0V 0.2A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul>	2. Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>-12.285</td> <td>-12.284</td> <td>-12.284</td> </tr> <tr> <td>-10</td> <td>-12.269</td> <td>-12.269</td> <td>-12.268</td> </tr> <tr> <td>0</td> <td>-12.249</td> <td>-12.249</td> <td>-12.248</td> </tr> <tr> <td>10</td> <td>-12.227</td> <td>-12.226</td> <td>-12.226</td> </tr> <tr> <td>20</td> <td>-12.204</td> <td>-12.204</td> <td>-12.203</td> </tr> <tr> <td>25</td> <td>-12.192</td> <td>-12.191</td> <td>-12.191</td> </tr> <tr> <td>30</td> <td>-12.180</td> <td>-12.179</td> <td>-12.178</td> </tr> <tr> <td>40</td> <td>-12.151</td> <td>-12.150</td> <td>-12.149</td> </tr> <tr> <td>50</td> <td>-12.121</td> <td>-12.120</td> <td>-12.119</td> </tr> <tr> <td>60</td> <td>-12.090</td> <td>-12.089</td> <td>-12.088</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	-12.285	-12.284	-12.284	-10	-12.269	-12.269	-12.268	0	-12.249	-12.249	-12.248	10	-12.227	-12.226	-12.226	20	-12.204	-12.204	-12.203	25	-12.192	-12.191	-12.191	30	-12.180	-12.179	-12.178	40	-12.151	-12.150	-12.149	50	-12.121	-12.120	-12.119	60	-12.090	-12.089	-12.088	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	-12.285	-12.284	-12.284																																																				
-10	-12.269	-12.269	-12.268																																																				
0	-12.249	-12.249	-12.248																																																				
10	-12.227	-12.226	-12.226																																																				
20	-12.204	-12.204	-12.203																																																				
25	-12.192	-12.191	-12.191																																																				
30	-12.180	-12.179	-12.178																																																				
40	-12.151	-12.150	-12.149																																																				
50	-12.121	-12.120	-12.119																																																				
60	-12.090	-12.089	-12.088																																																				
—	—	—	—																																																				

(注)斜線は定格周囲温度範囲を示す。

**COSEL**

COSEL

Model	RMC15A-1
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	-12.0V 0.2A




Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	61	64
-10	59	62
0	58	61
10	57	60
20	56	59
25	55	59
30	55	58
40	54	58
50	54	58
60	53	57
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

**COSEL**

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	70	125
-10	50	100
0	30	50
10	15	30
20	10	20
25	10	20
30	10	20
40	10	20
50	10	15
60	10	10
—	—	—

## 2. Values


Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	5	10
-10	5	10
0	5	10
10	5	10
20	5	5
25	5	5
30	5	5
40	5	5
50	5	5
60	5	5
—	—	—

**COSEL**

Model	RMC15A-1
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	-12.0V 0.2A

Testing Circuitry Figure A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Ripple Output Voltage [mV]	
	Load 50%	Load 100%
-20	5	10
-10	5	10
0	5	10
10	5	10
20	5	5
25	5	5
30	5	5
40	5	5
50	5	5
60	5	5
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

**COSEL**

Model	RMC15A-1
Item	Time Lapse Drift 経時ドリフト
Object	+5.0V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




Input Volt. 100V  
Load 100%

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	5.068
0.5	5.066
1.0	5.066
2.0	5.066
3.0	5.066
4.0	5.066
5.0	5.066
6.0	5.066
7.0	5.066
8.0	5.066

## Object +12.0V0.3A

## 1. Graph



Input Volt. 100V  
Load 100%

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	12.109
0.5	12.077
1.0	12.077
2.0	12.077
3.0	12.077
4.0	12.077
5.0	12.077
6.0	12.077
7.0	12.077
8.0	12.077

**COSEL**

Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure A																					
Item	Time Lapse Drift 経時ドリフト																							
Object	-12.0V 0.2A																							
1. Graph			2. Values																					
<p>[V]</p> <table> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.222</td></tr> <tr><td>0.5</td><td>-12.185</td></tr> <tr><td>1.0</td><td>-12.185</td></tr> <tr><td>2.0</td><td>-12.185</td></tr> <tr><td>3.0</td><td>-12.185</td></tr> <tr><td>4.0</td><td>-12.185</td></tr> <tr><td>5.0</td><td>-12.185</td></tr> <tr><td>6.0</td><td>-12.185</td></tr> <tr><td>7.0</td><td>-12.185</td></tr> <tr><td>8.0</td><td>-12.185</td></tr> </tbody> </table>			Time [H]	Output Voltage [V]	0.0	-12.222	0.5	-12.185	1.0	-12.185	2.0	-12.185	3.0	-12.185	4.0	-12.185	5.0	-12.185	6.0	-12.185	7.0	-12.185	8.0	-12.185
Time [H]	Output Voltage [V]																							
0.0	-12.222																							
0.5	-12.185																							
1.0	-12.185																							
2.0	-12.185																							
3.0	-12.185																							
4.0	-12.185																							
5.0	-12.185																							
6.0	-12.185																							
7.0	-12.185																							
8.0	-12.185																							
<p>Output Voltage</p> <p>Input Volt. 100V</p> <p>Load 100%</p>																								



Model RMC15A-1

Item Output Voltage Accuracy 定電圧精度

Testing Circuitry Figure A

## 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current (AVR 1) : 0~2 A (AVR 2) : 0~0.3 A (AVR 3) : 0~0.2 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

## 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 (AVR 1) : 0~2 A (AVR 2) : 0~0.3 A (AVR 3) : 0~0.2 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

## 2. Values

Object +5.0V2A		Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	Minimum Voltage							
-10	50			85	0	5.078		
				132	2	5.056	±11	±0.3

Object +12.0V0.3A		Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	Minimum Voltage							
-10	50			85	0.0	12.183		
				132	0.3	12.022	±81	±0.7

Object -12.0V0.2A		Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	Minimum Voltage							
-10	50			85	0.0	-12.277		
				132	0.2	-12.111	±83	±0.7



Model	RMC15A-1	Testing Circuitry Figure A
Item	Condensation 結露特性	

### 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

### 1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

### 2. Values

Object	+5.0V2A
--------	---------

Item	Data	Testing Conditions
Output Voltage [V]	5.066	Input Volt.: 100V, Load Current:2A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:2A
Load Regulation [mV]	4	Input Volt.: 100V, Load Current:0~2A

Object	+12.0V0.3A
--------	------------

Item	Data	Testing Conditions
Output Voltage [V]	12.079	Input Volt.: 100V, Load Current:0.3A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:0.3A
Load Regulation [mV]	18	Input Volt.: 100V, Load Current:0~0.3A

Object	-12.0V0.2A
--------	------------

Item	Data	Testing Conditions
Output Voltage [V]	-12.182	Input Volt.: 100V, Load Current:0.2A
Line Regulation [mV]	2	Input Volt.: 85~132V, Load Current:0.2A
Load Regulation [mV]	6	Input Volt.: 100V, Load Current:0~0.2A



Model	RMC15A-1	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current 漏洩電流		
Object	—		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.11	0.13	0.18
(B) IEC60950	0.12	0.14	0.18

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

**COSEL**

Model	RMC15A-1
Item	Conducted Emission 雜音端子電圧
Object	_____

Testing Circuitry

Figure D

## 1. Graph

## Remarks


Input Volt. 120 V(VCCI:100V)

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注) 斜線は許容値を示す。

No	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/μV]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B	○	0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60



COSEL




Figure A  
Data Acquisition/Control Unit  
データ集録システム




Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E