


DATA SHEET							Date	23-Mar-07																																														
Model	SFCS304812						Temp.	25degreeC																																														
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH																																														
							Tested by	S.Shiina																																														
LINE CONDUCTION																																																						
Model Name		SFCS304812			Temp.		25degreeC																																															
Model No.					Humi.		45%																																															
Serial No.					Date		2007/3/23 17:11																																															
Points		2			Test Equip.		R3132,ESPC																																															
Detector		PEAK/QP/Ave.			Load Line		100mm																																															
Line Mode		VA			Comment																																																	
Power Supply		DC 48V																																																				
Limit1:		[CISPR Pub11] Class A Gr.1(Ave.)																																																				
Limit2:		[CISPR Pub11] Class A Gr.1(Ave.)																																																				
							Limit1(Ave.) Limit2(Ave.) VA(PEAK) VB(PEAK) VA(QP) VA(Ave.)																																															
							Testing circuitry 2																																															
<table><tr><th>Frequency [MHz]</th><th>Meter Reading (Ave.) [dBuV]</th><th>Meter Reading (QP) [dBuV]</th><th>Factor [dB]</th><th>Level(Ave.) [dBuV]</th><th>Level(QP) [dBuV]</th><th>Line</th><th>Limit(Ave.) [dBuV]</th><th>Limit(QP) [dBuV]</th><th>Margin(Ave.) [dB]</th><th>Margin(QP) [dB]</th></tr><tr><td>0.4611</td><td>32.7</td><td>33.5</td><td>9.9</td><td>42.6</td><td>43.4</td><td>VA</td><td>66</td><td>66</td><td>23.4</td><td>23.4</td></tr><tr><td>23.0436</td><td>35.6</td><td>36.4</td><td>10.3</td><td>45.9</td><td>46.7</td><td>VA</td><td>60</td><td>60</td><td>14.1</td><td>14.1</td></tr></table>											Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]	0.4611	32.7	33.5	9.9	42.6	43.4	VA	66	66	23.4	23.4	23.0436	35.6	36.4	10.3	45.9	46.7	VA	60	60	14.1	14.1											
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]																																												
0.4611	32.7	33.5	9.9	42.6	43.4	VA	66	66	23.4	23.4																																												
23.0436	35.6	36.4	10.3	45.9	46.7	VA	60	60	14.1	14.1																																												
RADIATED EMISSION																																																						
Model Name		SFCS304812			Temp.		25degreeC																																															
Model No.					Humi.		45%																																															
Serial No.					Date		2007/3/23 17:17																																															
Points		3			Test Equip.		R3132,ESPC																																															
Detector		PEAK/QP			Load Line		100mm																																															
Polarization		Vertical			Comment																																																	
Power Supply		DC 48V																																																				
Limit:		[CISPR 11] Class A Group 1<3m>																																																				
							Limit(QP) Horizontal(PEAK) Vertical(PEAK) Vertical(QP)																																															
							Testing circuitry 2																																															
<table><tr><th>Frequency [MHz]</th><th>MeterReading (QP) [dBuV]</th><th>Ant. Type</th><th>Antenna Factor [dB/m]</th><th>Cable & Preamp [dB]</th><th>Level(QP) [dBuV/m]</th><th>Angle [°]</th><th>Height [cm]</th><th>Polar.</th><th>Limit [dBuV/m]</th><th>Margin [dB]</th></tr><tr><td>30.001</td><td>52.7</td><td>BL</td><td>18.2</td><td>-32.3</td><td>38.6</td><td>50</td><td>100</td><td>Vert.</td><td>50</td><td>11.4</td></tr><tr><td>68.709</td><td>54.2</td><td>BL</td><td>5.2</td><td>-32</td><td>27.4</td><td>120</td><td>110</td><td>Vert.</td><td>50</td><td>22.6</td></tr><tr><td>198.78</td><td>63.4</td><td>BL</td><td>8.5</td><td>-31.3</td><td>40.6</td><td>244</td><td>116</td><td>Vert.</td><td>50</td><td>9.4</td></tr></table>											Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	30.001	52.7	BL	18.2	-32.3	38.6	50	100	Vert.	50	11.4	68.709	54.2	BL	5.2	-32	27.4	120	110	Vert.	50	22.6	198.78	63.4	BL	8.5	-31.3	40.6	244	116	Vert.	50	9.4
Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]																																												
30.001	52.7	BL	18.2	-32.3	38.6	50	100	Vert.	50	11.4																																												
68.709	54.2	BL	5.2	-32	27.4	120	110	Vert.	50	22.6																																												
198.78	63.4	BL	8.5	-31.3	40.6	244	116	Vert.	50	9.4																																												

DATA SHEET		Date	23-Mar-07
Model	SFCS304812	Temp.	25degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	S.Shiina


1.Conditions

(1)Photographs of Test Set-Up


LINE CONDUCTION



Radiated emission





(2)Testing circuitry



C1 : 22µF 100V Electric capacitor
C2 : 1µF 100V Ceramic capacitor
C3 : 2200pF 630V Ceramic capacitor
C4 : 0.1µF 50V Ceramic capacitor

L1 : 1µH 2.4A Inductor
L2 : ACM1211-102-2PL : TDK

Fig. Testing circuitry2


DATA SHEET							Date	23-Mar-07																																														
Model	SFCS304812						Temp.	25degreeC																																														
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH																																														
							Tested by	S.Shiina																																														
LINE CONDUCTION																																																						
Model Name		SFCS304812			Temp.		25degreeC																																															
Model No.					Humi.		45%																																															
Serial No.					Date		2007/3/23 16:49																																															
Points		3			Test Equip.		R3132,ESPC																																															
Detector		PEAK/QP/Ave.			Load Line		100mm																																															
Line Mode		VA/VB			Comment																																																	
Power Supply		DC 48V																																																				
Limit1:		[CISPR Pub11] Class A Gr.1(QP)																																																				
Limit2:		[CISPR Pub11] Class A Gr.1(Ave.)																																																				
							Limit1(QP)		—																																													
							Limit2(Ave.)		- - -																																													
							VA(PEAK)		—																																													
							VB(PEAK)		—																																													
							VA(QP)		○																																													
							VA(Ave.)		●																																													
							VB(QP)		×																																													
							VB(Ave.)		×																																													
							Testing circuitry 1																																															
<table><tr><th>Frequency [MHz]</th><th>Meter Reading (Ave.) [dBuV]</th><th>Meter Reading (QP) [dBuV]</th><th>Factor [dB]</th><th>Level(Ave.) [dBuV]</th><th>Level(QP) [dBuV]</th><th>Line</th><th>Limit(Ave.) [dBuV]</th><th>Limit(QP) [dBuV]</th><th>Margin(Ave.) [dB]</th><th>Margin(QP) [dB]</th></tr><tr><td>9.6801</td><td>25.5</td><td>25.4</td><td>10.1</td><td>35.6</td><td>35.5</td><td>VA</td><td>60</td><td>73</td><td>24.4</td><td>37.5</td></tr><tr><td>21.6635</td><td>36.3</td><td>36.6</td><td>10.3</td><td>46.6</td><td>46.9</td><td>VA</td><td>60</td><td>73</td><td>13.4</td><td>26.1</td></tr><tr><td>0.4606</td><td>31.4</td><td>32.5</td><td>9.9</td><td>41.3</td><td>42.4</td><td>VB</td><td>66</td><td>79</td><td>24.7</td><td>36.6</td></tr></table>											Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]	9.6801	25.5	25.4	10.1	35.6	35.5	VA	60	73	24.4	37.5	21.6635	36.3	36.6	10.3	46.6	46.9	VA	60	73	13.4	26.1	0.4606	31.4	32.5	9.9	41.3	42.4	VB	66	79	24.7	36.6
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]																																												
9.6801	25.5	25.4	10.1	35.6	35.5	VA	60	73	24.4	37.5																																												
21.6635	36.3	36.6	10.3	46.6	46.9	VA	60	73	13.4	26.1																																												
0.4606	31.4	32.5	9.9	41.3	42.4	VB	66	79	24.7	36.6																																												
RADIATED EMISSION																																																						
Model Name		SFCS304812			Temp.		25degreeC																																															
Model No.					Humi.		45%																																															
Serial No.					Date		2007/3/23 16:56																																															
Points		3			Test Equip.		R3132,ESPC																																															
Detector		PEAK/QP			Load Line		100mm																																															
Polarization		Vertical			Comment																																																	
Power Supply		DC 48V																																																				
Limit:		[CISPR 11] Class A Group 1<3m>																																																				
							Limit(QP)		—																																													
							Horizontal(PEAK)		—																																													
							Vertical(PEAK)		—																																													
							Vertical(QP)		×																																													
							Testing circuitry 1																																															
<table><tr><th>Frequency [MHz]</th><th>MeterReading (QP) [dBuV]</th><th>Ant. Type</th><th>Antenna Factor [dB/m]</th><th>Cable & Preamp [dB]</th><th>Level(QP) [dBuV/m]</th><th>Angle [°]</th><th>Height [cm]</th><th>Polar.</th><th>Limit [dBuV/m]</th><th>Margin [dB]</th></tr><tr><td>30.001</td><td>50.6</td><td>BL</td><td>18.2</td><td>-32.3</td><td>36.5</td><td>11</td><td>100</td><td>Vert.</td><td>50</td><td>13.5</td></tr><tr><td>70.998</td><td>53.5</td><td>BL</td><td>5.6</td><td>-31.9</td><td>27.2</td><td>114</td><td>116</td><td>Vert.</td><td>50</td><td>22.8</td></tr><tr><td>199.222</td><td>63.5</td><td>BL</td><td>8.5</td><td>-31.3</td><td>40.7</td><td>242</td><td>111</td><td>Vert.</td><td>50</td><td>9.3</td></tr></table>											Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	30.001	50.6	BL	18.2	-32.3	36.5	11	100	Vert.	50	13.5	70.998	53.5	BL	5.6	-31.9	27.2	114	116	Vert.	50	22.8	199.222	63.5	BL	8.5	-31.3	40.7	242	111	Vert.	50	9.3
Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]																																												
30.001	50.6	BL	18.2	-32.3	36.5	11	100	Vert.	50	13.5																																												
70.998	53.5	BL	5.6	-31.9	27.2	114	116	Vert.	50	22.8																																												
199.222	63.5	BL	8.5	-31.3	40.7	242	111	Vert.	50	9.3																																												

DATA SHEET		Date	23-Mar-07
Model	SFCS304812	Temp.	25degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	S.Shiina


1.Conditions

(1)Photographs of Test Set-Up


LINE CONDUCTION



Radiated emission



(2)Testing circuitry




C1 : 22 μ F 100V Electric capacitor
C2 : 1 μ F 100V Ceramic capacitor
C3 : 2200pF 630V Ceramic capacitor
C4 : 0.1 μ F 50V Ceramic capacitor

L1 : 1 μ H 2.4A Inductor
L2 : ACM1211-102-2PL : TDK

Fig. Testing circuitry1

DATA SHEET		Date	23-Mar-07
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	S.Shiina

1. Line conduction



2. Radiated emission

