



M T B F

(E I A J R C R - 9 1 0 2)

|       |            |
|-------|------------|
| Model | SFLS154805 |
|-------|------------|

| No.                                      | P a r t s              |            | Q'ty of Device | Failure rate [10 <sup>-6</sup> /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1  | I C                    | Monolithic | 2              | 0.0390                             |                   |
| 2  |                        | Hybrid     | 0              | 0.0000                             |                   |
| 3  | Transistors            |            | 22             | 0.7095                             |                   |
| 4  | Diodes                 |            | 19             | 0.2580                             |                   |
| 5  | LED•Optocouplers       |            | 0              | 0.0000                             |                   |
| 6  | Resistors              |            | 91             | 0.0182                             |                   |
| 7  | Capacitors             |            | 41             | 0.3034                             |                   |
| 8  | Transformer•Choke Coil |            | 2              | 0.0460                             |                   |
| 9  | Connectors             |            | 462            | 0.0636                             |                   |
| 10                                       | Others                 |            | 1              | 0.1100                             |                   |
| Total Failure Rate [10 <sup>-6</sup> /H] |                        |            |                | 1.5477                             |                   |

|                     |      |         |
|---------------------|------|---------|
| M T B F             | [H]  | 647,000 |
| Ambient Temperature | [°C] | —       |
| Load Factor         | [%]  | —       |