




DATA SHEET							Date	21-Sep-06																																			
Model	SFLS15481R2						Temp.	25 degreeC																																			
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH																																			
							Tested by	K.Tsukada																																			
LINE CONDUCTION																																											
Model Name			SFLS15481R2		Temp.		25																																				
Model No.					Humi.		45																																				
Serial No.					Date		2006/9/21 10:11																																				
Points			2		Test Equip.		R3132,ESPC																																				
Detector			PEAK/QP/Ave.		Comment		K.Tsukada																																				
Line Mode			VA		Vin=48V																																						
Power Supply			DC 48V		Io=5.2A																																						
Limit1: [CISPR Pub11]			Class A Gr.1(QP)																																								
Limit2: [CISPR Pub11]			Class A Gr.1(Ave.)																																								
							Limit1(QP)		—																																		
							Limit2(Ave.)		- - -																																		
							VA(PEAK)		—																																		
							VB(PEAK)		—																																		
							VA(QP)		○																																		
							VA(Ave.)		●																																		
							Vin=48V																																				
							Io=5.2A																																				
<table><tr><th>Frequency [MHz]</th><th>Meter Reading (Ave.) [dBuV]</th><th>Meter Reading (QP) [dBuV]</th><th>Factor [dB]</th><th>Level(Ave.) [dBuV]</th><th>Level(QP) [dBuV]</th><th>Line</th><th>Limit(Ave.) [dBuV]</th><th>Limit(QP) [dBuV]</th><th>Margin(Ave.) [dB]</th><th>Margin(QP) [dB]</th></tr><tr><td>0.6476</td><td>37.3</td><td>37.3</td><td>9.9</td><td>47.2</td><td>47.2</td><td>VA</td><td>60</td><td>73</td><td>12.8</td><td>25.8</td></tr><tr><td>17.5035</td><td>24.9</td><td>25.1</td><td>10.2</td><td>35.1</td><td>35.3</td><td>VA</td><td>60</td><td>73</td><td>24.9</td><td>37.7</td></tr></table>											Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]	0.6476	37.3	37.3	9.9	47.2	47.2	VA	60	73	12.8	25.8	17.5035	24.9	25.1	10.2	35.1	35.3	VA	60	73	24.9	37.7
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]																																	
0.6476	37.3	37.3	9.9	47.2	47.2	VA	60	73	12.8	25.8																																	
17.5035	24.9	25.1	10.2	35.1	35.3	VA	60	73	24.9	37.7																																	
RADIATED EMISSION																																											
Model Name			SFLS15481R2		Temp.		25																																				
Model No.					Humi.		45																																				
Serial No.					Date		2007/2/2 9:29																																				
Points			2		Test Equip.		R3132,ESPC																																				
Detector			PEAK/QP		Comment		K.Tsukada																																				
Polarization			Vertical		Vin=48V																																						
Power Supply			DC 48V		Io=5.2A																																						
Limit: [CISPR 11]			Class A Group 1<3m>																																								
							Limit(QP)		—																																		
							Horizontal(PEAK)		—																																		
							Vertical(PEAK)		—																																		
							Vertical(QP)		×																																		
							Vin=48V																																				
							Io=5.2A																																				
<table><tr><th>Frequency [MHz]</th><th>MeterReading (QP) [dBuV]</th><th>Ant. Type</th><th>Antenna Factor [dB/m]</th><th>Cable & Preamp [dB]</th><th>Level(QP) [dBuV/m]</th><th>Angle [°]</th><th>Height [cm]</th><th>Polar.</th><th>Limit [dBuV/m]</th><th>Margin [dB]</th></tr><tr><td>223.297</td><td>61</td><td>BL</td><td>9.2</td><td>-31.2</td><td>39</td><td>195</td><td>115</td><td>Vert.</td><td>50</td><td>11</td></tr><tr><td>259.405</td><td>60.7</td><td>BL</td><td>13.6</td><td>-31.1</td><td>43.2</td><td>195</td><td>125</td><td>Vert.</td><td>57</td><td>13.8</td></tr></table>											Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	223.297	61	BL	9.2	-31.2	39	195	115	Vert.	50	11	259.405	60.7	BL	13.6	-31.1	43.2	195	125	Vert.	57	13.8
Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]																																	
223.297	61	BL	9.2	-31.2	39	195	115	Vert.	50	11																																	
259.405	60.7	BL	13.6	-31.1	43.2	195	125	Vert.	57	13.8																																	

DATA SHEET		Date	21-Sep-06
Model	SFLS15481R2	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	K.Tsukada

1. Line conduction



2. Radiated emission

