



TEST DATA OF SFS10481R2

Regulated DC Power Supply
Jan.22. 2004

Approved by : Isao Yasuda
Isao Yasuda Design Manager

Prepared by : Toshiyuki Tsuru
Toshiyuki Tsuru Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19


(Final Page 19)

COSEL

Model SFS10481R2

Item Input Current (by Input Voltage)

Object



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
8	0.002	0.002	0.002
16	0.002	0.002	0.002
24	0.002	0.002	0.002
33	0.002	0.002	0.002
35	0.017	0.080	0.145
36	0.017	0.078	0.142
40	0.017	0.072	0.129
48	0.016	0.062	0.109
60	0.016	0.052	0.090
70	0.016	0.047	0.079
76	0.016	0.044	0.074
80	0.016	0.043	0.071
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SFS10481R2																																																				
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object																																																					
1. Graph	<p>—△— Input Volt. 36V - -□-- Input Volt. 48V - -○--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36[V] [A]</th> <th>Input Volt. 48[V] [A]</th> <th>Input Volt. 76[V] [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.017</td><td>0.016</td><td>0.016</td></tr> <tr><td>0.60</td><td>0.038</td><td>0.032</td><td>0.026</td></tr> <tr><td>1.20</td><td>0.059</td><td>0.047</td><td>0.035</td></tr> <tr><td>1.80</td><td>0.081</td><td>0.063</td><td>0.045</td></tr> <tr><td>2.40</td><td>0.103</td><td>0.080</td><td>0.056</td></tr> <tr><td>3.00</td><td>0.125</td><td>0.096</td><td>0.066</td></tr> <tr><td>3.50</td><td>0.144</td><td>0.109</td><td>0.074</td></tr> <tr><td>3.85</td><td>0.157</td><td>0.120</td><td>0.081</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 36[V] [A]	Input Volt. 48[V] [A]	Input Volt. 76[V] [A]	0.00	0.017	0.016	0.016	0.60	0.038	0.032	0.026	1.20	0.059	0.047	0.035	1.80	0.081	0.063	0.045	2.40	0.103	0.080	0.056	3.00	0.125	0.096	0.066	3.50	0.144	0.109	0.074	3.85	0.157	0.120	0.081																
Load Current [A]	Input Volt. 36[V] [A]	Input Volt. 48[V] [A]	Input Volt. 76[V] [A]																																																		
0.00	0.017	0.016	0.016																																																		
0.60	0.038	0.032	0.026																																																		
1.20	0.059	0.047	0.035																																																		
1.80	0.081	0.063	0.045																																																		
2.40	0.103	0.080	0.056																																																		
3.00	0.125	0.096	0.066																																																		
3.50	0.144	0.109	0.074																																																		
3.85	0.157	0.120	0.081																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.017</td><td>0.016</td><td>0.016</td></tr> <tr><td>0.60</td><td>0.038</td><td>0.032</td><td>0.026</td></tr> <tr><td>1.20</td><td>0.059</td><td>0.047</td><td>0.035</td></tr> <tr><td>1.80</td><td>0.081</td><td>0.063</td><td>0.045</td></tr> <tr><td>2.40</td><td>0.103</td><td>0.080</td><td>0.056</td></tr> <tr><td>3.00</td><td>0.125</td><td>0.096</td><td>0.066</td></tr> <tr><td>3.50</td><td>0.144</td><td>0.109</td><td>0.074</td></tr> <tr><td>3.85</td><td>0.157</td><td>0.120</td><td>0.081</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.017	0.016	0.016	0.60	0.038	0.032	0.026	1.20	0.059	0.047	0.035	1.80	0.081	0.063	0.045	2.40	0.103	0.080	0.056	3.00	0.125	0.096	0.066	3.50	0.144	0.109	0.074	3.85	0.157	0.120	0.081	—	-	-	-	—	-	-	-	—	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	0.017	0.016	0.016																																																		
0.60	0.038	0.032	0.026																																																		
1.20	0.059	0.047	0.035																																																		
1.80	0.081	0.063	0.045																																																		
2.40	0.103	0.080	0.056																																																		
3.00	0.125	0.096	0.066																																																		
3.50	0.144	0.109	0.074																																																		
3.85	0.157	0.120	0.081																																																		
—	-	-	-																																																		
—	-	-	-																																																		
—	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SFS10481R2																																																				
Item	Input Power (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.60</td><td>0.77</td><td>1.20</td></tr> <tr><td>0.60</td><td>1.35</td><td>1.51</td><td>1.93</td></tr> <tr><td>1.20</td><td>2.12</td><td>2.28</td><td>2.69</td></tr> <tr><td>1.80</td><td>2.89</td><td>3.05</td><td>3.44</td></tr> <tr><td>2.40</td><td>3.68</td><td>3.83</td><td>4.21</td></tr> <tr><td>3.00</td><td>4.49</td><td>4.60</td><td>4.99</td></tr> <tr><td>3.50</td><td>5.16</td><td>5.25</td><td>5.65</td></tr> <tr><td>3.85</td><td>5.64</td><td>5.75</td><td>6.11</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.00	0.60	0.77	1.20	0.60	1.35	1.51	1.93	1.20	2.12	2.28	2.69	1.80	2.89	3.05	3.44	2.40	3.68	3.83	4.21	3.00	4.49	4.60	4.99	3.50	5.16	5.25	5.65	3.85	5.64	5.75	6.11																
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																		
0.00	0.60	0.77	1.20																																																		
0.60	1.35	1.51	1.93																																																		
1.20	2.12	2.28	2.69																																																		
1.80	2.89	3.05	3.44																																																		
2.40	3.68	3.83	4.21																																																		
3.00	4.49	4.60	4.99																																																		
3.50	5.16	5.25	5.65																																																		
3.85	5.64	5.75	6.11																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.60</td><td>0.77</td><td>1.20</td></tr> <tr><td>0.60</td><td>1.35</td><td>1.51</td><td>1.93</td></tr> <tr><td>1.20</td><td>2.12</td><td>2.28</td><td>2.69</td></tr> <tr><td>1.80</td><td>2.89</td><td>3.05</td><td>3.44</td></tr> <tr><td>2.40</td><td>3.68</td><td>3.83</td><td>4.21</td></tr> <tr><td>3.00</td><td>4.49</td><td>4.60</td><td>4.99</td></tr> <tr><td>3.50</td><td>5.16</td><td>5.25</td><td>5.65</td></tr> <tr><td>3.85</td><td>5.64</td><td>5.75</td><td>6.11</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.60	0.77	1.20	0.60	1.35	1.51	1.93	1.20	2.12	2.28	2.69	1.80	2.89	3.05	3.44	2.40	3.68	3.83	4.21	3.00	4.49	4.60	4.99	3.50	5.16	5.25	5.65	3.85	5.64	5.75	6.11	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	0.60	0.77	1.20																																																		
0.60	1.35	1.51	1.93																																																		
1.20	2.12	2.28	2.69																																																		
1.80	2.89	3.05	3.44																																																		
2.40	3.68	3.83	4.21																																																		
3.00	4.49	4.60	4.99																																																		
3.50	5.16	5.25	5.65																																																		
3.85	5.64	5.75	6.11																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.


COSEL

Model SFS10481R2

Item Efficiency (by Input Voltage)

Object

1. Graph



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
34	76.2	81.6
36	75.5	81.4
40	74.2	81.0
48	71.7	80.0
55	69.5	78.5
60	68.0	77.5
70	64.8	75.6
76	62.9	74.2
78	62.2	73.8

COSSEL

Model	SFS10481R2
Item	Efficiency (by Load Current)
Object	—



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	-	-	-
0.60	54.9	49.1	38.3
1.20	69.4	64.6	54.7
1.80	75.7	72.0	63.5
2.40	78.9	76.0	68.8
3.00	80.6	78.5	72.3
3.50	81.4	80.0	74.3
3.85	81.7	80.2	75.3
—	-	-	-
—	-	-	-
—	-	-	-

COSEL


Model SFS10481R2

Item Line Regulation

Object +1.2V3.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	1.210	1.197
36	1.211	1.198
40	1.212	1.200
48	1.214	1.201
55	1.214	1.201
60	1.213	1.200
70	1.211	1.198
76	1.210	1.197
78	1.209	1.196


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model SFS10481R2

Item Load Regulation

Object +1.2V3.5A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	1.223	1.225	1.221
0.60	1.219	1.221	1.217
1.20	1.215	1.217	1.213
1.80	1.210	1.213	1.209
2.40	1.206	1.209	1.205
3.00	1.202	1.205	1.201
3.50	1.198	1.201	1.197
3.85	1.195	1.198	1.194
-	-	-	-
-	-	-	-
-	-	-	-

COSEL







Model SFS10481R2

Item Dynamic Load Response

Object +1.2V3.5A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 48 V
Cycle 1000 mS

Load Current 3.5A / 200 μs

Min. Load (0A) ↔
Load 100% (3.5A)Min. Load (0A) ↔
Load 50% (1.75A)Load 50% (1.75A) ↔
Load 100% (3.5A)

COSEL


Model	SFS10481R2	Temperature Testing Circuitry 25°C Figure C																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+1.2V3.5A																																							
1. Graph																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1</td><td>1</td></tr> <tr><td>0.70</td><td>1</td><td>1</td></tr> <tr><td>1.40</td><td>1</td><td>1</td></tr> <tr><td>2.10</td><td>1</td><td>1</td></tr> <tr><td>2.80</td><td>1</td><td>1</td></tr> <tr><td>3.50</td><td>1</td><td>1</td></tr> <tr><td>3.85</td><td>1</td><td>1</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	1	1	0.70	1	1	1.40	1	1	2.10	1	1	2.80	1	1	3.50	1	1	3.85	1	1	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	1	1																																						
0.70	1	1																																						
1.40	1	1																																						
2.10	1	1																																						
2.80	1	1																																						
3.50	1	1																																						
3.85	1	1																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Measured by 100MHz Ossiloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Wave Form																																								

COSEL

Model	SFS10481R2
Item	Ripple-Noise
Object	+1.2V3.5A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	16	26
0.70	14	25
1.40	14	23
2.10	13	22
2.80	14	23
3.50	15	25
3.85	16	26
—	—	—
—	—	—
—	—	—
—	—	—

Measured by 100MHz Ossiloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Wave Form

COSEL

Model	SFS10481R2
Item	Ripple Voltage (by Ambient Temp.)
Object	+1.2V3.5A

1.Graph



Measured by 100MHz Ossiloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-45	2	2
-40	1	2
0	1	1
25	1	1
85	1	1
90	1	1
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-


COSEL

Model SFS10481R2

Item Ambient Temperature Drift

Object +1.2V3.5A

1. Graph
- | | |
|-----------|-----------------|
| —△— | Input Volt. 36V |
| - - -□- | Input Volt. 48V |
| - - ○ - - | Input Volt. 76V |



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-45	1.202	1.206	1.199
-40	1.202	1.206	1.199
-20	1.201	1.204	1.199
0	1.200	1.204	1.199
25	1.199	1.202	1.197
50	1.197	1.199	1.195
85	1.193	1.194	1.189
90	1.192	1.194	1.188
—	—	—	—
—	—	—	—
—	—	—	—



Model	SFS10481R2	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+1.2V3.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 36 - 76V

Load Current : 0 - 3.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	85	48	0	1.231	± 21	± 1.8
Minimum Voltage	85	76	3.5	1.189		

COSEL

Model	SFS10481R2
Item	Time Lapse Drift
Object	+1.2V3.5A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Input Volt. 48V
 Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	1.202
0.5	1.201
1.0	1.201
2.0	1.201
3.0	1.201
4.0	1.201
5.0	1.201
6.0	1.201
7.0	1.201
8.0	1.201

COSEL


Model SFS10481R2

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A


Object +1.2V3.5A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		60.3	0.8	61.1	0.1	0.2	
100 %		60.3	0.9	61.2	0.1	0.2	



COSEL

Model	SFS10481R2	Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+1.2V3.5A																																							
1. Graph		2. Values																																						
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>--- □--- Load 50%</p> <p>— △ — Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-45</td><td>31.7</td><td>31.8</td> </tr> <tr> <td>-40</td><td>31.7</td><td>31.9</td> </tr> <tr> <td>-20</td><td>31.9</td><td>31.8</td> </tr> <tr> <td>0</td><td>31.9</td><td>32.1</td> </tr> <tr> <td>25</td><td>32.1</td><td>32.2</td> </tr> <tr> <td>50</td><td>32.3</td><td>32.3</td> </tr> <tr> <td>85</td><td>32.5</td><td>32.4</td> </tr> <tr> <td>90</td><td>32.5</td><td>32.4</td> </tr> <tr> <td>—</td><td>—</td><td>—</td> </tr> <tr> <td>—</td><td>—</td><td>—</td> </tr> <tr> <td>—</td><td>—</td><td>—</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-45	31.7	31.8	-40	31.7	31.9	-20	31.9	31.8	0	31.9	32.1	25	32.1	32.2	50	32.3	32.3	85	32.5	32.4	90	32.5	32.4	—	—	—	—	—	—	—	—	—
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-45	31.7	31.8																																						
-40	31.7	31.9																																						
-20	31.9	31.8																																						
0	31.9	32.1																																						
25	32.1	32.2																																						
50	32.3	32.3																																						
85	32.5	32.4																																						
90	32.5	32.4																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	SFS10481R2	Temperature Testing Circuitry	25°C Figure A																																																															
Item	Overcurrent Protection																																																																	
Object	+1.2V3.5A																																																																	
1.Graph	<p>The graph plots Output Voltage [V] on the Y-axis (0.0 to 2.0) against Load Current [A] on the X-axis (0 to 6). Three horizontal lines represent different input voltages: 36V (top), 48V (middle), and 76V (bottom). A slanted line starts at approximately (3.2, 1.08) and slopes down to (5.5, 0.95), indicating the range of the rated load current where the output voltage drops below the minimum rating of 1.08V.</p>																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>1.20</td><td>3.57</td><td>3.68</td><td>3.57</td></tr> <tr><td>1.14</td><td>5.25</td><td>5.26</td><td>5.38</td></tr> <tr><td>1.08</td><td>5.27</td><td>5.29</td><td>5.42</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	1.20	3.57	3.68	3.57	1.14	5.25	5.26	5.38	1.08	5.27	5.29	5.42	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																	
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																															
1.20	3.57	3.68	3.57																																																															
1.14	5.25	5.26	5.38																																																															
1.08	5.27	5.29	5.42																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															

Note: Slanted line shows the range of the rated load current.

When the output voltage fell to less than 1.08V, the unit shuts off the output by operating low voltage protection.

Model	SFS10481R2
Item	Overvoltage Protection
Object	+1.2V3.5A

1.Graph —△— Input Volt. 48V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 48[V]	Input Volt.	Input Volt.
-40	1.61	-	-
25	1.60	-	-
85	1.58	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




Figure A




Figure B (General Electric Characteristic)




Figure C (Ripple and Ripple noise Characteristic)