



# TEST DATA OF SFS20481R8

Regulated DC Power Supply  
Sep 10, 2004

Approved by : Isao Yasuda  
Isao Yasuda Design Manager

Prepared by : Kazuhiko Horii  
Kazuhiko Horii Design Engineer

COSEL CO.,LTD.

## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	9
10. Ripple-Noise . . . . .	10
11. Ripple Voltage (by Ambient Temperature) . . . . .	11
12. Ambient Temperature Drift . . . . .	12
13. Output Voltage Accuracy . . . . .	13
14. Time Lapse Drift . . . . .	14
15. Rise and Fall Time . . . . .	15
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17. Overcurrent Protection . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19

(Final Page 19)


**COSEL**

Model	SFS20481R8	Temperature 25°C Testing Circuitry Figure A																																																																									
Item	Input Current (by Input Voltage)																																																																										
Object	—																																																																										
1.Graph	<p>—△— Load 100%</p> <p>- -□-- Load 50%</p> <p>- -○-- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>30</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>35</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.000</td><td>0.000</td><td>0.450</td></tr> <tr><td>45</td><td>0.000</td><td>0.000</td><td>0.350</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.250</td></tr> <tr><td>60</td><td>0.000</td><td>0.000</td><td>0.250</td></tr> <tr><td>70</td><td>0.000</td><td>0.000</td><td>0.200</td></tr> <tr><td>80</td><td>0.000</td><td>0.000</td><td>0.200</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	30	0.000	0.000	0.000	35	0.000	0.000	0.000	40	0.000	0.000	0.450	45	0.000	0.000	0.350	50	0.000	0.000	0.250	60	0.000	0.000	0.250	70	0.000	0.000	0.200	80	0.000	0.000	0.200																																		
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																								
0	0.000	0.000	0.000																																																																								
30	0.000	0.000	0.000																																																																								
35	0.000	0.000	0.000																																																																								
40	0.000	0.000	0.450																																																																								
45	0.000	0.000	0.350																																																																								
50	0.000	0.000	0.250																																																																								
60	0.000	0.000	0.250																																																																								
70	0.000	0.000	0.200																																																																								
80	0.000	0.000	0.200																																																																								
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>16</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>24</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>33</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>34</td><td>0.013</td><td>0.239</td><td>0.490</td></tr> <tr><td>36</td><td>0.013</td><td>0.229</td><td>0.475</td></tr> <tr><td>40</td><td>0.013</td><td>0.207</td><td>0.420</td></tr> <tr><td>48</td><td>0.013</td><td>0.174</td><td>0.352</td></tr> <tr><td>60</td><td>0.013</td><td>0.142</td><td>0.277</td></tr> <tr><td>70</td><td>0.013</td><td>0.123</td><td>0.239</td></tr> <tr><td>76</td><td>0.014</td><td>0.115</td><td>0.223</td></tr> <tr><td>80</td><td>0.014</td><td>0.110</td><td>0.210</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	8	0.001	0.001	0.001	16	0.001	0.001	0.001	24	0.002	0.002	0.002	33	0.002	0.002	0.002	34	0.013	0.239	0.490	36	0.013	0.229	0.475	40	0.013	0.207	0.420	48	0.013	0.174	0.352	60	0.013	0.142	0.277	70	0.013	0.123	0.239	76	0.014	0.115	0.223	80	0.014	0.110	0.210	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																										
	Load 0%	Load 50%	Load 100%																																																																								
0	0.000	0.000	0.000																																																																								
8	0.001	0.001	0.001																																																																								
16	0.001	0.001	0.001																																																																								
24	0.002	0.002	0.002																																																																								
33	0.002	0.002	0.002																																																																								
34	0.013	0.239	0.490																																																																								
36	0.013	0.229	0.475																																																																								
40	0.013	0.207	0.420																																																																								
48	0.013	0.174	0.352																																																																								
60	0.013	0.142	0.277																																																																								
70	0.013	0.123	0.239																																																																								
76	0.014	0.115	0.223																																																																								
80	0.014	0.110	0.210																																																																								
--	-	-	-																																																																								
--	-	-	-																																																																								
--	-	-	-																																																																								
Note:	Slanted line shows the range of the rated input voltage.																																																																										

Model	SFS20481R8	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 36V        - - -□- - - Input Volt. 48V        - - ○ - - Input Volt. 76V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.013</td><td>0.013</td><td>0.014</td></tr> <tr> <td>1.5</td><td>0.092</td><td>0.072</td><td>0.051</td></tr> <tr> <td>3.0</td><td>0.174</td><td>0.133</td><td>0.089</td></tr> <tr> <td>4.5</td><td>0.260</td><td>0.196</td><td>0.128</td></tr> <tr> <td>6.0</td><td>0.349</td><td>0.262</td><td>0.168</td></tr> <tr> <td>7.5</td><td>0.443</td><td>0.329</td><td>0.210</td></tr> <tr> <td>8.0</td><td>0.475</td><td>0.352</td><td>0.223</td></tr> <tr> <td>8.4</td><td>0.501</td><td>0.371</td><td>0.235</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.013	0.013	0.014	1.5	0.092	0.072	0.051	3.0	0.174	0.133	0.089	4.5	0.260	0.196	0.128	6.0	0.349	0.262	0.168	7.5	0.443	0.329	0.210	8.0	0.475	0.352	0.223	8.4	0.501	0.371	0.235	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.013	0.013	0.014																																																			
1.5	0.092	0.072	0.051																																																			
3.0	0.174	0.133	0.089																																																			
4.5	0.260	0.196	0.128																																																			
6.0	0.349	0.262	0.168																																																			
7.5	0.443	0.329	0.210																																																			
8.0	0.475	0.352	0.223																																																			
8.4	0.501	0.371	0.235																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SFS20481R8																																																					
Item	Input Power (by Load Current)																																																					
Object																																																						
1.Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Input Volt. 36V  <span style="color: gray;">□</span> Input Volt. 48V  <span style="color: gray;">○</span> Input Volt. 76V         </p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0 to 8). Three curves are shown for different input voltages: 36V (solid line with open triangle markers), 48V (dashed line with open square markers), and 76V (dotted line with open circle markers). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (0.5, 1.1) and ending at (8.0, 17.9), indicating the rated load current range.</p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.50</td> <td>0.64</td> <td>1.11</td> </tr> <tr> <td>1.5</td> <td>3.35</td> <td>3.49</td> <td>3.93</td> </tr> <tr> <td>3.0</td> <td>6.31</td> <td>6.43</td> <td>6.87</td> </tr> <tr> <td>4.5</td> <td>9.37</td> <td>9.44</td> <td>9.84</td> </tr> <tr> <td>6.0</td> <td>12.56</td> <td>12.56</td> <td>12.89</td> </tr> <tr> <td>7.5</td> <td>15.90</td> <td>15.80</td> <td>16.00</td> </tr> <tr> <td>8.0</td> <td>17.08</td> <td>16.88</td> <td>17.04</td> </tr> <tr> <td>8.4</td> <td>18.02</td> <td>17.78</td> <td>17.91</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.50	0.64	1.11	1.5	3.35	3.49	3.93	3.0	6.31	6.43	6.87	4.5	9.37	9.44	9.84	6.0	12.56	12.56	12.89	7.5	15.90	15.80	16.00	8.0	17.08	16.88	17.04	8.4	18.02	17.78	17.91	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.50	0.64	1.11																																																			
1.5	3.35	3.49	3.93																																																			
3.0	6.31	6.43	6.87																																																			
4.5	9.37	9.44	9.84																																																			
6.0	12.56	12.56	12.89																																																			
7.5	15.90	15.80	16.00																																																			
8.0	17.08	16.88	17.04																																																			
8.4	18.02	17.78	17.91																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSSEL**


Model SFS20481R8

Item Efficiency (by Input Voltage)

Object

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
34	87.1	84.2
36	87.2	84.5
40	87.2	85.1
48	86.5	85.6
55	85.8	85.5
60	85.3	85.3
70	83.4	84.5
76	82.6	84.3
78	82.3	83.9

Note: Slanted line shows the range of the rated input voltage.

**COSSEL**

Model	SFS20481R8																																																			
Item	Efficiency (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																		
Object																																																				
1.Graph																																																				
<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>1.5</td><td>81.4</td><td>78.6</td><td>70.1</td></tr> <tr><td>3.0</td><td>86.5</td><td>85.3</td><td>80.1</td></tr> <tr><td>4.5</td><td>87.3</td><td>86.9</td><td>83.4</td></tr> <tr><td>6.0</td><td>86.6</td><td>86.8</td><td>84.3</td></tr> <tr><td>7.5</td><td>85.3</td><td>85.9</td><td>84.4</td></tr> <tr><td>8.0</td><td>84.5</td><td>85.6</td><td>84.3</td></tr> <tr><td>8.4</td><td>84.0</td><td>85.2</td><td>84.0</td></tr> </tbody> </table>		Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	1.5	81.4	78.6	70.1	3.0	86.5	85.3	80.1	4.5	87.3	86.9	83.4	6.0	86.6	86.8	84.3	7.5	85.3	85.9	84.4	8.0	84.5	85.6	84.3	8.4	84.0	85.2	84.0																			
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																	
1.5	81.4	78.6	70.1																																																	
3.0	86.5	85.3	80.1																																																	
4.5	87.3	86.9	83.4																																																	
6.0	86.6	86.8	84.3																																																	
7.5	85.3	85.9	84.4																																																	
8.0	84.5	85.6	84.3																																																	
8.4	84.0	85.2	84.0																																																	
2.Values																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.5</td><td>81.4</td><td>78.6</td><td>70.1</td></tr> <tr><td>3.0</td><td>86.5</td><td>85.3</td><td>80.1</td></tr> <tr><td>4.5</td><td>87.3</td><td>86.9</td><td>83.4</td></tr> <tr><td>6.0</td><td>86.6</td><td>86.8</td><td>84.3</td></tr> <tr><td>7.5</td><td>85.3</td><td>85.9</td><td>84.4</td></tr> <tr><td>8.0</td><td>84.5</td><td>85.6</td><td>84.3</td></tr> <tr><td>8.4</td><td>84.0</td><td>85.2</td><td>84.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	1.5	81.4	78.6	70.1	3.0	86.5	85.3	80.1	4.5	87.3	86.9	83.4	6.0	86.6	86.8	84.3	7.5	85.3	85.9	84.4	8.0	84.5	85.6	84.3	8.4	84.0	85.2	84.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																	
0.0	-	-	-																																																	
1.5	81.4	78.6	70.1																																																	
3.0	86.5	85.3	80.1																																																	
4.5	87.3	86.9	83.4																																																	
6.0	86.6	86.8	84.3																																																	
7.5	85.3	85.9	84.4																																																	
8.0	84.5	85.6	84.3																																																	
8.4	84.0	85.2	84.0																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
<p>Note: Slanted line shows the range of the rated load current.</p>																																																				


**COSSEL**

Model SFS20481R8

Item Line Regulation

Object +1.8V8A

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A


## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	1.817	1.804
36	1.821	1.808
40	1.825	1.810
48	1.828	1.809
55	1.829	1.807
60	1.829	1.804
70	1.830	1.800
76	1.830	1.798
78	1.831	1.798

Model SFS20481R8

Item Load Regulation


Object +1.8V8A

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	1.835	1.848	1.857
1.5	1.828	1.841	1.846
3.0	1.823	1.833	1.838
4.5	1.820	1.826	1.826
6.0	1.815	1.819	1.814
7.5	1.810	1.812	1.803
8.0	1.808	1.810	1.799
8.4	1.806	1.808	1.796
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**


**COSEL**

Model SFS20481R8

Item Ripple Voltage (by Load Current)

Object +1.8V8A

## 1. Graph

Temperature 25°C  
Testing Circuitry Figure C

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	2	2
1.6	2	2
3.2	2	2
4.8	2	2
6.4	2	2
8.0	2	2
8.8	2	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100MHz Ossiloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

**COSEL**


Model SFS20481R8

Item Ripple-Noise

Object +1.8V8A

## 1. Graph

—△— Input Volt. 36V  
 -○--- Input Volt. 76V



Measured by 100MHz Ossiloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure C

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	4	6
1.6	4	5
3.2	5	6
4.8	5	6
6.4	6	8
8.0	6	8
8.8	7	9
--	-	-
--	-	-
--	-	-
--	-	-




Fig.Complex Ripple Noise Wave Form


**COSEL**

Model SFS20481R8

Item Ripple Voltage (by Ambient Temp.)

Object +1.8V8A

## 1. Graph



Measured by 100MHz Ossiloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

## 2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	2	3
-40	2	3
-20	2	2
0	2	2
25	2	2
85	2	2
90	2	2
--	--	--
--	--	--
--	--	--
--	--	--

**COSEL**

Model SFS20481R8

Item Ambient Temperature Drift

Object +1.8V8A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-45	1.818	1.817	1.793
-40	1.818	1.817	1.794
-20	1.815	1.816	1.796
0	1.814	1.815	1.798
25	1.808	1.810	1.799
50	1.803	1.806	1.797
85	1.791	1.794	1.784
90	1.789	1.792	1.782
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SFS20481R8
Item	Output Voltage Accuracy
Object	+1.8V8A

Testing Circuitry Figure A

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 36 - 76V

Load Current : 0 - 8A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	85	76	0	1.870	$\pm 43$	$\pm 2.4$
Minimum Voltage	85	76	8	1.784		

**COSEL**

Model	SFS20481R8
Item	Time Lapse Drift
Object	+1.8V8A

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



Input Volt. 48V  
 Load 100%


## 2. Values

Time since start [H]	Output Voltage [V]
0.0	1.810
0.5	1.808
1.0	1.808
2.0	1.808
3.0	1.808
4.0	1.808
5.0	1.808
6.0	1.808
7.0	1.808
8.0	1.808

**COSEL**


Model	SFS20481R8	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+1.8V8A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		57.8	0.1	57.9	0.3	2.0	
100 %		57.8	0.1	57.9	0.3	0.8	



Model	SFS20481R8
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+1.8V8A

## Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.


## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-45	32.0	31.9
-40	32.0	31.9
-20	32.1	32.1
0	32.0	32.1
25	32.2	32.3
50	32.2	32.3
85	32.4	32.4
90	32.4	32.4
--	-	-
--	-	-
--	-	-

Model	SFS20481R8
Item	Overcurrent Protection
Object	+1.8V8A

## 1.Graph

————— Input Volt. 36V  
 ————— Input Volt. 48V  
 ————— Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

When the output voltage fell to less than 1.62V, the unit shuts off the output by operating low voltage protection.

Temperature 25°C  
Testing Circuitry Figure A


## 2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
1.80	8.10	8.11	8.05
1.71	8.86	9.02	9.43
1.62	8.85	9.02	9.45
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Model	SFS20481R8
Item	Overvoltage Protection
Object	+1.8V8A

1.Graph

—△— Input Volt. 48V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 48[V]	Input Volt.	Input Volt.
-40	2.49	-	-
25	2.47	-	-
85	2.44	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




Figure A




Figure B (General Electric Characteristic)




Figure C (Ripple and Ripple noise Characteristic)