

TEST DATA OF SNDBS400B24

Regulated DC Power Supply
July 3, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

Model	SNDBS400B24																																																																																	
Item	Input Current (by Input Voltage)																																																																																	
Object																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Load 100% (solid line with triangles) Load 50% (dashed line with squares) Load 0% (dash-dot line with circles) <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>150</td><td>0.004</td><td>0.004</td><td>0.004</td></tr> <tr><td>165</td><td>0.019</td><td>1.389</td><td>2.846</td></tr> <tr><td>170</td><td>0.019</td><td>1.345</td><td>2.765</td></tr> <tr><td>180</td><td>0.019</td><td>1.268</td><td>2.598</td></tr> <tr><td>200</td><td>0.019</td><td>1.144</td><td>2.334</td></tr> <tr><td>250</td><td>0.019</td><td>0.923</td><td>1.868</td></tr> <tr><td>280</td><td>0.020</td><td>0.829</td><td>1.670</td></tr> <tr><td>300</td><td>0.020</td><td>0.777</td><td>1.562</td></tr> <tr><td>350</td><td>0.020</td><td>0.675</td><td>1.350</td></tr> <tr><td>400</td><td>0.021</td><td>0.599</td><td>1.191</td></tr> <tr><td>420</td><td>0.021</td><td>0.574</td><td>1.139</td></tr> <tr><td>425</td><td>0.021</td><td>0.568</td><td>1.127</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.003	0.003	0.003	150	0.004	0.004	0.004	165	0.019	1.389	2.846	170	0.019	1.345	2.765	180	0.019	1.268	2.598	200	0.019	1.144	2.334	250	0.019	0.923	1.868	280	0.020	0.829	1.670	300	0.020	0.777	1.562	350	0.020	0.675	1.350	400	0.021	0.599	1.191	420	0.021	0.574	1.139	425	0.021	0.568	1.127	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.003	0.003	0.003																																																																															
150	0.004	0.004	0.004																																																																															
165	0.019	1.389	2.846																																																																															
170	0.019	1.345	2.765																																																																															
180	0.019	1.268	2.598																																																																															
200	0.019	1.144	2.334																																																																															
250	0.019	0.923	1.868																																																																															
280	0.020	0.829	1.670																																																																															
300	0.020	0.777	1.562																																																																															
350	0.020	0.675	1.350																																																																															
400	0.021	0.599	1.191																																																																															
420	0.021	0.574	1.139																																																																															
425	0.021	0.568	1.127																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	SNDBS400B24
Item	Input Current (by Load Current)
Object	



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	0.019	0.020	0.021
3.0	0.422	0.312	0.231
6.0	0.813	0.593	0.432
9.0	1.213	0.877	0.633
12.0	1.622	1.169	0.838
15.0	2.048	1.467	1.048
17.0	2.334	1.670	1.191
18.7	2.594	1.852	1.313
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	SNDBS400B24																																																					
Item	Input Power (by Load Current)																																																					
Object																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (280V)</th> <th>Input Power [W] (400V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>4.7</td><td>6.5</td><td>9.7</td></tr> <tr><td>3.0</td><td>84.3</td><td>87.3</td><td>92.6</td></tr> <tr><td>6.0</td><td>162.5</td><td>166.0</td><td>172.8</td></tr> <tr><td>9.0</td><td>242.4</td><td>245.5</td><td>253.2</td></tr> <tr><td>12.0</td><td>324.2</td><td>327.1</td><td>335.3</td></tr> <tr><td>15.0</td><td>409.0</td><td>410.9</td><td>420.0</td></tr> <tr><td>17.0</td><td>467.0</td><td>467.8</td><td>477.0</td></tr> <tr><td>18.7</td><td>518.0</td><td>518.0</td><td>526.0</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)	0.0	4.7	6.5	9.7	3.0	84.3	87.3	92.6	6.0	162.5	166.0	172.8	9.0	242.4	245.5	253.2	12.0	324.2	327.1	335.3	15.0	409.0	410.9	420.0	17.0	467.0	467.8	477.0	18.7	518.0	518.0	526.0															
Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)																																																			
0.0	4.7	6.5	9.7																																																			
3.0	84.3	87.3	92.6																																																			
6.0	162.5	166.0	172.8																																																			
9.0	242.4	245.5	253.2																																																			
12.0	324.2	327.1	335.3																																																			
15.0	409.0	410.9	420.0																																																			
17.0	467.0	467.8	477.0																																																			
18.7	518.0	518.0	526.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>4.7</td><td>6.5</td><td>9.7</td></tr> <tr><td>3.0</td><td>84.3</td><td>87.3</td><td>92.6</td></tr> <tr><td>6.0</td><td>162.5</td><td>166.0</td><td>172.8</td></tr> <tr><td>9.0</td><td>242.4</td><td>245.5</td><td>253.2</td></tr> <tr><td>12.0</td><td>324.2</td><td>327.1</td><td>335.3</td></tr> <tr><td>15.0</td><td>409.0</td><td>410.9</td><td>420.0</td></tr> <tr><td>17.0</td><td>467.0</td><td>467.8</td><td>477.0</td></tr> <tr><td>18.7</td><td>518.0</td><td>518.0</td><td>526.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	4.7	6.5	9.7	3.0	84.3	87.3	92.6	6.0	162.5	166.0	172.8	9.0	242.4	245.5	253.2	12.0	324.2	327.1	335.3	15.0	409.0	410.9	420.0	17.0	467.0	467.8	477.0	18.7	518.0	518.0	526.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	4.7	6.5	9.7																																																			
3.0	84.3	87.3	92.6																																																			
6.0	162.5	166.0	172.8																																																			
9.0	242.4	245.5	253.2																																																			
12.0	324.2	327.1	335.3																																																			
15.0	409.0	410.9	420.0																																																			
17.0	467.0	467.8	477.0																																																			
18.7	518.0	518.0	526.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNDBS400B24
Item	Efficiency (by Input Voltage)
Object	

1.Graph



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
170	89.7	87.1
180	89.9	87.2
200	89.7	87.4
240	89.1	87.4
280	88.4	87.3
320	87.6	86.9
360	86.6	86.5
400	85.7	85.8
420	85.1	85.5

COSEL

Model	SNDBS400B24
Item	Efficiency (by Load Current)
Object	


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	-	-	-
3.0	86.4	83.4	78.7
6.0	89.3	87.4	84.0
9.0	89.6	87.4	85.9
12.0	89.3	87.3	86.4
15.0	88.4	86.9	86.1
17.0	87.4	87.3	85.8
18.7	86.9	86.9	85.6
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


COSEL

Model	SNDBS400B24
-------	-------------

Item	Line Regulation
------	-----------------

Object	+24V17A
--------	---------

1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature	25°C
Testing Circuitry	Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
170	24.140	24.107
180	24.141	24.108
200	24.142	24.108
240	24.143	24.108
280	24.143	24.110
320	24.144	24.111
360	24.143	24.111
400	24.144	24.113
420	24.144	24.114

COSSEL

Model	SNDBS400B24																																																					
Item	Load Regulation	Temperature Testing Circuitry	25°C Figure A																																																			
Object	+24V17A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 200V Input Volt. 280V Input Volt. 400V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>24.155</td> <td>24.157</td> <td>24.158</td> </tr> <tr> <td>3.0</td> <td>24.153</td> <td>24.155</td> <td>24.153</td> </tr> <tr> <td>6.0</td> <td>24.146</td> <td>24.150</td> <td>24.150</td> </tr> <tr> <td>9.0</td> <td>24.138</td> <td>24.142</td> <td>24.145</td> </tr> <tr> <td>12.0</td> <td>24.127</td> <td>24.132</td> <td>24.136</td> </tr> <tr> <td>15.0</td> <td>24.113</td> <td>24.117</td> <td>24.124</td> </tr> <tr> <td>17.0</td> <td>24.108</td> <td>24.110</td> <td>24.113</td> </tr> <tr> <td>18.7</td> <td>24.100</td> <td>24.103</td> <td>24.109</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	24.155	24.157	24.158	3.0	24.153	24.155	24.153	6.0	24.146	24.150	24.150	9.0	24.138	24.142	24.145	12.0	24.127	24.132	24.136	15.0	24.113	24.117	24.124	17.0	24.108	24.110	24.113	18.7	24.100	24.103	24.109	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	24.155	24.157	24.158																																																			
3.0	24.153	24.155	24.153																																																			
6.0	24.146	24.150	24.150																																																			
9.0	24.138	24.142	24.145																																																			
12.0	24.127	24.132	24.136																																																			
15.0	24.113	24.117	24.124																																																			
17.0	24.108	24.110	24.113																																																			
18.7	24.100	24.103	24.109																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNDBS400B24	Temperature Testing Circuitry 25°C Figure A
Item	Dynamic Load Response	
Object	+24V17A	

Input Volt. 280 V
 Cycle 1000 ms



Min. Load (0A) ↔
 Load 100% (17A)

500 mV/div

5 ms/div

5 ms/div

Min. Load (0A) ↔
 Load 50% (8.5A)

500 mV/div

5 ms/div

5 ms/div

Load 10% (1.7A) ↔
 Load 100% (17A)

500 mV/div

5 ms/div


5 ms/div

COSEL

Model	SNDBS400B24
Item	Ripple Voltage (by Load Current)
Object	+24V17A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	4	4
3.0	14	18
6.0	14	18
9.0	14	20
12.0	15	20
15.0	15	20
17.0	15	20
18.7	15	23
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model SNDBS400B24

 Temperature 25°C
 Testing Circuitry Figure B

Item Ripple-Noise

Object +24V17A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	8	13
3.0	20	26
6.0	20	28
9.0	22	30
12.0	23	30
15.0	24	30
17.0	25	30
18.7	25	33
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SNDBS400B24
Item	Ripple Voltage (by Ambient Temp.)
Object	+24V17A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	34	34
-20	26	28
0	22	26
15	19	23
25	17	21
40	18	21
55	18	21
70	20	22
80	22	23
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form



Model	SNDBS400B24
Item	Ambient Temperature Drift
Object	+24V17A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-40	24.019	24.019	24.023
-20	24.051	24.051	24.055
0	24.083	24.082	24.085
15	24.099	24.100	24.105
25	24.108	24.110	24.113
40	24.120	24.122	24.124
55	24.129	24.132	24.133
70	24.117	24.118	24.116
80	24.110	24.107	24.101
90	24.085	24.080	24.075
--	-	-	-



Model	SNDBS400B24	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+24V17A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 80°C

Input Voltage : 200 - 400V

Load Current : 0 - 17A


* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	400	0	24.217	±59	±0.2
Minimum Voltage	-20	280	17	24.099		


COSEL

Model	SNDBS400B24	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+24V17A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 280V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.112</td></tr> <tr><td>0.5</td><td>24.122</td></tr> <tr><td>1.0</td><td>24.122</td></tr> <tr><td>2.0</td><td>24.123</td></tr> <tr><td>3.0</td><td>24.123</td></tr> <tr><td>4.0</td><td>24.122</td></tr> <tr><td>5.0</td><td>24.122</td></tr> <tr><td>6.0</td><td>24.122</td></tr> <tr><td>7.0</td><td>24.122</td></tr> <tr><td>8.0</td><td>24.122</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.112	0.5	24.122	1.0	24.122	2.0	24.123	3.0	24.123	4.0	24.122	5.0	24.122	6.0	24.122	7.0	24.122	8.0	24.122
Time since start [H]	Output Voltage [V]																								
0.0	24.112																								
0.5	24.122																								
1.0	24.122																								
2.0	24.123																								
3.0	24.123																								
4.0	24.122																								
5.0	24.122																								
6.0	24.122																								
7.0	24.122																								
8.0	24.122																								

COSEL


Model	SNDBS400B24	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+24V17A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		14.0	28.3	42.3	0.9	11.2	
100 %		14.0	28.5	42.5	0.5	5.6	






Model	SNDBS400B24
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V17A

Testing Circuitry Figure A

1.Graph




Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	135	141
-20	135	141
0	136	142
15	136	143
25	135	143
40	135	144
55	135	145
70	135	145
80	134	146
90	135	146
--	-	-

COSEL

Model	SNDBS400B24
Item	Overcurrent Protection
Object	+24V17A



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 17V to 0V.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
22.8	19.29	19.83	21.09
21.6	19.34	19.87	21.15
19.2	19.46	19.93	21.30
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	SNDBS400B24
Item	Overvoltage Protection
Object	+24V17A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 200[V]	Input Volt. 400[V]
-40	29.46	29.46
-20	29.87	29.87
0	30.24	30.24
15	30.47	30.47
25	30.65	30.65
40	30.94	30.94
55	31.21	31.21
70	31.47	31.47
80	31.64	31.64
90	31.87	31.88
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)