

TEST DATA OF SNDHS100B12

Regulated DC Power Supply
June 30, 2011

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	SNDHS100B12	Temperature Testing Circuitry	25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																	
Object	—																																																																																	
1.Graph	<p>—△— Load 100% - -□--- Load 50% - -○--- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>200</td><td>0.000</td><td>0.300</td><td>0.600</td></tr> <tr><td>300</td><td>0.000</td><td>0.200</td><td>0.400</td></tr> <tr><td>400</td><td>0.000</td><td>0.150</td><td>0.300</td></tr> <tr><td>500</td><td>0.000</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	100	0.000	0.000	0.000	200	0.000	0.300	0.600	300	0.000	0.200	0.400	400	0.000	0.150	0.300	500	0.000	-	-																																																			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
0	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
200	0.000	0.300	0.600																																																																															
300	0.000	0.200	0.400																																																																															
400	0.000	0.150	0.300																																																																															
500	0.000	-	-																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>180</td><td>0.036</td><td>0.342</td><td>0.647</td></tr> <tr><td>200</td><td>0.035</td><td>0.306</td><td>0.591</td></tr> <tr><td>250</td><td>0.027</td><td>0.246</td><td>0.471</td></tr> <tr><td>280</td><td>0.013</td><td>0.221</td><td>0.422</td></tr> <tr><td>300</td><td>0.013</td><td>0.208</td><td>0.395</td></tr> <tr><td>350</td><td>0.013</td><td>0.182</td><td>0.342</td></tr> <tr><td>400</td><td>0.013</td><td>0.163</td><td>0.303</td></tr> <tr><td>420</td><td>0.013</td><td>0.156</td><td>0.290</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.002	0.002	0.002	170	0.003	0.003	0.003	180	0.036	0.342	0.647	200	0.035	0.306	0.591	250	0.027	0.246	0.471	280	0.013	0.221	0.422	300	0.013	0.208	0.395	350	0.013	0.182	0.342	400	0.013	0.163	0.303	420	0.013	0.156	0.290	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.002	0.002	0.002																																																																															
170	0.003	0.003	0.003																																																																															
180	0.036	0.342	0.647																																																																															
200	0.035	0.306	0.591																																																																															
250	0.027	0.246	0.471																																																																															
280	0.013	0.221	0.422																																																																															
300	0.013	0.208	0.395																																																																															
350	0.013	0.182	0.342																																																																															
400	0.013	0.163	0.303																																																																															
420	0.013	0.156	0.290																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
Note: Slanted line shows the range of the rated input voltage.																																																																																		

COSEL

Model	SNDHS100B12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object																																																						
1. Graph		2. Values																																																				
<p>—△— Input Volt. 200V - -□--- Input Volt. 280V - -○--- Input Volt. 400V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.036</td><td>0.013</td><td>0.013</td></tr> <tr><td>1.50</td><td>0.136</td><td>0.099</td><td>0.077</td></tr> <tr><td>3.00</td><td>0.232</td><td>0.168</td><td>0.125</td></tr> <tr><td>4.50</td><td>0.330</td><td>0.238</td><td>0.174</td></tr> <tr><td>6.00</td><td>0.430</td><td>0.308</td><td>0.223</td></tr> <tr><td>7.50</td><td>0.532</td><td>0.381</td><td>0.274</td></tr> <tr><td>8.40</td><td>0.594</td><td>0.425</td><td>0.304</td></tr> <tr><td>9.24</td><td>0.653</td><td>0.466</td><td>0.333</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.036	0.013	0.013	1.50	0.136	0.099	0.077	3.00	0.232	0.168	0.125	4.50	0.330	0.238	0.174	6.00	0.430	0.308	0.223	7.50	0.532	0.381	0.274	8.40	0.594	0.425	0.304	9.24	0.653	0.466	0.333	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.00	0.036	0.013	0.013																																																			
1.50	0.136	0.099	0.077																																																			
3.00	0.232	0.168	0.125																																																			
4.50	0.330	0.238	0.174																																																			
6.00	0.430	0.308	0.223																																																			
7.50	0.532	0.381	0.274																																																			
8.40	0.594	0.425	0.304																																																			
9.24	0.653	0.466	0.333																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL


Model	SNDHS100B12	Temperature 25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry Figure A																																																			
Object																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (280V)</th> <th>Input Power [W] (400V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>1.50</td><td>27.2</td><td>27.8</td><td>30.7</td></tr> <tr><td>3.00</td><td>46.4</td><td>47.0</td><td>50.0</td></tr> <tr><td>4.50</td><td>65.9</td><td>66.6</td><td>69.6</td></tr> <tr><td>6.00</td><td>85.9</td><td>86.4</td><td>89.5</td></tr> <tr><td>7.50</td><td>106.4</td><td>106.6</td><td>109.6</td></tr> <tr><td>8.40</td><td>118.8</td><td>118.9</td><td>121.9</td></tr> <tr><td>9.24</td><td>130.6</td><td>130.7</td><td>133.4</td></tr> </tbody> </table>		Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)	0.00	0	0	0	1.50	27.2	27.8	30.7	3.00	46.4	47.0	50.0	4.50	65.9	66.6	69.6	6.00	85.9	86.4	89.5	7.50	106.4	106.6	109.6	8.40	118.8	118.9	121.9	9.24	130.6	130.7	133.4															
Load Current [A]	Input Power [W] (200V)	Input Power [W] (280V)	Input Power [W] (400V)																																																		
0.00	0	0	0																																																		
1.50	27.2	27.8	30.7																																																		
3.00	46.4	47.0	50.0																																																		
4.50	65.9	66.6	69.6																																																		
6.00	85.9	86.4	89.5																																																		
7.50	106.4	106.6	109.6																																																		
8.40	118.8	118.9	121.9																																																		
9.24	130.6	130.7	133.4																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>7.1</td><td>3.5</td><td>5.1</td></tr> <tr><td>1.50</td><td>27.2</td><td>27.8</td><td>30.7</td></tr> <tr><td>3.00</td><td>46.4</td><td>47.0</td><td>50.0</td></tr> <tr><td>4.50</td><td>65.9</td><td>66.6</td><td>69.6</td></tr> <tr><td>6.00</td><td>85.9</td><td>86.4</td><td>89.5</td></tr> <tr><td>7.50</td><td>106.4</td><td>106.6</td><td>109.6</td></tr> <tr><td>8.40</td><td>118.8</td><td>118.9</td><td>121.9</td></tr> <tr><td>9.24</td><td>130.6</td><td>130.7</td><td>133.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	7.1	3.5	5.1	1.50	27.2	27.8	30.7	3.00	46.4	47.0	50.0	4.50	65.9	66.6	69.6	6.00	85.9	86.4	89.5	7.50	106.4	106.6	109.6	8.40	118.8	118.9	121.9	9.24	130.6	130.7	133.4	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																		
0.00	7.1	3.5	5.1																																																		
1.50	27.2	27.8	30.7																																																		
3.00	46.4	47.0	50.0																																																		
4.50	65.9	66.6	69.6																																																		
6.00	85.9	86.4	89.5																																																		
7.50	106.4	106.6	109.6																																																		
8.40	118.8	118.9	121.9																																																		
9.24	130.6	130.7	133.4																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNDHS100B12
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
195	83.8	86.8
200	83.9	86.9
240	83.7	87.0
280	82.9	86.7
320	81.8	86.1
360	80.4	85.4
400	79.1	84.6
420	78.3	84.0
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNDHS100B12	Temperature Testing Circuitry	25°C Figure A																																																				
Item	Efficiency (by Load Current)																																																						
Object	—																																																						
1.Graph	<p>—△— Input Volt. 200V - -□--- Input Volt. 280V - -○--- Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [280V] (%)</th> <th>Efficiency [400V] (%)</th> </tr> </thead> <tbody> <tr><td>1.50</td><td>69.5</td><td>68.1</td><td>61.6</td></tr> <tr><td>3.00</td><td>80.3</td><td>79.2</td><td>74.5</td></tr> <tr><td>4.50</td><td>84.3</td><td>83.4</td><td>79.8</td></tr> <tr><td>6.00</td><td>86.0</td><td>85.5</td><td>82.6</td></tr> <tr><td>7.50</td><td>86.6</td><td>86.5</td><td>84.1</td></tr> <tr><td>8.40</td><td>86.8</td><td>86.7</td><td>84.6</td></tr> <tr><td>9.24</td><td>86.8</td><td>86.7</td><td>85.0</td></tr> </tbody> </table>				Load Current [A]	Efficiency [200V] (%)	Efficiency [280V] (%)	Efficiency [400V] (%)	1.50	69.5	68.1	61.6	3.00	80.3	79.2	74.5	4.50	84.3	83.4	79.8	6.00	86.0	85.5	82.6	7.50	86.6	86.5	84.1	8.40	86.8	86.7	84.6	9.24	86.8	86.7	85.0																			
Load Current [A]	Efficiency [200V] (%)	Efficiency [280V] (%)	Efficiency [400V] (%)																																																				
1.50	69.5	68.1	61.6																																																				
3.00	80.3	79.2	74.5																																																				
4.50	84.3	83.4	79.8																																																				
6.00	86.0	85.5	82.6																																																				
7.50	86.6	86.5	84.1																																																				
8.40	86.8	86.7	84.6																																																				
9.24	86.8	86.7	85.0																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>69.5</td><td>68.1</td><td>61.6</td></tr> <tr><td>3.00</td><td>80.3</td><td>79.2</td><td>74.5</td></tr> <tr><td>4.50</td><td>84.3</td><td>83.4</td><td>79.8</td></tr> <tr><td>6.00</td><td>86.0</td><td>85.5</td><td>82.6</td></tr> <tr><td>7.50</td><td>86.6</td><td>86.5</td><td>84.1</td></tr> <tr><td>8.40</td><td>86.8</td><td>86.7</td><td>84.6</td></tr> <tr><td>9.24</td><td>86.8</td><td>86.7</td><td>85.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	-	-	-	1.50	69.5	68.1	61.6	3.00	80.3	79.2	74.5	4.50	84.3	83.4	79.8	6.00	86.0	85.5	82.6	7.50	86.6	86.5	84.1	8.40	86.8	86.7	84.6	9.24	86.8	86.7	85.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
0.00	-	-	-																																																				
1.50	69.5	68.1	61.6																																																				
3.00	80.3	79.2	74.5																																																				
4.50	84.3	83.4	79.8																																																				
6.00	86.0	85.5	82.6																																																				
7.50	86.6	86.5	84.1																																																				
8.40	86.8	86.7	84.6																																																				
9.24	86.8	86.7	85.0																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						


COSEL

Model	SNDHS100B12
Item	Line Regulation
Object	+12V8.4A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph

---□--- Load 50%
 —△— Load 100%




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
195	12.244	12.226
200	12.244	12.227
240	12.244	12.227
280	12.245	12.228
320	12.246	12.229
360	12.247	12.230
400	12.248	12.231
420	12.248	12.232
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNDHS100B12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V8.4A																																																					
1.Graph	<p>—△— Input Volt. 200V - -□--- Input Volt. 280V - -○--- Input Volt. 400V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (200V)</th> <th>Output Voltage [V] (280V)</th> <th>Output Voltage [V] (400V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.255</td><td>12.256</td><td>12.259</td></tr> <tr><td>1.50</td><td>12.246</td><td>12.248</td><td>12.252</td></tr> <tr><td>3.00</td><td>12.242</td><td>12.244</td><td>12.247</td></tr> <tr><td>4.50</td><td>12.237</td><td>12.239</td><td>12.242</td></tr> <tr><td>6.00</td><td>12.232</td><td>12.235</td><td>12.238</td></tr> <tr><td>7.50</td><td>12.227</td><td>12.230</td><td>12.233</td></tr> <tr><td>8.40</td><td>12.225</td><td>12.228</td><td>12.231</td></tr> <tr><td>9.24</td><td>12.222</td><td>12.225</td><td>12.228</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (200V)	Output Voltage [V] (280V)	Output Voltage [V] (400V)	0.00	12.255	12.256	12.259	1.50	12.246	12.248	12.252	3.00	12.242	12.244	12.247	4.50	12.237	12.239	12.242	6.00	12.232	12.235	12.238	7.50	12.227	12.230	12.233	8.40	12.225	12.228	12.231	9.24	12.222	12.225	12.228															
Load Current [A]	Output Voltage [V] (200V)	Output Voltage [V] (280V)	Output Voltage [V] (400V)																																																			
0.00	12.255	12.256	12.259																																																			
1.50	12.246	12.248	12.252																																																			
3.00	12.242	12.244	12.247																																																			
4.50	12.237	12.239	12.242																																																			
6.00	12.232	12.235	12.238																																																			
7.50	12.227	12.230	12.233																																																			
8.40	12.225	12.228	12.231																																																			
9.24	12.222	12.225	12.228																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.255</td><td>12.256</td><td>12.259</td></tr> <tr><td>1.50</td><td>12.246</td><td>12.248</td><td>12.252</td></tr> <tr><td>3.00</td><td>12.242</td><td>12.244</td><td>12.247</td></tr> <tr><td>4.50</td><td>12.237</td><td>12.239</td><td>12.242</td></tr> <tr><td>6.00</td><td>12.232</td><td>12.235</td><td>12.238</td></tr> <tr><td>7.50</td><td>12.227</td><td>12.230</td><td>12.233</td></tr> <tr><td>8.40</td><td>12.225</td><td>12.228</td><td>12.231</td></tr> <tr><td>9.24</td><td>12.222</td><td>12.225</td><td>12.228</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	12.255	12.256	12.259	1.50	12.246	12.248	12.252	3.00	12.242	12.244	12.247	4.50	12.237	12.239	12.242	6.00	12.232	12.235	12.238	7.50	12.227	12.230	12.233	8.40	12.225	12.228	12.231	9.24	12.222	12.225	12.228	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.00	12.255	12.256	12.259																																																			
1.50	12.246	12.248	12.252																																																			
3.00	12.242	12.244	12.247																																																			
4.50	12.237	12.239	12.242																																																			
6.00	12.232	12.235	12.238																																																			
7.50	12.227	12.230	12.233																																																			
8.40	12.225	12.228	12.231																																																			
9.24	12.222	12.225	12.228																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

COSEL

Model	SNDHS100B12
Item	Ripple Voltage (by Load Current)
Object	+12V8.4A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.00	5	5
1.50	30	40
3.00	25	40
4.50	30	40
6.00	25	40
7.50	25	40
8.40	30	40
9.24	30	40
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form


COSEL

Model SNDHS100B12

Item Ripple-Noise

Object +12V8.4A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.00	20	30
1.50	30	45
3.00	35	50
4.50	35	55
6.00	40	55
7.50	35	55
8.40	35	55
9.24	35	60
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SNDHS100B12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V8.4A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	45	50
-20	45	45
0	35	35
25	35	35
40	30	30
55	30	35
70	30	35
85	35	35
95	35	35
--	-	-
--	-	-

COSEL


Model SNDHS100B12

Item Ambient Temperature Drift

Object +12V8.4A

1. Graph

—△— Input Volt. 200V
 - - □ - - Input Volt. 280V
 - - ○ - - Input Volt. 400V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-40	12.166	12.174	12.186
-20	12.188	12.195	12.204
0	12.208	12.213	12.219
25	12.226	12.228	12.232
40	12.233	12.234	12.237
55	12.236	12.238	12.238
70	12.238	12.238	12.238
85	12.235	12.235	12.234
95	12.231	12.230	12.230
--	-	-	-
--	-	-	-



Model	SNDHS100B12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V8.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 8.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	200	0	12.285	± 49	± 0.4
Minimum Voltage	-20	200	8.4	12.188		

COSEL

Model	SNDHS100B12	Temperature Testing Circuitry 25°C Figure A
Item	Time Lapse Drift	
Object	+12V8.4A	

1. Graph

Time since start [H]	Output Voltage [V]
0.0	12.227
0.5	12.227
1.0	12.227
2.0	12.227
3.0	12.227
4.0	12.227
5.0	12.227
6.0	12.227
7.0	12.227
8.0	12.227

Input Volt. 280V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	12.227
0.5	12.227
1.0	12.227
2.0	12.227
3.0	12.227
4.0	12.227
5.0	12.227
6.0	12.227
7.0	12.227
8.0	12.227

COSEL

Model SNDHS100B12


Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A

Object +12V8.4A

1. Graph


Input Volt. 280 V



2. Values

[ms]


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	20.8	4.3	25.1	1.8	14.9
100 %	20.8	5.0	25.8	0.9	7.7



Model	SNDHS100B12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V8.4A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	160	166
-20	161	167
0	163	169
25	165	173
40	166	172
55	166	173
70	165	172
85	164	172
95	162	170
--	-	-
--	-	-

COSEL

Model	SNDHS100B12
Item	Overcurrent Protection
Object	+12V8.4A

1.Graph

Input Volt.	200V
Input Volt.	280V
Input Volt.	400V

Output Voltage [V]

Load Current [A]

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
8.4	10.27	10.49	10.78
7.2	10.40	10.62	11.08
6.0	10.53	10.72	10.93
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Intermittent operation occurs when the output voltage is from 6V to 0V.

Model	SNDHS100B12
Item	Overvoltage Protection
Object	+12V8.4A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 200[V]	Input Volt. 400[V]
-40	15.04	15.04
-20	15.04	15.04
0	15.16	15.16
25	15.16	15.16
40	15.15	15.16
55	15.15	15.15
70	15.27	15.27
85	15.27	15.27
95	15.32	15.27
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)