

TEST DATA OF SNDHS200A12

Regulated DC Power Supply
April 10, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer


COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

Model		SNDHS200A12		Temperature		25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry		Figure A																																																																																
Object		+12V16.7A																																																																																				
1.Graph				2.Values																																																																																		
<div><div><div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div></div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div></div><div>—△— Load 100%</div><div>---□--- Load 50%</div><div>-○- Load 0%</div></div> <div><p>Note: Slanted line shows the range of the rated input voltage.</p></div>				<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>40</td><td>0.008</td><td>0.008</td><td>0.008</td></tr><tr><td>50</td><td>0.005</td><td>0.005</td><td>0.005</td></tr><tr><td>55</td><td>0.004</td><td>0.004</td><td>0.004</td></tr><tr><td>56</td><td>0.029</td><td>2.064</td><td>4.234</td></tr><tr><td>60</td><td>0.028</td><td>1.912</td><td>3.924</td></tr><tr><td>66</td><td>0.024</td><td>1.730</td><td>3.543</td></tr><tr><td>80</td><td>0.019</td><td>1.431</td><td>2.917</td></tr><tr><td>95</td><td>0.018</td><td>1.208</td><td>2.446</td></tr><tr><td>110</td><td>0.017</td><td>1.049</td><td>2.114</td></tr><tr><td>125</td><td>0.015</td><td>0.928</td><td>1.861</td></tr><tr><td>140</td><td>0.013</td><td>0.833</td><td>1.662</td></tr><tr><td>160</td><td>0.012</td><td>0.736</td><td>1.461</td></tr><tr><td>170</td><td>0.011</td><td>0.716</td><td>1.409</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	40	0.008	0.008	0.008	50	0.005	0.005	0.005	55	0.004	0.004	0.004	56	0.029	2.064	4.234	60	0.028	1.912	3.924	66	0.024	1.730	3.543	80	0.019	1.431	2.917	95	0.018	1.208	2.446	110	0.017	1.049	2.114	125	0.015	0.928	1.861	140	0.013	0.833	1.662	160	0.012	0.736	1.461	170	0.011	0.716	1.409	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																					
	Load 0%	Load 50%	Load 100%																																																																																			
0	0.000	0.000	0.000																																																																																			
40	0.008	0.008	0.008																																																																																			
50	0.005	0.005	0.005																																																																																			
55	0.004	0.004	0.004																																																																																			
56	0.029	2.064	4.234																																																																																			
60	0.028	1.912	3.924																																																																																			
66	0.024	1.730	3.543																																																																																			
80	0.019	1.431	2.917																																																																																			
95	0.018	1.208	2.446																																																																																			
110	0.017	1.049	2.114																																																																																			
125	0.015	0.928	1.861																																																																																			
140	0.013	0.833	1.662																																																																																			
160	0.012	0.736	1.461																																																																																			
170	0.011	0.716	1.409																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			
--	-	-	-																																																																																			

Model		SNDHS200A12		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		+12V16.7A																																																						
1.Graph		<div><div>—△—</div>Input Volt. 60V</div> <div><div>---□---</div>Input Volt. 110V</div> <div><div>-·-○-·-</div>Input Volt. 160V</div>  <p>Note: Slanted line shows the range of the rated load current.</p>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>0.0</td><td>0.028</td><td>0.017</td><td>0.012</td></tr><tr><td>3.0</td><td>0.721</td><td>0.395</td><td>0.279</td></tr><tr><td>6.0</td><td>1.386</td><td>0.762</td><td>0.540</td></tr><tr><td>9.0</td><td>2.070</td><td>1.130</td><td>0.792</td></tr><tr><td>12.0</td><td>2.776</td><td>1.506</td><td>1.050</td></tr><tr><td>15.0</td><td>3.506</td><td>1.894</td><td>1.312</td></tr><tr><td>16.7</td><td>3.924</td><td>2.114</td><td>1.461</td></tr><tr><td>18.4</td><td>4.351</td><td>2.336</td><td>1.612</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	0.028	0.017	0.012	3.0	0.721	0.395	0.279	6.0	1.386	0.762	0.540	9.0	2.070	1.130	0.792	12.0	2.776	1.506	1.050	15.0	3.506	1.894	1.312	16.7	3.924	2.114	1.461	18.4	4.351	2.336	1.612	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	0.028	0.017	0.012																																																					
3.0	0.721	0.395	0.279																																																					
6.0	1.386	0.762	0.540																																																					
9.0	2.070	1.130	0.792																																																					
12.0	2.776	1.506	1.050																																																					
15.0	3.506	1.894	1.312																																																					
16.7	3.924	2.114	1.461																																																					
18.4	4.351	2.336	1.612																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

Model		SNDHS200A12		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		+12V16.7A																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt. 60V</div></div><div><div>---□---</div><div>Input Volt. 110V</div></div><div><div>-·-○-·-</div><div>Input Volt. 160V</div></div></div> <div><p>Input Power [W]</p><p>Load Current [A]</p></div> <div>Note: Slanted line shows the range of the rated load current.</div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>0.0</td><td>1.7</td><td>1.9</td><td>1.9</td></tr><tr><td>3.0</td><td>43.2</td><td>43.4</td><td>44.7</td></tr><tr><td>6.0</td><td>83.0</td><td>83.7</td><td>86.3</td></tr><tr><td>9.0</td><td>124.2</td><td>124.2</td><td>126.7</td></tr><tr><td>12.0</td><td>166.4</td><td>165.5</td><td>167.8</td></tr><tr><td>15.0</td><td>210.0</td><td>208.2</td><td>209.8</td></tr><tr><td>16.7</td><td>235.2</td><td>232.2</td><td>233.6</td></tr><tr><td>18.4</td><td>260.8</td><td>256.8</td><td>257.8</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Power [W]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	1.7	1.9	1.9	3.0	43.2	43.4	44.7	6.0	83.0	83.7	86.3	9.0	124.2	124.2	126.7	12.0	166.4	165.5	167.8	15.0	210.0	208.2	209.8	16.7	235.2	232.2	233.6	18.4	260.8	256.8	257.8	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	1.7	1.9	1.9																																																					
3.0	43.2	43.4	44.7																																																					
6.0	83.0	83.7	86.3																																																					
9.0	124.2	124.2	126.7																																																					
12.0	166.4	165.5	167.8																																																					
15.0	210.0	208.2	209.8																																																					
16.7	235.2	232.2	233.6																																																					
18.4	260.8	256.8	257.8																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					

Model		SNDHS200A12		Temperature 25°C																																		
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																		
Object		+12V16.7A																																				
1.Graph				2.Values																																		
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50% Efficiency [%]</th><th>Load 100% Efficiency [%]</th></tr></thead><tbody><tr><td>56</td><td>88.4</td><td>86.3</td></tr><tr><td>60</td><td>88.9</td><td>86.8</td></tr><tr><td>66</td><td>89.6</td><td>87.3</td></tr><tr><td>80</td><td>89.5</td><td>87.7</td></tr><tr><td>95</td><td>89.2</td><td>87.9</td></tr><tr><td>110</td><td>88.8</td><td>87.9</td></tr><tr><td>125</td><td>88.2</td><td>87.9</td></tr><tr><td>140</td><td>87.7</td><td>87.8</td></tr><tr><td>160</td><td>86.8</td><td>87.4</td></tr><tr><td>170</td><td>86.4</td><td>87.2</td></tr></tbody></table>				Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	56	88.4	86.3	60	88.9	86.8	66	89.6	87.3	80	89.5	87.7	95	89.2	87.9	110	88.8	87.9	125	88.2	87.9	140	87.7	87.8	160	86.8	87.4	170	86.4	87.2		
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																																				
56	88.4	86.3																																				
60	88.9	86.8																																				
66	89.6	87.3																																				
80	89.5	87.7																																				
95	89.2	87.9																																				
110	88.8	87.9																																				
125	88.2	87.9																																				
140	87.7	87.8																																				
160	86.8	87.4																																				
170	86.4	87.2																																				
Note: Slanted line shows the range of the rated input voltage.																																						

COSEL

Model		SNDHS200A12		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		+12V16.7A																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt. 60V</div></div><div><div>---□---</div><div>Input Volt. 110V</div></div><div><div>---○---</div><div>Input Volt. 160V</div></div></div> <div>Efficiency [%]</div> <div>Load Current [A]</div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>3.0</td><td>85.5</td><td>85.2</td><td>82.7</td></tr><tr><td>6.0</td><td>88.7</td><td>87.9</td><td>85.3</td></tr><tr><td>9.0</td><td>88.8</td><td>88.8</td><td>87.0</td></tr><tr><td>12.0</td><td>88.3</td><td>88.8</td><td>87.6</td></tr><tr><td>15.0</td><td>87.4</td><td>88.2</td><td>87.5</td></tr><tr><td>16.7</td><td>86.8</td><td>87.9</td><td>87.4</td></tr><tr><td>18.4</td><td>86.1</td><td>87.5</td><td>87.1</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Efficiency [%]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	-	-	-	3.0	85.5	85.2	82.7	6.0	88.7	87.9	85.3	9.0	88.8	88.8	87.0	12.0	88.3	88.8	87.6	15.0	87.4	88.2	87.5	16.7	86.8	87.9	87.4	18.4	86.1	87.5	87.1	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	-	-	-																																																					
3.0	85.5	85.2	82.7																																																					
6.0	88.7	87.9	85.3																																																					
9.0	88.8	88.8	87.0																																																					
12.0	88.3	88.8	87.6																																																					
15.0	87.4	88.2	87.5																																																					
16.7	86.8	87.9	87.4																																																					
18.4	86.1	87.5	87.1																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

-

5

-

BC-10645

Model	SNDHS200A12																																					
Item	Line Regulation	Temperature	25°C																																			
Object	+12V16.7A	Testing Circuitry	Figure A																																			
1.Graph		2.Values																																				
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>56</td><td>12.264</td><td>12.259</td></tr><tr><td>60</td><td>12.264</td><td>12.259</td></tr><tr><td>66</td><td>12.264</td><td>12.259</td></tr><tr><td>80</td><td>12.264</td><td>12.259</td></tr><tr><td>95</td><td>12.264</td><td>12.259</td></tr><tr><td>110</td><td>12.264</td><td>12.259</td></tr><tr><td>125</td><td>12.264</td><td>12.259</td></tr><tr><td>140</td><td>12.263</td><td>12.259</td></tr><tr><td>160</td><td>12.263</td><td>12.259</td></tr><tr><td>170</td><td>12.263</td><td>12.259</td></tr></table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	56	12.264	12.259	60	12.264	12.259	66	12.264	12.259	80	12.264	12.259	95	12.264	12.259	110	12.264	12.259	125	12.264	12.259	140	12.263	12.259	160	12.263	12.259	170	12.263	12.259
Input Voltage [V]	Output Voltage [V]																																					
	Load 50%	Load 100%																																				
56	12.264	12.259																																				
60	12.264	12.259																																				
66	12.264	12.259																																				
80	12.264	12.259																																				
95	12.264	12.259																																				
110	12.264	12.259																																				
125	12.264	12.259																																				
140	12.263	12.259																																				
160	12.263	12.259																																				
170	12.263	12.259																																				

COSEL

Model	SNDHS200A12																																																					
Item	Load Regulation	Temperature	25°C																																																			
Object	+12V16.7A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div>Input Volt. 60V</div><div>Input Volt. 110V</div><div>Input Volt. 160V</div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>0.0</td><td>12.270</td><td>12.271</td><td>12.271</td></tr><tr><td>3.0</td><td>12.268</td><td>12.269</td><td>12.270</td></tr><tr><td>6.0</td><td>12.267</td><td>12.268</td><td>12.268</td></tr><tr><td>9.0</td><td>12.266</td><td>12.267</td><td>12.267</td></tr><tr><td>12.0</td><td>12.265</td><td>12.266</td><td>12.266</td></tr><tr><td>15.0</td><td>12.264</td><td>12.265</td><td>12.266</td></tr><tr><td>16.7</td><td>12.264</td><td>12.264</td><td>12.265</td></tr><tr><td>18.4</td><td>12.264</td><td>12.264</td><td>12.265</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	12.270	12.271	12.271	3.0	12.268	12.269	12.270	6.0	12.267	12.268	12.268	9.0	12.266	12.267	12.267	12.0	12.265	12.266	12.266	15.0	12.264	12.265	12.266	16.7	12.264	12.264	12.265	18.4	12.264	12.264	12.265	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
0.0	12.270	12.271	12.271																																																			
3.0	12.268	12.269	12.270																																																			
6.0	12.267	12.268	12.268																																																			
9.0	12.266	12.267	12.267																																																			
12.0	12.265	12.266	12.266																																																			
15.0	12.264	12.265	12.266																																																			
16.7	12.264	12.264	12.265																																																			
18.4	12.264	12.264	12.265																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

- 7 -

BC-10645




Model	SNDHS200A12		
Item	Dynamic Load Response	Temperature	25°C
Object	+12V16.7A	Testing Circuitry	Figure A

Input Volt. 110 V
Cycle 1000 ms


Load Current 16.7A/50 μ s

Min. Load (0A) \longleftrightarrow
Load 100% (16.7A)

0.5 V/div




400 μ s/div




40ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (8.35A)

0.5 V/div




400 μ s/div




40ms/div

Load 10% (1.67A) \longleftrightarrow
Load 100% (16.7A)

0.5 V/div



400 μ s/div




40ms/div

Model	SNDHS200A12																																								
Item	Ripple Voltage (by Load Current)	Temperature	25°C																																						
Object	+12V16.7A	Testing Circuitry	Figure B																																						
1.Graph		2.Values																																							
<div><div><div>△</div><div>Input Volt. 60V</div></div><div><div>○</div><div>Input Volt. 160V</div></div></div> <table><thead><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 60 [V]</th><th>Input Volt. 160 [V]</th></tr></thead><tbody><tr><td>0</td><td>5</td><td>5</td></tr><tr><td>3</td><td>15</td><td>20</td></tr><tr><td>6</td><td>15</td><td>20</td></tr><tr><td>9</td><td>15</td><td>20</td></tr><tr><td>12</td><td>15</td><td>20</td></tr><tr><td>15</td><td>15</td><td>20</td></tr><tr><td>16.7</td><td>15</td><td>20</td></tr><tr><td>18.4</td><td>15</td><td>20</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 60 [V]	Input Volt. 160 [V]	0	5	5	3	15	20	6	15	20	9	15	20	12	15	20	15	15	20	16.7	15	20	18.4	15	20	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 60 [V]	Input Volt. 160 [V]																																							
0	5	5																																							
3	15	20																																							
6	15	20																																							
9	15	20																																							
12	15	20																																							
15	15	20																																							
16.7	15	20																																							
18.4	15	20																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									

Model	SNDHS200A12
Item	Ripple-Noise
Object	+12V16.7A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form


2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 60 [V]	Input Volt. 160 [V]
0	5	15
3	20	25
6	20	25
9	20	25
12	15	25
15	15	25
16.7	15	25
18.4	15	30
--	-	-
--	-	-
--	-	-

Model	SNDHS200A12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V16.7A

Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	35	35
-20	25	25
0	20	20
25	15	20
40	15	20
55	15	15
70	15	15
80	15	15
95	15	15
100	15	15
--	-	-

Model	SNDHS200A12																																																						
Item	Ambient Temperature Drift		Testing Circuitry Figure A																																																				
Object	+12V16.7A																																																						
1.Graph		2.Values																																																					
<div><div>—△— Input Volt. 60V</div><div>---□--- Input Volt. 110V</div><div>-·-○-·- Input Volt. 160V</div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>-40</td><td>12.211</td><td>12.212</td><td>12.213</td></tr><tr><td>-20</td><td>12.233</td><td>12.233</td><td>12.234</td></tr><tr><td>0</td><td>12.247</td><td>12.248</td><td>12.248</td></tr><tr><td>25</td><td>12.261</td><td>12.261</td><td>12.261</td></tr><tr><td>40</td><td>12.270</td><td>12.270</td><td>12.270</td></tr><tr><td>55</td><td>12.270</td><td>12.270</td><td>12.270</td></tr><tr><td>70</td><td>12.271</td><td>12.271</td><td>12.271</td></tr><tr><td>80</td><td>12.272</td><td>12.272</td><td>12.272</td></tr><tr><td>95</td><td>12.273</td><td>12.273</td><td>12.274</td></tr><tr><td>100</td><td>12.274</td><td>12.274</td><td>12.275</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	-40	12.211	12.212	12.213	-20	12.233	12.233	12.234	0	12.247	12.248	12.248	25	12.261	12.261	12.261	40	12.270	12.270	12.270	55	12.270	12.270	12.270	70	12.271	12.271	12.271	80	12.272	12.272	12.272	95	12.273	12.273	12.274	100	12.274	12.274	12.275	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																				
-40	12.211	12.212	12.213																																																				
-20	12.233	12.233	12.234																																																				
0	12.247	12.248	12.248																																																				
25	12.261	12.261	12.261																																																				
40	12.270	12.270	12.270																																																				
55	12.270	12.270	12.270																																																				
70	12.271	12.271	12.271																																																				
80	12.272	12.272	12.272																																																				
95	12.273	12.273	12.274																																																				
100	12.274	12.274	12.275																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							

- 12 -

BC-10645

COSEL

		Testing Circuitry Figure A
Model	SNDHS200A12	
Item	Output Voltage Accuracy	
Object	+12V16.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 60 - 160V


Load Current : 0 - 16.7A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	60	0	12.285	±26	±0.2
Minimum Voltage	-20	60	16.7	12.233		

Model	SNDHS200A12	Temperature 25°C Testing Circuitry Figure A																							
Item	Time Lapse Drift																								
Object	+12V16.7A																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 110V Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.258</td></tr><tr><td>0.5</td><td>12.256</td></tr><tr><td>1.0</td><td>12.260</td></tr><tr><td>2.0</td><td>12.260</td></tr><tr><td>3.0</td><td>12.261</td></tr><tr><td>4.0</td><td>12.261</td></tr><tr><td>5.0</td><td>12.260</td></tr><tr><td>6.0</td><td>12.261</td></tr><tr><td>7.0</td><td>12.261</td></tr><tr><td>8.0</td><td>12.261</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.258	0.5	12.256	1.0	12.260	2.0	12.260	3.0	12.261	4.0	12.261	5.0	12.260	6.0	12.261	7.0	12.261	8.0	12.261
Time since start [H]	Output Voltage [V]																								
0.0	12.258																								
0.5	12.256																								
1.0	12.260																								
2.0	12.260																								
3.0	12.261																								
4.0	12.261																								
5.0	12.260																								
6.0	12.261																								
7.0	12.261																								
8.0	12.261																								

COSEL




Model SNDHS200A12

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V16.7A

Testing Circuitry Figure A

1.Graph



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	49	52
-20	49	52
0	50	52
25	50	53
40	50	53
55	50	53
70	50	53
80	50	53
95	50	53
100	50	54
--	-	-

COSEL

Model	SNDHS200A12																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+12V16.7A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div></div><div></div><div></div></div><div><div>Input Volt. 60V</div><div>Input Volt. 110V</div><div>Input Volt. 160V</div></div></div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>Intermittent operation occurs when the output voltage is from 6V to 0V.</p>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 110[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>11.4</td><td>19.94</td><td>19.86</td><td>19.03</td></tr><tr><td>10.8</td><td>19.94</td><td>20.32</td><td>19.11</td></tr><tr><td>9.6</td><td>20.68</td><td>20.42</td><td>19.28</td></tr><tr><td>8.4</td><td>20.72</td><td>20.28</td><td>19.63</td></tr><tr><td>7.2</td><td>21.40</td><td>21.49</td><td>20.04</td></tr><tr><td>6.0</td><td>21.96</td><td>22.04</td><td>20.27</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	11.4	19.94	19.86	19.03	10.8	19.94	20.32	19.11	9.6	20.68	20.42	19.28	8.4	20.72	20.28	19.63	7.2	21.40	21.49	20.04	6.0	21.96	22.04	20.27	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																							
11.4	19.94	19.86	19.03																																																							
10.8	19.94	20.32	19.11																																																							
9.6	20.68	20.42	19.28																																																							
8.4	20.72	20.28	19.63																																																							
7.2	21.40	21.49	20.04																																																							
6.0	21.96	22.04	20.27																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							

- 17 -

BC-10645

Model	SNDHS200A12	Testing Circuitry Figure A																																							
Item	Overvoltage Protection																																								
Object	+12V16.7A																																								
1.Graph		2.Values																																							
<div><div><div>—△—</div><div>Input Volt. 60V</div></div><div><div>---□---</div><div>Input Volt. 160V</div></div></div>  <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Operating Point [V]</th></tr><tr><th>Input Volt. 60[V]</th><th>Input Volt. 160[V]</th></tr><tr><td>-40</td><td>14.88</td><td>14.88</td></tr><tr><td>-20</td><td>14.88</td><td>14.88</td></tr><tr><td>0</td><td>14.88</td><td>14.88</td></tr><tr><td>25</td><td>14.93</td><td>14.93</td></tr><tr><td>40</td><td>14.93</td><td>14.93</td></tr><tr><td>55</td><td>14.93</td><td>14.93</td></tr><tr><td>70</td><td>14.93</td><td>14.93</td></tr><tr><td>80</td><td>14.93</td><td>14.93</td></tr><tr><td>95</td><td>14.87</td><td>14.87</td></tr><tr><td>100</td><td>14.87</td><td>14.87</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 60[V]	Input Volt. 160[V]	-40	14.88	14.88	-20	14.88	14.88	0	14.88	14.88	25	14.93	14.93	40	14.93	14.93	55	14.93	14.93	70	14.93	14.93	80	14.93	14.93	95	14.87	14.87	100	14.87	14.87	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 60[V]	Input Volt. 160[V]																																							
-40	14.88	14.88																																							
-20	14.88	14.88																																							
0	14.88	14.88																																							
25	14.93	14.93																																							
40	14.93	14.93																																							
55	14.93	14.93																																							
70	14.93	14.93																																							
80	14.93	14.93																																							
95	14.87	14.87																																							
100	14.87	14.87																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)