



DATA SHEET		Date	19-Apr-12
Model	SNDHS200A15	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	T.ARAI




Frequency MHz	Ham	Line Phase	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/ Fail	Remark
			QP	AV		QP	AV	QP	AV	QP	AV		
0.3634		VB	40.7	40.4	10	50.7	50.4	79	66	28.3	15.6	Pass	
0.3649		VA	45.8	45.9	10	55.8	55.9	79	66	23.2	10.1	Pass	
3.64672		VB	40	40.4	10.2	50.2	50.6	73	60	22.8	9.4	Pass	
3.64542		VA	43.5	43.7	10.2	53.7	53.9	73	60	19.3	6.1	Pass	




Frequency MHz	Ham	Polariz ation	Level Check	Stabili ty	Reading dB(μV)			Space Loss dB	Level dB(mW)			Limit dB(mW)	Limit dB(mW)	Limit dB(mW)	Margin dB			Pass/ Fail	Height cm	Angle deg	Remark
					QP	AV	PK		QP	AV	PK				QP	AV	PK				
30.698		V		Stable	42.3			-13.6	28.7			50			21.3			Pass	151	56	
60.626		V		Stable	64.9			-24	40.9			50			9.1			Pass	159	122	

DATA SHEET		Date	19-Apr-12
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	T.ARAI

1. Line conduction



2. Radiated emission



Test: EMI

Model Name: SNDHS200A Series

○ Photographs of Test Set-Up

LINE CONDUCTION



RADIATED EMISSION

