

TEST DATA OF SNDHS250B15

Regulated DC Power Supply

June 30, 2011

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Ovvervoltage Protection	18
19.Figure of Testing Circuitry	19


(Final Page 19)



Model	SNDHS250B15																																																																																		
Item	Input Current (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																																																																	
Object	_____																																																																																		
1.Graph																																																																																			
<p style="text-align: center;"> △ Load 100% □ Load 50% ○ Load 0% </p>																																																																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																			
2.Values																																																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.004</td><td>0.000</td></tr> <tr><td>100</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>150</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>170</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>180</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>190</td><td>0.007</td><td>0.738</td><td>1.491</td></tr> <tr><td>195</td><td>0.007</td><td>0.717</td><td>1.452</td></tr> <tr><td>200</td><td>0.007</td><td>0.698</td><td>1.414</td></tr> <tr><td>250</td><td>0.007</td><td>0.561</td><td>1.129</td></tr> <tr><td>280</td><td>0.007</td><td>0.504</td><td>1.011</td></tr> <tr><td>300</td><td>0.007</td><td>0.472</td><td>0.945</td></tr> <tr><td>350</td><td>0.007</td><td>0.410</td><td>0.814</td></tr> <tr><td>400</td><td>0.007</td><td>0.363</td><td>0.717</td></tr> <tr><td>410</td><td>0.007</td><td>0.355</td><td>0.701</td></tr> <tr><td>420</td><td>0.005</td><td>0.347</td><td>0.686</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.004	0.000	100	0.002	0.002	0.002	150	0.002	0.002	0.002	170	0.002	0.002	0.002	180	0.002	0.002	0.002	190	0.007	0.738	1.491	195	0.007	0.717	1.452	200	0.007	0.698	1.414	250	0.007	0.561	1.129	280	0.007	0.504	1.011	300	0.007	0.472	0.945	350	0.007	0.410	0.814	400	0.007	0.363	0.717	410	0.007	0.355	0.701	420	0.005	0.347	0.686	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0	0.000	0.000	0.000																																																																																
50	0.000	0.004	0.000																																																																																
100	0.002	0.002	0.002																																																																																
150	0.002	0.002	0.002																																																																																
170	0.002	0.002	0.002																																																																																
180	0.002	0.002	0.002																																																																																
190	0.007	0.738	1.491																																																																																
195	0.007	0.717	1.452																																																																																
200	0.007	0.698	1.414																																																																																
250	0.007	0.561	1.129																																																																																
280	0.007	0.504	1.011																																																																																
300	0.007	0.472	0.945																																																																																
350	0.007	0.410	0.814																																																																																
400	0.007	0.363	0.717																																																																																
410	0.007	0.355	0.701																																																																																
420	0.005	0.347	0.686																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

COSEL

Model	SNDHS250B15
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	0.007	0.007	0.008
3.0	0.290	0.208	0.157
6.5	0.564	0.408	0.295
10.0	0.842	0.606	0.434
13.0	1.129	0.809	0.576
16.5	1.424	1.018	0.722
18.2	1.575	1.123	0.796
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model SNDHS250B15

Item Input Power (by Load Current)

Object _____

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	1.4	2.0	3.0
3.0	58.0	58.4	62.8
6.5	112.8	114.3	118.3
10.0	168.5	169.9	174.0
13.0	226.1	226.9	230.9
16.5	285.0	285.4	289.2
18.2	315.1	315.1	318.7
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNDHS250B15
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
195	89.8	88.5
200	90.0	88.6
240	89.9	88.8
280	89.1	88.5
320	88.3	88.2
360	87.5	87.9
400	86.6	87.3
420	86.2	87.0
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNDHS250B15
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	-	-	-
3.0	87.3	86.7	80.6
6.5	89.7	88.5	85.5
10.0	90.0	89.3	87.2
13.0	89.4	89.1	87.5
16.5	88.6	88.5	87.3
18.2	88.1	88.1	87.1
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.



Model	SNDHS250B15	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+15V16.5A																																		
1.Graph		2.Values																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td><td>15.306</td><td>15.301</td> </tr> <tr> <td>200</td><td>15.306</td><td>15.301</td> </tr> <tr> <td>240</td><td>15.306</td><td>15.301</td> </tr> <tr> <td>280</td><td>15.306</td><td>15.301</td> </tr> <tr> <td>320</td><td>15.306</td><td>15.301</td> </tr> <tr> <td>360</td><td>15.306</td><td>15.300</td> </tr> <tr> <td>400</td><td>15.306</td><td>15.300</td> </tr> <tr> <td>420</td><td>15.306</td><td>15.300</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	15.306	15.301	200	15.306	15.301	240	15.306	15.301	280	15.306	15.301	320	15.306	15.301	360	15.306	15.300	400	15.306	15.300	420	15.306	15.300	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
195	15.306	15.301																																	
200	15.306	15.301																																	
240	15.306	15.301																																	
280	15.306	15.301																																	
320	15.306	15.301																																	
360	15.306	15.300																																	
400	15.306	15.300																																	
420	15.306	15.300																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			










COSEL

Model	SNDHS250B15	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+15V16.5A																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.312</td><td>15.311</td><td>15.311</td></tr> <tr><td>3.0</td><td>15.309</td><td>15.309</td><td>15.309</td></tr> <tr><td>6.5</td><td>15.307</td><td>15.307</td><td>15.307</td></tr> <tr><td>10.0</td><td>15.305</td><td>15.305</td><td>15.305</td></tr> <tr><td>13.0</td><td>15.303</td><td>15.303</td><td>15.303</td></tr> <tr><td>16.5</td><td>15.301</td><td>15.301</td><td>15.300</td></tr> <tr><td>18.2</td><td>15.299</td><td>15.299</td><td>15.299</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	15.312	15.311	15.311	3.0	15.309	15.309	15.309	6.5	15.307	15.307	15.307	10.0	15.305	15.305	15.305	13.0	15.303	15.303	15.303	16.5	15.301	15.301	15.300	18.2	15.299	15.299	15.299	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																				
0.0	15.312	15.311	15.311																																																				
3.0	15.309	15.309	15.309																																																				
6.5	15.307	15.307	15.307																																																				
10.0	15.305	15.305	15.305																																																				
13.0	15.303	15.303	15.303																																																				
16.5	15.301	15.301	15.300																																																				
18.2	15.299	15.299	15.299																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model	SNDHS250B15	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V16.5A		

Input Volt. 280 V
 Cycle 1000 ms




COSEL

Model	SNDHS250B15
Item	Ripple Voltage (by Load Current)
Object	+15V16.5A

Temperature 25°C
 Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	5	5
3.0	30	35
6.5	30	40
10.0	30	40
13.0	30	40
16.5	30	40
18.2	30	40
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model SNDHS250B15

Item Ripple-Noise

Object +15V16.5A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	10	15
3.0	30	40
6.5	30	45
10.0	30	45
13.0	35	45
16.5	35	50
18.2	35	50
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SNDHS250B15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V16.5A

Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	60	65
-20	60	60
0	40	40
25	35	35
40	35	35
55	35	35
70	30	30
85	30	30
95	30	30
--	-	-
--	-	-

COSEL

Model	SNDHS250B15
Item	Ambient Temperature Drift
Object	+15V16.5A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-40	15.273	15.273	15.275
-20	15.292	15.292	15.293
0	15.304	15.304	15.305
25	15.309	15.309	15.309
40	15.304	15.304	15.304
55	15.307	15.306	15.305
70	15.302	15.302	15.301
85	15.299	15.299	15.299
95	15.300	15.300	15.301
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SNDHS250B15	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V16.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 16.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	200	0	15.314	± 195	± 1.3
Minimum Voltage	-20	200	16.5	14.924		

COSEL

Model	SNDHS250B15
Item	Time Lapse Drift
Object	+15V16.5A

1.Graph



Input Volt. 280V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.300
0.5	15.299
1.0	15.299
2.0	15.300
3.0	15.300
4.0	15.300
5.0	15.300
6.0	15.300
7.0	15.300
8.0	15.300

COSEL

Model SNDHS250B15


Item Rise and Fall Time

Object +15V16.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph


Input Volt. 280 V



2. Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		53.0	3.5	56.5	1.3	14.8
100 %		53.0	3.5	56.5	0.7	7.4





Model	SNDHS250B15	Testing Circuitry Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+15V16.5A																																								
1.Graph																																									
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>			2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>158</td><td>164</td></tr> <tr> <td>-20</td><td>158</td><td>164</td></tr> <tr> <td>0</td><td>159</td><td>165</td></tr> <tr> <td>25</td><td>159</td><td>165</td></tr> <tr> <td>40</td><td>158</td><td>166</td></tr> <tr> <td>55</td><td>159</td><td>166</td></tr> <tr> <td>70</td><td>159</td><td>166</td></tr> <tr> <td>85</td><td>159</td><td>167</td></tr> <tr> <td>95</td><td>159</td><td>167</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	158	164	-20	158	164	0	159	165	25	159	165	40	158	166	55	159	166	70	159	166	85	159	167	95	159	167	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-40	158	164																																							
-20	158	164																																							
0	159	165																																							
25	159	165																																							
40	158	166																																							
55	159	166																																							
70	159	166																																							
85	159	167																																							
95	159	167																																							
--	-	-																																							
--	-	-																																							

COSEL

Model	SNDHS250B15
Item	Overcurrent Protection
Object	+15V16.5A

1.Graph

Output Voltage [V]

Load Current [A]

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 8V to 0V.


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
14.3	21.17	21.15	21.37
13.5	21.33	21.37	21.55
12.0	21.62	21.82	22.14
10.5	21.99	22.22	22.66
9.0	22.39	22.63	23.17
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model	SNDHS250B15
Item	Oversupply Protection
Object	+15V16.5A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 200[V]	Input Volt. 400[V]
-40	18.47	18.47
-20	18.58	18.58
0	18.58	18.58
25	18.58	18.58
40	18.58	18.58
55	18.58	18.58
70	18.58	18.58
85	18.58	18.58
95	18.58	18.58
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)