

Approved : Takahiro Yoneda
Takahiro Yoneda

Prepared : Satoshi Kinoshita
Satoshi Kinoshita

No.	Test item	Conditions	Conditions of acceptability	Result
1	High temp./overload test	(1) Rated input AC100V (2) Overload (3) Base Plate end face temp 80°C (4) Test period 48 hours	(1)Power supply is not failed.	OK
2	Low voltage input test	(1) Input : Min. regulation voltage (2) Rated output (3) Base plate end face temp.:80°C (4) Test period 48 hours	(1)Power supply is not failed.	OK
3	Input ON/OFF test	(1) Input : Rated input AC100V Ton= 1s , Toff= 5s (2) Rated output (3) Ambient temp. 25±10°C (4) On/Off period 1,000 times	(1)Power supply is not failed. (2)The surge current of each components should not exceed the rated value.	OK
4	Output ON/OFF test	(1) Rated input AC200V (2) Output 0%←→100% T= 2sec Duty= 50% (3) Ambient temp. 25±10°C (4) On/Off period 1,000 times	(1)Power supply is not failed.	OK
5	Output-short start test	(1) Rated input AC200V (2) Output : Short start (3) Ambient temp. 25±10°C	(1)Power supply is not failed.	OK
6	Output short test	(1) Input AC200V (2) Output : Short (3) Ambient temp. 25±10°C (4) Test period 48 hours	(1)Power supply is not failed.	OK
7	Withstand voltage test (High-pot test)	(1) Input : Not applied. (2) Ambient temp. 25±10°C (3) The applied voltage is 1.4 times of specifications.	(1)Insulation breakdown , flashover electric arc is not occurred.	OK
8	Isolation resistance test	(1) Input : Not applied. (2) Ambient temp. 25±10°C	(1)When a regulation voltage is applied, isolation resistance is 1.4 times of specifications.	OK
9	Vibration/impact test	Vibration (1)f=10~150Hz : 29.4m/s ² (2)3 minutes period (3)60 minutes along X, Y and Z axis Impact (1)294.2m/s ² 11ms (2)Once each X, Y and Z axis	(1)No degradation of electric characteristics after test. (2)No crack at solder joint. (3)No marked damage of appearance.	OK
10	Line Noise Tolerance test	(1) Input AC230V (2) Rated Output (3) Ambient temp. 25±10°C (4) Test Voltage ±2 kV (5) Pulse width 50~1000nS (6) Mode Normal and Common	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure.	OK