

# TEST DATA OF SNDPG750

(100V INPUT)

AC-DC Front End Module  
June 30, 2011

Approved by : Takahiro Yoneda  
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai  
Tadashi Arai Design Engineer

**COSEL CO.,LTD.**


CONTENTS

1. Input Current (by Load Power) . . . . .	1
2. Input Power (by Load Power) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Power) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Power) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Power) . . . . .	12
13. Ambient Temperature Drift . . . . .	13
14. Output Voltage Accuracy . . . . .	14
15. Time Lapse Drift . . . . .	15
16. Rise and Fall Time . . . . .	16
17. Minimum Input Voltage for Regulated Output Voltage . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19

(Final Page 19)

**COSEL**

Model	SNDPG750
Item	Input Current (by Load Power)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Power [W]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	0.15	0.18	0.24
50	0.74	0.64	0.52
150	2.01	1.69	1.28
250	3.26	2.75	2.07
300	3.86	3.29	2.46
400	5.16	4.35	3.26
500	6.45	5.44	4.07
550	7.08	5.97	4.46
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load power.


**COSEL**

Model	SNDPG750	Temperature	25°C																																																			
Item	Input Power (by Load Power)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul> <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Power [W]</th> <th>Input Power [W] (85V)</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (132V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.0</td><td>3.0</td><td>2.9</td></tr> <tr><td>50</td><td>56.8</td><td>56.5</td><td>56.1</td></tr> <tr><td>150</td><td>162.7</td><td>161.9</td><td>160.3</td></tr> <tr><td>250</td><td>269.6</td><td>267.4</td><td>264.8</td></tr> <tr><td>300</td><td>322.2</td><td>322.3</td><td>316.7</td></tr> <tr><td>400</td><td>432.4</td><td>426.5</td><td>421.6</td></tr> <tr><td>500</td><td>540.4</td><td>537.1</td><td>527.4</td></tr> <tr><td>550</td><td>594.4</td><td>589.4</td><td>579.3</td></tr> </tbody> </table>			Load Power [W]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)	0	3.0	3.0	2.9	50	56.8	56.5	56.1	150	162.7	161.9	160.3	250	269.6	267.4	264.8	300	322.2	322.3	316.7	400	432.4	426.5	421.6	500	540.4	537.1	527.4	550	594.4	589.4	579.3															
Load Power [W]	Input Power [W] (85V)	Input Power [W] (100V)	Input Power [W] (132V)																																																			
0	3.0	3.0	2.9																																																			
50	56.8	56.5	56.1																																																			
150	162.7	161.9	160.3																																																			
250	269.6	267.4	264.8																																																			
300	322.2	322.3	316.7																																																			
400	432.4	426.5	421.6																																																			
500	540.4	537.1	527.4																																																			
550	594.4	589.4	579.3																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3.0</td><td>3.0</td><td>2.9</td></tr> <tr><td>50</td><td>56.8</td><td>56.5</td><td>56.1</td></tr> <tr><td>150</td><td>162.7</td><td>161.9</td><td>160.3</td></tr> <tr><td>250</td><td>269.6</td><td>267.4</td><td>264.8</td></tr> <tr><td>300</td><td>322.2</td><td>322.3</td><td>316.7</td></tr> <tr><td>400</td><td>432.4</td><td>426.5</td><td>421.6</td></tr> <tr><td>500</td><td>540.4</td><td>537.1</td><td>527.4</td></tr> <tr><td>550</td><td>594.4</td><td>589.4</td><td>579.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Power [W]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	3.0	3.0	2.9	50	56.8	56.5	56.1	150	162.7	161.9	160.3	250	269.6	267.4	264.8	300	322.2	322.3	316.7	400	432.4	426.5	421.6	500	540.4	537.1	527.4	550	594.4	589.4	579.3	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Input Power [W]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	3.0	3.0	2.9																																																			
50	56.8	56.5	56.1																																																			
150	162.7	161.9	160.3																																																			
250	269.6	267.4	264.8																																																			
300	322.2	322.3	316.7																																																			
400	432.4	426.5	421.6																																																			
500	540.4	537.1	527.4																																																			
550	594.4	589.4	579.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load power.																																																						

**COSEL**

Model	SNDPG750
Item	Efficiency (by Input Voltage)
Object	—

## 1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	93.2	92.8
85	93.4	93.2
90	93.2	93.1
100	94.1	93.7
110	94.5	94.7
120	94.9	94.4
132	95.0	95.5
140	95.2	95.7
--	-	-

**COSEL**

Model SNDPG750

Item Efficiency (by Load Power)

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Power [W]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	-	-	-
50	90.5	90.7	91.5
150	93.2	93.6	94.7
250	93.3	94.1	95.1
300	93.7	93.7	95.3
400	93.0	94.3	95.5
500	93.2	93.8	95.5
550	93.0	93.8	95.4
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load power.

**COSEL**


Model	SNDPG750	Temperature Testing Circuitry 25°C Figure A																																
Item	Power Factor (by Input Voltage)																																	
Object	—																																	
1.Graph																																		
<p>Power Factor</p> <p>Input Voltage [V]</p> <p>Load 50%      Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>0.980</td><td>0.982</td> </tr> <tr> <td>85</td><td>0.974</td><td>0.986</td> </tr> <tr> <td>90</td><td>0.978</td><td>0.987</td> </tr> <tr> <td>100</td><td>0.973</td><td>0.988</td> </tr> <tr> <td>110</td><td>0.975</td><td>0.986</td> </tr> <tr> <td>120</td><td>0.972</td><td>0.986</td> </tr> <tr> <td>132</td><td>0.969</td><td>0.983</td> </tr> <tr> <td>140</td><td>0.966</td><td>0.983</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.980	0.982	85	0.974	0.986	90	0.978	0.987	100	0.973	0.988	110	0.975	0.986	120	0.972	0.986	132	0.969	0.983	140	0.966	0.983	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
80	0.980	0.982																																
85	0.974	0.986																																
90	0.978	0.987																																
100	0.973	0.988																																
110	0.975	0.986																																
120	0.972	0.986																																
132	0.969	0.983																																
140	0.966	0.983																																
--	-	-																																
Note: Slanted line shows the range of the rated input voltage.																																		

**COSEL**

Model SNDPG750

Item Power Factor (by Load Power)

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A


## 2. Values

Load Power [W]	Power Factor		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
50	0.904	0.886	0.823
150	0.954	0.961	0.946
250	0.974	0.971	0.968
300	0.983	0.980	0.974
400	0.986	0.982	0.980
500	0.986	0.988	0.983
550	0.988	0.989	0.986
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load power.

**COSEL**


Model	SNDPG750	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	—		



Input Voltage 100 V  
 Frequency 60 Hz  
 Load 0 %

#### inrush current

- ① 12.0A Primary inrush current
- ② 25.5A (0.2msec or less)※1
- ③ 16.7A Secondary inrush current



※1 The specification of the inrush current (primary surge) means that the surge current to a built-in noise filter (0.2msec or less : waveform ②) is excluded.



Model	SNDPG750	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.13	0.16	0.20
(B)IEC60950-1	0.13	0.16	0.20

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 240 [V]	Input Volt. 264 [V]
(B)IEC60950-1	-	-	-

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	SNDPG750
Item	Line Regulation
Object	+360V 500W

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	360.36	360.41
85	360.36	360.42
90	360.36	360.43
100	360.36	360.44
110	360.35	360.43
120	360.35	360.43
132	360.35	360.43
140	360.35	360.42
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	SNDPG750	Temperature Testing Circuitry      25°C Figure A																																																					
Item	Load Regulation																																																						
Object	+360V 500W																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Load Power [W]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>360.38</td><td>360.37</td><td>360.40</td></tr> <tr><td>50</td><td>360.36</td><td>360.35</td><td>360.38</td></tr> <tr><td>150</td><td>360.33</td><td>360.33</td><td>360.35</td></tr> <tr><td>250</td><td>360.31</td><td>360.31</td><td>360.33</td></tr> <tr><td>300</td><td>360.31</td><td>360.31</td><td>360.32</td></tr> <tr><td>400</td><td>360.33</td><td>360.32</td><td>360.32</td></tr> <tr><td>500</td><td>360.33</td><td>360.34</td><td>360.33</td></tr> <tr><td>550</td><td>360.35</td><td>360.38</td><td>360.35</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Power [W]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	360.38	360.37	360.40	50	360.36	360.35	360.38	150	360.33	360.33	360.35	250	360.31	360.31	360.33	300	360.31	360.31	360.32	400	360.33	360.32	360.32	500	360.33	360.34	360.33	550	360.35	360.38	360.35	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0	360.38	360.37	360.40																																																				
50	360.36	360.35	360.38																																																				
150	360.33	360.33	360.35																																																				
250	360.31	360.31	360.33																																																				
300	360.31	360.31	360.32																																																				
400	360.33	360.32	360.32																																																				
500	360.33	360.34	360.33																																																				
550	360.35	360.38	360.35																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
		<p>Note: Slanted line shows the range of the rated load power.</p>																																																					


**COSEL**

**COSEL**

Model	SNDPG750
Item	Ripple Voltage (by Load Power)
Object	+360V500W

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load power.

## 2. Values

Load Power [W]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0	0.1	0.1
50	1.1	1.1
150	3.2	3.2
250	5.2	5.3
300	6.5	6.6
400	8.4	8.6
500	10.4	10.6
550	11.6	11.9
--	-	-
--	-	-
--	-	-



 T1: Due to AC Input Line  
 T2: Due to Switching


Fig. Complex Ripple Wave Form

**COSEL**

Model	SNDPG750	Testing Circuitry Figure A																																																								
Item	Ambient Temperature Drift																																																									
Object	+360V 500W																																																									
1.Graph	<p>—△— Input Volt. 85V      - - - □ - - Input Volt. 100V      - - ○ - - Input Volt. 132V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> </thead> <tbody> <tr> <td>85[V]</td> <td>100[V]</td> <td>132[V]</td> </tr> <tr> <td>-40</td> <td>357.60</td> <td>357.70</td> <td>357.76</td> </tr> <tr> <td>-20</td> <td>358.27</td> <td>358.36</td> <td>358.42</td> </tr> <tr> <td>0</td> <td>359.09</td> <td>359.17</td> <td>359.22</td> </tr> <tr> <td>25</td> <td>359.97</td> <td>360.03</td> <td>360.06</td> </tr> <tr> <td>40</td> <td>360.43</td> <td>360.46</td> <td>360.49</td> </tr> <tr> <td>55</td> <td>360.75</td> <td>360.80</td> <td>360.83</td> </tr> <tr> <td>70</td> <td>361.05</td> <td>361.07</td> <td>361.09</td> </tr> <tr> <td>85</td> <td>361.25</td> <td>361.28</td> <td>361.29</td> </tr> <tr> <td>95</td> <td>361.39</td> <td>361.42</td> <td>361.42</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	-40	357.60	357.70	357.76	-20	358.27	358.36	358.42	0	359.09	359.17	359.22	25	359.97	360.03	360.06	40	360.43	360.46	360.49	55	360.75	360.80	360.83	70	361.05	361.07	361.09	85	361.25	361.28	361.29	95	361.39	361.42	361.42	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																									
	Input Volt.	Input Volt.	Input Volt.																																																							
85[V]	100[V]	132[V]																																																								
-40	357.60	357.70	357.76																																																							
-20	358.27	358.36	358.42																																																							
0	359.09	359.17	359.22																																																							
25	359.97	360.03	360.06																																																							
40	360.43	360.46	360.49																																																							
55	360.75	360.80	360.83																																																							
70	361.05	361.07	361.09																																																							
85	361.25	361.28	361.29																																																							
95	361.39	361.42	361.42																																																							
--	-	-	-																																																							
--	-	-	-																																																							

Note: Slanted line shows the range of the rated ambient temperature.



Model	SNDPG750	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+360V 500W	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 85 - 132V

Load Power : 0 - 500W

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Power[W]	Voltage[V]	Value [V]	Ration [%]
Maximum Voltage	95	132	500	361.42	$\pm 2$	$\pm 0.5$
Minimum Voltage	-20	100	0	358.12		

**COSEL**

Model	SNDPG750
Item	Time Lapse Drift
Object	+360V 500W

Temperature 25°C  
Testing Circuitry Figure A


## 1. Graph



Input Volt. 100V  
Load 100%

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	360.36
0.5	360.47
1.0	360.47
2.0	360.47
3.0	360.47
4.0	360.47
5.0	360.47
6.0	360.47
7.0	360.47
8.0	360.47

**COSEL**

**COSEL**

Model	SNDPG750	Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+360V 500W																																							
1.Graph		2.Values																																						
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>72</td><td>76</td> </tr> <tr> <td>-20</td><td>72</td><td>75</td> </tr> <tr> <td>0</td><td>72</td><td>75</td> </tr> <tr> <td>25</td><td>72</td><td>75</td> </tr> <tr> <td>40</td><td>72</td><td>76</td> </tr> <tr> <td>55</td><td>72</td><td>76</td> </tr> <tr> <td>70</td><td>72</td><td>76</td> </tr> <tr> <td>85</td><td>72</td><td>76</td> </tr> <tr> <td>95</td><td>72</td><td>76</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	72	76	-20	72	75	0	72	75	25	72	75	40	72	76	55	72	76	70	72	76	85	72	76	95	72	76	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	72	76																																						
-20	72	75																																						
0	72	75																																						
25	72	75																																						
40	72	76																																						
55	72	76																																						
70	72	76																																						
85	72	76																																						
95	72	76																																						
--	-	-																																						
--	-	-																																						

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**


Model SNDPG750

Item Overvoltage Protection

Object +360V500W

## 1. Graph

—△— Input Volt. 85V  
 - - □ - - Input Volt. 132V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 85[V]	Input Volt. 132[V]
-40	421.00	421.00
-20	421.00	421.00
0	425.00	425.00
25	429.00	429.00
40	429.00	429.00
55	429.00	429.00
70	429.00	429.00
85	429.00	429.00
95	429.00	429.00
--	-	-
--	-	-

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950-1 )