



## SNTUNS100F series EMI/EMS Test result

July 27, 2013  
VS DESIGN DEPT.

Approved : Takahiro Yoneda  
Takahiro Yoneda

Prepared : Satoshi Kinoshita  
Satoshi Kinoshita

| No. | Test item   | Conditions  | Conditions of Acceptability   | Result |
|-----|---|---|---|--------|
| 1   | Line conduction   | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C  | (1)Meets the undermentioned standard.<br>FCC Part15 classB , VCCI classB<br>CISPR22 classB , EN55022-B  | OK     |
| 2   | Radiated emission   | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C  | (1)Meets the undermentioned standard.<br>FCC Part15 classB , VCCI classB<br>CISPR22 classB , EN55022-B  | OK     |
| 3   | Harmonic current<br>(EN61000-3-2)   | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C  | (1)Meets the undermentioned standard.<br>EN61000-3-2 classA   | OK     |
| 4   | Static electricity immunity test<br>(EN61000-4-2)   | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Contact discharge voltage 8[kV]<br>(Level 4)  | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |
| 5   | Radiated, radio-frequency,<br>electromagnetic field immunity test<br>(EN61000-4-3)          | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Testing field strength (Level 3)<br>① 10[V/m] (80MHz to 1.0GHz)<br>② 3[V/m] (1.4GHz to 2.0GHz)<br>③ 1[V/m] (2.0GHz to 2.7GHz) | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |
| 6   | Electrical fast transient/<br>burst immunity test<br>(EN61000-4-4)                          | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Test peak voltage 4[kV]<br>(Level 4)  | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |
| 7   | Surge immunity test<br>(EN61000-4-5)  | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Test voltage<br>Line to line 2[kV] (Level 3)<br>Line to earth 2[kV] (Level 3)   | (1)The power supply is not stop<br>(2)Circuit does not malfunction.<br>(3)No abnormality of the insulation destruction etc.<br>(4)Parts are no damaged. | OK     |
| 8   | Immunity to conducted disturbances,<br>induced by radio-frequency fields<br>(EN61000-4-6)   | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Voltage level (e.m.f.) 10[V]<br>(Level 3)   | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |
| 9   | Power frequency magnetic field<br>Immunity test<br>(EN61000-4-8)                            | (1) Input AC230V<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C<br>(4) Magnetic field strength 30[A/m]<br>(Level 4)  | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |
| 10  | Voltage dips, short interruptions<br>and voltage variations immunity test<br>(EN61000-4-11) | (1) Input AC230V<br>•30% reduction at 10ms min.<br>•60% reduction at 100ms min.<br>•95% reduction at 5s min.<br>•±10% variation at 15 minutes<br>(2) Outout Rated load<br>(3) Ambient temp. 25±10°C         | (1)No protection circuit failure.<br>(2)No output voltage drop with control circuit failure.<br>(3)No any other function failure.                       | OK     |