



DATA SHEET				Date	25-May-11
Model	SPLFA50F-12			Temp.	25 degreeC
Test	EMI			Humid.	40 %RH
	Line conduction & Radiated emission			Tested by	H.Kitamura




Frequency MHz	Line Phas	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/ Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.21379	VA	30	22.8	10.1	40.1	32.9	63.1	53.1	23	20.2	Pass	
25.1656	VA	26.9	25.4	11	37.9	36.4	60	50	22.1	13.6	Pass	
26.4078	VA	27.2	23.6	11	38.2	34.6	60	50	21.8	15.4	Pass	



Frequency MHz	Polarization	Reading dB(μV)		Space Loss dB	Level dB(mW)		Limit dB(mW)	Margin dB	Pass/ Fail	Height cm	Angle deg	Remark
		QP	AV		QP	AV						
68.85	H	61.4	-25.6		35.8		50	14.2	Pass	100	60	
240.5	H	61	-18.6		42.4		57	14.6	Pass	101	108	

DATA SHEET		Date	25-May-11
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	H.Kitamura

1. Line conduction



2. Radiated emission

