

DATA SHEET			Date	Jun.8,2000
Model	STA5000T		Temp.	25 °C
Test	Vibration/impact test 振動・衝撃試験		Humid.	45 %Rh
			Tested by	K.Tajima

1. Method
Vibration/impact test complies with JIS C 0911 (Vibration), JIS C 0912 (Impact)
JIS C 0911 (振動), JIS C 0912 (衝撃) に準ずる

2. Conditions
 - (1) Frequency : 10~150 Hz
(Vibration) 3 minutes period
周波数(振動)

 - (2) Direction・Time : 60 minutes along X, Y and Z axis (Vibration)
方向・時間 11mS, once each X, Y and Z axis (Impact)

3. Conditions of Acceptability
 - (1) No degradation of performance or loss of function after test.
試験後、諸機能が正常であること

 - (2) No remarkably damage of appearance.
外観上著しい損傷がないこと

 - (3) No looseness or a crack at solder joint.
はんだ付け、圧着など電氣的接合部分にクラックや緩みの発生がないこと

4. Result
 - (1) Vibration limit test

No.	Gravity [G]	Result	Note
1	3	OK	
2	—	—	
3	—	—	

All are satisfactory to item 3: OK

 - (2) Impact test

No.	Gravity [G]	Result	Note
1	30	OK	
2	—	—	
3	—	—	

All are satisfactory to item 3: OK