

# TEST DATA OF STMGFS804812

Regulated DC Power Supply  
May 20, 2021

Approved by : Hironobu Shimizu  
Hironobu Shimizu Design Manager

Prepared by : Hikaru Inagaki  
Hikaru Inagaki Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Line Regulation . . . . .	3
4.Load Regulation . . . . .	4
5.Ripple-Noise . . . . .	4
6.Rise and Fall Time . . . . .	5
7.Overcurrent Protection . . . . .	6
8.Ambient Temperature Drift . . . . .	7
9.Minimum Input Voltage for Regulated Output Voltage . . . . .	7
10.Overvoltage Protection . . . . .	7
11.Figure of Testing Circuitry . . . . .	8

(Final Page 8)

**COSEL**

Model	STMGFS804812	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
			2.Values																																																																													
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.038</td> <td>0.032</td> <td>0.025</td> <td>0.010</td> <td>0.011</td> </tr> <tr> <td>1.3</td> <td>0.946</td> <td>0.707</td> <td>0.476</td> <td>0.361</td> <td>0.236</td> </tr> <tr> <td>2.7</td> <td>1.922</td> <td>1.439</td> <td>0.966</td> <td>0.727</td> <td>0.469</td> </tr> <tr> <td>4.0</td> <td>2.852</td> <td>2.124</td> <td>1.419</td> <td>1.065</td> <td>0.686</td> </tr> <tr> <td>4.7</td> <td>3.373</td> <td>2.501</td> <td>1.662</td> <td>1.249</td> <td>0.800</td> </tr> <tr> <td>5.4</td> <td>-※1</td> <td>2.870</td> <td>1.909</td> <td>1.433</td> <td>0.915</td> </tr> <tr> <td>6.7</td> <td>-※1</td> <td>-※2</td> <td>2.367</td> <td>1.774</td> <td>1.127</td> </tr> <tr> <td>7.4</td> <td>-※1</td> <td>-※2</td> <td>2.619</td> <td>1.960</td> <td>1.243</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.038	0.032	0.025	0.010	0.011	1.3	0.946	0.707	0.476	0.361	0.236	2.7	1.922	1.439	0.966	0.727	0.469	4.0	2.852	2.124	1.419	1.065	0.686	4.7	3.373	2.501	1.662	1.249	0.800	5.4	-※1	2.870	1.909	1.433	0.915	6.7	-※1	-※2	2.367	1.774	1.127	7.4	-※1	-※2	2.619	1.960	1.243	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	0.038	0.032	0.025	0.010	0.011																																																																											
1.3	0.946	0.707	0.476	0.361	0.236																																																																											
2.7	1.922	1.439	0.966	0.727	0.469																																																																											
4.0	2.852	2.124	1.419	1.065	0.686																																																																											
4.7	3.373	2.501	1.662	1.249	0.800																																																																											
5.4	-※1	2.870	1.909	1.433	0.915																																																																											
6.7	-※1	-※2	2.367	1.774	1.127																																																																											
7.4	-※1	-※2	2.619	1.960	1.243																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note: Slanted line shows the range of the rated load current.			※1 Maximam output current at minimum input Voltage is 70% of rated load current. ※2 Maximam output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																													

**COSEL**

Model	STMGFS804812	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Efficiency (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		<p>Efficiency [%]</p> <p>Load Current [A]</p>																																																																														
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.3</td> <td>91.7</td> <td>91.6</td> <td>91.0</td> <td>89.9</td> <td>87.0</td> </tr> <tr> <td>2.7</td> <td>93.3</td> <td>93.5</td> <td>93.1</td> <td>92.8</td> <td>90.9</td> </tr> <tr> <td>4.0</td> <td>93.4</td> <td>93.9</td> <td>94.0</td> <td>93.8</td> <td>92.1</td> </tr> <tr> <td>4.7</td> <td>93.2</td> <td>93.9</td> <td>94.2</td> <td>94.1</td> <td>92.7</td> </tr> <tr> <td>5.4</td> <td>-※1</td> <td>93.8</td> <td>94.3</td> <td>94.2</td> <td>93.2</td> </tr> <tr> <td>6.7</td> <td>-※1</td> <td>-※2</td> <td>94.2</td> <td>94.4</td> <td>93.8</td> </tr> <tr> <td>7.4</td> <td>-※1</td> <td>-※2</td> <td>94.1</td> <td>94.3</td> <td>94.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	-	-	-	-	-	1.3	91.7	91.6	91.0	89.9	87.0	2.7	93.3	93.5	93.1	92.8	90.9	4.0	93.4	93.9	94.0	93.8	92.1	4.7	93.2	93.9	94.2	94.1	92.7	5.4	-※1	93.8	94.3	94.2	93.2	6.7	-※1	-※2	94.2	94.4	93.8	7.4	-※1	-※2	94.1	94.3	94.0	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	-	-	-	-	-																																																																											
1.3	91.7	91.6	91.0	89.9	87.0																																																																											
2.7	93.3	93.5	93.1	92.8	90.9																																																																											
4.0	93.4	93.9	94.0	93.8	92.1																																																																											
4.7	93.2	93.9	94.2	94.1	92.7																																																																											
5.4	-※1	93.8	94.3	94.2	93.2																																																																											
6.7	-※1	-※2	94.2	94.4	93.8																																																																											
7.4	-※1	-※2	94.1	94.3	94.0																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

Note: Slanted line shows the range of the rated load current.

※1 Maximam output current at minimum input Voltage is 70% of rated load current.

※2 Maximam output current at 24V input Voltage is 80% of rated load current.


Refer to instruction manuals for details of input derating.

**COSEL**

Model	STMGFS804812
Item	Line Regulation
Object	+12V6.7A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.

## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	12.013	-
18	12.014	-
24	12.014	-
30	12.015	12.009
36	12.014	12.009
48	12.014	12.009
60	12.012	12.008
76	12.011	12.007
80	12.010	12.007

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSSEL**


Model	STMGFS804812	Temperature	25°C																																																																													
Item	Load Regulation	Testing Circuitry	Figure A																																																																													
Object	+12V6.7A																																																																															
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																															
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.030</td><td>12.028</td><td>12.027</td><td>12.030</td><td>12.029</td></tr> <tr><td>1.3</td><td>12.025</td><td>12.023</td><td>12.022</td><td>12.022</td><td>12.019</td></tr> <tr><td>2.7</td><td>12.021</td><td>12.020</td><td>12.019</td><td>12.018</td><td>12.015</td></tr> <tr><td>4.0</td><td>12.017</td><td>12.017</td><td>12.017</td><td>12.016</td><td>12.013</td></tr> <tr><td>4.7</td><td>12.015</td><td>12.015</td><td>12.015</td><td>12.015</td><td>12.012</td></tr> <tr><td>5.4</td><td>-※1</td><td>12.013</td><td>12.013</td><td>12.013</td><td>12.010</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>12.010</td><td>12.009</td><td>12.007</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>12.008</td><td>12.007</td><td>12.006</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.      ※2 Maximum output current at 18V input Voltage is 80% of rated load current.      Refer to instruction manuals for details of input derating.</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	12.030	12.028	12.027	12.030	12.029	1.3	12.025	12.023	12.022	12.022	12.019	2.7	12.021	12.020	12.019	12.018	12.015	4.0	12.017	12.017	12.017	12.016	12.013	4.7	12.015	12.015	12.015	12.015	12.012	5.4	-※1	12.013	12.013	12.013	12.010	6.7	-※1	-※2	12.010	12.009	12.007	7.4	-※1	-※2	12.008	12.007	12.006	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	12.030	12.028	12.027	12.030	12.029																																																																											
1.3	12.025	12.023	12.022	12.022	12.019																																																																											
2.7	12.021	12.020	12.019	12.018	12.015																																																																											
4.0	12.017	12.017	12.017	12.016	12.013																																																																											
4.7	12.015	12.015	12.015	12.015	12.012																																																																											
5.4	-※1	12.013	12.013	12.013	12.010																																																																											
6.7	-※1	-※2	12.010	12.009	12.007																																																																											
7.4	-※1	-※2	12.008	12.007	12.006																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+12V6.7A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 48V Load 100%</p> <p>20[mV/div]</p> <p>5[μs/div]</p>																																																																															

**COSEL**

Model	STMGFS804812
Item	Rise and Fall Time
Object	+12V6.7A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.6	4.1	10.7	0.3	2.1	
100 %		6.6	5.9	12.5	0.2	0.7	





Model	STMGFS804812	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+12V6.7A																																																																																					
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V</p> <p>Input Volt. 24V</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>																																																																																				
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>12.0</td> <td>5.737</td> <td>7.030</td> <td>8.039</td> <td>8.181</td> <td>8.491</td> </tr> <tr> <td>11.4</td> <td>-※1</td> <td>-※2</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>10.8</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>9.6</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>8.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>7.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>6.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.8</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.6</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	12.0	5.737	7.030	8.039	8.181	8.491	11.4	-※1	-※2	-	-	-	10.8	-	-	-	-	-	9.6	-	-	-	-	-	8.4	-	-	-	-	-	7.2	-	-	-	-	-	6.0	-	-	-	-	-	4.8	-	-	-	-	-	3.6	-	-	-	-	-	2.4	-	-	-	-	-	1.2	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
12.0	5.737	7.030	8.039	8.181	8.491																																																																																	
11.4	-※1	-※2	-	-	-																																																																																	
10.8	-	-	-	-	-																																																																																	
9.6	-	-	-	-	-																																																																																	
8.4	-	-	-	-	-																																																																																	
7.2	-	-	-	-	-																																																																																	
6.0	-	-	-	-	-																																																																																	
4.8	-	-	-	-	-																																																																																	
3.6	-	-	-	-	-																																																																																	
2.4	-	-	-	-	-																																																																																	
1.2	-	-	-	-	-																																																																																	
0.0	-	-	-	-	-																																																																																	

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.  
Refer to instruction manuals for details of input derating.



Model	STMGFS804812	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V6.7A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-20	11.982	11.983	11.980	11.980	11.979
25	12.014	12.015	12.007	12.007	12.006
40	12.018	12.018	12.011	12.011	12.010

Note: In case of input Volt.18V, Load 70%. 24V, Load 80%.

Other case Load 100%.

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V6.7A	

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 70%
-20	15.2	15.4
25	15.2	15.4
40	15.2	15.2

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+12V6.7A	

## 1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]				
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-20	14.86	14.86	14.86	14.87	14.87
25	14.92	14.93	14.93	14.94	14.94
50	14.92	14.93	14.93	14.94	14.93

COSEL




Figure A




Figure B (Ripple noise Characteristic)