



TEST DATA OF STMGFW302405

Regulated DC Power Supply
January 30, 2013

Approved by :

Takahiro Yoneda

Takahiro Yoneda

Design Manager

Prepared by :

Satoshi Kinoshita

Satoshi Kinoshita

Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple Voltage (by Load Current)	8
9.Ripple-Noise	10
10.Ripple Voltage (by Ambient Temperature)	12
11.Ambient Temperature Drift	13
12.Output Voltage Accuracy	14
13.Time Lapse Drift	15
14.Rise and Fall Time	16
15.Minimum Input Voltage for Regulated Output Voltage	18
16.Overcurrent Protection	19
17.Overvoltage Protection	20
18.Figure of Testing Circuitry	21

(Final Page 21)

Model	STMGFW302405	Temperature 25°C Testing Circuitry Figure A																																																																																
Item	Input Current (by Input Voltage)																																																																																	
Object	—																																																																																	
1.Graph	<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend: Load 100% (△), Load 50% (□), Load 0% (○)</p>																																																																																	
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.003</td></tr> <tr><td>7.0</td><td>0.003</td><td>0.002</td><td>0.003</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.002</td></tr> <tr><td>8.4</td><td>0.034</td><td>1.411</td><td>0.002</td></tr> <tr><td>8.5</td><td>0.035</td><td>1.399</td><td>0.002</td></tr> <tr><td>8.8</td><td>0.035</td><td>1.338</td><td>2.856</td></tr> <tr><td>9.0</td><td>0.035</td><td>1.287</td><td>2.625</td></tr> <tr><td>9.2</td><td>0.036</td><td>1.286</td><td>2.784</td></tr> <tr><td>9.8</td><td>0.035</td><td>1.200</td><td>2.601</td></tr> <tr><td>12.0</td><td>0.028</td><td>0.970</td><td>2.007</td></tr> <tr><td>18.0</td><td>0.020</td><td>0.664</td><td>1.315</td></tr> <tr><td>24.0</td><td>0.017</td><td>0.508</td><td>0.984</td></tr> <tr><td>36.0</td><td>0.017</td><td>0.354</td><td>0.674</td></tr> <tr><td>40.0</td><td>0.016</td><td>0.324</td><td>0.645</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.002	0.002	0.003	7.0	0.003	0.002	0.003	8.0	0.003	0.003	0.002	8.4	0.034	1.411	0.002	8.5	0.035	1.399	0.002	8.8	0.035	1.338	2.856	9.0	0.035	1.287	2.625	9.2	0.036	1.286	2.784	9.8	0.035	1.200	2.601	12.0	0.028	0.970	2.007	18.0	0.020	0.664	1.315	24.0	0.017	0.508	0.984	36.0	0.017	0.354	0.674	40.0	0.016	0.324	0.645	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
6.0	0.002	0.002	0.003																																																																															
7.0	0.003	0.002	0.003																																																																															
8.0	0.003	0.003	0.002																																																																															
8.4	0.034	1.411	0.002																																																																															
8.5	0.035	1.399	0.002																																																																															
8.8	0.035	1.338	2.856																																																																															
9.0	0.035	1.287	2.625																																																																															
9.2	0.036	1.286	2.784																																																																															
9.8	0.035	1.200	2.601																																																																															
12.0	0.028	0.970	2.007																																																																															
18.0	0.020	0.664	1.315																																																																															
24.0	0.017	0.508	0.984																																																																															
36.0	0.017	0.354	0.674																																																																															
40.0	0.016	0.324	0.645																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
	<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	

COSEL

Model	STMGFW302405	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Input Current (by Load Current)																																																																																			
Object	_____																																																																																			
1.Graph	<p>—△— Input Volt. 9V - - □ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◆ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.036</td><td>0.027</td><td>0.020</td><td>0.018</td><td>0.016</td></tr> <tr><td>20</td><td>0.558</td><td>0.422</td><td>0.288</td><td>0.225</td><td>0.165</td></tr> <tr><td>40</td><td>1.063</td><td>0.797</td><td>0.542</td><td>0.416</td><td>0.293</td></tr> <tr><td>60</td><td>1.575</td><td>1.177</td><td>0.795</td><td>0.605</td><td>0.420</td></tr> <tr><td>80</td><td>2.084</td><td>1.571</td><td>1.048</td><td>0.792</td><td>0.545</td></tr> <tr><td>100</td><td>2.625</td><td>2.007</td><td>1.315</td><td>0.984</td><td>0.674</td></tr> <tr><td>110</td><td>2.895</td><td>2.147</td><td>1.443</td><td>1.083</td><td>0.740</td></tr> </tbody> </table>	Load Ration [%]	9V [A]	12V [A]	18V [A]	24V [A]	36V [A]	0	0.036	0.027	0.020	0.018	0.016	20	0.558	0.422	0.288	0.225	0.165	40	1.063	0.797	0.542	0.416	0.293	60	1.575	1.177	0.795	0.605	0.420	80	2.084	1.571	1.048	0.792	0.545	100	2.625	2.007	1.315	0.984	0.674	110	2.895	2.147	1.443	1.083	0.740																																			
Load Ration [%]	9V [A]	12V [A]	18V [A]	24V [A]	36V [A]																																																																															
0	0.036	0.027	0.020	0.018	0.016																																																																															
20	0.558	0.422	0.288	0.225	0.165																																																																															
40	1.063	0.797	0.542	0.416	0.293																																																																															
60	1.575	1.177	0.795	0.605	0.420																																																																															
80	2.084	1.571	1.048	0.792	0.545																																																																															
100	2.625	2.007	1.315	0.984	0.674																																																																															
110	2.895	2.147	1.443	1.083	0.740																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.036</td><td>0.027</td><td>0.020</td><td>0.018</td><td>0.016</td></tr> <tr><td>20</td><td>0.558</td><td>0.422</td><td>0.288</td><td>0.225</td><td>0.165</td></tr> <tr><td>40</td><td>1.063</td><td>0.797</td><td>0.542</td><td>0.416</td><td>0.293</td></tr> <tr><td>60</td><td>1.575</td><td>1.177</td><td>0.795</td><td>0.605</td><td>0.420</td></tr> <tr><td>80</td><td>2.084</td><td>1.571</td><td>1.048</td><td>0.792</td><td>0.545</td></tr> <tr><td>100</td><td>2.625</td><td>2.007</td><td>1.315</td><td>0.984</td><td>0.674</td></tr> <tr><td>110</td><td>2.895</td><td>2.147</td><td>1.443</td><td>1.083</td><td>0.740</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.036	0.027	0.020	0.018	0.016	20	0.558	0.422	0.288	0.225	0.165	40	1.063	0.797	0.542	0.416	0.293	60	1.575	1.177	0.795	0.605	0.420	80	2.084	1.571	1.048	0.792	0.545	100	2.625	2.007	1.315	0.984	0.674	110	2.895	2.147	1.443	1.083	0.740	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-						
Load Ration [%]	Input Current [A]																																																																																			
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
0	0.036	0.027	0.020	0.018	0.016																																																																															
20	0.558	0.422	0.288	0.225	0.165																																																																															
40	1.063	0.797	0.542	0.416	0.293																																																																															
60	1.575	1.177	0.795	0.605	0.420																																																																															
80	2.084	1.571	1.048	0.792	0.545																																																																															
100	2.625	2.007	1.315	0.984	0.674																																																																															
110	2.895	2.147	1.443	1.083	0.740																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															


COSEL

Model	STMGFW302405	Temperature	25°C																																																																								
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																																								
Object																																																																											
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - -□-- Input Volt. 12V - -*-- Input Volt. 18V - -○-- Input Volt. 24V - -◇-- Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.32</td><td>0.33</td><td>0.35</td><td>0.42</td><td>0.58</td></tr> <tr><td>20</td><td>5.00</td><td>5.09</td><td>5.19</td><td>5.40</td><td>5.93</td></tr> <tr><td>40</td><td>9.53</td><td>9.57</td><td>9.75</td><td>9.98</td><td>10.55</td></tr> <tr><td>60</td><td>14.22</td><td>14.15</td><td>14.28</td><td>14.48</td><td>15.05</td></tr> <tr><td>80</td><td>18.90</td><td>18.82</td><td>18.90</td><td>19.07</td><td>19.62</td></tr> <tr><td>100</td><td>23.75</td><td>23.84</td><td>23.66</td><td>23.73</td><td>24.25</td></tr> <tr><td>110</td><td>26.23</td><td>26.00</td><td>25.87</td><td>26.11</td><td>26.59</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	9[V]	12[V]	18[V]	24[V]	36[V]	0	0.32	0.33	0.35	0.42	0.58	20	5.00	5.09	5.19	5.40	5.93	40	9.53	9.57	9.75	9.98	10.55	60	14.22	14.15	14.28	14.48	15.05	80	18.90	18.82	18.90	19.07	19.62	100	23.75	23.84	23.66	23.73	24.25	110	26.23	26.00	25.87	26.11	26.59	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																						
0	0.32	0.33	0.35	0.42	0.58																																																																						
20	5.00	5.09	5.19	5.40	5.93																																																																						
40	9.53	9.57	9.75	9.98	10.55																																																																						
60	14.22	14.15	14.28	14.48	15.05																																																																						
80	18.90	18.82	18.90	19.07	19.62																																																																						
100	23.75	23.84	23.66	23.73	24.25																																																																						
110	26.23	26.00	25.87	26.11	26.59																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
2.Values																																																																											

COSEL

Model	STMGFW302405
Item	Efficiency (by Input Voltage)
Object	—

1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.5	85.9	85.2
9.0	86.4	85.5
12.0	85.9	86.1
15.0	85.1	86.2
18.0	83.8	86.1
24.0	82.9	85.7
30.0	81.0	84.8
36.0	79.1	83.8
40.0	77.9	83.0

COSEL

Model	STMGFW302405	Temperature	25°C																																																																													
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																																													
Object																																																																																
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>81.2</td><td>79.8</td><td>78.1</td><td>75.2</td><td>68.4</td></tr> <tr><td>40</td><td>85.2</td><td>84.9</td><td>83.3</td><td>81.4</td><td>77.0</td></tr> <tr><td>60</td><td>85.7</td><td>86.1</td><td>85.4</td><td>84.2</td><td>81.0</td></tr> <tr><td>80</td><td>86.0</td><td>86.4</td><td>86.0</td><td>85.3</td><td>82.9</td></tr> <tr><td>100</td><td>85.5</td><td>85.2</td><td>85.9</td><td>85.6</td><td>83.8</td></tr> <tr><td>110</td><td>85.2</td><td>86.0</td><td>86.4</td><td>85.6</td><td>84.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	-	-	20	81.2	79.8	78.1	75.2	68.4	40	85.2	84.9	83.3	81.4	77.0	60	85.7	86.1	85.4	84.2	81.0	80	86.0	86.4	86.0	85.3	82.9	100	85.5	85.2	85.9	85.6	83.8	110	85.2	86.0	86.4	85.6	84.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																															
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																											
0	-	-	-	-	-																																																																											
20	81.2	79.8	78.1	75.2	68.4																																																																											
40	85.2	84.9	83.3	81.4	77.0																																																																											
60	85.7	86.1	85.4	84.2	81.0																																																																											
80	86.0	86.4	86.0	85.3	82.9																																																																											
100	85.5	85.2	85.9	85.6	83.8																																																																											
110	85.2	86.0	86.4	85.6	84.1																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

Model	STMGFW302405	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+5V2A																																		
1.Graph			2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>5.123</td><td>5.076</td></tr> <tr><td>9.0</td><td>5.123</td><td>5.077</td></tr> <tr><td>12.0</td><td>5.122</td><td>5.078</td></tr> <tr><td>15.0</td><td>5.122</td><td>5.079</td></tr> <tr><td>18.0</td><td>5.122</td><td>5.079</td></tr> <tr><td>24.0</td><td>5.121</td><td>5.080</td></tr> <tr><td>30.0</td><td>5.121</td><td>5.080</td></tr> <tr><td>36.0</td><td>5.121</td><td>5.080</td></tr> <tr><td>40.0</td><td>5.121</td><td>5.080</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	5.123	5.076	9.0	5.123	5.077	12.0	5.122	5.078	15.0	5.122	5.079	18.0	5.122	5.079	24.0	5.121	5.080	30.0	5.121	5.080	36.0	5.121	5.080	40.0	5.121	5.080
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.5	5.123	5.076																																	
9.0	5.123	5.077																																	
12.0	5.122	5.078																																	
15.0	5.122	5.079																																	
18.0	5.122	5.079																																	
24.0	5.121	5.080																																	
30.0	5.121	5.080																																	
36.0	5.121	5.080																																	
40.0	5.121	5.080																																	
Object			2.Values																																
1.Graph			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>-5.125</td><td>-5.073</td></tr> <tr><td>9.0</td><td>-5.124</td><td>-5.073</td></tr> <tr><td>12.0</td><td>-5.121</td><td>-5.072</td></tr> <tr><td>15.0</td><td>-5.119</td><td>-5.071</td></tr> <tr><td>18.0</td><td>-5.118</td><td>-5.071</td></tr> <tr><td>24.0</td><td>-5.117</td><td>-5.071</td></tr> <tr><td>30.0</td><td>-5.117</td><td>-5.071</td></tr> <tr><td>36.0</td><td>-5.116</td><td>-5.071</td></tr> <tr><td>40.0</td><td>-5.116</td><td>-5.071</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	-5.125	-5.073	9.0	-5.124	-5.073	12.0	-5.121	-5.072	15.0	-5.119	-5.071	18.0	-5.118	-5.071	24.0	-5.117	-5.071	30.0	-5.117	-5.071	36.0	-5.116	-5.071	40.0	-5.116	-5.071
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.5	-5.125	-5.073																																	
9.0	-5.124	-5.073																																	
12.0	-5.121	-5.072																																	
15.0	-5.119	-5.071																																	
18.0	-5.118	-5.071																																	
24.0	-5.117	-5.071																																	
30.0	-5.117	-5.071																																	
36.0	-5.116	-5.071																																	
40.0	-5.116	-5.071																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																			
Note: Slanted line shows the range of the rated input voltage.																																			

COSEL


Model	STMGFW302405	Temperature	25°C																																																																								
Item	Load Regulation	Testing Circuitry	Figure A																																																																								
Object	+5V2A	2.Values																																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																										
	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.564</td><td>5.571</td><td>5.600</td><td>5.615</td><td>5.647</td></tr> <tr><td>0.4</td><td>5.161</td><td>5.161</td><td>5.160</td><td>5.161</td><td>5.162</td></tr> <tr><td>0.8</td><td>5.135</td><td>5.135</td><td>5.134</td><td>5.134</td><td>5.134</td></tr> <tr><td>1.2</td><td>5.114</td><td>5.114</td><td>5.114</td><td>5.114</td><td>5.114</td></tr> <tr><td>1.6</td><td>5.095</td><td>5.096</td><td>5.096</td><td>5.096</td><td>5.096</td></tr> <tr><td>2.0</td><td>5.076</td><td>5.078</td><td>5.079</td><td>5.079</td><td>5.079</td></tr> <tr><td>2.2</td><td>5.067</td><td>5.069</td><td>5.070</td><td>5.071</td><td>5.071</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.0	5.564	5.571	5.600	5.615	5.647	0.4	5.161	5.161	5.160	5.161	5.162	0.8	5.135	5.135	5.134	5.134	5.134	1.2	5.114	5.114	5.114	5.114	5.114	1.6	5.095	5.096	5.096	5.096	5.096	2.0	5.076	5.078	5.079	5.079	5.079	2.2	5.067	5.069	5.070	5.071	5.071	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																						
0.0	5.564	5.571	5.600	5.615	5.647																																																																						
0.4	5.161	5.161	5.160	5.161	5.162																																																																						
0.8	5.135	5.135	5.134	5.134	5.134																																																																						
1.2	5.114	5.114	5.114	5.114	5.114																																																																						
1.6	5.095	5.096	5.096	5.096	5.096																																																																						
2.0	5.076	5.078	5.079	5.079	5.079																																																																						
2.2	5.067	5.069	5.070	5.071	5.071																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
Object	-5V2A	2.Values																																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																										
	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.413</td><td>-5.462</td><td>-5.432</td><td>-5.520</td><td>-5.758</td></tr> <tr><td>0.4</td><td>-5.170</td><td>-5.171</td><td>-5.177</td><td>-5.179</td><td>-5.184</td></tr> <tr><td>0.8</td><td>-5.136</td><td>-5.132</td><td>-5.130</td><td>-5.129</td><td>-5.130</td></tr> <tr><td>1.2</td><td>-5.113</td><td>-5.110</td><td>-5.108</td><td>-5.106</td><td>-5.106</td></tr> <tr><td>1.6</td><td>-5.093</td><td>-5.090</td><td>-5.089</td><td>-5.088</td><td>-5.088</td></tr> <tr><td>2.0</td><td>-5.073</td><td>-5.072</td><td>-5.071</td><td>-5.070</td><td>-5.070</td></tr> <tr><td>2.2</td><td>-5.064</td><td>-5.063</td><td>-5.062</td><td>-5.062</td><td>-5.062</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.0	-5.413	-5.462	-5.432	-5.520	-5.758	0.4	-5.170	-5.171	-5.177	-5.179	-5.184	0.8	-5.136	-5.132	-5.130	-5.129	-5.130	1.2	-5.113	-5.110	-5.108	-5.106	-5.106	1.6	-5.093	-5.090	-5.089	-5.088	-5.088	2.0	-5.073	-5.072	-5.071	-5.070	-5.070	2.2	-5.064	-5.063	-5.062	-5.062	-5.062	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																						
0.0	-5.413	-5.462	-5.432	-5.520	-5.758																																																																						
0.4	-5.170	-5.171	-5.177	-5.179	-5.184																																																																						
0.8	-5.136	-5.132	-5.130	-5.129	-5.130																																																																						
1.2	-5.113	-5.110	-5.108	-5.106	-5.106																																																																						
1.6	-5.093	-5.090	-5.089	-5.088	-5.088																																																																						
2.0	-5.073	-5.072	-5.071	-5.070	-5.070																																																																						
2.2	-5.064	-5.063	-5.062	-5.062	-5.062																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
--	-	-	-	-	-																																																																						
Note:	Slanted line shows the range of the rated load current.																																																																										

COSEL

Model	STMGFW302405
Item	Ripple Voltage (by Load Current)
Object	+5V2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	15	15
0.4	15	15
0.8	15	15
1.2	15	15
1.6	15	15
2.0	15	15
2.2	15	15
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	STMGFW302405
Item	Ripple Voltage (by Load Current)
Object	-5V2A

1. Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

Temperature 25°C
 Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	20	20
0.4	20	20
0.8	20	20
1.2	20	20
1.6	20	20
2.0	20	20
2.2	20	20
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

COSEL


Model STMGFW302405

Item Ripple-Noise

Object +5V2A

1. Graph

—△— Input Volt. 9V
 -○--- Input Volt. 36V



Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	20	20
0.4	20	20
0.8	20	20
1.2	20	20
1.6	20	20
2.0	20	20
2.2	20	20
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current




Fig.Complex Ripple Noise Wave Form


COSEL

Model	STMGFW302405																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-5V2A																																							
1.Graph																																								
		2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>30</td><td>30</td></tr> <tr><td>0.4</td><td>30</td><td>30</td></tr> <tr><td>0.8</td><td>30</td><td>30</td></tr> <tr><td>1.2</td><td>30</td><td>30</td></tr> <tr><td>1.6</td><td>30</td><td>30</td></tr> <tr><td>2.0</td><td>30</td><td>30</td></tr> <tr><td>2.2</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	30	30	0.4	30	30	0.8	30	30	1.2	30	30	1.6	30	30	2.0	30	30	2.2	30	30	--	-	-	--	-	-	--	-	-	--	-	-	+5V: Rated output current
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.0	30	30																																						
0.4	30	30																																						
0.8	30	30																																						
1.2	30	30																																						
1.6	30	30																																						
2.0	30	30																																						
2.2	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

COSEL

Model	STMGFW302405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2A

1.Graph



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	20	20
-20	20	20
0	15	15
25	15	15
60	15	15
65	15	15
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Object	-5V2A
--------	-------

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	25	25
-20	25	25
0	20	20
25	20	20
60	20	20
65	20	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-40	5.054	5.055	5.057	5.057	5.058
-20	5.063	5.064	5.065	5.066	5.066
0	5.070	5.072	5.073	5.074	5.074
10	5.073	5.075	5.076	5.076	5.076
25	5.076	5.078	5.079	5.079	5.079
30	5.077	5.079	5.080	5.080	5.080
40	5.078	5.080	5.081	5.082	5.082
50	5.079	5.081	5.082	5.082	5.082
60	5.080	5.081	5.082	5.083	5.083
65	5.080	5.081	5.082	5.083	5.083
--	-	-	-	-	-

2. Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-40	-5.049	-5.049	-5.049	-5.049	-5.049
-20	-5.058	-5.058	-5.057	-5.057	-5.058
0	-5.066	-5.065	-5.065	-5.065	-5.065
10	-5.069	-5.068	-5.067	-5.067	-5.068
25	-5.072	-5.071	-5.070	-5.070	-5.070
30	-5.073	-5.072	-5.071	-5.071	-5.071
40	-5.075	-5.073	-5.072	-5.072	-5.072
50	-5.076	-5.074	-5.073	-5.073	-5.073
60	-5.076	-5.075	-5.074	-5.073	-5.073
65	-5.076	-5.075	-5.074	-5.073	-5.073
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	STMGFW302405	Testing Circuitry . Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 2A (AVR 2) : 0 - 2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	10	36	0	5.645	±291	±5.8
Minimum Voltage	-20	9	2	5.063		

Object	-5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	36	0	-5.796	±370	±7.4
Minimum Voltage	-20	24	2	-5.057		


COSEL

Model STMGFW302405

Item Time Lapse Drift

Object +5V2A

1.Graph




Input Volt. 24V

Load 100%

Object -5V2A

1.Graph



Input Volt. 24V

Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	5.065
0.5	5.068
1.0	5.068
2.0	5.068
3.0	5.068
4.0	5.068
5.0	5.068
6.0	5.068
7.0	5.068
8.0	5.068

2.Values


Time since start [H]	Output Voltage [V]
0.0	-5.078
0.5	-5.084
1.0	-5.084
2.0	-5.084
3.0	-5.084
4.0	-5.084
5.0	-5.084
6.0	-5.084
7.0	-5.084
8.0	-5.084

COSEL

Model STMGFW302405


Temperature 25°C
Testing Circuitry Figure AItem Rise and Fall Time
Object +5V2A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.9	7.9	9.8	0.3	1.0	
100 %		1.9	8.2	10.1	0.2	0.6	




COSEL

Model STMGFW302405

Temperature 25°C
Testing Circuitry Figure AItem Rise and Fall Time
Object -5V2A

1. Graph


Input Volt. 24 V



2. Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.9	7.5	9.4	0.3	1.1
100 %		1.9	7.4	9.3	0.2	0.7




COSEL

Model	STMGFW302405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	8.0	8.2
-20	8.1	8.2
0	8.1	8.1
10	8.2	8.1
25	8.1	8.2
30	8.1	8.3
40	8.1	8.3
50	8.1	8.3
60	8.2	8.3
65	8.2	8.3
--	-	-

Object	-5V2A
--------	-------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	7.9	8.1
-20	8.0	8.1
0	8.0	8.2
10	8.0	8.2
25	8.0	8.2
30	8.0	8.2
40	8.0	8.2
50	8.0	8.2
60	8.1	8.1
65	8.1	8.1
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	STMGFW302405	Temperature	25°C																																																																																			
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																																			
Object	+5V2A																																																																																					
1.Graph																																																																																						
Object	-5V2A																																																																																					
1.Graph																																																																																						
Note:	Slanted line shows the range of the rated load current.																																																																																					
	Intermittent operation occurs when overcurrent protection is activated.																																																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>3.065</td><td>3.459</td><td>3.718</td><td>3.671</td><td>3.203</td></tr> <tr><td>4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	5.00	3.065	3.459	3.718	3.671	3.203	4.75	-	-	-	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																	
5.00	3.065	3.459	3.718	3.671	3.203																																																																																	
4.75	-	-	-	-	-																																																																																	
4.50	-	-	-	-	-																																																																																	
4.00	-	-	-	-	-																																																																																	
3.50	-	-	-	-	-																																																																																	
3.00	-	-	-	-	-																																																																																	
2.50	-	-	-	-	-																																																																																	
2.00	-	-	-	-	-																																																																																	
1.50	-	-	-	-	-																																																																																	
1.00	-	-	-	-	-																																																																																	
0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-5.00</td><td>3.081</td><td>3.466</td><td>3.713</td><td>3.660</td><td>3.221</td></tr> <tr><td>-4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-5.00	3.081	3.466	3.713	3.660	3.221	-4.75	-	-	-	-	-	-4.50	-	-	-	-	-	-4.00	-	-	-	-	-	-3.50	-	-	-	-	-	-3.00	-	-	-	-	-	-2.50	-	-	-	-	-	-2.00	-	-	-	-	-	-1.50	-	-	-	-	-	-1.00	-	-	-	-	-	-0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																	
-5.00	3.081	3.466	3.713	3.660	3.221																																																																																	
-4.75	-	-	-	-	-																																																																																	
-4.50	-	-	-	-	-																																																																																	
-4.00	-	-	-	-	-																																																																																	
-3.50	-	-	-	-	-																																																																																	
-3.00	-	-	-	-	-																																																																																	
-2.50	-	-	-	-	-																																																																																	
-2.00	-	-	-	-	-																																																																																	
-1.50	-	-	-	-	-																																																																																	
-1.00	-	-	-	-	-																																																																																	
-0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	

Model	STMGFW302405
Item	Overvoltage Protection
Object	+10V2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-40	13.48	13.49
-20	13.63	13.64
0	13.77	13.78
25	13.98	14.00
60	14.20	14.29
65	14.28	14.29
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)