



TEST DATA OF SUW100515 SUCW100515

Regulated DC Power Supply
Mar 28, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)



Model		SUW100515/SUCW100515		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object																																																																																				
1. Graph			2. Values																																																																																	
<p> —△— Load 100% - - - □ - - Load 50% - - - ○ - - Load 0% </p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.16</td><td>0.126</td><td>1.463</td><td>2.990</td></tr> <tr><td>4.50</td><td>0.117</td><td>1.356</td><td>2.727</td></tr> <tr><td>5.00</td><td>0.105</td><td>1.245</td><td>2.471</td></tr> <tr><td>6.00</td><td>0.092</td><td>1.031</td><td>2.040</td></tr> <tr><td>7.00</td><td>0.080</td><td>0.891</td><td>1.723</td></tr> <tr><td>8.00</td><td>0.071</td><td>0.789</td><td>1.507</td></tr> <tr><td>9.00</td><td>0.065</td><td>0.688</td><td>1.335</td></tr> <tr><td>10.00</td><td>0.059</td><td>0.612</td><td>1.219</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.000	0.000	0.000	2.00	0.000	0.000	0.000	3.00	0.000	0.000	0.000	4.00	0.000	0.000	0.000	4.16	0.126	1.463	2.990	4.50	0.117	1.356	2.727	5.00	0.105	1.245	2.471	6.00	0.092	1.031	2.040	7.00	0.080	0.891	1.723	8.00	0.071	0.789	1.507	9.00	0.065	0.688	1.335	10.00	0.059	0.612	1.219	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.00	0.000	0.000	0.000																																																																																	
1.70	0.000	0.000	0.000																																																																																	
2.00	0.000	0.000	0.000																																																																																	
3.00	0.000	0.000	0.000																																																																																	
4.00	0.000	0.000	0.000																																																																																	
4.16	0.126	1.463	2.990																																																																																	
4.50	0.117	1.356	2.727																																																																																	
5.00	0.105	1.245	2.471																																																																																	
6.00	0.092	1.031	2.040																																																																																	
7.00	0.080	0.891	1.723																																																																																	
8.00	0.071	0.789	1.507																																																																																	
9.00	0.065	0.688	1.335																																																																																	
10.00	0.059	0.612	1.219																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		SUW100515/SUCW100515		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph			—△— Input Volt. 4.5V	2. Values																																																				
			- - -□- - Input Volt. 5V																																																					
			- · - ○ - · - Input Volt. 9V																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.117</td><td>0.107</td><td>0.066</td></tr> <tr><td>20</td><td>0.615</td><td>0.549</td><td>0.320</td></tr> <tr><td>40</td><td>1.136</td><td>1.013</td><td>0.559</td></tr> <tr><td>60</td><td>1.637</td><td>1.496</td><td>0.838</td></tr> <tr><td>80</td><td>2.154</td><td>1.960</td><td>1.078</td></tr> <tr><td>100</td><td>2.769</td><td>2.422</td><td>1.343</td></tr> <tr><td>110</td><td>2.997</td><td>2.655</td><td>1.460</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.117	0.107	0.066	20	0.615	0.549	0.320	40	1.136	1.013	0.559	60	1.637	1.496	0.838	80	2.154	1.960	1.078	100	2.769	2.422	1.343	110	2.997	2.655	1.460	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.117	0.107	0.066																																																					
20	0.615	0.549	0.320																																																					
40	1.136	1.013	0.559																																																					
60	1.637	1.496	0.838																																																					
80	2.154	1.960	1.078																																																					
100	2.769	2.422	1.343																																																					
110	2.997	2.655	1.460																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					




Model		SUW100515/SUCW100515		Temperature	25°C																																																			
Item		Input Power (by Load Current)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1. Graph			—△— Input Volt. 4.5V	2. Values																																																				
			- - -□- - - Input Volt. 5V																																																					
			- · - ○ - · - - Input Volt. 9V																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.52</td><td>0.53</td><td>0.59</td></tr> <tr><td>20</td><td>2.73</td><td>2.73</td><td>2.88</td></tr> <tr><td>40</td><td>5.07</td><td>5.08</td><td>5.00</td></tr> <tr><td>60</td><td>7.37</td><td>7.35</td><td>7.50</td></tr> <tr><td>80</td><td>9.76</td><td>9.71</td><td>9.73</td></tr> <tr><td>100</td><td>12.22</td><td>12.09</td><td>12.00</td></tr> <tr><td>110</td><td>13.49</td><td>13.32</td><td>13.13</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.52	0.53	0.59	20	2.73	2.73	2.88	40	5.07	5.08	5.00	60	7.37	7.35	7.50	80	9.76	9.71	9.73	100	12.22	12.09	12.00	110	13.49	13.32	13.13	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.52	0.53	0.59																																																					
20	2.73	2.73	2.88																																																					
40	5.07	5.08	5.00																																																					
60	7.37	7.35	7.50																																																					
80	9.76	9.71	9.73																																																					
100	12.22	12.09	12.00																																																					
110	13.49	13.32	13.13																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		SUW100515/SUCW100515		Temperature		25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry		Figure A																																	
Object		_____																																					
1. Graph				2. Values																																			
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>84.5</td><td>84.9</td></tr> <tr><td>4.5</td><td>84.5</td><td>85.6</td></tr> <tr><td>5.0</td><td>84.6</td><td>86.4</td></tr> <tr><td>6.0</td><td>84.2</td><td>87.1</td></tr> <tr><td>7.0</td><td>83.7</td><td>87.4</td></tr> <tr><td>8.0</td><td>83.0</td><td>87.4</td></tr> <tr><td>9.0</td><td>83.5</td><td>87.2</td></tr> <tr><td>10.0</td><td>84.5</td><td>86.9</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	84.5	84.9	4.5	84.5	85.6	5.0	84.6	86.4	6.0	84.2	87.1	7.0	83.7	87.4	8.0	83.0	87.4	9.0	83.5	87.2	10.0	84.5	86.9	-	-	-
Input Voltage [V]	Efficiency [%]																																						
	Load 50%	Load 100%																																					
4.0	84.5	84.9																																					
4.5	84.5	85.6																																					
5.0	84.6	86.4																																					
6.0	84.2	87.1																																					
7.0	83.7	87.4																																					
8.0	83.0	87.4																																					
9.0	83.5	87.2																																					
10.0	84.5	86.9																																					
-	-	-																																					
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																							




Model		SUW100515/SUCW100515		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph		—△— Input Volt. 4.5V - - - □ - - Input Volt. 5V - · - ○ - · - Input Volt. 9V		2. Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>77.3</td><td>77.2</td><td>73.3</td></tr> <tr><td>40</td><td>82.7</td><td>82.5</td><td>83.9</td></tr> <tr><td>60</td><td>85.2</td><td>85.4</td><td>83.7</td></tr> <tr><td>80</td><td>85.7</td><td>86.1</td><td>86.0</td></tr> <tr><td>100</td><td>85.4</td><td>86.3</td><td>87.0</td></tr> <tr><td>110</td><td>85.1</td><td>86.2</td><td>87.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	77.3	77.2	73.3	40	82.7	82.5	83.9	60	85.2	85.4	83.7	80	85.7	86.1	86.0	100	85.4	86.3	87.0	110	85.1	86.2	87.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	-	-	-																																																					
20	77.3	77.2	73.3																																																					
40	82.7	82.5	83.9																																																					
60	85.2	85.4	83.7																																																					
80	85.7	86.1	86.0																																																					
100	85.4	86.3	87.0																																																					
110	85.1	86.2	87.4																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	14.964	14.865
4.5	14.957	14.865
5.0	14.952	14.864
6.0	14.945	14.864
7.0	14.940	14.864
8.0	14.937	14.864
9.0	14.935	14.864
10.0	14.933	14.864
--	-	-



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	-14.960	-14.860
4.5	-14.954	-14.860
5.0	-14.949	-14.861
6.0	-14.942	-14.861
7.0	-14.936	-14.860
8.0	-14.933	-14.860
9.0	-14.931	-14.860
10.0	-14.930	-14.859
--	-	-



<p>Model SUW100515/SUCW100515</p> <p>Item Load Regulation</p> <p>Object +15V0.35A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																			
<p>1.Graph</p> <p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>-·-○-·- Input Volt. 9V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.208</td><td>15.205</td><td>15.234</td></tr> <tr><td>0.070</td><td>15.019</td><td>15.012</td><td>14.998</td></tr> <tr><td>0.140</td><td>14.976</td><td>14.970</td><td>14.952</td></tr> <tr><td>0.210</td><td>14.937</td><td>14.933</td><td>14.920</td></tr> <tr><td>0.280</td><td>14.900</td><td>14.899</td><td>14.891</td></tr> <tr><td>0.350</td><td>14.863</td><td>14.864</td><td>14.864</td></tr> <tr><td>0.385</td><td>14.845</td><td>14.846</td><td>14.850</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	15.208	15.205	15.234	0.070	15.019	15.012	14.998	0.140	14.976	14.970	14.952	0.210	14.937	14.933	14.920	0.280	14.900	14.899	14.891	0.350	14.863	14.864	14.864	0.385	14.845	14.846	14.850	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	15.208	15.205	15.234																																																		
0.070	15.019	15.012	14.998																																																		
0.140	14.976	14.970	14.952																																																		
0.210	14.937	14.933	14.920																																																		
0.280	14.900	14.899	14.891																																																		
0.350	14.863	14.864	14.864																																																		
0.385	14.845	14.846	14.850																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Object -15V0.35A</p> <p>1.Graph</p> <p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>-·-○-·- Input Volt. 9V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.177</td><td>-15.166</td><td>-15.192</td></tr> <tr><td>0.070</td><td>-15.016</td><td>-15.008</td><td>-14.993</td></tr> <tr><td>0.140</td><td>-14.973</td><td>-14.967</td><td>-14.948</td></tr> <tr><td>0.210</td><td>-14.934</td><td>-14.930</td><td>-14.916</td></tr> <tr><td>0.280</td><td>-14.897</td><td>-14.895</td><td>-14.887</td></tr> <tr><td>0.350</td><td>-14.860</td><td>-14.860</td><td>-14.860</td></tr> <tr><td>0.385</td><td>-14.842</td><td>-14.844</td><td>-14.847</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-15.177	-15.166	-15.192	0.070	-15.016	-15.008	-14.993	0.140	-14.973	-14.967	-14.948	0.210	-14.934	-14.930	-14.916	0.280	-14.897	-14.895	-14.887	0.350	-14.860	-14.860	-14.860	0.385	-14.842	-14.844	-14.847	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	-15.177	-15.166	-15.192																																																		
0.070	-15.016	-15.008	-14.993																																																		
0.140	-14.973	-14.967	-14.948																																																		
0.210	-14.934	-14.930	-14.916																																																		
0.280	-14.897	-14.895	-14.887																																																		
0.350	-14.860	-14.860	-14.860																																																		
0.385	-14.842	-14.844	-14.847																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




Model	SUW100515/SUCW100515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.35A		


Input Volt. 5 V
Cycle 100 mS



Min. Load (0A) ←→
Load 100% (0.35A)




500µs/div




500µs/div

Min. Load (0A) ←→
Load 50% (0.175A)




500µs/div




500µs/div

Load 50% (0.175A) ←→
Load 100% (0.35A)



500µs/div




500µs/div




Model		SUW100515/SUCW100515	
Item		Temperature	25°C
Object		Testing Circuitry	Figure A
		-15V0.35A	

Input Volt. 5 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.35A)

200mV/div




500µs/div




500µs/div

Min. Load (0A) ←→
Load 50% (0.175A)

200mV/div




500µs/div




500µs/div

Load 50% (0.175A) ←→
Load 100% (0.35A)

200mV/div



500µs/div



500µs/div



<p>Model SUW100515/SUCW100515</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object +15V0.35A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> </div> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>3</td></tr> <tr><td>0.070</td><td>2</td><td>3</td></tr> <tr><td>0.140</td><td>3</td><td>3</td></tr> <tr><td>0.210</td><td>4</td><td>4</td></tr> <tr><td>0.280</td><td>5</td><td>4</td></tr> <tr><td>0.350</td><td>6</td><td>5</td></tr> <tr><td>0.385</td><td>6</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	2	3	0.070	2	3	0.140	3	3	0.210	4	4	0.280	5	4	0.350	6	5	0.385	6	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	2	3																																						
0.070	2	3																																						
0.140	3	3																																						
0.210	4	4																																						
0.280	5	4																																						
0.350	6	5																																						
0.385	6	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																								



<p>Model SUW100515/SUCW100515</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object -15V0.35A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1. Graph</p> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>3</td></tr> <tr><td>0.070</td><td>2</td><td>3</td></tr> <tr><td>0.140</td><td>3</td><td>3</td></tr> <tr><td>0.210</td><td>4</td><td>4</td></tr> <tr><td>0.280</td><td>5</td><td>4</td></tr> <tr><td>0.350</td><td>6</td><td>5</td></tr> <tr><td>0.385</td><td>6</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	2	3	0.070	2	3	0.140	3	3	0.210	4	4	0.280	5	4	0.350	6	5	0.385	6	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	2	3																																						
0.070	2	3																																						
0.140	3	3																																						
0.210	4	4																																						
0.280	5	4																																						
0.350	6	5																																						
0.385	6	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																								



<p>Model SUW100515/SUCW100515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +15V0.35A</p>																																								
<p>1. Graph</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> </div> <div style="text-align: center;"> </div> </div>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>3</td><td>4</td></tr> <tr><td>0.070</td><td>5</td><td>5</td></tr> <tr><td>0.140</td><td>6</td><td>6</td></tr> <tr><td>0.210</td><td>6</td><td>7</td></tr> <tr><td>0.280</td><td>6</td><td>8</td></tr> <tr><td>0.350</td><td>7</td><td>8</td></tr> <tr><td>0.385</td><td>7</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	3	4	0.070	5	5	0.140	6	6	0.210	6	7	0.280	6	8	0.350	7	8	0.385	7	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	3	4																																						
0.070	5	5																																						
0.140	6	6																																						
0.210	6	7																																						
0.280	6	8																																						
0.350	7	8																																						
0.385	7	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>Ripple Noise[mVp-p]</p> </div> <div style="text-align: center;"> <p>Fig. Complex Ripple Noise Wave Form</p> </div> </div>																																								



<p>Model SUW100515/SUCW100515</p> <p>Item Ripple-Noise</p> <p>Object -15V0.35A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - -○- - Input Volt. 9V </p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>3</td><td>4</td></tr> <tr><td>0.070</td><td>5</td><td>5</td></tr> <tr><td>0.140</td><td>6</td><td>6</td></tr> <tr><td>0.210</td><td>6</td><td>7</td></tr> <tr><td>0.280</td><td>6</td><td>8</td></tr> <tr><td>0.350</td><td>7</td><td>8</td></tr> <tr><td>0.385</td><td>7</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	3	4	0.070	5	5	0.140	6	6	0.210	6	7	0.280	6	8	0.350	7	8	0.385	7	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	3	4																																						
0.070	5	5																																						
0.140	6	6																																						
0.210	6	7																																						
0.280	6	8																																						
0.350	7	8																																						
0.385	7	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



Model SUW100515/SUCW100515		Testing Circuitry Figure B																																						
Item Ripple Voltage (by Ambient Temp.)																																								
Object +15V0.35A																																								
1.Graph <div style="text-align: right; margin-bottom: 5px;"> ---□--- Load 50% —△— Load 100% </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 5V</p>		2.Values <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>6</td><td>10</td></tr> <tr><td>-40</td><td>5</td><td>10</td></tr> <tr><td>-20</td><td>5</td><td>8</td></tr> <tr><td>0</td><td>4</td><td>7</td></tr> <tr><td>25</td><td>4</td><td>5</td></tr> <tr><td>55</td><td>2</td><td>4</td></tr> <tr><td>60</td><td>3</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	6	10	-40	5	10	-20	5	8	0	4	7	25	4	5	55	2	4	60	3	4	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	6	10																																						
-40	5	10																																						
-20	5	8																																						
0	4	7																																						
25	4	5																																						
55	2	4																																						
60	3	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Object -15V0.35A																																								
1.Graph <div style="text-align: right; margin-bottom: 5px;"> ---□--- Load 50% —△— Load 100% </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 5V</p>		2.Values <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>9</td><td>10</td></tr> <tr><td>-40</td><td>9</td><td>10</td></tr> <tr><td>-20</td><td>8</td><td>8</td></tr> <tr><td>0</td><td>6</td><td>7</td></tr> <tr><td>25</td><td>4</td><td>5</td></tr> <tr><td>55</td><td>4</td><td>4</td></tr> <tr><td>60</td><td>2</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	9	10	-40	9	10	-20	8	8	0	6	7	25	4	5	55	4	4	60	2	4	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	9	10																																						
-40	9	10																																						
-20	8	8																																						
0	6	7																																						
25	4	5																																						
55	4	4																																						
60	2	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.																																								



Model		SUW100515/SUCW100515		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift		2.Values																																																				
Object		+15V0.35A		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.912</td><td>14.911</td><td>14.912</td></tr> <tr><td>-40</td><td>14.914</td><td>14.913</td><td>14.914</td></tr> <tr><td>-20</td><td>14.908</td><td>14.907</td><td>14.907</td></tr> <tr><td>0</td><td>14.893</td><td>14.893</td><td>14.893</td></tr> <tr><td>25</td><td>14.867</td><td>14.866</td><td>14.866</td></tr> <tr><td>55</td><td>14.824</td><td>14.823</td><td>14.822</td></tr> <tr><td>60</td><td>14.816</td><td>14.815</td><td>14.814</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	14.912	14.911	14.912	-40	14.914	14.913	14.914	-20	14.908	14.907	14.907	0	14.893	14.893	14.893	25	14.867	14.866	14.866	55	14.824	14.823	14.822	60	14.816	14.815	14.814	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	14.912	14.911	14.912																																																					
-40	14.914	14.913	14.914																																																					
-20	14.908	14.907	14.907																																																					
0	14.893	14.893	14.893																																																					
25	14.867	14.866	14.866																																																					
55	14.824	14.823	14.822																																																					
60	14.816	14.815	14.814																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>-·-○-·- Input Volt. 9V</p>																																																						
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																								
Object		-15V0.35A		2.Values																																																				
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>-·-○-·- Input Volt. 9V</p>																																																						
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.907</td><td>-14.907</td><td>-14.907</td></tr> <tr><td>-40</td><td>-14.909</td><td>-14.909</td><td>-14.909</td></tr> <tr><td>-20</td><td>-14.903</td><td>-14.903</td><td>-14.902</td></tr> <tr><td>0</td><td>-14.889</td><td>-14.888</td><td>-14.888</td></tr> <tr><td>25</td><td>-14.862</td><td>-14.862</td><td>-14.861</td></tr> <tr><td>55</td><td>-14.819</td><td>-14.819</td><td>-14.818</td></tr> <tr><td>60</td><td>-14.811</td><td>-14.811</td><td>-14.810</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-14.907	-14.907	-14.907	-40	-14.909	-14.909	-14.909	-20	-14.903	-14.903	-14.902	0	-14.889	-14.888	-14.888	25	-14.862	-14.862	-14.861	55	-14.819	-14.819	-14.818	60	-14.811	-14.811	-14.810	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	-14.907	-14.907	-14.907																																																					
-40	-14.909	-14.909	-14.909																																																					
-20	-14.903	-14.903	-14.902																																																					
0	-14.889	-14.888	-14.888																																																					
25	-14.862	-14.862	-14.861																																																					
55	-14.819	-14.819	-14.818																																																					
60	-14.811	-14.811	-14.810																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



COSEL		
Model	SUW100515/SUCW100515	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.35A (AVR 2) : 0 - 0.35A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+15V0.35A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	9	0	15.258	±218	±1.5
Minimum Voltage	55	9	0.35	14.822		

Object		-15V0.35A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	9	0	-15.216	±199	±1.3
Minimum Voltage	55	9	0.35	-14.818		




COSEL																									
Model	SUW100515/SUCW100515	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.35A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.886</td></tr> <tr><td>0.5</td><td>14.874</td></tr> <tr><td>1.0</td><td>14.874</td></tr> <tr><td>2.0</td><td>14.874</td></tr> <tr><td>3.0</td><td>14.874</td></tr> <tr><td>4.0</td><td>14.874</td></tr> <tr><td>5.0</td><td>14.874</td></tr> <tr><td>6.0</td><td>14.874</td></tr> <tr><td>7.0</td><td>14.874</td></tr> <tr><td>8.0</td><td>14.874</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	14.886	0.5	14.874	1.0	14.874	2.0	14.874	3.0	14.874	4.0	14.874	5.0	14.874	6.0	14.874	7.0	14.874	8.0	14.874
Time since start [H]	Output Voltage [V]																								
0.0	14.886																								
0.5	14.874																								
1.0	14.874																								
2.0	14.874																								
3.0	14.874																								
4.0	14.874																								
5.0	14.874																								
6.0	14.874																								
7.0	14.874																								
8.0	14.874																								
Object	-15V0.35A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.865</td></tr> <tr><td>0.5</td><td>-14.852</td></tr> <tr><td>1.0</td><td>-14.853</td></tr> <tr><td>2.0</td><td>-14.853</td></tr> <tr><td>3.0</td><td>-14.852</td></tr> <tr><td>4.0</td><td>-14.853</td></tr> <tr><td>5.0</td><td>-14.853</td></tr> <tr><td>6.0</td><td>-14.853</td></tr> <tr><td>7.0</td><td>-14.852</td></tr> <tr><td>8.0</td><td>-14.852</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-14.865	0.5	-14.852	1.0	-14.853	2.0	-14.853	3.0	-14.852	4.0	-14.853	5.0	-14.853	6.0	-14.853	7.0	-14.852	8.0	-14.852
Time since start [H]	Output Voltage [V]																								
0.0	-14.865																								
0.5	-14.852																								
1.0	-14.853																								
2.0	-14.853																								
3.0	-14.852																								
4.0	-14.853																								
5.0	-14.853																								
6.0	-14.853																								
7.0	-14.852																								
8.0	-14.852																								




Model	SUW100515/SUCW100515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.35A		

1. Graph



2. Values


Load	Time	[mS]				
		Td	Tr	Ts	Th	Tf
50 %		0.6	4.4	5.0	0.2	2.2
100 %		0.6	4.6	5.2	0.2	1.1






Model	SUW100515/SUCW100515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.35A		

1. Graph



2. Values

		[mS]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		0.6	4.6	5.2	0.2	2.4
100 %		0.6	4.8	5.4	0.2	1.2





COSEL																																									
Model	SUW100515/SUCW100515																																								
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+15V0.35A																																								
1.Graph		2.Values																																							
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>2.2</td><td>3.0</td></tr> <tr><td>-40</td><td>2.4</td><td>3.0</td></tr> <tr><td>-20</td><td>2.4</td><td>3.0</td></tr> <tr><td>0</td><td>2.6</td><td>3.2</td></tr> <tr><td>25</td><td>2.6</td><td>3.2</td></tr> <tr><td>55</td><td>2.8</td><td>3.4</td></tr> <tr><td>60</td><td>2.8</td><td>3.4</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	2.2	3.0	-40	2.4	3.0	-20	2.4	3.0	0	2.6	3.2	25	2.6	3.2	55	2.8	3.4	60	2.8	3.4	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	2.2	3.0																																							
-40	2.4	3.0																																							
-20	2.4	3.0																																							
0	2.6	3.2																																							
25	2.6	3.2																																							
55	2.8	3.4																																							
60	2.8	3.4																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
Object		-15V0.35A																																							
1.Graph		2.Values																																							
		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>2.1</td><td>2.9</td></tr> <tr><td>-40</td><td>2.3</td><td>2.9</td></tr> <tr><td>-20</td><td>2.3</td><td>2.9</td></tr> <tr><td>0</td><td>2.5</td><td>3.1</td></tr> <tr><td>25</td><td>2.5</td><td>3.1</td></tr> <tr><td>55</td><td>2.7</td><td>3.3</td></tr> <tr><td>60</td><td>2.7</td><td>3.3</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	2.1	2.9	-40	2.3	2.9	-20	2.3	2.9	0	2.5	3.1	25	2.5	3.1	55	2.7	3.3	60	2.7	3.3	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	2.1	2.9																																							
-40	2.3	2.9																																							
-20	2.3	2.9																																							
0	2.5	3.1																																							
25	2.5	3.1																																							
55	2.7	3.3																																							
60	2.7	3.3																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									



<p>Model SUW100515/SUCW100515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																								
<p>Item Overcurrent Protection</p>																																																										
<p>Object +15V0.35A</p>																																																										
<p>1.Graph</p> <p> Input Volt. 4.5V Input Volt. 5V Input Volt. 9V </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.47</td><td>0.47</td><td>0.45</td></tr> <tr><td>14.3</td><td>0.70</td><td>0.74</td><td>0.83</td></tr> <tr><td>13.5</td><td>0.75</td><td>0.79</td><td>0.89</td></tr> <tr><td>12.0</td><td>0.84</td><td>0.88</td><td>0.98</td></tr> <tr><td>10.5</td><td>0.89</td><td>0.93</td><td>1.00</td></tr> <tr><td>9.0</td><td>0.94</td><td>0.97</td><td>1.01</td></tr> <tr><td>7.5</td><td>1.00</td><td>1.03</td><td>1.03</td></tr> <tr><td>6.0</td><td>1.07</td><td>1.09</td><td>1.05</td></tr> <tr><td>4.5</td><td>1.15</td><td>1.17</td><td>1.09</td></tr> <tr><td>3.0</td><td>1.23</td><td>1.24</td><td>1.07</td></tr> <tr><td>1.5</td><td>1.24</td><td>1.23</td><td>0.98</td></tr> <tr><td>0.0</td><td>1.41</td><td>1.40</td><td>1.18</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	15.0	0.47	0.47	0.45	14.3	0.70	0.74	0.83	13.5	0.75	0.79	0.89	12.0	0.84	0.88	0.98	10.5	0.89	0.93	1.00	9.0	0.94	0.97	1.01	7.5	1.00	1.03	1.03	6.0	1.07	1.09	1.05	4.5	1.15	1.17	1.09	3.0	1.23	1.24	1.07	1.5	1.24	1.23	0.98	0.0	1.41	1.40	1.18	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
15.0	0.47	0.47	0.45																																																							
14.3	0.70	0.74	0.83																																																							
13.5	0.75	0.79	0.89																																																							
12.0	0.84	0.88	0.98																																																							
10.5	0.89	0.93	1.00																																																							
9.0	0.94	0.97	1.01																																																							
7.5	1.00	1.03	1.03																																																							
6.0	1.07	1.09	1.05																																																							
4.5	1.15	1.17	1.09																																																							
3.0	1.23	1.24	1.07																																																							
1.5	1.24	1.23	0.98																																																							
0.0	1.41	1.40	1.18																																																							
<p>Object -15V0.35A</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																								
<p>1.Graph</p> <p> Input Volt. 4.5V Input Volt. 5V Input Volt. 9V </p> <p style="text-align: center;">Load Current [A]</p>			<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.35</td><td>0.37</td><td>0.57</td></tr> <tr><td>-14.25</td><td>0.70</td><td>0.73</td><td>0.83</td></tr> <tr><td>-13.50</td><td>0.75</td><td>0.78</td><td>0.89</td></tr> <tr><td>-12.00</td><td>0.85</td><td>0.88</td><td>0.98</td></tr> <tr><td>-10.50</td><td>0.90</td><td>0.93</td><td>1.00</td></tr> <tr><td>-9.00</td><td>0.95</td><td>0.98</td><td>1.02</td></tr> <tr><td>-7.50</td><td>1.00</td><td>1.03</td><td>1.04</td></tr> <tr><td>-6.00</td><td>1.08</td><td>1.09</td><td>1.06</td></tr> <tr><td>-4.50</td><td>1.16</td><td>1.17</td><td>1.09</td></tr> <tr><td>-3.00</td><td>1.23</td><td>1.24</td><td>1.07</td></tr> <tr><td>-1.50</td><td>1.25</td><td>1.24</td><td>0.98</td></tr> <tr><td>0.00</td><td>1.43</td><td>1.42</td><td>1.20</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-15.00	0.35	0.37	0.57	-14.25	0.70	0.73	0.83	-13.50	0.75	0.78	0.89	-12.00	0.85	0.88	0.98	-10.50	0.90	0.93	1.00	-9.00	0.95	0.98	1.02	-7.50	1.00	1.03	1.04	-6.00	1.08	1.09	1.06	-4.50	1.16	1.17	1.09	-3.00	1.23	1.24	1.07	-1.50	1.25	1.24	0.98	0.00	1.43	1.42	1.20
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
-15.00	0.35	0.37	0.57																																																							
-14.25	0.70	0.73	0.83																																																							
-13.50	0.75	0.78	0.89																																																							
-12.00	0.85	0.88	0.98																																																							
-10.50	0.90	0.93	1.00																																																							
-9.00	0.95	0.98	1.02																																																							
-7.50	1.00	1.03	1.04																																																							
-6.00	1.08	1.09	1.06																																																							
-4.50	1.16	1.17	1.09																																																							
-3.00	1.23	1.24	1.07																																																							
-1.50	1.25	1.24	0.98																																																							
0.00	1.43	1.42	1.20																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										




Figure A




Figure B(Ripple and Ripple noise Characteristic)