



TEST DATA OF SUW104815 SUCW104815

Regulated DC Power Supply
Mar 25, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Engineer

COSEL CO.,LTD.



CONTENTS


1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUW104815/SUCW104815	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Input Current (by Input Voltage)																																																																																			
Object	_____																																																																																			
1.Graph	<p>The graph plots Input Current [A] on the y-axis (0.00 to 0.50) against Input Voltage [V] on the x-axis (0 to 80). Three data series are shown: Load 100% (solid triangles), Load 50% (open squares), and Load 0% (open circles). A slanted line at approximately 30V marks the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.000</td><td>0.001</td></tr> <tr><td>27.2</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>28.2</td><td>0.015</td><td>0.216</td><td>0.439</td></tr> <tr><td>28.8</td><td>0.015</td><td>0.212</td><td>0.428</td></tr> <tr><td>33.0</td><td>0.014</td><td>0.186</td><td>0.371</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.171</td><td>0.339</td></tr> <tr><td>40.0</td><td>0.014</td><td>0.155</td><td>0.305</td></tr> <tr><td>48.0</td><td>0.014</td><td>0.130</td><td>0.254</td></tr> <tr><td>60.0</td><td>0.014</td><td>0.107</td><td>0.204</td></tr> <tr><td>70.0</td><td>0.014</td><td>0.092</td><td>0.177</td></tr> <tr><td>76.0</td><td>0.014</td><td>0.085</td><td>0.164</td></tr> <tr><td>80.0</td><td>0.014</td><td>0.081</td><td>0.156</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.000	0.001	27.2	0.001	0.001	0.001	28.2	0.015	0.216	0.439	28.8	0.015	0.212	0.428	33.0	0.014	0.186	0.371	36.0	0.015	0.171	0.339	40.0	0.014	0.155	0.305	48.0	0.014	0.130	0.254	60.0	0.014	0.107	0.204	70.0	0.014	0.092	0.177	76.0	0.014	0.085	0.164	80.0	0.014	0.081	0.156	-	-	-	-	-	-	-	-	-	-	-	-							
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.000	0.000	0.000																																																																																	
16.0	0.000	0.000	0.000																																																																																	
24.0	0.001	0.000	0.001																																																																																	
27.2	0.001	0.001	0.001																																																																																	
28.2	0.015	0.216	0.439																																																																																	
28.8	0.015	0.212	0.428																																																																																	
33.0	0.014	0.186	0.371																																																																																	
36.0	0.015	0.171	0.339																																																																																	
40.0	0.014	0.155	0.305																																																																																	
48.0	0.014	0.130	0.254																																																																																	
60.0	0.014	0.107	0.204																																																																																	
70.0	0.014	0.092	0.177																																																																																	
76.0	0.014	0.085	0.164																																																																																	
80.0	0.014	0.081	0.156																																																																																	
-	-	-	-																																																																																	
-	-	-	-																																																																																	
-	-	-	-																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.000</td><td>0.001</td></tr> <tr><td>27.2</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>28.2</td><td>0.015</td><td>0.216</td><td>0.439</td></tr> <tr><td>28.8</td><td>0.015</td><td>0.212</td><td>0.428</td></tr> <tr><td>33.0</td><td>0.014</td><td>0.186</td><td>0.371</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.171</td><td>0.339</td></tr> <tr><td>40.0</td><td>0.014</td><td>0.155</td><td>0.305</td></tr> <tr><td>48.0</td><td>0.014</td><td>0.130</td><td>0.254</td></tr> <tr><td>60.0</td><td>0.014</td><td>0.107</td><td>0.204</td></tr> <tr><td>70.0</td><td>0.014</td><td>0.092</td><td>0.177</td></tr> <tr><td>76.0</td><td>0.014</td><td>0.085</td><td>0.164</td></tr> <tr><td>80.0</td><td>0.014</td><td>0.081</td><td>0.156</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.000	0.001	27.2	0.001	0.001	0.001	28.2	0.015	0.216	0.439	28.8	0.015	0.212	0.428	33.0	0.014	0.186	0.371	36.0	0.015	0.171	0.339	40.0	0.014	0.155	0.305	48.0	0.014	0.130	0.254	60.0	0.014	0.107	0.204	70.0	0.014	0.092	0.177	76.0	0.014	0.085	0.164	80.0	0.014	0.081	0.156	-	-	-	-	-	-	-	-	-	-	-	-				
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.000	0.000	0.000																																																																																	
16.0	0.000	0.000	0.000																																																																																	
24.0	0.001	0.000	0.001																																																																																	
27.2	0.001	0.001	0.001																																																																																	
28.2	0.015	0.216	0.439																																																																																	
28.8	0.015	0.212	0.428																																																																																	
33.0	0.014	0.186	0.371																																																																																	
36.0	0.015	0.171	0.339																																																																																	
40.0	0.014	0.155	0.305																																																																																	
48.0	0.014	0.130	0.254																																																																																	
60.0	0.014	0.107	0.204																																																																																	
70.0	0.014	0.092	0.177																																																																																	
76.0	0.014	0.085	0.164																																																																																	
80.0	0.014	0.081	0.156																																																																																	
-	-	-	-																																																																																	
-	-	-	-																																																																																	
-	-	-	-																																																																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Ration [%]	Input Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0	0.015	0.014	0.014
20	0.077	0.061	0.041
40	0.141	0.108	0.071
60	0.205	0.155	0.103
80	0.270	0.203	0.132
100	0.336	0.252	0.163
110	0.371	0.276	0.178
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-


COSEL

Model	SUW104815/SUCW104815																																																					
Item	Input Power (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph																																																						
<p>Input Power [W]</p> <p>Load Ration [%]</p> <ul style="list-style-type: none"> — △ — Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V 																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.53</td><td>0.68</td><td>1.09</td></tr> <tr> <td>20</td><td>2.79</td><td>2.94</td><td>3.09</td></tr> <tr> <td>40</td><td>5.07</td><td>5.16</td><td>5.42</td></tr> <tr> <td>60</td><td>7.35</td><td>7.45</td><td>7.80</td></tr> <tr> <td>80</td><td>9.69</td><td>9.74</td><td>10.05</td></tr> <tr> <td>100</td><td>12.08</td><td>12.07</td><td>12.34</td></tr> <tr> <td>110</td><td>13.31</td><td>13.25</td><td>13.49</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.53	0.68	1.09	20	2.79	2.94	3.09	40	5.07	5.16	5.42	60	7.35	7.45	7.80	80	9.69	9.74	10.05	100	12.08	12.07	12.34	110	13.31	13.25	13.49	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.53	0.68	1.09																																																			
20	2.79	2.94	3.09																																																			
40	5.07	5.16	5.42																																																			
60	7.35	7.45	7.80																																																			
80	9.69	9.74	10.05																																																			
100	12.08	12.07	12.34																																																			
110	13.31	13.25	13.49																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			

COSEL

Model	SUW104815/SUCW104815
Item	Efficiency (by Input Voltage)
Object	—

1. Graph





Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
33	85.1	86.7
36	84.6	86.8
40	84.3	87.0
48	83.2	86.9
55	82.2	86.7
60	81.6	86.4
70	81.0	85.5
76	81.0	85.1
80	80.9	84.6


COSEL

Model	SUW104815/SUCW104815																																																				
Item	Efficiency (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object	<hr/>																																																				
1.Graph																																																					
<p style="text-align: center;"> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p> 																																																					
																																																					
2.Values																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>75.6</td><td>71.8</td><td>68.2</td></tr> <tr> <td>40</td><td>82.9</td><td>81.4</td><td>77.6</td></tr> <tr> <td>60</td><td>85.8</td><td>84.7</td><td>80.9</td></tr> <tr> <td>80</td><td>86.7</td><td>86.3</td><td>83.5</td></tr> <tr> <td>100</td><td>86.9</td><td>87.0</td><td>85.1</td></tr> <tr> <td>110</td><td>86.8</td><td>87.1</td><td>85.6</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	75.6	71.8	68.2	40	82.9	81.4	77.6	60	85.8	84.7	80.9	80	86.7	86.3	83.5	100	86.9	87.0	85.1	110	86.8	87.1	85.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	75.6	71.8	68.2																																																		
40	82.9	81.4	77.6																																																		
60	85.8	84.7	80.9																																																		
80	86.7	86.3	83.5																																																		
100	86.9	87.0	85.1																																																		
110	86.8	87.1	85.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		


Model	SUW104815/SUCW104815	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+15V0.35A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>15.079</td><td>14.971</td></tr> <tr><td>36</td><td>15.074</td><td>14.971</td></tr> <tr><td>40</td><td>15.069</td><td>14.971</td></tr> <tr><td>48</td><td>15.062</td><td>14.970</td></tr> <tr><td>55</td><td>15.058</td><td>14.970</td></tr> <tr><td>60</td><td>15.056</td><td>14.970</td></tr> <tr><td>70</td><td>15.053</td><td>14.969</td></tr> <tr><td>76</td><td>15.052</td><td>14.970</td></tr> <tr><td>80</td><td>15.051</td><td>14.970</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	15.079	14.971	36	15.074	14.971	40	15.069	14.971	48	15.062	14.970	55	15.058	14.970	60	15.056	14.970	70	15.053	14.969	76	15.052	14.970	80	15.051	14.970
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	15.079	14.971																																	
36	15.074	14.971																																	
40	15.069	14.971																																	
48	15.062	14.970																																	
55	15.058	14.970																																	
60	15.056	14.970																																	
70	15.053	14.969																																	
76	15.052	14.970																																	
80	15.051	14.970																																	
Object -15V0.35A			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-15.066</td><td>-14.957</td></tr> <tr><td>36</td><td>-15.062</td><td>-14.957</td></tr> <tr><td>40</td><td>-15.058</td><td>-14.958</td></tr> <tr><td>48</td><td>-15.051</td><td>-14.958</td></tr> <tr><td>55</td><td>-15.048</td><td>-14.959</td></tr> <tr><td>60</td><td>-15.046</td><td>-14.959</td></tr> <tr><td>70</td><td>-15.042</td><td>-14.958</td></tr> <tr><td>76</td><td>-15.041</td><td>-14.959</td></tr> <tr><td>80</td><td>-15.040</td><td>-14.958</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-15.066	-14.957	36	-15.062	-14.957	40	-15.058	-14.958	48	-15.051	-14.958	55	-15.048	-14.959	60	-15.046	-14.959	70	-15.042	-14.958	76	-15.041	-14.959	80	-15.040	-14.958
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	-15.066	-14.957																																	
36	-15.062	-14.957																																	
40	-15.058	-14.958																																	
48	-15.051	-14.958																																	
55	-15.048	-14.959																																	
60	-15.046	-14.959																																	
70	-15.042	-14.958																																	
76	-15.041	-14.959																																	
80	-15.040	-14.958																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	SUW104815/SUCW104815	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.35A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —▲— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.310</td><td>15.305</td><td>15.300</td></tr> <tr><td>0.070</td><td>15.145</td><td>15.132</td><td>15.127</td></tr> <tr><td>0.140</td><td>15.096</td><td>15.083</td><td>15.072</td></tr> <tr><td>0.210</td><td>15.052</td><td>15.043</td><td>15.034</td></tr> <tr><td>0.280</td><td>15.011</td><td>15.005</td><td>15.000</td></tr> <tr><td>0.350</td><td>14.970</td><td>14.970</td><td>14.969</td></tr> <tr><td>0.385</td><td>14.950</td><td>14.951</td><td>14.954</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	15.310	15.305	15.300	0.070	15.145	15.132	15.127	0.140	15.096	15.083	15.072	0.210	15.052	15.043	15.034	0.280	15.011	15.005	15.000	0.350	14.970	14.970	14.969	0.385	14.950	14.951	14.954	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	15.310	15.305	15.300																																																			
0.070	15.145	15.132	15.127																																																			
0.140	15.096	15.083	15.072																																																			
0.210	15.052	15.043	15.034																																																			
0.280	15.011	15.005	15.000																																																			
0.350	14.970	14.970	14.969																																																			
0.385	14.950	14.951	14.954																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
Object	-15V0.35A	2.Values																																																				
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —▲— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.332</td><td>-15.318</td><td>-15.330</td></tr> <tr><td>0.070</td><td>-15.133</td><td>-15.121</td><td>-15.116</td></tr> <tr><td>0.140</td><td>-15.084</td><td>-15.071</td><td>-15.061</td></tr> <tr><td>0.210</td><td>-15.040</td><td>-15.032</td><td>-15.022</td></tr> <tr><td>0.280</td><td>-14.998</td><td>-14.995</td><td>-14.989</td></tr> <tr><td>0.350</td><td>-14.957</td><td>-14.958</td><td>-14.959</td></tr> <tr><td>0.385</td><td>-14.937</td><td>-14.940</td><td>-14.944</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-15.332	-15.318	-15.330	0.070	-15.133	-15.121	-15.116	0.140	-15.084	-15.071	-15.061	0.210	-15.040	-15.032	-15.022	0.280	-14.998	-14.995	-14.989	0.350	-14.957	-14.958	-14.959	0.385	-14.937	-14.940	-14.944	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	-15.332	-15.318	-15.330																																																			
0.070	-15.133	-15.121	-15.116																																																			
0.140	-15.084	-15.071	-15.061																																																			
0.210	-15.040	-15.032	-15.022																																																			
0.280	-14.998	-14.995	-14.989																																																			
0.350	-14.957	-14.958	-14.959																																																			
0.385	-14.937	-14.940	-14.944																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


COSEL



COSEL

Model	SUW104815/SUCW104815
Item	Ripple Voltage (by Load Current)
Object	+15V0.35A

1. Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C
 Testing Circuitry Figure B


2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	2	2
0.070	4	6
0.140	5	7
0.210	5	8
0.280	6	8
0.350	6	6
0.385	7	6
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model	SUW104815/SUCW104815
Item	Ripple Voltage (by Load Current)
Object	-15V0.35A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated
load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values


Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	2	3
0.070	6	8
0.140	6	9
0.210	6	6
0.280	7	7
0.350	8	7
0.385	8	6
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model	SUW104815/SUCW104815
Item	Ripple-Noise
Object	+15V0.35A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	3	8
0.070	4	6
0.140	5	7
0.210	5	8
0.280	6	8
0.350	7	6
0.385	7	6
-	-	-
-	-	-
-	-	-
-	-	-





Fig.Complex Ripple Noise Wave Form

COSEL


Model	SUW104815/SUCW104815
Item	Ripple-Noise
Object	-15V0.35A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	4	9
0.070	7	8
0.140	6	9
0.210	7	8
0.280	7	8
0.350	8	8
0.385	8	8
--	-	-
--	-	-
--	-	-
--	-	-


COSEL
Model SUW104815/SUCW104815

Item Ripple Voltage (by Ambient Temp.)

Object +15V0.35A

1. Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure B
2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	11
-40	9	11
-20	9	10
0	8	9
25	7	8
55	7	7
60	6	7
—	—	—
—	—	—
—	—	—
—	—	—

Object -15V0.35A

1. Graph

---□--- Load 50%
—△— Load 100%


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	8	13
-40	7	12
-20	7	12
0	6	9
25	5	7
55	3	5
60	3	5
—	—	—
—	—	—
—	—	—
—	—	—

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model SUW104815/SUCW104815

Item Ambient Temperature Drift


Object +15V0.35A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.970	14.970	14.970
-40	14.983	14.982	14.982
-20	14.988	14.987	14.986
0	14.985	14.984	14.983
25	14.972	14.971	14.970
55	14.946	14.944	14.943
60	14.940	14.939	14.938
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-14.956	-14.957	-14.958
-40	-14.968	-14.969	-14.971
-20	-14.973	-14.974	-14.975
0	-14.970	-14.972	-14.972
25	-14.958	-14.958	-14.959
55	-14.931	-14.932	-14.932
60	-14.926	-14.927	-14.927
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUW104815/SUCW104815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.35A (AVR 2) : 0 - 0.35A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object		+15V0.35A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	25	36	0	15.299	± 178	± 1.2	
Minimum Voltage	55	76	0.35	14.943			

Object		-15V0.35A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	25	36	0	-15.325	± 197	± 1.3	
Minimum Voltage	55	76	0.35	-14.932			

COSEL

Model	SUW104815/SUCW104815
Item	Time Lapse Drift
Object	+15V0.35A


1.Graph



Input Volt. 48V
Load 100%

Object	-15V0.35A
--------	-----------

1.Graph



Input Volt. 48V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	14.975
0.5	14.967
1.0	14.967
2.0	14.967
3.0	14.967
4.0	14.967
5.0	14.967
6.0	14.967
7.0	14.967
8.0	14.967

2.Values

Time since start [H]	Output Voltage [V]
0.0	-14.968
0.5	-14.961
1.0	-14.961
2.0	-14.961
3.0	-14.961
4.0	-14.961
5.0	-14.961
6.0	-14.961
7.0	-14.961
8.0	-14.961

COSEL


Model SUW104815/SUCW104815

Item Rise and Fall Time

Object +15V0.35A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.0	4.0	13.0	0.1	2.3	
100 %		9.1	4.1	13.2	0.1	1.1	



COSEL


Model SUW104815/SUCW104815

Item Rise and Fall Time

Object -15V0.35A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.0	4.1	13.1	0.1	2.4	
100 %		9.1	4.1	13.2	0.1	1.2	



COSEL

		Testing Circuitry Figure A																																							
Model	SUW104815/SUCW104815																																								
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+15V0.35A																																								
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>26.9</td><td>27.1</td></tr> <tr><td>-40</td><td>27.1</td><td>27.2</td></tr> <tr><td>-20</td><td>27.5</td><td>27.6</td></tr> <tr><td>0</td><td>27.5</td><td>27.6</td></tr> <tr><td>25</td><td>27.9</td><td>28.0</td></tr> <tr><td>55</td><td>28.3</td><td>27.9</td></tr> <tr><td>60</td><td>28.3</td><td>28.4</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	26.9	27.1	-40	27.1	27.2	-20	27.5	27.6	0	27.5	27.6	25	27.9	28.0	55	28.3	27.9	60	28.3	28.4	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	26.9	27.1																																							
-40	27.1	27.2																																							
-20	27.5	27.6																																							
0	27.5	27.6																																							
25	27.9	28.0																																							
55	28.3	27.9																																							
60	28.3	28.4																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
Object	-15V0.35A	2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>26.8</td><td>26.9</td></tr> <tr><td>-40</td><td>26.9</td><td>27.0</td></tr> <tr><td>-20</td><td>27.3</td><td>27.4</td></tr> <tr><td>0</td><td>27.3</td><td>27.5</td></tr> <tr><td>25</td><td>27.7</td><td>27.8</td></tr> <tr><td>55</td><td>28.1</td><td>27.8</td></tr> <tr><td>60</td><td>28.1</td><td>28.2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	26.8	26.9	-40	26.9	27.0	-20	27.3	27.4	0	27.3	27.5	25	27.7	27.8	55	28.1	27.8	60	28.1	28.2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	26.8	26.9																																							
-40	26.9	27.0																																							
-20	27.3	27.4																																							
0	27.3	27.5																																							
25	27.7	27.8																																							
55	28.1	27.8																																							
60	28.1	28.2																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

COSEL


Model SUW104815/SUCW104815

Item Overcurrent Protection

Object +15V0.35A

1.Graph

Input Volt. 36V
 Input Volt. 48V
 Input Volt. 76V

Temperature 25°C
Testing Circuitry Figure A

2.Values


Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
15.0	0.43	0.39	0.39
14.3	0.68	0.75	0.81
13.5	0.73	0.82	0.87
12.0	0.84	0.94	0.98
10.5	0.95	1.05	1.08
9.0	1.03	1.11	1.13
7.5	1.09	1.16	1.15
6.0	1.15	1.21	1.13
4.5	1.24	1.27	1.08
3.0	1.33	1.26	1.04
1.5	1.35	1.26	0.99
0.0	1.40	1.24	1.14

Object

-15V0.35A

1.Graph

Input Volt. 36V
 Input Volt. 48V
 Input Volt. 76V



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-15.00	0.41	0.43	0.43
-14.25	0.65	0.75	0.80
-13.50	0.71	0.81	0.86
-12.00	0.83	0.94	0.98
-10.50	0.93	1.05	1.08
-9.00	1.01	1.11	1.12
-7.50	1.07	1.16	1.14
-6.00	1.14	1.21	1.12
-4.50	1.22	1.27	1.08
-3.00	1.32	1.26	1.04
-1.50	1.34	1.26	0.98
0.00	1.39	1.23	1.20

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)