



M T B F (EIAJ RCR-9102)

| | |
|-------|-------------|
| Model | SUCW1R52412 |
|-------|-------------|

| No. | P a r t s | | Q'ty of Device | Failure rate [$10^{-6}/H$] | Reference |
|------------------------------------|------------------------|------------|----------------|------------------------------|-----------|
| 1 | I C | Monolithic | 1 | 0.0240 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 3 | 0.1012 | |
| 4 | D i o d e s | | 10 | 0.1740 | |
| 5 | LED·Optocouplers | | 1 | 0.0700 | |
| 6 | R e s i s t o r s | | 24 | 0.0048 | |
| 7 | C a p a c i t o r s | | 11 | 0.0814 | |
| 8 | Transformer·Choke Coil | | 4 | 0.0920 | |
| 9 | C o n n e c t o r s | | 93 | 0.0127 | |
| 10 | O t h e r s | | 2 | 0.1300 | |
| Total Failure Rate [$10^{-6}/H$] | | | | 0.6901 | |

| | | |
|---------------------|------|-----------|
| M T B F | [H] | 1,450,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |