

TEST DATA OF SUCW1R52412

Regulated DC Power Supply
Sep 28, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Figure of Testing Circuitry	22

(Final Page 22)



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure A																																																																							
Item	Input Current (by Input Voltage)																																																																								
Object	_____																																																																								
1.Graph <div style="float: right;"> —△— Load 100% - - □ - - Load 50% - · ○ - · Load 0% </div> <p style="margin-top: 10px;">Note: Slanted line shows the range of the rated input voltage.</p>		2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.025</td><td>0.208</td><td>0.187</td></tr> <tr><td>10.0</td><td>0.019</td><td>0.116</td><td>0.223</td></tr> <tr><td>12.0</td><td>0.017</td><td>0.092</td><td>0.179</td></tr> <tr><td>16.0</td><td>0.014</td><td>0.071</td><td>0.131</td></tr> <tr><td>18.0</td><td>0.013</td><td>0.063</td><td>0.116</td></tr> <tr><td>20.0</td><td>0.013</td><td>0.057</td><td>0.105</td></tr> <tr><td>24.0</td><td>0.012</td><td>0.049</td><td>0.089</td></tr> <tr><td>28.0</td><td>0.011</td><td>0.043</td><td>0.077</td></tr> <tr><td>32.0</td><td>0.010</td><td>0.038</td><td>0.068</td></tr> <tr><td>36.0</td><td>0.010</td><td>0.035</td><td>0.061</td></tr> <tr><td>40.0</td><td>0.011</td><td>0.033</td><td>0.056</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.025	0.208	0.187	10.0	0.019	0.116	0.223	12.0	0.017	0.092	0.179	16.0	0.014	0.071	0.131	18.0	0.013	0.063	0.116	20.0	0.013	0.057	0.105	24.0	0.012	0.049	0.089	28.0	0.011	0.043	0.077	32.0	0.010	0.038	0.068	36.0	0.010	0.035	0.061	40.0	0.011	0.033	0.056	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																								
	Load 0%	Load 50%	Load 100%																																																																						
0	0.000	0.000	0.000																																																																						
4.0	0.000	0.000	0.000																																																																						
8.0	0.025	0.208	0.187																																																																						
10.0	0.019	0.116	0.223																																																																						
12.0	0.017	0.092	0.179																																																																						
16.0	0.014	0.071	0.131																																																																						
18.0	0.013	0.063	0.116																																																																						
20.0	0.013	0.057	0.105																																																																						
24.0	0.012	0.049	0.089																																																																						
28.0	0.011	0.043	0.077																																																																						
32.0	0.010	0.038	0.068																																																																						
36.0	0.010	0.035	0.061																																																																						
40.0	0.011	0.033	0.056																																																																						
-	-	-	-																																																																						
-	-	-	-																																																																						
-	-	-	-																																																																						



Model		SUCW1R52412		Temperature		25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1.Graph				2.Values																																																						
<p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V - · - ○ - · - Input Volt. 36V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.013</td><td>0.012</td><td>0.010</td></tr> <tr><td>20</td><td>0.033</td><td>0.027</td><td>0.021</td></tr> <tr><td>40</td><td>0.054</td><td>0.042</td><td>0.031</td></tr> <tr><td>60</td><td>0.074</td><td>0.057</td><td>0.041</td></tr> <tr><td>80</td><td>0.095</td><td>0.072</td><td>0.051</td></tr> <tr><td>100</td><td>0.116</td><td>0.088</td><td>0.061</td></tr> <tr><td>110</td><td>0.127</td><td>0.095</td><td>0.066</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.013	0.012	0.010	20	0.033	0.027	0.021	40	0.054	0.042	0.031	60	0.074	0.057	0.041	80	0.095	0.072	0.051	100	0.116	0.088	0.061	110	0.127	0.095	0.066	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
0	0.013	0.012	0.010																																																							
20	0.033	0.027	0.021																																																							
40	0.054	0.042	0.031																																																							
60	0.074	0.057	0.041																																																							
80	0.095	0.072	0.051																																																							
100	0.116	0.088	0.061																																																							
110	0.127	0.095	0.066																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure A																																																			
Item	Input Power (by Load Current)																																																				
Object																																																					
1.Graph	<p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V - · - ○ - · - - Input Volt. 36V </p> <p> The graph plots Input Power [W] on the y-axis (0.0 to 5.0) against Load Ration [%] on the x-axis (0 to 120). Three data series are shown: 18V (solid line with triangles), 24V (dashed line with squares), and 36V (dash-dot line with circles). All series show a linear increase in power with load ratio. </p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.24</td><td>0.27</td><td>0.38</td></tr> <tr><td>20</td><td>0.60</td><td>0.64</td><td>0.74</td></tr> <tr><td>40</td><td>0.97</td><td>1.00</td><td>1.10</td></tr> <tr><td>60</td><td>1.33</td><td>1.36</td><td>1.46</td></tr> <tr><td>80</td><td>1.71</td><td>1.73</td><td>1.82</td></tr> <tr><td>100</td><td>2.09</td><td>2.10</td><td>2.19</td></tr> <tr><td>110</td><td>2.28</td><td>2.29</td><td>2.37</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.24	0.27	0.38	20	0.60	0.64	0.74	40	0.97	1.00	1.10	60	1.33	1.36	1.46	80	1.71	1.73	1.82	100	2.09	2.10	2.19	110	2.28	2.29	2.37	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	0.24	0.27	0.38																																																		
20	0.60	0.64	0.74																																																		
40	0.97	1.00	1.10																																																		
60	1.33	1.36	1.46																																																		
80	1.71	1.73	1.82																																																		
100	2.09	2.10	2.19																																																		
110	2.28	2.29	2.37																																																		
-	-	-	-																																																		
-	-	-	-																																																		
-	-	-	-																																																		
-	-	-	-																																																		



Model		SUCW1R52412																																	
Item		Efficiency (by Input Voltage)																																	
Object		Temperature 25°C Testing Circuitry Figure A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td> <td>70.5</td> <td>76.1</td> </tr> <tr> <td>18</td> <td>69.6</td> <td>76.0</td> </tr> <tr> <td>20</td> <td>69.1</td> <td>76.0</td> </tr> <tr> <td>24</td> <td>67.6</td> <td>75.5</td> </tr> <tr> <td>30</td> <td>65.4</td> <td>74.3</td> </tr> <tr> <td>36</td> <td>62.6</td> <td>72.4</td> </tr> <tr> <td>40</td> <td>60.2</td> <td>71.0</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	70.5	76.1	18	69.6	76.0	20	69.1	76.0	24	67.6	75.5	30	65.4	74.3	36	62.6	72.4	40	60.2	71.0	-	-	-	-	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
16	70.5	76.1																																	
18	69.6	76.0																																	
20	69.1	76.0																																	
24	67.6	75.5																																	
30	65.4	74.3																																	
36	62.6	72.4																																	
40	60.2	71.0																																	
-	-	-																																	
-	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model		SUCW1R52412		Temperature		25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1.Graph				2.Values																																																						
		—△— Input Volt. 18V - - □ - - Input Volt. 24V - · ○ - · Input Volt. 36V																																																								
				<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>54.5</td><td>51.3</td><td>44.4</td></tr> <tr><td>40</td><td>66.4</td><td>64.2</td><td>58.4</td></tr> <tr><td>60</td><td>71.8</td><td>70.1</td><td>65.4</td></tr> <tr><td>80</td><td>74.6</td><td>73.4</td><td>69.7</td></tr> <tr><td>100</td><td>76.1</td><td>75.4</td><td>72.4</td></tr> <tr><td>110</td><td>76.5</td><td>76.2</td><td>73.4</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	54.5	51.3	44.4	40	66.4	64.2	58.4	60	71.8	70.1	65.4	80	74.6	73.4	69.7	100	76.1	75.4	72.4	110	76.5	76.2	73.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
0	-	-	-																																																							
20	54.5	51.3	44.4																																																							
40	66.4	64.2	58.4																																																							
60	71.8	70.1	65.4																																																							
80	74.6	73.4	69.7																																																							
100	76.1	75.4	72.4																																																							
110	76.5	76.2	73.4																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							



<p>Model SUCW1R52412</p>		<p>Temperature 25°C</p>																																	
<p>Item Line Regulation</p>		<p>Testing Circuitry Figure A</p>																																	
<p>Object +12V0.065A</p>																																			
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>12.209</td><td>12.090</td></tr> <tr><td>18</td><td>12.202</td><td>12.090</td></tr> <tr><td>20</td><td>12.197</td><td>12.090</td></tr> <tr><td>24</td><td>12.190</td><td>12.090</td></tr> <tr><td>30</td><td>12.184</td><td>12.089</td></tr> <tr><td>36</td><td>12.181</td><td>12.089</td></tr> <tr><td>40</td><td>12.179</td><td>12.089</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	12.209	12.090	18	12.202	12.090	20	12.197	12.090	24	12.190	12.090	30	12.184	12.089	36	12.181	12.089	40	12.179	12.089	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	12.209	12.090																																	
18	12.202	12.090																																	
20	12.197	12.090																																	
24	12.190	12.090																																	
30	12.184	12.089																																	
36	12.181	12.089																																	
40	12.179	12.089																																	
--	-	-																																	
--	-	-																																	
<p>Object -12V0.065A</p>																																			
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>-12.205</td><td>-12.084</td></tr> <tr><td>18</td><td>-12.197</td><td>-12.084</td></tr> <tr><td>20</td><td>-12.191</td><td>-12.085</td></tr> <tr><td>24</td><td>-12.185</td><td>-12.084</td></tr> <tr><td>30</td><td>-12.180</td><td>-12.084</td></tr> <tr><td>36</td><td>-12.176</td><td>-12.084</td></tr> <tr><td>40</td><td>-12.175</td><td>-12.084</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	-12.205	-12.084	18	-12.197	-12.084	20	-12.191	-12.085	24	-12.185	-12.084	30	-12.180	-12.084	36	-12.176	-12.084	40	-12.175	-12.084	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	-12.205	-12.084																																	
18	-12.197	-12.084																																	
20	-12.191	-12.085																																	
24	-12.185	-12.084																																	
30	-12.180	-12.084																																	
36	-12.176	-12.084																																	
40	-12.175	-12.084																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			




Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure A																																																			
Item	Load Regulation																																																				
Object	+12V0.065A																																																				
1.Graph <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 45%;"> </div> <div style="width: 50%;"> 2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.492</td><td>12.486</td><td>12.483</td></tr> <tr><td>0.010</td><td>12.307</td><td>12.297</td><td>12.289</td></tr> <tr><td>0.020</td><td>12.250</td><td>12.237</td><td>12.226</td></tr> <tr><td>0.030</td><td>12.211</td><td>12.198</td><td>12.189</td></tr> <tr><td>0.040</td><td>12.176</td><td>12.165</td><td>12.158</td></tr> <tr><td>0.050</td><td>12.142</td><td>12.135</td><td>12.130</td></tr> <tr><td>0.060</td><td>12.108</td><td>12.105</td><td>12.103</td></tr> <tr><td>0.065</td><td>12.091</td><td>12.091</td><td>12.090</td></tr> <tr><td>0.072</td><td>12.068</td><td>12.071</td><td>12.073</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> </div> </div>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	12.492	12.486	12.483	0.010	12.307	12.297	12.289	0.020	12.250	12.237	12.226	0.030	12.211	12.198	12.189	0.040	12.176	12.165	12.158	0.050	12.142	12.135	12.130	0.060	12.108	12.105	12.103	0.065	12.091	12.091	12.090	0.072	12.068	12.071	12.073	-	-	-	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.000	12.492	12.486	12.483																																																		
0.010	12.307	12.297	12.289																																																		
0.020	12.250	12.237	12.226																																																		
0.030	12.211	12.198	12.189																																																		
0.040	12.176	12.165	12.158																																																		
0.050	12.142	12.135	12.130																																																		
0.060	12.108	12.105	12.103																																																		
0.065	12.091	12.091	12.090																																																		
0.072	12.068	12.071	12.073																																																		
-	-	-	-																																																		
-	-	-	-																																																		
Object -12V0.065A		2.Values																																																			
1.Graph <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 45%;"> </div> <div style="width: 50%;"> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.489</td><td>-12.483</td><td>-12.478</td></tr> <tr><td>0.010</td><td>-12.302</td><td>-12.293</td><td>-12.285</td></tr> <tr><td>0.020</td><td>-12.246</td><td>-12.232</td><td>-12.222</td></tr> <tr><td>0.030</td><td>-12.206</td><td>-12.193</td><td>-12.184</td></tr> <tr><td>0.040</td><td>-12.171</td><td>-12.161</td><td>-12.153</td></tr> <tr><td>0.050</td><td>-12.137</td><td>-12.130</td><td>-12.124</td></tr> <tr><td>0.060</td><td>-12.103</td><td>-12.100</td><td>-12.098</td></tr> <tr><td>0.065</td><td>-12.085</td><td>-12.085</td><td>-12.085</td></tr> <tr><td>0.072</td><td>-12.062</td><td>-12.066</td><td>-12.068</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> </div> </div>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-12.489	-12.483	-12.478	0.010	-12.302	-12.293	-12.285	0.020	-12.246	-12.232	-12.222	0.030	-12.206	-12.193	-12.184	0.040	-12.171	-12.161	-12.153	0.050	-12.137	-12.130	-12.124	0.060	-12.103	-12.100	-12.098	0.065	-12.085	-12.085	-12.085	0.072	-12.062	-12.066	-12.068	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.000	-12.489	-12.483	-12.478																																																		
0.010	-12.302	-12.293	-12.285																																																		
0.020	-12.246	-12.232	-12.222																																																		
0.030	-12.206	-12.193	-12.184																																																		
0.040	-12.171	-12.161	-12.153																																																		
0.050	-12.137	-12.130	-12.124																																																		
0.060	-12.103	-12.100	-12.098																																																		
0.065	-12.085	-12.085	-12.085																																																		
0.072	-12.062	-12.066	-12.068																																																		
-	-	-	-																																																		
-	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




Model	SUCW1R52412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.065A		


Input Volt. 24 V
 Cycle 100 mS



Min. Load (0A) ←→
 Load 100% (0.065A)




2ms/div




2ms/div

Min. Load (0A) ←→
 Load 50% (0.0325A)




2ms/div




2ms/div

Load 50% (0.0325A) ←→
 Load 100% (0.065A)



2ms/div




2ms/div



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	-12V0.065A	

Input Volt. 24 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.065A)

200mV/div




2ms/div




2ms/div

Min. Load (0A) ←→
Load 50% (0.0325A)

200mV/div



2ms/div




2ms/div

Load 50% (0.0325A) ←→
Load 100% (0.065A)

200mV/div



2ms/div



2ms/div



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+12V0.065A																																							
<p>1. Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>- -○- - Input Volt. 36V</p> </div> <div style="text-align: center;"> </div> </div>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1</td><td>2</td></tr> <tr><td>20</td><td>1</td><td>2</td></tr> <tr><td>40</td><td>1</td><td>2</td></tr> <tr><td>60</td><td>2</td><td>2</td></tr> <tr><td>80</td><td>2</td><td>2</td></tr> <tr><td>100</td><td>3</td><td>2</td></tr> <tr><td>110</td><td>4</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	1	2	20	1	2	40	1	2	60	2	2	80	2	2	100	3	2	110	4	2	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	1	2																																						
20	1	2																																						
40	1	2																																						
60	2	2																																						
80	2	2																																						
100	3	2																																						
110	4	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p>																																								
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;">Ripple [mVp-p]</div> </div> <p>Fig. Complex Ripple Wave Form</p>																																								



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure B																																					
Item	Ripple Voltage (by Load Current)																																						
Object	-12V0.065A																																						
<p>1. Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>-·-○-·- Input Volt. 36V</p> </div> </div> <p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>2</td></tr> <tr><td>20</td><td>2</td><td>3</td></tr> <tr><td>40</td><td>2</td><td>3</td></tr> <tr><td>60</td><td>2</td><td>3</td></tr> <tr><td>80</td><td>2</td><td>3</td></tr> <tr><td>100</td><td>3</td><td>3</td></tr> <tr><td>110</td><td>4</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	2	2	20	2	3	40	2	3	60	2	3	80	2	3	100	3	3	110	4	3	--	-	-	--	-	-	--	-	-	--	-	-
Load Ration [%]	Ripple Voltage [mV]																																						
	Input Volt. 18 [V]	Input Volt. 36 [V]																																					
0	2	2																																					
20	2	3																																					
40	2	3																																					
60	2	3																																					
80	2	3																																					
100	3	3																																					
110	4	3																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p> <div style="text-align: center;"> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p> </div>																																							



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple-Noise																																							
Object	+12V0.065A																																							
1. Graph <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>- -○- - Input Volt. 36V</p> </div> </div>		2. Values <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>3</td><td>3</td></tr> <tr><td>20</td><td>3</td><td>3</td></tr> <tr><td>40</td><td>3</td><td>3</td></tr> <tr><td>60</td><td>3</td><td>3</td></tr> <tr><td>80</td><td>4</td><td>3</td></tr> <tr><td>100</td><td>5</td><td>4</td></tr> <tr><td>110</td><td>5</td><td>4</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	3	3	20	3	3	40	3	3	60	3	3	80	4	3	100	5	4	110	5	4	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	3	3																																						
20	3	3																																						
40	3	3																																						
60	3	3																																						
80	4	3																																						
100	5	4																																						
110	5	4																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



<p>Model SUCW1R52412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object -12V0.065A</p>																																								
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>- - -○- - - Input Volt. 36V</p> </div> <div style="text-align: center;"> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>4</td><td>4</td></tr> <tr><td>20</td><td>5</td><td>5</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>80</td><td>5</td><td>5</td></tr> <tr><td>100</td><td>5</td><td>5</td></tr> <tr><td>110</td><td>6</td><td>6</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	4	4	20	5	5	40	5	5	60	5	5	80	5	5	100	5	5	110	6	6	-	-	-	-	-	-	-	-	-	--	-	-
Load Ration [%]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	4	4																																						
20	5	5																																						
40	5	5																																						
60	5	5																																						
80	5	5																																						
100	5	5																																						
110	6	6																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <div style="text-align: center;"> </div> <p>Fig.Complex Ripple Noise Wave Form</p>																																								




Model SUCW1R52412		Testing Circuitry Figure B 2.Values <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>2</td><td>3</td></tr> <tr><td>-40</td><td>2</td><td>3</td></tr> <tr><td>-20</td><td>2</td><td>2</td></tr> <tr><td>0</td><td>2</td><td>2</td></tr> <tr><td>25</td><td>2</td><td>3</td></tr> <tr><td>55</td><td>1</td><td>2</td></tr> <tr><td>60</td><td>1</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	2	3	-40	2	3	-20	2	2	0	2	2	25	2	3	55	1	2	60	1	2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%		Load 100%																																					
-60	2	3																																						
-40	2	3																																						
-20	2	2																																						
0	2	2																																						
25	2	3																																						
55	1	2																																						
60	1	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
Item	Ripple Voltage (by Ambient Temp.)																																							
Object	+12V0.065A																																							
1.Graph <div style="text-align: right; margin-bottom: 5px;"> ---□--- Load 50% —△— Load 100% </div> <p style="text-align: center;">Ambient Temperature [°C] Input Volt. 24V</p>																																								
Object -12V0.065A		2.Values <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3</td><td>2</td></tr> <tr><td>-40</td><td>3</td><td>2</td></tr> <tr><td>-20</td><td>2</td><td>2</td></tr> <tr><td>0</td><td>2</td><td>2</td></tr> <tr><td>25</td><td>2</td><td>2</td></tr> <tr><td>55</td><td>2</td><td>2</td></tr> <tr><td>60</td><td>2</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	3	2	-40	3	2	-20	2	2	0	2	2	25	2	2	55	2	2	60	2	2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%		Load 100%																																					
-60	3	2																																						
-40	3	2																																						
-20	2	2																																						
0	2	2																																						
25	2	2																																						
55	2	2																																						
60	2	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
1.Graph <div style="text-align: right; margin-bottom: 5px;"> ---□--- Load 50% —△— Load 100% </div> <p style="text-align: center;">Ambient Temperature [°C] Input Volt. 24V</p> <p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model	SUCW1R52412
Item	Ambient Temperature Drift
Object	+12V0.065A


Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	12.084	12.084	12.084
-40	12.095	12.095	12.095
-20	12.100	12.099	12.099
0	12.099	12.099	12.098
25	12.091	12.090	12.089
55	12.074	12.072	12.071
60	12.069	12.068	12.067
-	-	-	-
-	-	-	-
-	-	-	-

Object	-12V0.065A
--------	------------



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-12.080	-12.080	-12.080
-40	-12.090	-12.090	-12.091
-20	-12.094	-12.094	-12.095
0	-12.093	-12.093	-12.093
25	-12.085	-12.084	-12.084
55	-12.066	-12.065	-12.064
60	-12.061	-12.061	-12.060
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		
Model	SUCW1R52412	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.065A (AVR 2):0 - 0.065A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$


2. Values

Object		+12V0.065A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	18	0	12.490	±210	±1.8
Minimum Voltage	55	36	0.065	12.071		

Object		-12V0.065A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	18	0	-12.487	±212	±1.8
Minimum Voltage	55	36	0.065	-12.064		



Model SUCW1R52412		Temperature 25°C Testing Circuitry Figure A																						
Item Time Lapse Drift																								
Object +12V0.065A																								
1.Graph  Input Volt. 24V Load 100%		2.Values <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.095</td></tr> <tr><td>0.5</td><td>12.090</td></tr> <tr><td>1.0</td><td>12.091</td></tr> <tr><td>2.0</td><td>12.092</td></tr> <tr><td>3.0</td><td>12.092</td></tr> <tr><td>4.0</td><td>12.092</td></tr> <tr><td>5.0</td><td>12.092</td></tr> <tr><td>6.0</td><td>12.091</td></tr> <tr><td>7.0</td><td>12.090</td></tr> <tr><td>8.0</td><td>12.088</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.095	0.5	12.090	1.0	12.091	2.0	12.092	3.0	12.092	4.0	12.092	5.0	12.092	6.0	12.091	7.0	12.090	8.0	12.088
Time since start [H]	Output Voltage [V]																							
0.0	12.095																							
0.5	12.090																							
1.0	12.091																							
2.0	12.092																							
3.0	12.092																							
4.0	12.092																							
5.0	12.092																							
6.0	12.091																							
7.0	12.090																							
8.0	12.088																							


Object -12V0.065A		2.Values																					
1.Graph  Input Volt. 24V Load 100%																							
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.095</td></tr> <tr><td>0.5</td><td>-12.091</td></tr> <tr><td>1.0</td><td>-12.091</td></tr> <tr><td>2.0</td><td>-12.092</td></tr> <tr><td>3.0</td><td>-12.091</td></tr> <tr><td>4.0</td><td>-12.092</td></tr> <tr><td>5.0</td><td>-12.091</td></tr> <tr><td>6.0</td><td>-12.091</td></tr> <tr><td>7.0</td><td>-12.090</td></tr> <tr><td>8.0</td><td>-12.088</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	-12.095	0.5	-12.091	1.0	-12.091	2.0	-12.092	3.0	-12.091	4.0	-12.092	5.0	-12.091	6.0	-12.091	7.0	-12.090	8.0
Time since start [H]	Output Voltage [V]																						
0.0	-12.095																						
0.5	-12.091																						
1.0	-12.091																						
2.0	-12.092																						
3.0	-12.091																						
4.0	-12.092																						
5.0	-12.091																						
6.0	-12.091																						
7.0	-12.090																						
8.0	-12.088																						



Model	SUCW1R52412	Temperature 25°C Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+12V0.065A	


1. Graph

Input Volt. 18 V



2. Values


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.1	3.6	3.7	0.2	1.3
100 %	0.1	3.8	3.9	0.1	0.7






Model	SUCW1R52412	Temperature 25°C Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+12V0.065A	

1. Graph



2. Values

		[mS]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.6	3.7	0.2	1.3
100 %		0.1	3.8	3.9	0.1	0.7





Model SUCW1R52412		Testing Circuitry Figure A																																							
Item Minimum Input Voltage for Regulated Output Voltage																																									
Object +12V0.065A																																									
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>9.2</td><td>9.5</td></tr> <tr><td>-40</td><td>8.9</td><td>9.6</td></tr> <tr><td>-20</td><td>8.7</td><td>9.7</td></tr> <tr><td>0</td><td>8.4</td><td>10.0</td></tr> <tr><td>25</td><td>8.1</td><td>10.1</td></tr> <tr><td>55</td><td>7.9</td><td>10.5</td></tr> <tr><td>60</td><td>7.9</td><td>10.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	9.2	9.5	-40	8.9	9.6	-20	8.7	9.7	0	8.4	10.0	25	8.1	10.1	55	7.9	10.5	60	7.9	10.6	--	-	-	--	-	-	--	-	-	--	-	-	
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	9.2	9.5																																							
-40	8.9	9.6																																							
-20	8.7	9.7																																							
0	8.4	10.0																																							
25	8.1	10.1																																							
55	7.9	10.5																																							
60	7.9	10.6																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object -12V0.065A		Testing Circuitry Figure A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p>			<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>9.0</td><td>9.4</td></tr> <tr><td>-40</td><td>8.9</td><td>9.5</td></tr> <tr><td>-20</td><td>8.6</td><td>9.6</td></tr> <tr><td>0</td><td>8.3</td><td>9.8</td></tr> <tr><td>25</td><td>8.0</td><td>10.1</td></tr> <tr><td>55</td><td>7.9</td><td>10.4</td></tr> <tr><td>60</td><td>7.9</td><td>10.4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	9.0	9.4	-40	8.9	9.5	-20	8.6	9.6	0	8.3	9.8	25	8.0	10.1	55	7.9	10.4	60	7.9	10.4	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	9.0	9.4																																							
-40	8.9	9.5																																							
-20	8.6	9.6																																							
0	8.3	9.8																																							
25	8.0	10.1																																							
55	7.9	10.4																																							
60	7.9	10.4																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									




Model	SUCW1R52412
Item	Overcurrent Protection
Object	+12V0.065A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

— Input Volt. 18V
— Input Volt. 24V
— Input Volt. 36V




2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
12.0	0.07	0.07	0.07
11.4	0.16	0.16	0.14
10.8	0.17	0.17	0.15
9.6	0.19	0.19	0.17
8.4	0.22	0.21	0.19
7.2	0.24	0.23	0.21
6.0	0.26	0.25	0.23
4.8	0.29	0.27	0.24
3.6	0.31	0.28	0.26
2.4	0.33	0.30	0.27
1.2	0.34	0.30	0.28
0.0	0.35	0.30	0.29

Object	-12V0.065A
--------	------------

1.Graph

— Input Volt. 18V
— Input Volt. 24V
— Input Volt. 36V



Note: Slanted line shows the range of the rated load current.

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-12.0	0.07	0.07	0.07
-11.4	0.16	0.16	0.14
-10.8	0.17	0.17	0.15
-9.6	0.19	0.19	0.17
-8.4	0.21	0.21	0.19
-7.2	0.24	0.23	0.21
-6.0	0.26	0.25	0.23
-4.8	0.29	0.27	0.24
-3.6	0.31	0.28	0.26
-2.4	0.33	0.29	0.27
-1.2	0.34	0.30	0.28
0.0	0.35	0.30	0.29




Figure A




Figure B (Ripple and Ripple noise Characteristic)