



TEST DATA OF SUCW30512

Regulated DC Power Supply
Mar 17, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo
Hayato Nakatsubo Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL


Model	SUCW30512	Temperature Testing Circuitry	25°C Figure A																																																																														
Item	Input Current (by Input Voltage)																																																																																
Object	_____																																																																																
1. Graph		<p>Legend:</p> <ul style="list-style-type: none"> Load 100%: Solid line with triangle markers Load 50%: Dashed line with square markers Load 0%: Dotted line with circle markers <p>Input Current [A]</p> <p>Input Voltage [V]</p>																																																																															
			2. Values																																																																														
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.49</td><td>0.126</td><td>0.024</td><td>0.009</td></tr> <tr><td>2.66</td><td>0.117</td><td>0.922</td><td>0.039</td></tr> <tr><td>2.83</td><td>0.110</td><td>0.874</td><td>1.970</td></tr> <tr><td>3.00</td><td>0.107</td><td>0.812</td><td>1.855</td></tr> <tr><td>4.00</td><td>0.085</td><td>0.556</td><td>1.120</td></tr> <tr><td>4.50</td><td>0.077</td><td>0.491</td><td>0.966</td></tr> <tr><td>5.00</td><td>0.071</td><td>0.439</td><td>0.850</td></tr> <tr><td>6.00</td><td>0.062</td><td>0.367</td><td>0.703</td></tr> <tr><td>7.00</td><td>0.058</td><td>0.319</td><td>0.599</td></tr> <tr><td>8.00</td><td>0.056</td><td>0.283</td><td>0.524</td></tr> <tr><td>9.00</td><td>0.055</td><td>0.257</td><td>0.470</td></tr> <tr><td>10.00</td><td>0.055</td><td>0.237</td><td>0.427</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.000	0.000	0.000	2.00	0.000	0.000	0.000	2.49	0.126	0.024	0.009	2.66	0.117	0.922	0.039	2.83	0.110	0.874	1.970	3.00	0.107	0.812	1.855	4.00	0.085	0.556	1.120	4.50	0.077	0.491	0.966	5.00	0.071	0.439	0.850	6.00	0.062	0.367	0.703	7.00	0.058	0.319	0.599	8.00	0.056	0.283	0.524	9.00	0.055	0.257	0.470	10.00	0.055	0.237	0.427	--	-	-	-	--	-	-	-	--	-	-	-		
Input Voltage [V]		Input Current [A]																																																																															
	Load 0%	Load 50%	Load 100%																																																																														
0.00	0.000	0.000	0.000																																																																														
1.70	0.000	0.000	0.000																																																																														
2.00	0.000	0.000	0.000																																																																														
2.49	0.126	0.024	0.009																																																																														
2.66	0.117	0.922	0.039																																																																														
2.83	0.110	0.874	1.970																																																																														
3.00	0.107	0.812	1.855																																																																														
4.00	0.085	0.556	1.120																																																																														
4.50	0.077	0.491	0.966																																																																														
5.00	0.071	0.439	0.850																																																																														
6.00	0.062	0.367	0.703																																																																														
7.00	0.058	0.319	0.599																																																																														
8.00	0.056	0.283	0.524																																																																														
9.00	0.055	0.257	0.470																																																																														
10.00	0.055	0.237	0.427																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														

Note: Slanted line shows the range of the rated input voltage.

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.00	0.000	0.000	0.000
1.70	0.000	0.000	0.000
2.00	0.000	0.000	0.000
2.49	0.126	0.024	0.009
2.66	0.117	0.922	0.039
2.83	0.110	0.874	1.970
3.00	0.107	0.812	1.855
4.00	0.085	0.556	1.120
4.50	0.077	0.491	0.966
5.00	0.071	0.439	0.850
6.00	0.062	0.367	0.703
7.00	0.058	0.319	0.599
8.00	0.056	0.283	0.524
9.00	0.055	0.257	0.470
10.00	0.055	0.237	0.427
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model	SUCW30512
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ration [%]	Input Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0	0.076	0.070	0.055
20	0.240	0.217	0.136
40	0.410	0.369	0.217
60	0.576	0.514	0.298
80	0.765	0.676	0.380
100	0.966	0.848	0.463
110	1.054	0.939	0.506
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Ration [%]	Input Power [W]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0	0.34	0.35	0.50
20	1.07	1.08	1.24
40	1.82	1.82	1.96
60	2.59	2.58	2.69
80	3.40	3.36	3.43
100	4.26	4.18	4.17
110	4.69	4.61	4.55
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SUCW30512																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>70.7</td> <td>71.8</td> </tr> <tr> <td>4.5</td> <td>71.5</td> <td>74.0</td> </tr> <tr> <td>5.0</td> <td>71.8</td> <td>75.4</td> </tr> <tr> <td>6.0</td> <td>71.7</td> <td>76.4</td> </tr> <tr> <td>7.0</td> <td>70.7</td> <td>76.7</td> </tr> <tr> <td>8.0</td> <td>69.4</td> <td>76.4</td> </tr> <tr> <td>9.0</td> <td>68.0</td> <td>75.8</td> </tr> <tr> <td>9.5</td> <td>67.1</td> <td>75.3</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	70.7	71.8	4.5	71.5	74.0	5.0	71.8	75.4	6.0	71.7	76.4	7.0	70.7	76.7	8.0	69.4	76.4	9.0	68.0	75.8	9.5	67.1	75.3	-	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.0	70.7	71.8																																
4.5	71.5	74.0																																
5.0	71.8	75.4																																
6.0	71.7	76.4																																
7.0	70.7	76.7																																
8.0	69.4	76.4																																
9.0	68.0	75.8																																
9.5	67.1	75.3																																
-	-	-																																

COSEL

Model	SUCW30512	Temperature Testing Circuitry	25°C Figure A																										
Item	Efficiency (by Load Current)																												
Object	_____	2.Values																											
1.Graph	<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - -○- - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [%]</th> <th>5V [%]</th> <th>9V [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>56</td><td>54</td><td>48</td></tr> <tr><td>40</td><td>68</td><td>65</td><td>60</td></tr> <tr><td>60</td><td>72</td><td>70</td><td>65</td></tr> <tr><td>80</td><td>74</td><td>73</td><td>68</td></tr> <tr><td>100</td><td>74</td><td>74</td><td>74</td></tr> <tr><td>110</td><td>74</td><td>75</td><td>76</td></tr> </tbody> </table>	Load Ration [%]	4.5V [%]	5V [%]	9V [%]	20	56	54	48	40	68	65	60	60	72	70	65	80	74	73	68	100	74	74	74	110	74	75	76
Load Ration [%]	4.5V [%]	5V [%]	9V [%]																										
20	56	54	48																										
40	68	65	60																										
60	72	70	65																										
80	74	73	68																										
100	74	74	74																										
110	74	75	76																										
		Load Ration [%]	Efficiency [%]																										
			Input Volt. 4.5[V] Input Volt. 5[V] Input Volt. 9[V]																										
0	-	-	-																										
20	59.2	58.6	51.5																										
40	69.5	69.6	64.6																										
60	73.2	73.5	70.3																										
80	74.1	75.2	73.8																										
100	74.0	75.6	75.6																										
110	74.0	75.2	76.3																										
--	-	-	-																										
--	-	-	-																										
--	-	-	-																										
--	-	-	-																										

COSEL

Model	SUCW30512	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+12V0.13A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.186</td><td>12.120</td></tr> <tr><td>4.5</td><td>12.181</td><td>12.119</td></tr> <tr><td>5.0</td><td>12.179</td><td>12.119</td></tr> <tr><td>6.0</td><td>12.175</td><td>12.118</td></tr> <tr><td>7.0</td><td>12.172</td><td>12.118</td></tr> <tr><td>8.0</td><td>12.171</td><td>12.118</td></tr> <tr><td>9.0</td><td>12.170</td><td>12.117</td></tr> <tr><td>9.5</td><td>12.169</td><td>12.117</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	12.186	12.120	4.5	12.181	12.119	5.0	12.179	12.119	6.0	12.175	12.118	7.0	12.172	12.118	8.0	12.171	12.118	9.0	12.170	12.117	9.5	12.169	12.117	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	12.186	12.120																																	
4.5	12.181	12.119																																	
5.0	12.179	12.119																																	
6.0	12.175	12.118																																	
7.0	12.172	12.118																																	
8.0	12.171	12.118																																	
9.0	12.170	12.117																																	
9.5	12.169	12.117																																	
-	-	-																																	
Object			2.Values																																
1.Graph			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.182</td><td>-12.111</td></tr> <tr><td>4.5</td><td>-12.179</td><td>-12.112</td></tr> <tr><td>5.0</td><td>-12.177</td><td>-12.113</td></tr> <tr><td>6.0</td><td>-12.174</td><td>-12.114</td></tr> <tr><td>7.0</td><td>-12.171</td><td>-12.114</td></tr> <tr><td>8.0</td><td>-12.170</td><td>-12.114</td></tr> <tr><td>9.0</td><td>-12.169</td><td>-12.115</td></tr> <tr><td>9.5</td><td>-12.168</td><td>-12.115</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-12.182	-12.111	4.5	-12.179	-12.112	5.0	-12.177	-12.113	6.0	-12.174	-12.114	7.0	-12.171	-12.114	8.0	-12.170	-12.114	9.0	-12.169	-12.115	9.5	-12.168	-12.115	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	-12.182	-12.111																																	
4.5	-12.179	-12.112																																	
5.0	-12.177	-12.113																																	
6.0	-12.174	-12.114																																	
7.0	-12.171	-12.114																																	
8.0	-12.170	-12.114																																	
9.0	-12.169	-12.115																																	
9.5	-12.168	-12.115																																	
-	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


COSEL

Model	SUCW30512
Item	Load Regulation
Object	+12V0.13A
1.Graph	<p style="text-align: center;"> Input Volt. 4.5V Input Volt. 5V Input Volt. 9V </p>

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	12.350	12.344	12.335
0.026	12.238	12.235	12.225
0.052	12.197	12.194	12.184
0.078	12.168	12.165	12.157
0.104	12.142	12.140	12.135
0.130	12.118	12.118	12.116
0.143	12.106	12.107	12.107
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-





2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	-12.368	-12.358	-12.347
0.026	-12.237	-12.234	-12.225
0.052	-12.194	-12.191	-12.184
0.078	-12.163	-12.161	-12.155
0.104	-12.137	-12.135	-12.133
0.130	-12.111	-12.112	-12.114
0.143	-12.098	-12.100	-12.104
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL



COSEL

COSEL

Model	SUCW30512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.13A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 4.5V (solid line with triangle markers) and Input Volt. 9V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.00 to 0.16. The y-axis represents Ripple Voltage [mV] from 0 to 50. A slanted line is drawn through the data points, indicating the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 9V)</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>1</td><td>1</td></tr> <tr><td>0.026</td><td>1</td><td>1</td></tr> <tr><td>0.052</td><td>1</td><td>1</td></tr> <tr><td>0.078</td><td>1</td><td>1</td></tr> <tr><td>0.104</td><td>2</td><td>1</td></tr> <tr><td>0.130</td><td>5</td><td>1</td></tr> <tr><td>0.143</td><td>6</td><td>2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)	0.000	1	1	0.026	1	1	0.052	1	1	0.078	1	1	0.104	2	1	0.130	5	1	0.143	6	2	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)																																						
0.000	1	1																																						
0.026	1	1																																						
0.052	1	1																																						
0.078	1	1																																						
0.104	2	1																																						
0.130	5	1																																						
0.143	6	2																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>1</td><td>1</td></tr> <tr><td>0.026</td><td>1</td><td>1</td></tr> <tr><td>0.052</td><td>1</td><td>1</td></tr> <tr><td>0.078</td><td>1</td><td>1</td></tr> <tr><td>0.104</td><td>2</td><td>1</td></tr> <tr><td>0.130</td><td>5</td><td>1</td></tr> <tr><td>0.143</td><td>6</td><td>2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	1	1	0.026	1	1	0.052	1	1	0.078	1	1	0.104	2	1	0.130	5	1	0.143	6	2	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	1	1																																						
0.026	1	1																																						
0.052	1	1																																						
0.078	1	1																																						
0.104	2	1																																						
0.130	5	1																																						
0.143	6	2																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL


Model	SUCW30512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-12V0.13A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 50 mV, and the X-axis ranges from 0.00 to 0.16 A. Two curves are plotted: one for Input Volt. 4.5V (solid line with triangles) and one for Input Volt. 9V (dashed line with circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 9V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>1</td></tr> <tr><td>0.026</td><td>2</td><td>1</td></tr> <tr><td>0.052</td><td>2</td><td>1</td></tr> <tr><td>0.078</td><td>2</td><td>1</td></tr> <tr><td>0.104</td><td>2</td><td>1</td></tr> <tr><td>0.130</td><td>4</td><td>1</td></tr> <tr><td>0.143</td><td>5</td><td>1</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)	0.00	2	1	0.026	2	1	0.052	2	1	0.078	2	1	0.104	2	1	0.130	4	1	0.143	5	1	—	—	—	—	—	—	—	—	—	—	—	—			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)																																						
0.00	2	1																																						
0.026	2	1																																						
0.052	2	1																																						
0.078	2	1																																						
0.104	2	1																																						
0.130	4	1																																						
0.143	5	1																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>1</td></tr> <tr><td>0.026</td><td>2</td><td>1</td></tr> <tr><td>0.052</td><td>2</td><td>1</td></tr> <tr><td>0.078</td><td>2</td><td>1</td></tr> <tr><td>0.104</td><td>2</td><td>1</td></tr> <tr><td>0.130</td><td>4</td><td>1</td></tr> <tr><td>0.143</td><td>5</td><td>1</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	2	1	0.026	2	1	0.052	2	1	0.078	2	1	0.104	2	1	0.130	4	1	0.143	5	1	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	2	1																																						
0.026	2	1																																						
0.052	2	1																																						
0.078	2	1																																						
0.104	2	1																																						
0.130	4	1																																						
0.143	5	1																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	SUCW30512
Item	Ripple-Noise
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	3	4
0.026	4	4
0.052	5	4
0.078	5	5
0.104	6	6
0.130	10	7
0.143	12	7
-	-	-
-	-	-
-	-	-
-	-	-






Fig.Complex Ripple Noise Wave Form

COSEL

Model	SUCW30512																																						
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																					
Object	-12V0.13A																																						
1.Graph																																							
<p style="text-align: center;"> Input Volt. 4.5V Input Volt. 9V </p> 																																							
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
																																							
<p>Fig.Complex Ripple Noise Wave Form</p>																																							
2.Values																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>14</td><td>17</td></tr> <tr><td>0.026</td><td>16</td><td>17</td></tr> <tr><td>0.052</td><td>16</td><td>17</td></tr> <tr><td>0.078</td><td>17</td><td>18</td></tr> <tr><td>0.104</td><td>18</td><td>19</td></tr> <tr><td>0.130</td><td>19</td><td>20</td></tr> <tr><td>0.143</td><td>20</td><td>20</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	14	17	0.026	16	17	0.052	16	17	0.078	17	18	0.104	18	19	0.130	19	20	0.143	20	20	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																						
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																					
0.000	14	17																																					
0.026	16	17																																					
0.052	16	17																																					
0.078	17	18																																					
0.104	18	19																																					
0.130	19	20																																					
0.143	20	20																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					

COSEL

<p>Model SUCW30512</p> <p>Item Ripple Voltage (by Ambient Temp.)</p> <p>Object +12V0.13A</p>	Testing Circuitry Figure B																																							
	2.Values																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>4</td><td>9</td></tr> <tr><td>-40</td><td>3</td><td>7</td></tr> <tr><td>-20</td><td>2</td><td>5</td></tr> <tr><td>0</td><td>2</td><td>4</td></tr> <tr><td>25</td><td>2</td><td>3</td></tr> <tr><td>55</td><td>1</td><td>2</td></tr> <tr><td>60</td><td>1</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	4	9	-40	3	7	-20	2	5	0	2	4	25	2	3	55	1	2	60	1	2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	4	9																																						
-40	3	7																																						
-20	2	5																																						
0	2	4																																						
25	2	3																																						
55	1	2																																						
60	1	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>1.Graph</p> <p>Ambient Temperature [°C]</p> <p>Ripple Voltage [mV]</p> <p>Input Volt. 5V</p> <p>Object -12V0.13A</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3</td><td>4</td></tr> <tr><td>-40</td><td>3</td><td>4</td></tr> <tr><td>-20</td><td>3</td><td>4</td></tr> <tr><td>0</td><td>3</td><td>3</td></tr> <tr><td>25</td><td>2</td><td>2</td></tr> <tr><td>55</td><td>1</td><td>2</td></tr> <tr><td>60</td><td>1</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	3	4	-40	3	4	-20	3	4	0	3	3	25	2	2	55	1	2	60	1	2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	3	4																																						
-40	3	4																																						
-20	3	4																																						
0	3	3																																						
25	2	2																																						
55	1	2																																						
60	1	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>1.Graph</p> <p>Ambient Temperature [°C]</p> <p>Ripple Voltage [mV]</p> <p>Input Volt. 5V</p> <p>Measured by 100 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3</td><td>4</td></tr> <tr><td>-40</td><td>3</td><td>4</td></tr> <tr><td>-20</td><td>3</td><td>4</td></tr> <tr><td>0</td><td>3</td><td>3</td></tr> <tr><td>25</td><td>2</td><td>2</td></tr> <tr><td>55</td><td>1</td><td>2</td></tr> <tr><td>60</td><td>1</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	3	4	-40	3	4	-20	3	4	0	3	3	25	2	2	55	1	2	60	1	2	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	3	4																																						
-40	3	4																																						
-20	3	4																																						
0	3	3																																						
25	2	2																																						
55	1	2																																						
60	1	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						

COSEL

<p>Model SUCW30512</p> <p>Item Ambient Temperature Drift</p> <p>Object +12V0.13A</p>	<p>Testing Circuitry Figure A</p>																																																					
	<p>2.Values</p>																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.058</td><td>12.058</td><td>12.057</td></tr> <tr><td>-40</td><td>12.082</td><td>12.081</td><td>12.080</td></tr> <tr><td>-20</td><td>12.099</td><td>12.099</td><td>12.097</td></tr> <tr><td>0</td><td>12.112</td><td>12.111</td><td>12.110</td></tr> <tr><td>25</td><td>12.120</td><td>12.119</td><td>12.118</td></tr> <tr><td>55</td><td>12.121</td><td>12.119</td><td>12.118</td></tr> <tr><td>60</td><td>12.120</td><td>12.119</td><td>12.116</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.058	12.058	12.057	-40	12.082	12.081	12.080	-20	12.099	12.099	12.097	0	12.112	12.111	12.110	25	12.120	12.119	12.118	55	12.121	12.119	12.118	60	12.120	12.119	12.116	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	12.058	12.058	12.057																																																			
-40	12.082	12.081	12.080																																																			
-20	12.099	12.099	12.097																																																			
0	12.112	12.111	12.110																																																			
25	12.120	12.119	12.118																																																			
55	12.121	12.119	12.118																																																			
60	12.120	12.119	12.116																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<p>2.Values</p>																																																					
<p>Object -12V0.13A</p> <p>1.Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<p>2.Values</p>																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.050</td><td>-12.052</td><td>-12.055</td></tr> <tr><td>-40</td><td>-12.073</td><td>-12.075</td><td>-12.078</td></tr> <tr><td>-20</td><td>-12.091</td><td>-12.093</td><td>-12.095</td></tr> <tr><td>0</td><td>-12.103</td><td>-12.105</td><td>-12.107</td></tr> <tr><td>25</td><td>-12.112</td><td>-12.113</td><td>-12.115</td></tr> <tr><td>55</td><td>-12.112</td><td>-12.113</td><td>-12.115</td></tr> <tr><td>60</td><td>-12.111</td><td>-12.112</td><td>-12.113</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.050	-12.052	-12.055	-40	-12.073	-12.075	-12.078	-20	-12.091	-12.093	-12.095	0	-12.103	-12.105	-12.107	25	-12.112	-12.113	-12.115	55	-12.112	-12.113	-12.115	60	-12.111	-12.112	-12.113	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	-12.050	-12.052	-12.055																																																			
-40	-12.073	-12.075	-12.078																																																			
-20	-12.091	-12.093	-12.095																																																			
0	-12.103	-12.105	-12.107																																																			
25	-12.112	-12.113	-12.115																																																			
55	-12.112	-12.113	-12.115																																																			
60	-12.111	-12.112	-12.113																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			



Model	SUCW30512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.13A (AVR 2) : 0 - 0.13A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values


Object	+12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	12.354	±137	±1.1
Minimum Voltage	-40	9	0.13	12.080		

Object	-12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	-12.369	±146	±1.2
Minimum Voltage	-40	9	0.13	-12.078		

COSEL

Model	SUCW30512	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+12V0.13A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.119</td></tr> <tr><td>0.5</td><td>12.118</td></tr> <tr><td>1.0</td><td>12.118</td></tr> <tr><td>2.0</td><td>12.118</td></tr> <tr><td>3.0</td><td>12.118</td></tr> <tr><td>4.0</td><td>12.119</td></tr> <tr><td>5.0</td><td>12.119</td></tr> <tr><td>6.0</td><td>12.119</td></tr> <tr><td>7.0</td><td>12.119</td></tr> <tr><td>8.0</td><td>12.119</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.119	0.5	12.118	1.0	12.118	2.0	12.118	3.0	12.118	4.0	12.119	5.0	12.119	6.0	12.119	7.0	12.119	8.0	12.119
Time since start [H]	Output Voltage [V]																								
0.0	12.119																								
0.5	12.118																								
1.0	12.118																								
2.0	12.118																								
3.0	12.118																								
4.0	12.119																								
5.0	12.119																								
6.0	12.119																								
7.0	12.119																								
8.0	12.119																								
Object			1.Graph																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>			2.Values																						
			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.113</td></tr> <tr><td>0.5</td><td>-12.115</td></tr> <tr><td>1.0</td><td>-12.115</td></tr> <tr><td>2.0</td><td>-12.115</td></tr> <tr><td>3.0</td><td>-12.114</td></tr> <tr><td>4.0</td><td>-12.114</td></tr> <tr><td>5.0</td><td>-12.115</td></tr> <tr><td>6.0</td><td>-12.115</td></tr> <tr><td>7.0</td><td>-12.115</td></tr> <tr><td>8.0</td><td>-12.115</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.113	0.5	-12.115	1.0	-12.115	2.0	-12.115	3.0	-12.114	4.0	-12.114	5.0	-12.115	6.0	-12.115	7.0	-12.115	8.0	-12.115
Time since start [H]	Output Voltage [V]																								
0.0	-12.113																								
0.5	-12.115																								
1.0	-12.115																								
2.0	-12.115																								
3.0	-12.114																								
4.0	-12.114																								
5.0	-12.115																								
6.0	-12.115																								
7.0	-12.115																								
8.0	-12.115																								

COSEL


COSEL

COSEL

Model	SUCW30512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.13A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.5	3.1
-40	2.3	2.9
-20	2.4	2.9
0	2.4	2.9
25	2.4	2.9
55	2.4	3.1
60	2.4	3.1
-	-	-
-	-	-
-	-	-
-	-	-

Object	-12V0.13A
--------	-----------

1.Graph

---□--- Load 50%
—△— Load 100%





2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.4	3.3
-40	2.1	2.8
-20	2.3	2.8
0	2.3	2.8
25	2.3	2.8
55	2.3	3.0
60	2.3	3.0
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SUCW30512	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+12V0.13A																																																									
1.Graph	<p style="text-align: center;">Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p> 	2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>11.4</td><td>0.31</td><td>0.33</td><td>0.35</td></tr> <tr><td>10.8</td><td>0.33</td><td>0.35</td><td>0.36</td></tr> <tr><td>9.6</td><td>0.36</td><td>0.37</td><td>0.38</td></tr> <tr><td>8.4</td><td>0.40</td><td>0.40</td><td>0.40</td></tr> <tr><td>7.2</td><td>0.43</td><td>0.43</td><td>0.41</td></tr> <tr><td>6.0</td><td>0.46</td><td>0.46</td><td>0.42</td></tr> <tr><td>4.8</td><td>0.48</td><td>0.48</td><td>0.43</td></tr> <tr><td>3.6</td><td>0.50</td><td>0.49</td><td>0.43</td></tr> <tr><td>2.4</td><td>0.50</td><td>0.48</td><td>0.41</td></tr> <tr><td>1.2</td><td>0.46</td><td>0.44</td><td>0.39</td></tr> <tr><td>0.0</td><td>0.42</td><td>0.42</td><td>0.39</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	12.0	0.13	0.13	0.13	11.4	0.31	0.33	0.35	10.8	0.33	0.35	0.36	9.6	0.36	0.37	0.38	8.4	0.40	0.40	0.40	7.2	0.43	0.43	0.41	6.0	0.46	0.46	0.42	4.8	0.48	0.48	0.43	3.6	0.50	0.49	0.43	2.4	0.50	0.48	0.41	1.2	0.46	0.44	0.39	0.0	0.42	0.42	0.39	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
12.0	0.13	0.13	0.13																																																							
11.4	0.31	0.33	0.35																																																							
10.8	0.33	0.35	0.36																																																							
9.6	0.36	0.37	0.38																																																							
8.4	0.40	0.40	0.40																																																							
7.2	0.43	0.43	0.41																																																							
6.0	0.46	0.46	0.42																																																							
4.8	0.48	0.48	0.43																																																							
3.6	0.50	0.49	0.43																																																							
2.4	0.50	0.48	0.41																																																							
1.2	0.46	0.44	0.39																																																							
0.0	0.42	0.42	0.39																																																							
Object	-12V0.13A	2.Values																																																								
1.Graph	<p style="text-align: center;">Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p> 	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>-11.4</td><td>0.31</td><td>0.33</td><td>0.35</td></tr> <tr><td>-10.8</td><td>0.33</td><td>0.34</td><td>0.36</td></tr> <tr><td>-9.6</td><td>0.36</td><td>0.37</td><td>0.38</td></tr> <tr><td>-8.4</td><td>0.39</td><td>0.40</td><td>0.40</td></tr> <tr><td>-7.2</td><td>0.43</td><td>0.43</td><td>0.41</td></tr> <tr><td>-6.0</td><td>0.46</td><td>0.46</td><td>0.42</td></tr> <tr><td>-4.8</td><td>0.48</td><td>0.48</td><td>0.43</td></tr> <tr><td>-3.6</td><td>0.50</td><td>0.49</td><td>0.43</td></tr> <tr><td>-2.4</td><td>0.50</td><td>0.48</td><td>0.42</td></tr> <tr><td>-1.2</td><td>0.46</td><td>0.44</td><td>0.39</td></tr> <tr><td>0.0</td><td>0.42</td><td>0.42</td><td>0.39</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-12.0	0.13	0.13	0.13	-11.4	0.31	0.33	0.35	-10.8	0.33	0.34	0.36	-9.6	0.36	0.37	0.38	-8.4	0.39	0.40	0.40	-7.2	0.43	0.43	0.41	-6.0	0.46	0.46	0.42	-4.8	0.48	0.48	0.43	-3.6	0.50	0.49	0.43	-2.4	0.50	0.48	0.42	-1.2	0.46	0.44	0.39	0.0	0.42	0.42	0.39	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
-12.0	0.13	0.13	0.13																																																							
-11.4	0.31	0.33	0.35																																																							
-10.8	0.33	0.34	0.36																																																							
-9.6	0.36	0.37	0.38																																																							
-8.4	0.39	0.40	0.40																																																							
-7.2	0.43	0.43	0.41																																																							
-6.0	0.46	0.46	0.42																																																							
-4.8	0.48	0.48	0.43																																																							
-3.6	0.50	0.49	0.43																																																							
-2.4	0.50	0.48	0.42																																																							
-1.2	0.46	0.44	0.39																																																							
0.0	0.42	0.42	0.39																																																							

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)