



# TEST DATA OF SUS32412

Regulated DC Power Supply  
Mar 8, 2005

Approved by : Tetsuo Sugimori  
Tetsuo Sugimori                                  Design Manager

Prepared by : Hayato Nakatsubo  
Hayato Nakatsubo                                  Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Figure of Testing Circuitry . . . . .	18

(Final Page 18)


**COSEL**

Model	SUS32412	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
1. Graph		—△— Load 100% -□--- Load 50% -○--- Load 0%																																																																																
		2. Values																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.8</td><td>0.019</td><td>0.001</td><td>0.001</td></tr> <tr><td>9.2</td><td>0.019</td><td>0.213</td><td>0.004</td></tr> <tr><td>10.0</td><td>0.018</td><td>0.194</td><td>0.386</td></tr> <tr><td>12.0</td><td>0.017</td><td>0.160</td><td>0.314</td></tr> <tr><td>16.0</td><td>0.015</td><td>0.121</td><td>0.231</td></tr> <tr><td>18.0</td><td>0.014</td><td>0.108</td><td>0.209</td></tr> <tr><td>20.0</td><td>0.013</td><td>0.098</td><td>0.184</td></tr> <tr><td>24.0</td><td>0.013</td><td>0.083</td><td>0.154</td></tr> <tr><td>28.0</td><td>0.013</td><td>0.073</td><td>0.133</td></tr> <tr><td>32.0</td><td>0.013</td><td>0.066</td><td>0.118</td></tr> <tr><td>36.0</td><td>0.014</td><td>0.061</td><td>0.107</td></tr> <tr><td>40.0</td><td>0.016</td><td>0.057</td><td>0.098</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	8.8	0.019	0.001	0.001	9.2	0.019	0.213	0.004	10.0	0.018	0.194	0.386	12.0	0.017	0.160	0.314	16.0	0.015	0.121	0.231	18.0	0.014	0.108	0.209	20.0	0.013	0.098	0.184	24.0	0.013	0.083	0.154	28.0	0.013	0.073	0.133	32.0	0.013	0.066	0.118	36.0	0.014	0.061	0.107	40.0	0.016	0.057	0.098	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
8.8	0.019	0.001	0.001																																																																															
9.2	0.019	0.213	0.004																																																																															
10.0	0.018	0.194	0.386																																																																															
12.0	0.017	0.160	0.314																																																																															
16.0	0.015	0.121	0.231																																																																															
18.0	0.014	0.108	0.209																																																																															
20.0	0.013	0.098	0.184																																																																															
24.0	0.013	0.083	0.154																																																																															
28.0	0.013	0.073	0.133																																																																															
32.0	0.013	0.066	0.118																																																																															
36.0	0.014	0.061	0.107																																																																															
40.0	0.016	0.057	0.098																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	SUS32412
Item	Input Current (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A



## 2.Values

Load Current [A]	Input Current [A]		
	18[V]	24[V]	36[V]
0.000	0.014	0.013	0.014
0.050	0.052	0.041	0.033
0.100	0.090	0.069	0.052
0.150	0.128	0.098	0.070
0.200	0.167	0.126	0.089
0.250	0.207	0.155	0.108
0.275	0.227	0.170	0.117
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SUS32412
Item	Input Power (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A


## 2.Values


Load Current [A]	Input Power [W]		
	18[V]	24[V]	36[V]
0.000	0.25	0.30	0.52
0.050	0.93	0.99	1.19
0.100	1.61	1.66	1.86
0.150	2.30	2.34	2.52
0.200	3.00	3.03	3.19
0.250	3.71	3.72	3.87
0.275	4.06	4.07	4.21
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SUS32412	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1.Graph																																			
<p>The graph plots Efficiency [%] on the Y-axis (30 to 86) against Input Voltage [V] on the X-axis (10 to 50). Two data series are shown: Load 50% (dashed line with open squares) and Load 100% (solid line with solid triangles). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>77.1</td><td>80.6</td></tr> <tr><td>18</td><td>76.7</td><td>80.8</td></tr> <tr><td>20</td><td>76.1</td><td>80.8</td></tr> <tr><td>24</td><td>75.0</td><td>80.5</td></tr> <tr><td>30</td><td>72.2</td><td>79.3</td></tr> <tr><td>36</td><td>68.5</td><td>77.4</td></tr> <tr><td>40</td><td>65.5</td><td>75.7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	77.1	80.6	18	76.7	80.8	20	76.1	80.8	24	75.0	80.5	30	72.2	79.3	36	68.5	77.4	40	65.5	75.7	--	-	-	--	-	-		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																	
16	77.1	80.6																																	
18	76.7	80.8																																	
20	76.1	80.8																																	
24	75.0	80.5																																	
30	72.2	79.3																																	
36	68.5	77.4																																	
40	65.5	75.7																																	
--	-	-																																	
--	-	-																																	
2.Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>77.1</td><td>80.6</td></tr> <tr><td>18</td><td>76.7</td><td>80.8</td></tr> <tr><td>20</td><td>76.1</td><td>80.8</td></tr> <tr><td>24</td><td>75.0</td><td>80.5</td></tr> <tr><td>30</td><td>72.2</td><td>79.3</td></tr> <tr><td>36</td><td>68.5</td><td>77.4</td></tr> <tr><td>40</td><td>65.5</td><td>75.7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	77.1	80.6	18	76.7	80.8	20	76.1	80.8	24	75.0	80.5	30	72.2	79.3	36	68.5	77.4	40	65.5	75.7	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
16	77.1	80.6																																	
18	76.7	80.8																																	
20	76.1	80.8																																	
24	75.0	80.5																																	
30	72.2	79.3																																	
36	68.5	77.4																																	
40	65.5	75.7																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

**COSEL**


Model	SUS32412	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -○--- Input Volt. 36V																																																				
		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.050</td><td>64.6</td><td>61.1</td><td>50.7</td></tr> <tr> <td>0.100</td><td>74.4</td><td>72.2</td><td>64.7</td></tr> <tr> <td>0.150</td><td>78.1</td><td>76.8</td><td>71.3</td></tr> <tr> <td>0.200</td><td>79.9</td><td>79.2</td><td>75.0</td></tr> <tr> <td>0.250</td><td>80.8</td><td>80.5</td><td>77.4</td></tr> <tr> <td>0.275</td><td>81.0</td><td>81.0</td><td>78.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-	-	-	0.050	64.6	61.1	50.7	0.100	74.4	72.2	64.7	0.150	78.1	76.8	71.3	0.200	79.9	79.2	75.0	0.250	80.8	80.5	77.4	0.275	81.0	81.0	78.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-	-	-																																																			
0.050	64.6	61.1	50.7																																																			
0.100	74.4	72.2	64.7																																																			
0.150	78.1	76.8	71.3																																																			
0.200	79.9	79.2	75.0																																																			
0.250	80.8	80.5	77.4																																																			
0.275	81.0	81.0	78.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**

Model	SUS32412
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.


## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	11.948	11.947
18	11.949	11.947
20	11.949	11.947
24	11.949	11.947
30	11.949	11.947
36	11.949	11.947
40	11.949	11.947
--	-	-
--	-	-

**COSEL**

Model	SUS32412	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.25A																																																					
1.Graph		2.Values																																																				
<p>The graph plots Output Voltage [V] on the Y-axis (11.60 to 12.30) against Load Current [A] on the X-axis (0.00 to 0.30). Three data series are shown for Input Voltages of 18V, 24V, and 36V. Each series consists of a horizontal line at a constant output voltage and two slanted lines extending from the ends of the horizontal line. The output voltage is approximately 11.95V for all three input voltages.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>11.950</td><td>11.950</td><td>11.951</td></tr> <tr><td>0.050</td><td>11.950</td><td>11.950</td><td>11.950</td></tr> <tr><td>0.100</td><td>11.949</td><td>11.949</td><td>11.949</td></tr> <tr><td>0.150</td><td>11.949</td><td>11.949</td><td>11.949</td></tr> <tr><td>0.200</td><td>11.948</td><td>11.948</td><td>11.948</td></tr> <tr><td>0.250</td><td>11.948</td><td>11.948</td><td>11.948</td></tr> <tr><td>0.275</td><td>11.947</td><td>11.947</td><td>11.947</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	11.950	11.950	11.951	0.050	11.950	11.950	11.950	0.100	11.949	11.949	11.949	0.150	11.949	11.949	11.949	0.200	11.948	11.948	11.948	0.250	11.948	11.948	11.948	0.275	11.947	11.947	11.947	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	11.950	11.950	11.951																																																			
0.050	11.950	11.950	11.950																																																			
0.100	11.949	11.949	11.949																																																			
0.150	11.949	11.949	11.949																																																			
0.200	11.948	11.948	11.948																																																			
0.250	11.948	11.948	11.948																																																			
0.275	11.947	11.947	11.947																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL




**COSEL**

Model	SUS32412
Item	Ripple Voltage (by Load Current)
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	1	1
0.050	2	1
0.100	3	1
0.150	5	2
0.200	6	3
0.250	7	4
0.275	8	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	SUS32412
Item	Ripple-Noise
Object	+12V0.25A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C  
Testing Circuitry Figure B


## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	5	8
0.050	6	9
0.100	8	9
0.150	9	9
0.200	10	10
0.250	11	11
0.275	11	11
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	SUS32412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A

## 1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure B

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	11	14
-40	11	14
-20	10	13
0	9	11
25	8	9
55	5	6
60	5	6
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	11.925	11.926	11.927
-40	11.939	11.940	11.941
-20	11.948	11.949	11.949
0	11.952	11.952	11.952
25	11.949	11.949	11.948
55	11.937	11.937	11.936
60	11.927	11.926	11.925
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	SUS32412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.25A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current : 0 - 0.25A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	36	0	11.955	±10	±0.1
Minimum Voltage	55	36	0.25	11.936		


# COSEL

Model	SUS32412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
1.Graph			2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.951</td></tr> <tr><td>0.5</td><td>11.950</td></tr> <tr><td>1.0</td><td>11.949</td></tr> <tr><td>2.0</td><td>11.949</td></tr> <tr><td>3.0</td><td>11.949</td></tr> <tr><td>4.0</td><td>11.949</td></tr> <tr><td>5.0</td><td>11.949</td></tr> <tr><td>6.0</td><td>11.949</td></tr> <tr><td>7.0</td><td>11.949</td></tr> <tr><td>8.0</td><td>11.949</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	11.951	0.5	11.950	1.0	11.949	2.0	11.949	3.0	11.949	4.0	11.949	5.0	11.949	6.0	11.949	7.0	11.949	8.0	11.949
Time since start [H]	Output Voltage [V]																								
0.0	11.951																								
0.5	11.950																								
1.0	11.949																								
2.0	11.949																								
3.0	11.949																								
4.0	11.949																								
5.0	11.949																								
6.0	11.949																								
7.0	11.949																								
8.0	11.949																								

**COSEL**


Model	SUS32412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.25A		

## 1.Graph



## 2.Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	3.4	3.5	0.1	2.4	
100 %		0.1	3.4	3.5	0.1	1.2	



**COSEL**

Model	SUS32412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

## 1.Graph




Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.4	9.6
-40	6.4	9.7
-20	6.5	9.9
0	6.5	10.1
25	6.6	10.3
55	6.9	10.6
60	7.1	10.7
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	SUS32412	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V0.25A																																																									
1.Graph	<p>— Input Volt. 18V      — Input Volt. 24V      — Input Volt. 36V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.25</td><td>0.25</td><td>0.25</td></tr> <tr><td>11.4</td><td>0.43</td><td>0.44</td><td>0.43</td></tr> <tr><td>10.8</td><td>0.44</td><td>0.45</td><td>0.43</td></tr> <tr><td>9.6</td><td>0.46</td><td>0.46</td><td>0.44</td></tr> <tr><td>8.4</td><td>0.48</td><td>0.48</td><td>0.45</td></tr> <tr><td>7.2</td><td>0.49</td><td>0.49</td><td>0.45</td></tr> <tr><td>6.0</td><td>0.51</td><td>0.49</td><td>0.46</td></tr> <tr><td>4.8</td><td>0.52</td><td>0.50</td><td>0.45</td></tr> <tr><td>3.6</td><td>0.52</td><td>0.49</td><td>0.44</td></tr> <tr><td>2.4</td><td>0.50</td><td>0.46</td><td>0.42</td></tr> <tr><td>1.2</td><td>0.45</td><td>0.41</td><td>0.39</td></tr> <tr><td>0.0</td><td>0.56</td><td>0.47</td><td>0.48</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			18[V]	24[V]	36[V]	12.0	0.25	0.25	0.25	11.4	0.43	0.44	0.43	10.8	0.44	0.45	0.43	9.6	0.46	0.46	0.44	8.4	0.48	0.48	0.45	7.2	0.49	0.49	0.45	6.0	0.51	0.49	0.46	4.8	0.52	0.50	0.45	3.6	0.52	0.49	0.44	2.4	0.50	0.46	0.42	1.2	0.45	0.41	0.39	0.0	0.56	0.47	0.48
Output Voltage [V]	Load Current [A]																																																									
	18[V]	24[V]	36[V]																																																							
12.0	0.25	0.25	0.25																																																							
11.4	0.43	0.44	0.43																																																							
10.8	0.44	0.45	0.43																																																							
9.6	0.46	0.46	0.44																																																							
8.4	0.48	0.48	0.45																																																							
7.2	0.49	0.49	0.45																																																							
6.0	0.51	0.49	0.46																																																							
4.8	0.52	0.50	0.45																																																							
3.6	0.52	0.49	0.44																																																							
2.4	0.50	0.46	0.42																																																							
1.2	0.45	0.41	0.39																																																							
0.0	0.56	0.47	0.48																																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)