



TEST DATA OF SUS34815

Regulated DC Power Supply
Mar 7, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo
Hayato Nakatsubo Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Figure of Testing Circuitry	18

(Final Page 18)



Model		SUS34815		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p>Legend: —△— Load 100% - - □ - - Load 50% - · ○ - · Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>19.2</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>21.6</td><td>0.009</td><td>0.089</td><td>0.174</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.080</td><td>0.155</td></tr> <tr><td>33.0</td><td>0.008</td><td>0.059</td><td>0.111</td></tr> <tr><td>36.0</td><td>0.008</td><td>0.054</td><td>0.102</td></tr> <tr><td>40.0</td><td>0.007</td><td>0.049</td><td>0.092</td></tr> <tr><td>48.0</td><td>0.007</td><td>0.041</td><td>0.077</td></tr> <tr><td>60.0</td><td>0.007</td><td>0.034</td><td>0.062</td></tr> <tr><td>70.0</td><td>0.007</td><td>0.031</td><td>0.055</td></tr> <tr><td>76.0</td><td>0.007</td><td>0.029</td><td>0.051</td></tr> <tr><td>80.0</td><td>0.008</td><td>0.028</td><td>0.049</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	19.2	0.000	0.000	0.000	21.6	0.009	0.089	0.174	24.0	0.009	0.080	0.155	33.0	0.008	0.059	0.111	36.0	0.008	0.054	0.102	40.0	0.007	0.049	0.092	48.0	0.007	0.041	0.077	60.0	0.007	0.034	0.062	70.0	0.007	0.031	0.055	76.0	0.007	0.029	0.051	80.0	0.008	0.028	0.049	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.000	0.000	0.000																																																																																	
16.0	0.000	0.000	0.000																																																																																	
19.2	0.000	0.000	0.000																																																																																	
21.6	0.009	0.089	0.174																																																																																	
24.0	0.009	0.080	0.155																																																																																	
33.0	0.008	0.059	0.111																																																																																	
36.0	0.008	0.054	0.102																																																																																	
40.0	0.007	0.049	0.092																																																																																	
48.0	0.007	0.041	0.077																																																																																	
60.0	0.007	0.034	0.062																																																																																	
70.0	0.007	0.031	0.055																																																																																	
76.0	0.007	0.029	0.051																																																																																	
80.0	0.008	0.028	0.049																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model SUS34815		Temperature 25°C Testing Circuitry Figure A																																																			
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> </p> <p> △ Input Volt. 36V □ Input Volt. 48V ○ Input Volt. 76V </p> <p style="margin-top: 10px;">Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.008</td><td>0.007</td><td>0.007</td></tr> <tr><td>0.04</td><td>0.026</td><td>0.021</td><td>0.016</td></tr> <tr><td>0.08</td><td>0.045</td><td>0.035</td><td>0.025</td></tr> <tr><td>0.12</td><td>0.064</td><td>0.049</td><td>0.034</td></tr> <tr><td>0.16</td><td>0.083</td><td>0.063</td><td>0.042</td></tr> <tr><td>0.20</td><td>0.103</td><td>0.077</td><td>0.051</td></tr> <tr><td>0.22</td><td>0.113</td><td>0.084</td><td>0.056</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.008	0.007	0.007	0.04	0.026	0.021	0.016	0.08	0.045	0.035	0.025	0.12	0.064	0.049	0.034	0.16	0.083	0.063	0.042	0.20	0.103	0.077	0.051	0.22	0.113	0.084	0.056	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	0.008	0.007	0.007																																																		
0.04	0.026	0.021	0.016																																																		
0.08	0.045	0.035	0.025																																																		
0.12	0.064	0.049	0.034																																																		
0.16	0.083	0.063	0.042																																																		
0.20	0.103	0.077	0.051																																																		
0.22	0.113	0.084	0.056																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




Model		SUS34815		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p> —△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ · - Input Volt. 76V </p> <p>Input Power [W]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.28</td><td>0.33</td><td>0.56</td></tr> <tr><td>0.04</td><td>0.95</td><td>1.00</td><td>1.23</td></tr> <tr><td>0.08</td><td>1.62</td><td>1.67</td><td>1.89</td></tr> <tr><td>0.12</td><td>2.30</td><td>2.34</td><td>2.55</td></tr> <tr><td>0.16</td><td>2.99</td><td>3.02</td><td>3.22</td></tr> <tr><td>0.20</td><td>3.69</td><td>3.71</td><td>3.89</td></tr> <tr><td>0.22</td><td>4.05</td><td>4.05</td><td>4.23</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.28	0.33	0.56	0.04	0.95	1.00	1.23	0.08	1.62	1.67	1.89	0.12	2.30	2.34	2.55	0.16	2.99	3.02	3.22	0.20	3.69	3.71	3.89	0.22	4.05	4.05	4.23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	0.28	0.33	0.56																																																					
0.04	0.95	1.00	1.23																																																					
0.08	1.62	1.67	1.89																																																					
0.12	2.30	2.34	2.55																																																					
0.16	2.99	3.02	3.22																																																					
0.20	3.69	3.71	3.89																																																					
0.22	4.05	4.05	4.23																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model	SUS34815
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
30	77.3	81.0
36	76.7	81.3
40	76.2	81.3
48	75.1	81.0
55	73.9	80.5
60	72.8	79.9
70	69.9	78.4
76	67.9	77.2
80	66.4	76.4




Model		SUS34815		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			—△— Input Volt. 36V	2.Values																																																				
			- - □ - - Input Volt. 48V																																																					
			- - ○ - - Input Volt. 76V																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.04</td><td>63.9</td><td>60.8</td><td>49.4</td></tr> <tr><td>0.08</td><td>74.3</td><td>72.3</td><td>63.8</td></tr> <tr><td>0.12</td><td>78.3</td><td>77.0</td><td>70.7</td></tr> <tr><td>0.16</td><td>80.3</td><td>79.6</td><td>74.7</td></tr> <tr><td>0.20</td><td>81.4</td><td>81.0</td><td>77.2</td></tr> <tr><td>0.22</td><td>81.6</td><td>81.5</td><td>78.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.04	63.9	60.8	49.4	0.08	74.3	72.3	63.8	0.12	78.3	77.0	70.7	0.16	80.3	79.6	74.7	0.20	81.4	81.0	77.2	0.22	81.6	81.5	78.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	-	-	-																																																					
0.04	63.9	60.8	49.4																																																					
0.08	74.3	72.3	63.8																																																					
0.12	78.3	77.0	70.7																																																					
0.16	80.3	79.6	74.7																																																					
0.20	81.4	81.0	77.2																																																					
0.22	81.6	81.5	78.1																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model	SUS34815
Item	Line Regulation
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
30	14.983	14.982
36	14.983	14.982
40	14.983	14.981
48	14.983	14.981
55	14.983	14.981
60	14.983	14.981
70	14.983	14.982
76	14.983	14.981
80	14.983	14.981




COSEL																																																						
Model	SUS34815	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.2A																																																					
<p>1.Graph</p> <p> —△— Input Volt. 36V - - - □ - - - Input Volt. 48V - - - ○ - - - Input Volt. 76V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>14.984</td><td>14.984</td><td>14.985</td></tr> <tr><td>0.04</td><td>14.984</td><td>14.984</td><td>14.984</td></tr> <tr><td>0.08</td><td>14.983</td><td>14.983</td><td>14.983</td></tr> <tr><td>0.12</td><td>14.982</td><td>14.983</td><td>14.983</td></tr> <tr><td>0.16</td><td>14.982</td><td>14.982</td><td>14.982</td></tr> <tr><td>0.20</td><td>14.982</td><td>14.981</td><td>14.981</td></tr> <tr><td>0.22</td><td>14.981</td><td>14.981</td><td>14.981</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	14.984	14.984	14.985	0.04	14.984	14.984	14.984	0.08	14.983	14.983	14.983	0.12	14.982	14.983	14.983	0.16	14.982	14.982	14.982	0.20	14.982	14.981	14.981	0.22	14.981	14.981	14.981	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	14.984	14.984	14.985																																																			
0.04	14.984	14.984	14.984																																																			
0.08	14.983	14.983	14.983																																																			
0.12	14.982	14.983	14.983																																																			
0.16	14.982	14.982	14.982																																																			
0.20	14.982	14.981	14.981																																																			
0.22	14.981	14.981	14.981																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						




Model	SUS34815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.2A		


Input Volt. 48 V
 Cycle 100 mS



Min. Load (0A) \longleftrightarrow
 Load 100% (0.2A)




2ms/div



2ms/div

Min. Load (0A) \longleftrightarrow
 Load 50% (0.1A)




2ms/div




2ms/div

Load 50% (0.1A) \longleftrightarrow
 Load 100% (0.2A)



2ms/div




2ms/div



Model	SUS34815
Item	Ripple Voltage (by Load Current)
Object	+15V0.2A

Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	3	2
0.04	3	2
0.08	4	2
0.12	4	2
0.16	5	2
0.20	6	3
0.22	7	4
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form



COSEL																																									
Model	SUS34815	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+15V0.2A																																								
<p>1.Graph</p> <div style="text-align: center;"> <p>—△— Input Volt. 36V</p> <p>- -○- - Input Volt. 76V</p> </div> <p style="text-align: center;">Ripple-Noise [mV]</p> <p style="text-align: center;">Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p style="text-align: center;">Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>8</td></tr> <tr><td>0.04</td><td>13</td><td>9</td></tr> <tr><td>0.08</td><td>11</td><td>10</td></tr> <tr><td>0.12</td><td>9</td><td>10</td></tr> <tr><td>0.16</td><td>11</td><td>10</td></tr> <tr><td>0.20</td><td>13</td><td>11</td></tr> <tr><td>0.22</td><td>15</td><td>12</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	10	8	0.04	13	9	0.08	11	10	0.12	9	10	0.16	11	10	0.20	13	11	0.22	15	12	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.00	10	8																																							
0.04	13	9																																							
0.08	11	10																																							
0.12	9	10																																							
0.16	11	10																																							
0.20	13	11																																							
0.22	15	12																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							



COSEL																																								
Model	SUS34815																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+15V0.2A																																							
<p>1. Graph</p> <p style="text-align: center;">Input Volt. 48V</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>10</td><td>10</td></tr> <tr><td>-40</td><td>10</td><td>10</td></tr> <tr><td>-20</td><td>8</td><td>9</td></tr> <tr><td>0</td><td>7</td><td>9</td></tr> <tr><td>25</td><td>6</td><td>7</td></tr> <tr><td>55</td><td>4</td><td>5</td></tr> <tr><td>60</td><td>4</td><td>5</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	10	10	-40	10	10	-20	8	9	0	7	9	25	6	7	55	4	5	60	4	5	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	10	10																																						
-40	10	10																																						
-20	8	9																																						
0	7	9																																						
25	6	7																																						
55	4	5																																						
60	4	5																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model SUS34815</p> <p>Item Ambient Temperature Drift</p> <p>Object +15V0.2A</p>		<p>Testing Circuitry Figure A</p>																																																			
<p>1.Graph</p> <p> —△— Input Volt. 36V - - - □ - - - Input Volt. 48V - - - ○ - - - Input Volt. 76V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.913</td><td>14.914</td><td>14.915</td></tr> <tr><td>-40</td><td>14.940</td><td>14.941</td><td>14.942</td></tr> <tr><td>-20</td><td>14.960</td><td>14.961</td><td>14.962</td></tr> <tr><td>0</td><td>14.974</td><td>14.975</td><td>14.975</td></tr> <tr><td>25</td><td>14.982</td><td>14.982</td><td>14.982</td></tr> <tr><td>55</td><td>14.979</td><td>14.979</td><td>14.978</td></tr> <tr><td>60</td><td>14.977</td><td>14.977</td><td>14.977</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	14.913	14.914	14.915	-40	14.940	14.941	14.942	-20	14.960	14.961	14.962	0	14.974	14.975	14.975	25	14.982	14.982	14.982	55	14.979	14.979	14.978	60	14.977	14.977	14.977	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
-60	14.913	14.914	14.915																																																		
-40	14.940	14.941	14.942																																																		
-20	14.960	14.961	14.962																																																		
0	14.974	14.975	14.975																																																		
25	14.982	14.982	14.982																																																		
55	14.979	14.979	14.978																																																		
60	14.977	14.977	14.977																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL		Testing Circuitry Figure A
Model	SUS34815	
Item	Output Voltage Accuracy	
Object	+15V0.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

- Temperature : -40 - 55°C
- Input Voltage : 36 - 76V
- Load Current : 0 - 0.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	76	0	14.985	±23	±0.2
Minimum Voltage	-40	36	0.2	14.940		




COSEL																									
Model	SUS34815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.2A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.980</td></tr> <tr><td>0.5</td><td>14.982</td></tr> <tr><td>1.0</td><td>14.982</td></tr> <tr><td>2.0</td><td>14.982</td></tr> <tr><td>3.0</td><td>14.982</td></tr> <tr><td>4.0</td><td>14.982</td></tr> <tr><td>5.0</td><td>14.982</td></tr> <tr><td>6.0</td><td>14.982</td></tr> <tr><td>7.0</td><td>14.982</td></tr> <tr><td>8.0</td><td>14.982</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	14.980	0.5	14.982	1.0	14.982	2.0	14.982	3.0	14.982	4.0	14.982	5.0	14.982	6.0	14.982	7.0	14.982	8.0	14.982
Time since start [H]	Output Voltage [V]																								
0.0	14.980																								
0.5	14.982																								
1.0	14.982																								
2.0	14.982																								
3.0	14.982																								
4.0	14.982																								
5.0	14.982																								
6.0	14.982																								
7.0	14.982																								
8.0	14.982																								



Model		SUS34815	
Item		Rise and Fall Time	
Object		+15V0.2A	
		Temperature 25°C Testing Circuitry Figure A	


1. Graph

Input Volt. 48 V



2. Values

		[mS]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.5	3.6	0.1	2.0
100 %		0.1	3.6	3.7	0.1	1.0





COSEL																																								
Model	SUS34815	Testing Circuitry Figure A 2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>13.5</td><td>18.3</td></tr> <tr><td>-40</td><td>13.5</td><td>18.5</td></tr> <tr><td>-20</td><td>13.2</td><td>18.9</td></tr> <tr><td>0</td><td>12.9</td><td>19.3</td></tr> <tr><td>25</td><td>13.2</td><td>20.1</td></tr> <tr><td>55</td><td>13.5</td><td>20.9</td></tr> <tr><td>60</td><td>13.6</td><td>21.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	13.5	18.3	-40	13.5	18.5	-20	13.2	18.9	0	12.9	19.3	25	13.2	20.1	55	13.5	20.9	60	13.6	21.2	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%		Load 100%																																					
-60	13.5		18.3																																					
-40	13.5	18.5																																						
-20	13.2	18.9																																						
0	12.9	19.3																																						
25	13.2	20.1																																						
55	13.5	20.9																																						
60	13.6	21.2																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+15V0.2A																																							
1.Graph <div style="text-align: right;"> ---□--- Load 50% —△— Load 100% </div> <p style="margin-top: 10px;">Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



COSEL																																																										
Model	SUS34815	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+15V0.2A																																																									
<p>1.Graph</p> <p> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>14.3</td><td>0.32</td><td>0.32</td><td>0.34</td></tr> <tr><td>13.5</td><td>0.33</td><td>0.33</td><td>0.35</td></tr> <tr><td>12.0</td><td>0.36</td><td>0.36</td><td>0.37</td></tr> <tr><td>10.5</td><td>0.38</td><td>0.38</td><td>0.38</td></tr> <tr><td>9.0</td><td>0.41</td><td>0.40</td><td>0.40</td></tr> <tr><td>7.5</td><td>0.44</td><td>0.43</td><td>0.42</td></tr> <tr><td>6.0</td><td>0.47</td><td>0.45</td><td>0.44</td></tr> <tr><td>4.5</td><td>0.49</td><td>0.46</td><td>0.45</td></tr> <tr><td>3.0</td><td>0.50</td><td>0.46</td><td>0.45</td></tr> <tr><td>1.5</td><td>0.48</td><td>0.43</td><td>0.43</td></tr> <tr><td>0.0</td><td>0.57</td><td>0.48</td><td>0.56</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	15.0	0.20	0.20	0.20	14.3	0.32	0.32	0.34	13.5	0.33	0.33	0.35	12.0	0.36	0.36	0.37	10.5	0.38	0.38	0.38	9.0	0.41	0.40	0.40	7.5	0.44	0.43	0.42	6.0	0.47	0.45	0.44	4.5	0.49	0.46	0.45	3.0	0.50	0.46	0.45	1.5	0.48	0.43	0.43	0.0	0.57	0.48	0.56
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
15.0	0.20	0.20	0.20																																																							
14.3	0.32	0.32	0.34																																																							
13.5	0.33	0.33	0.35																																																							
12.0	0.36	0.36	0.37																																																							
10.5	0.38	0.38	0.38																																																							
9.0	0.41	0.40	0.40																																																							
7.5	0.44	0.43	0.42																																																							
6.0	0.47	0.45	0.44																																																							
4.5	0.49	0.46	0.45																																																							
3.0	0.50	0.46	0.45																																																							
1.5	0.48	0.43	0.43																																																							
0.0	0.57	0.48	0.56																																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)