



TEST DATA OF SUS64812 SUCS64812

Regulated DC Power Supply
Feb 17, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshikazu Mizuno
Yoshikazu Mizuno Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Figure of Testing Circuitry	18

(Final Page 18)



Model		SUS64812/SUCS64812		Temperature 25°C																																																																								
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																								
Object		_____																																																																										
1. Graph			2. Values																																																																									
<p>Legend: —△— Load 100% - - □ - - Load 50% - - ○ - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>32.2</td><td>0.010</td><td>0.112</td><td>0.218</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.109</td><td>0.213</td></tr> <tr><td>36.0</td><td>0.010</td><td>0.100</td><td>0.195</td></tr> <tr><td>40.0</td><td>0.009</td><td>0.091</td><td>0.175</td></tr> <tr><td>48.0</td><td>0.009</td><td>0.076</td><td>0.146</td></tr> <tr><td>60.0</td><td>0.008</td><td>0.063</td><td>0.119</td></tr> <tr><td>70.0</td><td>0.009</td><td>0.056</td><td>0.104</td></tr> <tr><td>76.0</td><td>0.009</td><td>0.053</td><td>0.097</td></tr> <tr><td>80.0</td><td>0.009</td><td>0.051</td><td>0.093</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.001	0.001	32.2	0.010	0.112	0.218	33.0	0.010	0.109	0.213	36.0	0.010	0.100	0.195	40.0	0.009	0.091	0.175	48.0	0.009	0.076	0.146	60.0	0.008	0.063	0.119	70.0	0.009	0.056	0.104	76.0	0.009	0.053	0.097	80.0	0.009	0.051	0.093	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																											
	Load 0%	Load 50%	Load 100%																																																																									
0.0	0.000	0.000	0.000																																																																									
8.0	0.000	0.000	0.000																																																																									
16.0	0.000	0.000	0.000																																																																									
24.0	0.001	0.001	0.001																																																																									
32.2	0.010	0.112	0.218																																																																									
33.0	0.010	0.109	0.213																																																																									
36.0	0.010	0.100	0.195																																																																									
40.0	0.009	0.091	0.175																																																																									
48.0	0.009	0.076	0.146																																																																									
60.0	0.008	0.063	0.119																																																																									
70.0	0.009	0.056	0.104																																																																									
76.0	0.009	0.053	0.097																																																																									
80.0	0.009	0.051	0.093																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																												



Model		SUS64812/SUCS64812		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V		2. Values																																																				
<p>The graph plots Input Current [A] on the y-axis (0.00 to 0.30) against Load Current [A] on the x-axis (0.0 to 0.6). Three data series are shown: 36V (solid line with triangles), 48V (dashed line with squares), and 76V (dotted line with circles). A slanted line is drawn from approximately (0.1, 0.05) to (0.5, 0.20), indicating the rated load current range.</p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.010</td><td>0.008</td><td>0.009</td></tr> <tr><td>0.10</td><td>0.046</td><td>0.036</td><td>0.027</td></tr> <tr><td>0.20</td><td>0.082</td><td>0.063</td><td>0.045</td></tr> <tr><td>0.30</td><td>0.120</td><td>0.091</td><td>0.062</td></tr> <tr><td>0.40</td><td>0.157</td><td>0.119</td><td>0.079</td></tr> <tr><td>0.50</td><td>0.196</td><td>0.147</td><td>0.097</td></tr> <tr><td>0.55</td><td>0.215</td><td>0.161</td><td>0.105</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.010	0.008	0.009	0.10	0.046	0.036	0.027	0.20	0.082	0.063	0.045	0.30	0.120	0.091	0.062	0.40	0.157	0.119	0.079	0.50	0.196	0.147	0.097	0.55	0.215	0.161	0.105	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	0.010	0.008	0.009																																																					
0.10	0.046	0.036	0.027																																																					
0.20	0.082	0.063	0.045																																																					
0.30	0.120	0.091	0.062																																																					
0.40	0.157	0.119	0.079																																																					
0.50	0.196	0.147	0.097																																																					
0.55	0.215	0.161	0.105																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SUS64812/SUCS64812		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 36V - - - □ - - - Input Volt. 48V - · - ○ - · - - Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.35</td><td>0.41</td><td>0.71</td></tr> <tr><td>0.10</td><td>1.65</td><td>1.72</td><td>2.09</td></tr> <tr><td>0.20</td><td>2.97</td><td>3.03</td><td>3.40</td></tr> <tr><td>0.30</td><td>4.30</td><td>4.35</td><td>4.71</td></tr> <tr><td>0.40</td><td>5.66</td><td>5.69</td><td>6.03</td></tr> <tr><td>0.50</td><td>7.04</td><td>7.05</td><td>7.36</td></tr> <tr><td>0.55</td><td>7.74</td><td>7.73</td><td>8.03</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.35	0.41	0.71	0.10	1.65	1.72	2.09	0.20	2.97	3.03	3.40	0.30	4.30	4.35	4.71	0.40	5.66	5.69	6.03	0.50	7.04	7.05	7.36	0.55	7.74	7.73	8.03	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	0.35	0.41	0.71																																																					
0.10	1.65	1.72	2.09																																																					
0.20	2.97	3.03	3.40																																																					
0.30	4.30	4.35	4.71																																																					
0.40	5.66	5.69	6.03																																																					
0.50	7.04	7.05	7.36																																																					
0.55	7.74	7.73	8.03																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model SUS64812/SUCS64812		Temperature 25°C Testing Circuitry Figure A																															
Item	Efficiency (by Input Voltage)																																
Object	_____																																
1. Graph <p>---□--- Load 50% —△— Load 100%</p> <p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>83.1</td><td>85.3</td></tr> <tr><td>36</td><td>82.9</td><td>85.5</td></tr> <tr><td>40</td><td>82.6</td><td>85.6</td></tr> <tr><td>48</td><td>81.7</td><td>85.4</td></tr> <tr><td>55</td><td>80.3</td><td>84.9</td></tr> <tr><td>60</td><td>79.1</td><td>84.4</td></tr> <tr><td>70</td><td>76.3</td><td>82.8</td></tr> <tr><td>76</td><td>74.3</td><td>81.8</td></tr> <tr><td>80</td><td>72.9</td><td>81.0</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	83.1	85.3	36	82.9	85.5	40	82.6	85.6	48	81.7	85.4	55	80.3	84.9	60	79.1	84.4	70	76.3	82.8	76	74.3	81.8	80	72.9	81.0
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
33	83.1	85.3																															
36	82.9	85.5																															
40	82.6	85.6																															
48	81.7	85.4																															
55	80.3	84.9																															
60	79.1	84.4																															
70	76.3	82.8																															
76	74.3	81.8																															
80	72.9	81.0																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	



Model		SUS64812/SUCS64812		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V		2. Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>73.0</td><td>70.2</td><td>57.7</td></tr> <tr><td>0.20</td><td>81.2</td><td>79.5</td><td>70.9</td></tr> <tr><td>0.30</td><td>84.0</td><td>83.0</td><td>76.7</td></tr> <tr><td>0.40</td><td>85.1</td><td>84.6</td><td>79.8</td></tr> <tr><td>0.50</td><td>85.5</td><td>85.4</td><td>81.8</td></tr> <tr><td>0.55</td><td>85.6</td><td>85.7</td><td>82.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.10	73.0	70.2	57.7	0.20	81.2	79.5	70.9	0.30	84.0	83.0	76.7	0.40	85.1	84.6	79.8	0.50	85.5	85.4	81.8	0.55	85.6	85.7	82.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	-	-	-																																																					
0.10	73.0	70.2	57.7																																																					
0.20	81.2	79.5	70.9																																																					
0.30	84.0	83.0	76.7																																																					
0.40	85.1	84.6	79.8																																																					
0.50	85.5	85.4	81.8																																																					
0.55	85.6	85.7	82.4																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model SUS64812/SUCS64812		Temperature 25°C Testing Circuitry Figure A																																
Item	Line Regulation																																	
Object	+12V0.5A																																	
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>12.016</td><td>12.015</td></tr> <tr><td>36</td><td>12.016</td><td>12.015</td></tr> <tr><td>40</td><td>12.017</td><td>12.015</td></tr> <tr><td>48</td><td>12.016</td><td>12.015</td></tr> <tr><td>55</td><td>12.016</td><td>12.014</td></tr> <tr><td>60</td><td>12.016</td><td>12.014</td></tr> <tr><td>70</td><td>12.016</td><td>12.014</td></tr> <tr><td>76</td><td>12.016</td><td>12.014</td></tr> <tr><td>80</td><td>12.016</td><td>12.014</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	12.016	12.015	36	12.016	12.015	40	12.017	12.015	48	12.016	12.015	55	12.016	12.014	60	12.016	12.014	70	12.016	12.014	76	12.016	12.014	80	12.016	12.014
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	12.016	12.015																																
36	12.016	12.015																																
40	12.017	12.015																																
48	12.016	12.015																																
55	12.016	12.014																																
60	12.016	12.014																																
70	12.016	12.014																																
76	12.016	12.014																																
80	12.016	12.014																																




Model		SUS64812/SUCS64812		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+12V0.5A																																																						
1.Graph <div style="display: flex; justify-content: space-between; align-items: flex-start; margin-top: 10px;"> <div style="width: 60%;"> </div> <div style="width: 35%;"> <p>—△— Input Volt. 36V</p> <p>---□--- Input Volt. 48V</p> <p>---○--- Input Volt. 76V</p> </div> </div>			2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.018</td><td>12.019</td><td>12.020</td></tr> <tr><td>0.10</td><td>12.018</td><td>12.018</td><td>12.018</td></tr> <tr><td>0.20</td><td>12.017</td><td>12.017</td><td>12.017</td></tr> <tr><td>0.30</td><td>12.016</td><td>12.016</td><td>12.016</td></tr> <tr><td>0.40</td><td>12.016</td><td>12.016</td><td>12.016</td></tr> <tr><td>0.50</td><td>12.015</td><td>12.015</td><td>12.015</td></tr> <tr><td>0.55</td><td>12.015</td><td>12.014</td><td>12.014</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	12.018	12.019	12.020	0.10	12.018	12.018	12.018	0.20	12.017	12.017	12.017	0.30	12.016	12.016	12.016	0.40	12.016	12.016	12.016	0.50	12.015	12.015	12.015	0.55	12.015	12.014	12.014	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.00	12.018	12.019	12.020																																																					
0.10	12.018	12.018	12.018																																																					
0.20	12.017	12.017	12.017																																																					
0.30	12.016	12.016	12.016																																																					
0.40	12.016	12.016	12.016																																																					
0.50	12.015	12.015	12.015																																																					
0.55	12.015	12.014	12.014																																																					
—	—	—	—																																																					
—	—	—	—																																																					
—	—	—	—																																																					
—	—	—	—																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								





Model	SUS64812/SUCS64812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.5A		



Input Volt. 48 V
Cycle 100 mS





Min. Load (0A) ←→
Load 100% (0.5A)



Min. Load (0A) ←→
Load 50% (0.25A)



Load 50% (0.25A) ←→
Load 100% (0.5A)






Model		SUS64812/SUCS64812		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		+12V0.5A																																									
1.Graph			2.Values																																								
<p> —△— Input Volt. 36V - - ○ - - Input Volt. 76V </p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>4</td></tr> <tr><td>0.10</td><td>4</td><td>4</td></tr> <tr><td>0.20</td><td>4</td><td>4</td></tr> <tr><td>0.30</td><td>4</td><td>4</td></tr> <tr><td>0.40</td><td>4</td><td>4</td></tr> <tr><td>0.50</td><td>7</td><td>4</td></tr> <tr><td>0.55</td><td>9</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	4	4	0.10	4	4	0.20	4	4	0.30	4	4	0.40	4	4	0.50	7	4	0.55	9	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 36 [V]	Input Volt. 76 [V]																																									
0.00	4	4																																									
0.10	4	4																																									
0.20	4	4																																									
0.30	4	4																																									
0.40	4	4																																									
0.50	7	4																																									
0.55	9	4																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Ripple [mVp-p]</p>																																											
<p>Fig.Complex Ripple Wave Form</p>																																											



Model	SUS64812/SUCS64812
Item	Ripple-Noise
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	4	4
0.10	13	12
0.20	19	17
0.30	25	21
0.40	31	26
0.50	36	29
0.55	40	31
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form



Model	SUS64812/SUCS64812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.5A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	6
-40	6	6
-20	5	6
0	4	5
25	3	4
55	3	4
60	3	4
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
 Note: Slanted line shows the range of the rated ambient temperature.




Model	SUS64812/SUCS64812
Item	Ambient Temperature Drift
Object	+12V0.5A

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 36V
 - - - □ - - - Input Volt. 48V
 - - - ○ - - - Input Volt. 76V

2. Values



Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	11.985	11.987	11.988
-40	12.001	12.002	12.003
-20	12.011	12.012	12.012
0	12.016	12.016	12.016
25	12.016	12.015	12.015
55	12.007	12.006	12.005
60	12.004	12.003	12.002
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		
Model	SUS64812/SUCS64812	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V0.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.5A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	76	0	12.021	±10	±0.1
Minimum Voltage	-40	36	0.5	12.001		




Model		SUS64812/SUCS64812		Temperature 25°C Testing Circuitry Figure A																						
Item		Time Lapse Drift																								
Object		+12V0.5A																								
1.Graph  <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>			2.Values <table border="1" data-bbox="933 504 1300 1041"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.016</td></tr> <tr><td>0.5</td><td>12.015</td></tr> <tr><td>1.0</td><td>12.015</td></tr> <tr><td>2.0</td><td>12.015</td></tr> <tr><td>3.0</td><td>12.015</td></tr> <tr><td>4.0</td><td>12.015</td></tr> <tr><td>5.0</td><td>12.015</td></tr> <tr><td>6.0</td><td>12.015</td></tr> <tr><td>7.0</td><td>12.015</td></tr> <tr><td>8.0</td><td>12.015</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.016	0.5	12.015	1.0	12.015	2.0	12.015	3.0	12.015	4.0	12.015	5.0	12.015	6.0	12.015	7.0	12.015	8.0	12.015
Time since start [H]	Output Voltage [V]																									
0.0	12.016																									
0.5	12.015																									
1.0	12.015																									
2.0	12.015																									
3.0	12.015																									
4.0	12.015																									
5.0	12.015																									
6.0	12.015																									
7.0	12.015																									
8.0	12.015																									




Model	SUS64812/SUCS64812	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.5A		

1. Graph



2. Values

Load	Time	[ms]				
		Td	Tr	Ts	Th	Tf
50 %		0.3	2.6	2.9	0.1	2.1
100 %		0.3	2.7	3.0	0.1	1.0





COSEL																																								
Model	SUS64812/SUCS64812																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V0.5A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>30.7</td><td>30.7</td></tr> <tr><td>-40</td><td>30.5</td><td>30.6</td></tr> <tr><td>-20</td><td>30.4</td><td>30.5</td></tr> <tr><td>0</td><td>30.2</td><td>30.3</td></tr> <tr><td>25</td><td>30.0</td><td>30.1</td></tr> <tr><td>55</td><td>29.8</td><td>30.0</td></tr> <tr><td>60</td><td>29.7</td><td>29.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	30.7	30.7	-40	30.5	30.6	-20	30.4	30.5	0	30.2	30.3	25	30.0	30.1	55	29.8	30.0	60	29.7	29.9	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	30.7	30.7																																						
-40	30.5	30.6																																						
-20	30.4	30.5																																						
0	30.2	30.3																																						
25	30.0	30.1																																						
55	29.8	30.0																																						
60	29.7	29.9																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model SUS64812/SUCS64812		Temperature 25°C Testing Circuitry Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.5A																																																								
<p>1.Graph</p> <p> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.50</td><td>0.50</td><td>0.50</td></tr> <tr><td>11.4</td><td>0.70</td><td>0.72</td><td>0.71</td></tr> <tr><td>10.8</td><td>0.71</td><td>0.73</td><td>0.72</td></tr> <tr><td>9.6</td><td>0.80</td><td>0.82</td><td>0.79</td></tr> <tr><td>8.4</td><td>0.85</td><td>0.87</td><td>0.84</td></tr> <tr><td>7.2</td><td>0.90</td><td>0.91</td><td>0.87</td></tr> <tr><td>6.0</td><td>0.93</td><td>0.94</td><td>0.90</td></tr> <tr><td>4.8</td><td>0.97</td><td>0.96</td><td>0.92</td></tr> <tr><td>3.6</td><td>0.99</td><td>0.97</td><td>0.93</td></tr> <tr><td>2.4</td><td>0.97</td><td>0.95</td><td>0.92</td></tr> <tr><td>1.2</td><td>0.92</td><td>0.89</td><td>0.88</td></tr> <tr><td>0.0</td><td>0.85</td><td>0.84</td><td>0.87</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.50	0.50	0.50	11.4	0.70	0.72	0.71	10.8	0.71	0.73	0.72	9.6	0.80	0.82	0.79	8.4	0.85	0.87	0.84	7.2	0.90	0.91	0.87	6.0	0.93	0.94	0.90	4.8	0.97	0.96	0.92	3.6	0.99	0.97	0.93	2.4	0.97	0.95	0.92	1.2	0.92	0.89	0.88	0.0	0.85	0.84	0.87
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
12.0	0.50	0.50	0.50																																																						
11.4	0.70	0.72	0.71																																																						
10.8	0.71	0.73	0.72																																																						
9.6	0.80	0.82	0.79																																																						
8.4	0.85	0.87	0.84																																																						
7.2	0.90	0.91	0.87																																																						
6.0	0.93	0.94	0.90																																																						
4.8	0.97	0.96	0.92																																																						
3.6	0.99	0.97	0.93																																																						
2.4	0.97	0.95	0.92																																																						
1.2	0.92	0.89	0.88																																																						
0.0	0.85	0.84	0.87																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)