

TEST DATA OF SUTS101212

Regulated DC Power Supply
February 10, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18

(Final Page 18)

Model	SUTS101212	Temperature Testing Circuitry Figure A	25°C																																																																														
Item	Input Current (by Input Voltage)																																																																																
Object	_____																																																																																
1. Graph		<p>The graph plots Input Current [A] on the y-axis (0.0 to 5.0) against Input Voltage [V] on the x-axis (0 to 20). Three data series are shown: Load 0% (solid line with open circles), Load 50% (dashed line with open squares), and Load 100% (solid line with open triangles). All series show a sharp increase from 0V to approximately 5V, followed by a gradual decrease as voltage increases further. A slanted line is drawn across the graph, representing the rated input voltage range.</p>																																																																															
2. Values																																																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.001</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.001</td><td>0.001</td><td>0.000</td></tr> <tr><td>4.8</td><td>0.001</td><td>-0.001</td><td>0.001</td></tr> <tr><td>5.2</td><td>0.047</td><td>0.004</td><td>2.778</td></tr> <tr><td>6.0</td><td>0.044</td><td>1.154</td><td>2.357</td></tr> <tr><td>8.0</td><td>0.034</td><td>0.858</td><td>1.720</td></tr> <tr><td>9.0</td><td>0.029</td><td>0.760</td><td>1.515</td></tr> <tr><td>10.0</td><td>0.027</td><td>0.684</td><td>1.355</td></tr> <tr><td>12.0</td><td>0.023</td><td>0.571</td><td>1.130</td></tr> <tr><td>14.0</td><td>0.022</td><td>0.493</td><td>0.968</td></tr> <tr><td>16.0</td><td>0.021</td><td>0.434</td><td>0.845</td></tr> <tr><td>18.0</td><td>0.021</td><td>0.389</td><td>0.752</td></tr> <tr><td>20.0</td><td>0.020</td><td>0.350</td><td>0.678</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.001	0.000	4.0	0.001	0.001	0.000	4.8	0.001	-0.001	0.001	5.2	0.047	0.004	2.778	6.0	0.044	1.154	2.357	8.0	0.034	0.858	1.720	9.0	0.029	0.760	1.515	10.0	0.027	0.684	1.355	12.0	0.023	0.571	1.130	14.0	0.022	0.493	0.968	16.0	0.021	0.434	0.845	18.0	0.021	0.389	0.752	20.0	0.020	0.350	0.678	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																
	Load 0%	Load 50%	Load 100%																																																																														
0.0	0.000	0.000	0.000																																																																														
2.0	0.000	0.001	0.000																																																																														
4.0	0.001	0.001	0.000																																																																														
4.8	0.001	-0.001	0.001																																																																														
5.2	0.047	0.004	2.778																																																																														
6.0	0.044	1.154	2.357																																																																														
8.0	0.034	0.858	1.720																																																																														
9.0	0.029	0.760	1.515																																																																														
10.0	0.027	0.684	1.355																																																																														
12.0	0.023	0.571	1.130																																																																														
14.0	0.022	0.493	0.968																																																																														
16.0	0.021	0.434	0.845																																																																														
18.0	0.021	0.389	0.752																																																																														
20.0	0.020	0.350	0.678																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														
--	-	-	-																																																																														

Model	SUTS101212																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○- - Input Volt. 18V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.030</td><td>0.024</td><td>0.021</td></tr> <tr><td>0.2</td><td>0.323</td><td>0.247</td><td>0.163</td></tr> <tr><td>0.4</td><td>0.619</td><td>0.466</td><td>0.309</td></tr> <tr><td>0.6</td><td>0.902</td><td>0.685</td><td>0.461</td></tr> <tr><td>0.8</td><td>1.230</td><td>0.898</td><td>0.609</td></tr> <tr><td>1.0</td><td>1.518</td><td>1.141</td><td>0.750</td></tr> <tr><td>1.1</td><td>1.665</td><td>1.239</td><td>0.834</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.0	0.030	0.024	0.021	0.2	0.323	0.247	0.163	0.4	0.619	0.466	0.309	0.6	0.902	0.685	0.461	0.8	1.230	0.898	0.609	1.0	1.518	1.141	0.750	1.1	1.665	1.239	0.834	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.0	0.030	0.024	0.021																																																			
0.2	0.323	0.247	0.163																																																			
0.4	0.619	0.466	0.309																																																			
0.6	0.902	0.685	0.461																																																			
0.8	1.230	0.898	0.609																																																			
1.0	1.518	1.141	0.750																																																			
1.1	1.665	1.239	0.834																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS101212																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - · -○--- Input Volt. 18V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.27</td><td>0.29</td><td>0.38</td></tr> <tr> <td>0.2</td><td>2.89</td><td>2.96</td><td>2.93</td></tr> <tr> <td>0.4</td><td>5.50</td><td>5.56</td><td>5.53</td></tr> <tr> <td>0.6</td><td>8.15</td><td>8.16</td><td>8.29</td></tr> <tr> <td>0.8</td><td>10.85</td><td>10.80</td><td>10.89</td></tr> <tr> <td>1.0</td><td>13.63</td><td>13.52</td><td>13.52</td></tr> <tr> <td>1.1</td><td>15.07</td><td>14.87</td><td>14.86</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.0	0.27	0.29	0.38	0.2	2.89	2.96	2.93	0.4	5.50	5.56	5.53	0.6	8.15	8.16	8.29	0.8	10.85	10.80	10.89	1.0	13.63	13.52	13.52	1.1	15.07	14.87	14.86	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.0	0.27	0.29	0.38																																																			
0.2	2.89	2.96	2.93																																																			
0.4	5.50	5.56	5.53																																																			
0.6	8.15	8.16	8.29																																																			
0.8	10.85	10.80	10.89																																																			
1.0	13.63	13.52	13.52																																																			
1.1	15.07	14.87	14.86																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


Model	SUTS101212	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (6 to 22). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>8</td><td>88.0</td><td>87.3</td></tr> <tr><td>9</td><td>88.1</td><td>87.9</td></tr> <tr><td>10</td><td>87.9</td><td>88.6</td></tr> <tr><td>12</td><td>87.5</td><td>88.9</td></tr> <tr><td>15</td><td>86.9</td><td>89.3</td></tr> <tr><td>18</td><td>86.2</td><td>88.9</td></tr> <tr><td>20</td><td>86.2</td><td>88.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	8	88.0	87.3	9	88.1	87.9	10	87.9	88.6	12	87.5	88.9	15	86.9	89.3	18	86.2	88.9	20	86.2	88.6	--	-	-	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
8	88.0	87.3																													
9	88.1	87.9																													
10	87.9	88.6																													
12	87.5	88.9																													
15	86.9	89.3																													
18	86.2	88.9																													
20	86.2	88.6																													
--	-	-																													
--	-	-																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTS101212	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○ - - Input Volt. 18V</p>																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.2</td><td>83.2</td><td>81.3</td><td>82.1</td></tr> <tr><td>0.4</td><td>87.2</td><td>86.3</td><td>86.8</td></tr> <tr><td>0.6</td><td>88.4</td><td>88.4</td><td>86.9</td></tr> <tr><td>0.8</td><td>88.6</td><td>89.0</td><td>88.3</td></tr> <tr><td>1.0</td><td>88.1</td><td>88.9</td><td>88.9</td></tr> <tr><td>1.1</td><td>87.7</td><td>88.9</td><td>89.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.0	-	-	-	0.2	83.2	81.3	82.1	0.4	87.2	86.3	86.8	0.6	88.4	88.4	86.9	0.8	88.6	89.0	88.3	1.0	88.1	88.9	88.9	1.1	87.7	88.9	89.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0.0	-	-	-																																																		
0.2	83.2	81.3	82.1																																																		
0.4	87.2	86.3	86.8																																																		
0.6	88.4	88.4	86.9																																																		
0.8	88.6	89.0	88.3																																																		
1.0	88.1	88.9	88.9																																																		
1.1	87.7	88.9	89.0																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note:	Slanted line shows the range of the rated load current.																																																				

Model	SUTS101212
Item	Line Regulation
Object	+12V1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	12.014	12.007
9	12.014	12.008
10	12.015	12.009
12	12.014	12.009
15	12.014	12.010
18	12.014	12.010
20	12.014	12.010
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS101212	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Load Regulation																																																						
Object	+12V1A																																																						
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - -○- - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V [V]</th> <th>12V [V]</th> <th>18V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.021</td><td>12.020</td><td>12.022</td></tr> <tr><td>0.2</td><td>12.018</td><td>12.018</td><td>12.018</td></tr> <tr><td>0.4</td><td>12.016</td><td>12.016</td><td>12.016</td></tr> <tr><td>0.6</td><td>12.013</td><td>12.014</td><td>12.014</td></tr> <tr><td>0.8</td><td>12.011</td><td>12.012</td><td>12.012</td></tr> <tr><td>1.0</td><td>12.008</td><td>12.009</td><td>12.010</td></tr> <tr><td>1.1</td><td>12.006</td><td>12.008</td><td>12.009</td></tr> </tbody> </table>	Load Current [A]	9V [V]	12V [V]	18V [V]	0.0	12.021	12.020	12.022	0.2	12.018	12.018	12.018	0.4	12.016	12.016	12.016	0.6	12.013	12.014	12.014	0.8	12.011	12.012	12.012	1.0	12.008	12.009	12.010	1.1	12.006	12.008	12.009																						
Load Current [A]	9V [V]	12V [V]	18V [V]																																																				
0.0	12.021	12.020	12.022																																																				
0.2	12.018	12.018	12.018																																																				
0.4	12.016	12.016	12.016																																																				
0.6	12.013	12.014	12.014																																																				
0.8	12.011	12.012	12.012																																																				
1.0	12.008	12.009	12.010																																																				
1.1	12.006	12.008	12.009																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.021</td><td>12.020</td><td>12.022</td></tr> <tr><td>0.2</td><td>12.018</td><td>12.018</td><td>12.018</td></tr> <tr><td>0.4</td><td>12.016</td><td>12.016</td><td>12.016</td></tr> <tr><td>0.6</td><td>12.013</td><td>12.014</td><td>12.014</td></tr> <tr><td>0.8</td><td>12.011</td><td>12.012</td><td>12.012</td></tr> <tr><td>1.0</td><td>12.008</td><td>12.009</td><td>12.010</td></tr> <tr><td>1.1</td><td>12.006</td><td>12.008</td><td>12.009</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.0	12.021	12.020	12.022	0.2	12.018	12.018	12.018	0.4	12.016	12.016	12.016	0.6	12.013	12.014	12.014	0.8	12.011	12.012	12.012	1.0	12.008	12.009	12.010	1.1	12.006	12.008	12.009	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																				
0.0	12.021	12.020	12.022																																																				
0.2	12.018	12.018	12.018																																																				
0.4	12.016	12.016	12.016																																																				
0.6	12.013	12.014	12.014																																																				
0.8	12.011	12.012	12.012																																																				
1.0	12.008	12.009	12.010																																																				
1.1	12.006	12.008	12.009																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.


COSEL



Model	SUTS101212
Item	Ripple Voltage (by Load Current)
Object	+12V1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.0	3	3
0.2	4	4
0.4	6	4
0.6	7	5
0.8	8	6
1.0	9	6
1.1	9	6
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS101212
Item	Ripple-Noise
Object	+12V1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.0	4	6
0.2	8	9
0.4	11	12
0.6	14	14
0.8	18	16
1.0	21	19
1.1	23	20
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS101212
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1A

1. Graph



Measured by 150 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	16
-40	10	14
-20	8	14
0	8	-
25	8	13
55	6	10
60	6	10
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS101212
Item	Ambient Temperature Drift
Object	+12V1A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	11.958	11.965	11.968
-40	11.977	11.981	11.984
-20	11.990	11.993	11.996
0	12.000	12.002	12.004
25	12.007	12.009	12.010
55	12.009	12.009	12.009
60	12.008	12.008	12.008
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS101212	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V1A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current : 0 - 1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	18	0	12.023	±23	±0.2
Minimum Voltage	-40	9	1	11.977		

COSEL

Model	SUTS101212
Item	Time Lapse Drift
Object	+12V1A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Input Volt. 12V
Load 100%

2. Values


Time since start [H]	Output Voltage [V]
0.0	12.006
0.5	12.009
1.0	12.010
2.0	12.009
3.0	12.010
4.0	12.010
5.0	12.009
6.0	12.010
7.0	12.010
8.0	12.010

COSEL

Model	SUTS101212
Item	Rise and Fall Time
Object	+12V1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.5	1.9	2.4	0.2	2.5
100 %		0.5	2.0	2.5	0.2	1.3



Model	SUTS101212
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1A

Testing Circuitry Figure A


1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.6	4.7
-40	3.7	4.8
-20	4.0	4.9
0	4.2	5.1
25	4.4	5.5
55	4.7	5.8
60	4.7	5.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS101212	Temperature Testing Circuitry 25°C Figure A																																																						
Item	Overcurrent Protection																																																							
Object	+12V1A																																																							
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>1.19</td><td>1.22</td><td>1.22</td></tr> <tr><td>11.4</td><td>1.37</td><td>1.45</td><td>1.49</td></tr> <tr><td>10.8</td><td>1.19</td><td>1.22</td><td>1.22</td></tr> <tr><td>9.6</td><td>1.38</td><td>1.47</td><td>1.49</td></tr> <tr><td>8.4</td><td>1.40</td><td>1.47</td><td>1.46</td></tr> <tr><td>7.2</td><td>1.41</td><td>1.47</td><td>1.44</td></tr> <tr><td>6.0</td><td>1.44</td><td>1.49</td><td>1.42</td></tr> <tr><td>4.8</td><td>1.48</td><td>1.51</td><td>1.43</td></tr> <tr><td>3.6</td><td>1.55</td><td>1.56</td><td>1.40</td></tr> <tr><td>2.4</td><td>1.66</td><td>1.60</td><td>1.39</td></tr> <tr><td>1.2</td><td>1.78</td><td>1.69</td><td>1.46</td></tr> <tr><td>0.0</td><td>2.14</td><td>2.16</td><td>3.10</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	12.0	1.19	1.22	1.22	11.4	1.37	1.45	1.49	10.8	1.19	1.22	1.22	9.6	1.38	1.47	1.49	8.4	1.40	1.47	1.46	7.2	1.41	1.47	1.44	6.0	1.44	1.49	1.42	4.8	1.48	1.51	1.43	3.6	1.55	1.56	1.40	2.4	1.66	1.60	1.39	1.2	1.78	1.69	1.46	0.0	2.14	2.16	3.10
Output Voltage [V]	Load Current [A]																																																							
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																					
12.0	1.19	1.22	1.22																																																					
11.4	1.37	1.45	1.49																																																					
10.8	1.19	1.22	1.22																																																					
9.6	1.38	1.47	1.49																																																					
8.4	1.40	1.47	1.46																																																					
7.2	1.41	1.47	1.44																																																					
6.0	1.44	1.49	1.42																																																					
4.8	1.48	1.51	1.43																																																					
3.6	1.55	1.56	1.40																																																					
2.4	1.66	1.60	1.39																																																					
1.2	1.78	1.69	1.46																																																					
0.0	2.14	2.16	3.10																																																					

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)