

TEST DATA OF SUTS104805


Regulated DC Power Supply

Approved by : Kazunari Asano
Kazunari Asano Design Manager


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18

(Final Page 18)


Model	SUTS104805	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>26.6</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>29.0</td><td>0.013</td><td>0.206</td><td>0.411</td></tr> <tr><td>33.0</td><td>0.014</td><td>0.182</td><td>0.360</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.169</td><td>0.330</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.153</td><td>0.296</td></tr> <tr><td>48.0</td><td>0.014</td><td>0.129</td><td>0.248</td></tr> <tr><td>60.0</td><td>0.015</td><td>0.104</td><td>0.201</td></tr> <tr><td>70.0</td><td>0.015</td><td>0.092</td><td>0.176</td></tr> <tr><td>76.0</td><td>0.016</td><td>0.087</td><td>0.163</td></tr> <tr><td>80.0</td><td>0.016</td><td>0.084</td><td>0.156</td></tr> <tr><td>83.2</td><td>0.016</td><td>0.082</td><td>0.151</td></tr> <tr><td>86.4</td><td>0.016</td><td>0.079</td><td>0.146</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.001	0.001	26.6	0.001	0.001	0.001	29.0	0.013	0.206	0.411	33.0	0.014	0.182	0.360	36.0	0.015	0.169	0.330	40.0	0.015	0.153	0.296	48.0	0.014	0.129	0.248	60.0	0.015	0.104	0.201	70.0	0.015	0.092	0.176	76.0	0.016	0.087	0.163	80.0	0.016	0.084	0.156	83.2	0.016	0.082	0.151	86.4	0.016	0.079	0.146	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
16.0	0.000	0.000	0.000																																																																																
24.0	0.001	0.001	0.001																																																																																
26.6	0.001	0.001	0.001																																																																																
29.0	0.013	0.206	0.411																																																																																
33.0	0.014	0.182	0.360																																																																																
36.0	0.015	0.169	0.330																																																																																
40.0	0.015	0.153	0.296																																																																																
48.0	0.014	0.129	0.248																																																																																
60.0	0.015	0.104	0.201																																																																																
70.0	0.015	0.092	0.176																																																																																
76.0	0.016	0.087	0.163																																																																																
80.0	0.016	0.084	0.156																																																																																
83.2	0.016	0.082	0.151																																																																																
86.4	0.016	0.079	0.146																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTS104805																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (36V)</th> <th>Input Current [A] (48V)</th> <th>Input Current [A] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.015</td><td>0.014</td><td>0.015</td></tr> <tr><td>0.4</td><td>0.076</td><td>0.059</td><td>0.044</td></tr> <tr><td>0.8</td><td>0.138</td><td>0.103</td><td>0.074</td></tr> <tr><td>1.2</td><td>0.201</td><td>0.154</td><td>0.101</td></tr> <tr><td>1.6</td><td>0.266</td><td>0.201</td><td>0.134</td></tr> <tr><td>2.0</td><td>0.332</td><td>0.249</td><td>0.164</td></tr> <tr><td>2.2</td><td>0.366</td><td>0.274</td><td>0.179</td></tr> </tbody> </table>			Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)	0.0	0.015	0.014	0.015	0.4	0.076	0.059	0.044	0.8	0.138	0.103	0.074	1.2	0.201	0.154	0.101	1.6	0.266	0.201	0.134	2.0	0.332	0.249	0.164	2.2	0.366	0.274	0.179																			
Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)																																																			
0.0	0.015	0.014	0.015																																																			
0.4	0.076	0.059	0.044																																																			
0.8	0.138	0.103	0.074																																																			
1.2	0.201	0.154	0.101																																																			
1.6	0.266	0.201	0.134																																																			
2.0	0.332	0.249	0.164																																																			
2.2	0.366	0.274	0.179																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.015</td><td>0.014</td><td>0.015</td></tr> <tr><td>0.4</td><td>0.076</td><td>0.059</td><td>0.044</td></tr> <tr><td>0.8</td><td>0.138</td><td>0.103</td><td>0.074</td></tr> <tr><td>1.2</td><td>0.201</td><td>0.154</td><td>0.101</td></tr> <tr><td>1.6</td><td>0.266</td><td>0.201</td><td>0.134</td></tr> <tr><td>2.0</td><td>0.332</td><td>0.249</td><td>0.164</td></tr> <tr><td>2.2</td><td>0.366</td><td>0.274</td><td>0.179</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.015	0.014	0.015	0.4	0.076	0.059	0.044	0.8	0.138	0.103	0.074	1.2	0.201	0.154	0.101	1.6	0.266	0.201	0.134	2.0	0.332	0.249	0.164	2.2	0.366	0.274	0.179	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.015	0.014	0.015																																																			
0.4	0.076	0.059	0.044																																																			
0.8	0.138	0.103	0.074																																																			
1.2	0.201	0.154	0.101																																																			
1.6	0.266	0.201	0.134																																																			
2.0	0.332	0.249	0.164																																																			
2.2	0.366	0.274	0.179																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS104805																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p>  <p>The graph plots Input Power [W] on the Y-axis (0.0 to 20.0) against Load Current [A] on the X-axis (0.0 to 2.0). Three curves are shown for input voltages of 36V, 48V, and 76V. A slanted line represents the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.53</td><td>0.69</td><td>1.17</td></tr> <tr><td>0.4</td><td>2.72</td><td>2.84</td><td>3.37</td></tr> <tr><td>0.8</td><td>4.98</td><td>4.96</td><td>5.65</td></tr> <tr><td>1.2</td><td>7.23</td><td>7.40</td><td>7.70</td></tr> <tr><td>1.6</td><td>9.54</td><td>9.65</td><td>10.21</td></tr> <tr><td>2.0</td><td>11.92</td><td>11.96</td><td>12.43</td></tr> <tr><td>2.2</td><td>13.14</td><td>13.13</td><td>13.58</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.0	0.53	0.69	1.17	0.4	2.72	2.84	3.37	0.8	4.98	4.96	5.65	1.2	7.23	7.40	7.70	1.6	9.54	9.65	10.21	2.0	11.92	11.96	12.43	2.2	13.14	13.13	13.58																			
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																			
0.0	0.53	0.69	1.17																																																			
0.4	2.72	2.84	3.37																																																			
0.8	4.98	4.96	5.65																																																			
1.2	7.23	7.40	7.70																																																			
1.6	9.54	9.65	10.21																																																			
2.0	11.92	11.96	12.43																																																			
2.2	13.14	13.13	13.58																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.53</td><td>0.69</td><td>1.17</td></tr> <tr><td>0.4</td><td>2.72</td><td>2.84</td><td>3.37</td></tr> <tr><td>0.8</td><td>4.98</td><td>4.96</td><td>5.65</td></tr> <tr><td>1.2</td><td>7.23</td><td>7.40</td><td>7.70</td></tr> <tr><td>1.6</td><td>9.54</td><td>9.65</td><td>10.21</td></tr> <tr><td>2.0</td><td>11.92</td><td>11.96</td><td>12.43</td></tr> <tr><td>2.2</td><td>13.14</td><td>13.13</td><td>13.58</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.53	0.69	1.17	0.4	2.72	2.84	3.37	0.8	4.98	4.96	5.65	1.2	7.23	7.40	7.70	1.6	9.54	9.65	10.21	2.0	11.92	11.96	12.43	2.2	13.14	13.13	13.58	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.53	0.69	1.17																																																			
0.4	2.72	2.84	3.37																																																			
0.8	4.98	4.96	5.65																																																			
1.2	7.23	7.40	7.70																																																			
1.6	9.54	9.65	10.21																																																			
2.0	11.92	11.96	12.43																																																			
2.2	13.14	13.13	13.58																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS104805	Temperature Testing Circuitry	25°C Figure A
Item	Efficiency (by Input Voltage)		
Object	_____		


1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
33	83.8	84.8
36	83.1	84.8
40	82.3	84.9
48	81.1	84.6
55	80.9	84.1
60	80.7	83.6
70	78.7	82.1
76	76.7	81.5
80	75.6	80.8


Note: Slanted line shows the range of the rated input voltage.

Model	SUTS104805	Temperature	25°C																																																		
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																		
Object	_____																																																				
1. Graph		2. Values																																																			
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p>  <p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Load Current [A] on the x-axis (0.0 to 2.0). Three data series are shown: 36V (solid triangles), 48V (dashed squares), and 76V (dotted circles). All curves show efficiency increasing with load current. A slanted line from the top-left to the bottom-right of the graph area indicates the rated load current range.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>74.3</td><td>71.3</td><td>60.0</td></tr> <tr><td>0.8</td><td>81.4</td><td>81.6</td><td>71.8</td></tr> <tr><td>1.2</td><td>84.0</td><td>82.1</td><td>78.9</td></tr> <tr><td>1.6</td><td>84.9</td><td>83.9</td><td>79.4</td></tr> <tr><td>2.0</td><td>84.9</td><td>84.6</td><td>81.4</td></tr> <tr><td>2.2</td><td>84.7</td><td>84.8</td><td>81.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	0.4	74.3	71.3	60.0	0.8	81.4	81.6	71.8	1.2	84.0	82.1	78.9	1.6	84.9	83.9	79.4	2.0	84.9	84.6	81.4	2.2	84.7	84.8	81.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.0	-	-	-																																																		
0.4	74.3	71.3	60.0																																																		
0.8	81.4	81.6	71.8																																																		
1.2	84.0	82.1	78.9																																																		
1.6	84.9	83.9	79.4																																																		
2.0	84.9	84.6	81.4																																																		
2.2	84.7	84.8	81.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

Model	SUTS104805
Item	Line Regulation
Object	+5V2A

Temperature 25°C
Testing Circuitry Figure A


1. Graph




2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	5.057	5.048
36	5.057	5.048
40	5.057	5.048
48	5.057	5.049
55	5.057	5.049
60	5.057	5.049
70	5.057	5.049
76	5.057	5.049
80	5.057	5.049

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS104805	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+5V2A																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - -○- - Input Volt. 76V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>5.066</td> <td>5.066</td> <td>5.066</td> </tr> <tr> <td>0.4</td> <td>5.062</td> <td>5.062</td> <td>5.062</td> </tr> <tr> <td>0.8</td> <td>5.059</td> <td>5.059</td> <td>5.059</td> </tr> <tr> <td>1.2</td> <td>5.056</td> <td>5.055</td> <td>5.056</td> </tr> <tr> <td>1.6</td> <td>5.052</td> <td>5.052</td> <td>5.052</td> </tr> <tr> <td>2.0</td> <td>5.049</td> <td>5.049</td> <td>5.049</td> </tr> <tr> <td>2.2</td> <td>5.047</td> <td>5.047</td> <td>5.047</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	5.066	5.066	5.066	0.4	5.062	5.062	5.062	0.8	5.059	5.059	5.059	1.2	5.056	5.055	5.056	1.6	5.052	5.052	5.052	2.0	5.049	5.049	5.049	2.2	5.047	5.047	5.047	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	5.066	5.066	5.066																																																			
0.4	5.062	5.062	5.062																																																			
0.8	5.059	5.059	5.059																																																			
1.2	5.056	5.055	5.056																																																			
1.6	5.052	5.052	5.052																																																			
2.0	5.049	5.049	5.049																																																			
2.2	5.047	5.047	5.047																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


COSEL



Model	SUTS104805
Item	Ripple Voltage (by Load Current)
Object	+5V2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	4	5
0.4	8	10
0.8	11	11
1.2	17	15
1.6	21	16
2.0	27	18
2.2	29	19
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS104805
Item	Ripple-Noise
Object	+5V2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	11	20
0.4	16	22
0.8	24	25
1.2	31	28
1.6	38	32
2.0	44	35
2.2	48	37
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS104805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2A

1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	28	36
-40	28	35
-20	21	35
0	20	32
25	19	30
55	17	27
60	17	27
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS104805
Item	Ambient Temperature Drift
Object	+5V2A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	5.016	5.018	5.019
-40	5.026	5.028	5.029
-20	5.035	5.036	5.037
0	5.041	5.043	5.043
25	5.047	5.047	5.048
55	5.049	5.050	5.050
60	5.049	5.050	5.050
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS104805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	76	0	5.068	±21	±0.4
Minimum Voltage	-40	36	2	5.026		

COSEL

Model	SUTS104805
Item	Time Lapse Drift
Object	+5V2A

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values


Time since start [H]	Output Voltage [V]
0.0	5.044
0.5	5.049
1.0	5.049
2.0	5.049
3.0	5.049
4.0	5.049
5.0	5.049
6.0	5.049
7.0	5.049
8.0	5.049

COSEL

Model	SUTS104805
Item	Rise and Fall Time
Object	+5V2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.3	0.6	9.9	0.1	1.2	
100 %		9.4	0.7	10.1	0.1	0.7	



Model	SUTS104805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	27.6	27.6
-40	27.6	27.8
-20	27.8	28.0
0	28.0	28.0
25	28.4	28.4
55	28.6	28.6
60	28.7	28.6
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS104805
Item	Overcurrent Protection
Object	+5V2A



Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
5.00	2.01	2.01	2.01
4.75	2.64	2.81	2.94
4.50	2.73	2.94	3.07
4.00	2.98	3.22	3.38
3.50	3.24	3.50	3.63
3.00	3.39	3.61	3.67
2.50	3.45	3.66	3.64
2.00	3.50	3.71	3.59
1.50	3.63	3.79	3.33
1.00	3.82	3.70	0.00
0.50	3.75	3.47	0.00
0.00	3.42	3.15	3.74




Figure A




Figure B (Ripple and Ripple noise Characteristic)