

TEST DATA OF SUTS10483R3

Regulated DC Power Supply

Approved by : Kazunari Asano
Kazunari Asano Design Manager


Prepared by : Sho Saito Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18

(Final Page 18)

Model	SUTS10483R3	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>26.6</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>29.0</td><td>0.011</td><td>0.179</td><td>0.360</td></tr> <tr><td>33.0</td><td>0.011</td><td>0.158</td><td>0.312</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.146</td><td>0.285</td></tr> <tr><td>40.0</td><td>0.012</td><td>0.131</td><td>0.257</td></tr> <tr><td>48.0</td><td>0.012</td><td>0.109</td><td>0.215</td></tr> <tr><td>60.0</td><td>0.013</td><td>0.092</td><td>0.175</td></tr> <tr><td>70.0</td><td>0.013</td><td>0.082</td><td>0.153</td></tr> <tr><td>76.0</td><td>0.014</td><td>0.076</td><td>0.142</td></tr> <tr><td>80.0</td><td>0.014</td><td>0.074</td><td>0.136</td></tr> <tr><td>82.4</td><td>0.014</td><td>0.072</td><td>0.132</td></tr> <tr><td>84.8</td><td>0.014</td><td>0.070</td><td>0.129</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.001	0.001	26.6	0.001	0.001	0.001	29.0	0.011	0.179	0.360	33.0	0.011	0.158	0.312	36.0	0.012	0.146	0.285	40.0	0.012	0.131	0.257	48.0	0.012	0.109	0.215	60.0	0.013	0.092	0.175	70.0	0.013	0.082	0.153	76.0	0.014	0.076	0.142	80.0	0.014	0.074	0.136	82.4	0.014	0.072	0.132	84.8	0.014	0.070	0.129	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
16.0	0.000	0.000	0.000																																																																																
24.0	0.001	0.001	0.001																																																																																
26.6	0.001	0.001	0.001																																																																																
29.0	0.011	0.179	0.360																																																																																
33.0	0.011	0.158	0.312																																																																																
36.0	0.012	0.146	0.285																																																																																
40.0	0.012	0.131	0.257																																																																																
48.0	0.012	0.109	0.215																																																																																
60.0	0.013	0.092	0.175																																																																																
70.0	0.013	0.082	0.153																																																																																
76.0	0.014	0.076	0.142																																																																																
80.0	0.014	0.074	0.136																																																																																
82.4	0.014	0.072	0.132																																																																																
84.8	0.014	0.070	0.129																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTS10483R3																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - ○ - - Input Volt. 76V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.012</td><td>0.012</td><td>0.014</td></tr> <tr><td>0.52</td><td>0.064</td><td>0.051</td><td>0.039</td></tr> <tr><td>1.04</td><td>0.115</td><td>0.092</td><td>0.064</td></tr> <tr><td>1.56</td><td>0.173</td><td>0.131</td><td>0.089</td></tr> <tr><td>2.08</td><td>0.229</td><td>0.174</td><td>0.113</td></tr> <tr><td>2.60</td><td>0.286</td><td>0.216</td><td>0.142</td></tr> <tr><td>2.86</td><td>0.316</td><td>0.237</td><td>0.155</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.012	0.012	0.014	0.52	0.064	0.051	0.039	1.04	0.115	0.092	0.064	1.56	0.173	0.131	0.089	2.08	0.229	0.174	0.113	2.60	0.286	0.216	0.142	2.86	0.316	0.237	0.155	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	0.012	0.012	0.014																																																			
0.52	0.064	0.051	0.039																																																			
1.04	0.115	0.092	0.064																																																			
1.56	0.173	0.131	0.089																																																			
2.08	0.229	0.174	0.113																																																			
2.60	0.286	0.216	0.142																																																			
2.86	0.316	0.237	0.155																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS10483R3																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>36V [W]</th> <th>48V [W]</th> <th>76V [W]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.44</td><td>0.59</td><td>1.03</td></tr> <tr><td>0.52</td><td>2.29</td><td>2.47</td><td>2.95</td></tr> <tr><td>1.04</td><td>4.15</td><td>4.40</td><td>4.84</td></tr> <tr><td>1.56</td><td>6.24</td><td>6.31</td><td>6.80</td></tr> <tr><td>2.08</td><td>8.24</td><td>8.35</td><td>8.63</td></tr> <tr><td>2.60</td><td>10.30</td><td>10.35</td><td>10.83</td></tr> <tr><td>2.86</td><td>11.35</td><td>11.36</td><td>11.80</td></tr> </tbody> </table>			Load Current [A]	36V [W]	48V [W]	76V [W]	0.00	0.44	0.59	1.03	0.52	2.29	2.47	2.95	1.04	4.15	4.40	4.84	1.56	6.24	6.31	6.80	2.08	8.24	8.35	8.63	2.60	10.30	10.35	10.83	2.86	11.35	11.36	11.80																			
Load Current [A]	36V [W]	48V [W]	76V [W]																																																			
0.00	0.44	0.59	1.03																																																			
0.52	2.29	2.47	2.95																																																			
1.04	4.15	4.40	4.84																																																			
1.56	6.24	6.31	6.80																																																			
2.08	8.24	8.35	8.63																																																			
2.60	10.30	10.35	10.83																																																			
2.86	11.35	11.36	11.80																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.44</td><td>0.59</td><td>1.03</td></tr> <tr><td>0.52</td><td>2.29</td><td>2.47</td><td>2.95</td></tr> <tr><td>1.04</td><td>4.15</td><td>4.40</td><td>4.84</td></tr> <tr><td>1.56</td><td>6.24</td><td>6.31</td><td>6.80</td></tr> <tr><td>2.08</td><td>8.24</td><td>8.35</td><td>8.63</td></tr> <tr><td>2.60</td><td>10.30</td><td>10.35</td><td>10.83</td></tr> <tr><td>2.86</td><td>11.35</td><td>11.36</td><td>11.80</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.44	0.59	1.03	0.52	2.29	2.47	2.95	1.04	4.15	4.40	4.84	1.56	6.24	6.31	6.80	2.08	8.24	8.35	8.63	2.60	10.30	10.35	10.83	2.86	11.35	11.36	11.80	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	0.44	0.59	1.03																																																			
0.52	2.29	2.47	2.95																																																			
1.04	4.15	4.40	4.84																																																			
1.56	6.24	6.31	6.80																																																			
2.08	8.24	8.35	8.63																																																			
2.60	10.30	10.35	10.83																																																			
2.86	11.35	11.36	11.80																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS10483R3	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>81.9</td><td>82.5</td></tr> <tr><td>36</td><td>81.5</td><td>82.7</td></tr> <tr><td>40</td><td>81.7</td><td>82.8</td></tr> <tr><td>48</td><td>81.4</td><td>82.3</td></tr> <tr><td>55</td><td>79.0</td><td>81.8</td></tr> <tr><td>60</td><td>77.2</td><td>81.1</td></tr> <tr><td>70</td><td>74.6</td><td>79.7</td></tr> <tr><td>76</td><td>73.4</td><td>79.0</td></tr> <tr><td>80</td><td>72.8</td><td>78.5</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	81.9	82.5	36	81.5	82.7	40	81.7	82.8	48	81.4	82.3	55	79.0	81.8	60	77.2	81.1	70	74.6	79.7	76	73.4	79.0	80	72.8	78.5
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
33	81.9	82.5																													
36	81.5	82.7																													
40	81.7	82.8																													
48	81.4	82.3																													
55	79.0	81.8																													
60	77.2	81.1																													
70	74.6	79.7																													
76	73.4	79.0																													
80	72.8	78.5																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTS10483R3	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>The graph shows efficiency increasing with load current for all input voltages. The 36V curve is the highest, followed by 48V, and then 76V. A slanted line from the top left to the bottom right indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36V [%]</th> <th>Input Volt. 48V [%]</th> <th>Input Volt. 76V [%]</th> </tr> </thead> <tbody> <tr><td>0.52</td><td>74.9</td><td>69.4</td><td>58.1</td></tr> <tr><td>1.04</td><td>82.5</td><td>77.9</td><td>70.9</td></tr> <tr><td>1.56</td><td>82.2</td><td>81.4</td><td>75.5</td></tr> <tr><td>2.08</td><td>83.0</td><td>81.9</td><td>79.2</td></tr> <tr><td>2.60</td><td>82.8</td><td>82.5</td><td>78.8</td></tr> <tr><td>2.86</td><td>82.6</td><td>82.5</td><td>79.5</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 36V [%]	Input Volt. 48V [%]	Input Volt. 76V [%]	0.52	74.9	69.4	58.1	1.04	82.5	77.9	70.9	1.56	82.2	81.4	75.5	2.08	83.0	81.9	79.2	2.60	82.8	82.5	78.8	2.86	82.6	82.5	79.5																							
Load Current [A]	Input Volt. 36V [%]	Input Volt. 48V [%]	Input Volt. 76V [%]																																																		
0.52	74.9	69.4	58.1																																																		
1.04	82.5	77.9	70.9																																																		
1.56	82.2	81.4	75.5																																																		
2.08	83.0	81.9	79.2																																																		
2.60	82.8	82.5	78.8																																																		
2.86	82.6	82.5	79.5																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.52</td><td>74.9</td><td>69.4</td><td>58.1</td></tr> <tr><td>1.04</td><td>82.5</td><td>77.9</td><td>70.9</td></tr> <tr><td>1.56</td><td>82.2</td><td>81.4</td><td>75.5</td></tr> <tr><td>2.08</td><td>83.0</td><td>81.9</td><td>79.2</td></tr> <tr><td>2.60</td><td>82.8</td><td>82.5</td><td>78.8</td></tr> <tr><td>2.86</td><td>82.6</td><td>82.5</td><td>79.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.52	74.9	69.4	58.1	1.04	82.5	77.9	70.9	1.56	82.2	81.4	75.5	2.08	83.0	81.9	79.2	2.60	82.8	82.5	78.8	2.86	82.6	82.5	79.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	-	-	-																																																		
0.52	74.9	69.4	58.1																																																		
1.04	82.5	77.9	70.9																																																		
1.56	82.2	81.4	75.5																																																		
2.08	83.0	81.9	79.2																																																		
2.60	82.8	82.5	78.8																																																		
2.86	82.6	82.5	79.5																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.


Model	SUTS10483R3	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+3.3V2.6A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: - - - □ - - - Load 50% — △ — Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>3.293</td><td>3.280</td></tr> <tr><td>36</td><td>3.293</td><td>3.280</td></tr> <tr><td>40</td><td>3.293</td><td>3.281</td></tr> <tr><td>48</td><td>3.293</td><td>3.282</td></tr> <tr><td>55</td><td>3.293</td><td>3.282</td></tr> <tr><td>60</td><td>3.293</td><td>3.282</td></tr> <tr><td>70</td><td>3.293</td><td>3.282</td></tr> <tr><td>76</td><td>3.293</td><td>3.283</td></tr> <tr><td>80</td><td>3.293</td><td>3.283</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	3.293	3.280	36	3.293	3.280	40	3.293	3.281	48	3.293	3.282	55	3.293	3.282	60	3.293	3.282	70	3.293	3.282	76	3.293	3.283	80	3.293	3.283
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	3.293	3.280																																
36	3.293	3.280																																
40	3.293	3.281																																
48	3.293	3.282																																
55	3.293	3.282																																
60	3.293	3.282																																
70	3.293	3.282																																
76	3.293	3.283																																
80	3.293	3.283																																

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS10483R3	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Load Regulation																																																						
Object	+3.3V2.6A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 36V ---□--- Input Volt. 48V ---○--- Input Volt. 76V </p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>36V [V]</th> <th>48V [V]</th> <th>76V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.305</td><td>3.306</td><td>3.306</td></tr> <tr><td>0.52</td><td>3.301</td><td>3.301</td><td>3.301</td></tr> <tr><td>1.04</td><td>3.296</td><td>3.296</td><td>3.296</td></tr> <tr><td>1.56</td><td>3.291</td><td>3.291</td><td>3.292</td></tr> <tr><td>2.08</td><td>3.286</td><td>3.286</td><td>3.287</td></tr> <tr><td>2.60</td><td>3.280</td><td>3.281</td><td>3.282</td></tr> <tr><td>2.86</td><td>3.277</td><td>3.278</td><td>3.279</td></tr> </tbody> </table>	Load Current [A]	36V [V]	48V [V]	76V [V]	0.0	3.305	3.306	3.306	0.52	3.301	3.301	3.301	1.04	3.296	3.296	3.296	1.56	3.291	3.291	3.292	2.08	3.286	3.286	3.287	2.60	3.280	3.281	3.282	2.86	3.277	3.278	3.279																						
Load Current [A]	36V [V]	48V [V]	76V [V]																																																				
0.0	3.305	3.306	3.306																																																				
0.52	3.301	3.301	3.301																																																				
1.04	3.296	3.296	3.296																																																				
1.56	3.291	3.291	3.292																																																				
2.08	3.286	3.286	3.287																																																				
2.60	3.280	3.281	3.282																																																				
2.86	3.277	3.278	3.279																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.305</td><td>3.306</td><td>3.306</td></tr> <tr><td>0.52</td><td>3.301</td><td>3.301</td><td>3.301</td></tr> <tr><td>1.04</td><td>3.296</td><td>3.296</td><td>3.296</td></tr> <tr><td>1.56</td><td>3.291</td><td>3.291</td><td>3.292</td></tr> <tr><td>2.08</td><td>3.286</td><td>3.286</td><td>3.287</td></tr> <tr><td>2.60</td><td>3.280</td><td>3.281</td><td>3.282</td></tr> <tr><td>2.86</td><td>3.277</td><td>3.278</td><td>3.279</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	3.305	3.306	3.306	0.52	3.301	3.301	3.301	1.04	3.296	3.296	3.296	1.56	3.291	3.291	3.292	2.08	3.286	3.286	3.287	2.60	3.280	3.281	3.282	2.86	3.277	3.278	3.279	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.00	3.305	3.306	3.306																																																				
0.52	3.301	3.301	3.301																																																				
1.04	3.296	3.296	3.296																																																				
1.56	3.291	3.291	3.292																																																				
2.08	3.286	3.286	3.287																																																				
2.60	3.280	3.281	3.282																																																				
2.86	3.277	3.278	3.279																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.


COSEL



Model	SUTS10483R3
Item	Ripple Voltage (by Load Current)
Object	+3.3V2.6A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	2	7
0.52	11	10
1.04	17	15
1.56	24	18
2.08	29	22
2.60	32	25
2.86	35	28
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS10483R3
Item	Ripple-Noise
Object	+3.3V2.6A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	11	16
0.52	22	23
1.04	29	30
1.56	36	35
2.08	43	40
2.60	50	47
2.86	54	51
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS10483R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V2.6A

1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	28	45
-40	28	45
-20	25	38
0	21	33
25	18	30
55	14	21
60	14	21
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS10483R3
Item	Ambient Temperature Drift
Object	+3.3V2.6A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	3.248	3.252	3.254
-40	3.260	3.263	3.264
-20	3.269	3.272	3.273
0	3.277	3.278	3.280
25	3.282	3.283	3.284
55	3.283	3.284	3.285
60	3.283	3.284	3.285
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS10483R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V2.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 2.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	76	0	3.310	±25	±0.8
Minimum Voltage	-40	36	2.6	3.260		

COSEL

Model	SUTS10483R3
Item	Time Lapse Drift
Object	+3.3V2.6A

1. Graph



Temperature 25°C
Testing Circuitry Figure A


2. Values

Time since start [H]	Output Voltage [V]
0.0	3.277
0.5	3.282
1.0	3.282
2.0	3.282
3.0	3.282
4.0	3.282
5.0	3.282
6.0	3.282
7.0	3.282
8.0	3.282

COSEL


Model	SUTS10483R3	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+3.3V2.6A	

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		9.9	0.9	10.8	0.1	0.8
100 %		9.9	0.9	10.8	0.1	0.5



Model	SUTS10483R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V2.6A

Testing Circuitry Figure A


1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	27.7	27.6
-40	27.7	27.8
-20	27.9	27.9
0	28.1	28.0
25	28.3	28.4
55	28.7	28.7
60	28.7	28.6
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS10483R3																																																									
Item	Overcurrent Protection	Temperature Testing Circuitry	25°C Figure A																																																							
Object	+3.3V2.6A																																																									
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>2.60</td><td>2.60</td><td>2.60</td></tr> <tr><td>3.14</td><td>3.63</td><td>3.88</td><td>3.98</td></tr> <tr><td>2.97</td><td>3.75</td><td>4.04</td><td>4.15</td></tr> <tr><td>2.64</td><td>3.97</td><td>4.27</td><td>4.31</td></tr> <tr><td>2.31</td><td>4.04</td><td>4.31</td><td>4.23</td></tr> <tr><td>1.98</td><td>4.07</td><td>4.30</td><td>4.15</td></tr> <tr><td>1.65</td><td>4.09</td><td>4.33</td><td>4.12</td></tr> <tr><td>1.32</td><td>4.16</td><td>4.37</td><td>3.98</td></tr> <tr><td>0.99</td><td>4.32</td><td>4.49</td><td>0.00</td></tr> <tr><td>0.66</td><td>4.59</td><td>4.49</td><td>0.00</td></tr> <tr><td>0.33</td><td>4.63</td><td>4.24</td><td>0.00</td></tr> <tr><td>0.00</td><td>3.87</td><td>3.81</td><td>3.34</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	3.30	2.60	2.60	2.60	3.14	3.63	3.88	3.98	2.97	3.75	4.04	4.15	2.64	3.97	4.27	4.31	2.31	4.04	4.31	4.23	1.98	4.07	4.30	4.15	1.65	4.09	4.33	4.12	1.32	4.16	4.37	3.98	0.99	4.32	4.49	0.00	0.66	4.59	4.49	0.00	0.33	4.63	4.24	0.00	0.00	3.87	3.81	3.34
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
3.30	2.60	2.60	2.60																																																							
3.14	3.63	3.88	3.98																																																							
2.97	3.75	4.04	4.15																																																							
2.64	3.97	4.27	4.31																																																							
2.31	4.04	4.31	4.23																																																							
1.98	4.07	4.30	4.15																																																							
1.65	4.09	4.33	4.12																																																							
1.32	4.16	4.37	3.98																																																							
0.99	4.32	4.49	0.00																																																							
0.66	4.59	4.49	0.00																																																							
0.33	4.63	4.24	0.00																																																							
0.00	3.87	3.81	3.34																																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)