

TEST DATA OF SUTS3123R3

Regulated DC Power Supply

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

CONTENTS


1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	9
10.Ripple-Noise · · · · ·	10
11.Ripple Voltage (by Ambient Temperature) · · · · ·	11
12.Ambient Temperature Drift · · · · ·	12
13.Output Voltage Accuracy · · · · ·	13
14.Time Lapse Drift · · · · ·	14
15.Rise and Fall Time · · · · ·	15
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17.Overcurrent Protection · · · · ·	17
18.Figure of Testing Circuitry · · · · ·	18

(Final Page 18)

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																																																																		
Item	Input Current (by Input Voltage)																																																																																			
Object	_____	2.Values																																																																																		
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□- - Load 50% - -○--- Load 0%</p> <p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>2.4</td><td>0.047</td><td>0.457</td><td>0.031</td></tr> <tr><td>2.6</td><td>0.042</td><td>0.467</td><td>0.127</td></tr> <tr><td>4.0</td><td>0.026</td><td>0.385</td><td>0.441</td></tr> <tr><td>5.2</td><td>0.022</td><td>0.268</td><td>0.459</td></tr> <tr><td>6.0</td><td>0.020</td><td>0.226</td><td>0.475</td></tr> <tr><td>8.0</td><td>0.017</td><td>0.168</td><td>0.333</td></tr> <tr><td>9.0</td><td>0.017</td><td>0.149</td><td>0.292</td></tr> <tr><td>10.0</td><td>0.016</td><td>0.134</td><td>0.260</td></tr> <tr><td>12.0</td><td>0.016</td><td>0.113</td><td>0.215</td></tr> <tr><td>14.0</td><td>0.015</td><td>0.099</td><td>0.186</td></tr> <tr><td>16.0</td><td>0.015</td><td>0.088</td><td>0.164</td></tr> <tr><td>18.0</td><td>0.016</td><td>0.080</td><td>0.147</td></tr> <tr><td>20.0</td><td>0.017</td><td>0.074</td><td>0.133</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.009	0.009	0.009	2.4	0.047	0.457	0.031	2.6	0.042	0.467	0.127	4.0	0.026	0.385	0.441	5.2	0.022	0.268	0.459	6.0	0.020	0.226	0.475	8.0	0.017	0.168	0.333	9.0	0.017	0.149	0.292	10.0	0.016	0.134	0.260	12.0	0.016	0.113	0.215	14.0	0.015	0.099	0.186	16.0	0.015	0.088	0.164	18.0	0.016	0.080	0.147	20.0	0.017	0.074	0.133	--	-	-	-	--	-	-	-	--	-	-	-			
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
2.0	0.009	0.009	0.009																																																																																	
2.4	0.047	0.457	0.031																																																																																	
2.6	0.042	0.467	0.127																																																																																	
4.0	0.026	0.385	0.441																																																																																	
5.2	0.022	0.268	0.459																																																																																	
6.0	0.020	0.226	0.475																																																																																	
8.0	0.017	0.168	0.333																																																																																	
9.0	0.017	0.149	0.292																																																																																	
10.0	0.016	0.134	0.260																																																																																	
12.0	0.016	0.113	0.215																																																																																	
14.0	0.015	0.099	0.186																																																																																	
16.0	0.015	0.088	0.164																																																																																	
18.0	0.016	0.080	0.147																																																																																	
20.0	0.017	0.074	0.133																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - ○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.017</td><td>0.016</td><td>0.016</td></tr> <tr><td>0.12</td><td>0.068</td><td>0.054</td><td>0.042</td></tr> <tr><td>0.24</td><td>0.121</td><td>0.093</td><td>0.067</td></tr> <tr><td>0.36</td><td>0.176</td><td>0.133</td><td>0.093</td></tr> <tr><td>0.48</td><td>0.233</td><td>0.174</td><td>0.119</td></tr> <tr><td>0.60</td><td>0.293</td><td>0.216</td><td>0.145</td></tr> <tr><td>0.66</td><td>0.323</td><td>0.238</td><td>0.159</td></tr> </tbody> </table>	Load Current [A]	9V [A]	12V [A]	18V [A]	0.00	0.017	0.016	0.016	0.12	0.068	0.054	0.042	0.24	0.121	0.093	0.067	0.36	0.176	0.133	0.093	0.48	0.233	0.174	0.119	0.60	0.293	0.216	0.145	0.66	0.323	0.238	0.159																				
Load Current [A]	9V [A]	12V [A]	18V [A]																																																		
0.00	0.017	0.016	0.016																																																		
0.12	0.068	0.054	0.042																																																		
0.24	0.121	0.093	0.067																																																		
0.36	0.176	0.133	0.093																																																		
0.48	0.233	0.174	0.119																																																		
0.60	0.293	0.216	0.145																																																		
0.66	0.323	0.238	0.159																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.017</td><td>0.016</td><td>0.016</td></tr> <tr><td>0.12</td><td>0.068</td><td>0.054</td><td>0.042</td></tr> <tr><td>0.24</td><td>0.121</td><td>0.093</td><td>0.067</td></tr> <tr><td>0.36</td><td>0.176</td><td>0.133</td><td>0.093</td></tr> <tr><td>0.48</td><td>0.233</td><td>0.174</td><td>0.119</td></tr> <tr><td>0.60</td><td>0.293</td><td>0.216</td><td>0.145</td></tr> <tr><td>0.66</td><td>0.323</td><td>0.238</td><td>0.159</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	0.017	0.016	0.016	0.12	0.068	0.054	0.042	0.24	0.121	0.093	0.067	0.36	0.176	0.133	0.093	0.48	0.233	0.174	0.119	0.60	0.293	0.216	0.145	0.66	0.323	0.238	0.159	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Input Current [A]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0.00	0.017	0.016	0.016																																																		
0.12	0.068	0.054	0.042																																																		
0.24	0.121	0.093	0.067																																																		
0.36	0.176	0.133	0.093																																																		
0.48	0.233	0.174	0.119																																																		
0.60	0.293	0.216	0.145																																																		
0.66	0.323	0.238	0.159																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

Model	SUTS3123R3																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - ○--- Input Volt. 18V</p>  <p>The graph plots Input Power [W] on the Y-axis (0.0 to 5.0) against Load Current [A] on the X-axis (0.0 to 0.6). Three curves are shown for input voltages of 9V, 12V, and 18V. A slanted line represents the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (9V)</th> <th>Input Power [W] (12V)</th> <th>Input Power [W] (18V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.16</td><td>0.26</td></tr> <tr><td>0.12</td><td>0.60</td><td>0.64</td><td>0.74</td></tr> <tr><td>0.24</td><td>1.08</td><td>1.11</td><td>1.20</td></tr> <tr><td>0.36</td><td>1.58</td><td>1.59</td><td>1.67</td></tr> <tr><td>0.48</td><td>2.09</td><td>2.08</td><td>2.14</td></tr> <tr><td>0.60</td><td>2.61</td><td>2.58</td><td>2.62</td></tr> <tr><td>0.66</td><td>2.88</td><td>2.84</td><td>2.87</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (9V)	Input Power [W] (12V)	Input Power [W] (18V)	0.00	0.13	0.16	0.26	0.12	0.60	0.64	0.74	0.24	1.08	1.11	1.20	0.36	1.58	1.59	1.67	0.48	2.09	2.08	2.14	0.60	2.61	2.58	2.62	0.66	2.88	2.84	2.87	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Power [W] (9V)	Input Power [W] (12V)	Input Power [W] (18V)																																																			
0.00	0.13	0.16	0.26																																																			
0.12	0.60	0.64	0.74																																																			
0.24	1.08	1.11	1.20																																																			
0.36	1.58	1.59	1.67																																																			
0.48	2.09	2.08	2.14																																																			
0.60	2.61	2.58	2.62																																																			
0.66	2.88	2.84	2.87																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.16</td><td>0.26</td></tr> <tr><td>0.12</td><td>0.60</td><td>0.64</td><td>0.74</td></tr> <tr><td>0.24</td><td>1.08</td><td>1.11</td><td>1.20</td></tr> <tr><td>0.36</td><td>1.58</td><td>1.59</td><td>1.67</td></tr> <tr><td>0.48</td><td>2.09</td><td>2.08</td><td>2.14</td></tr> <tr><td>0.60</td><td>2.61</td><td>2.58</td><td>2.62</td></tr> <tr><td>0.66</td><td>2.88</td><td>2.84</td><td>2.87</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	0.13	0.16	0.26	0.12	0.60	0.64	0.74	0.24	1.08	1.11	1.20	0.36	1.58	1.59	1.67	0.48	2.09	2.08	2.14	0.60	2.61	2.58	2.62	0.66	2.88	2.84	2.87	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	0.13	0.16	0.26																																																			
0.12	0.60	0.64	0.74																																																			
0.24	1.08	1.11	1.20																																																			
0.36	1.58	1.59	1.67																																																			
0.48	2.09	2.08	2.14																																																			
0.60	2.61	2.58	2.62																																																			
0.66	2.88	2.84	2.87																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (6 to 22). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line across the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>8</td><td>75.0</td><td>75.4</td></tr> <tr><td>9</td><td>74.8</td><td>76.2</td></tr> <tr><td>10</td><td>74.8</td><td>76.7</td></tr> <tr><td>12</td><td>73.9</td><td>77.1</td></tr> <tr><td>15</td><td>71.9</td><td>76.7</td></tr> <tr><td>18</td><td>69.5</td><td>75.8</td></tr> <tr><td>20</td><td>67.4</td><td>74.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	8	75.0	75.4	9	74.8	76.2	10	74.8	76.7	12	73.9	77.1	15	71.9	76.7	18	69.5	75.8	20	67.4	74.9	--	-	-	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
8	75.0	75.4																													
9	74.8	76.2																													
10	74.8	76.7																													
12	73.9	77.1																													
15	71.9	76.7																													
18	69.5	75.8																													
20	67.4	74.9																													
--	-	-																													
--	-	-																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															


Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Efficiency (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>The graph shows efficiency increasing with load current for all input voltages. The 9V curve is the highest, followed by 12V, and then 18V. A slanted line from the top left to the bottom right indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [9V %]</th> <th>Efficiency [12V %]</th> <th>Efficiency [18V %]</th> </tr> </thead> <tbody> <tr><td>0.12</td><td>65.9</td><td>62.2</td><td>53.3</td></tr> <tr><td>0.24</td><td>73.3</td><td>71.7</td><td>66.0</td></tr> <tr><td>0.36</td><td>75.5</td><td>75.1</td><td>71.3</td></tr> <tr><td>0.48</td><td>76.2</td><td>76.3</td><td>74.2</td></tr> <tr><td>0.60</td><td>76.0</td><td>76.9</td><td>75.7</td></tr> <tr><td>0.66</td><td>75.9</td><td>77.0</td><td>76.3</td></tr> </tbody> </table>	Load Current [A]	Efficiency [9V %]	Efficiency [12V %]	Efficiency [18V %]	0.12	65.9	62.2	53.3	0.24	73.3	71.7	66.0	0.36	75.5	75.1	71.3	0.48	76.2	76.3	74.2	0.60	76.0	76.9	75.7	0.66	75.9	77.0	76.3	2.Values																									
Load Current [A]	Efficiency [9V %]	Efficiency [12V %]	Efficiency [18V %]																																																				
0.12	65.9	62.2	53.3																																																				
0.24	73.3	71.7	66.0																																																				
0.36	75.5	75.1	71.3																																																				
0.48	76.2	76.3	74.2																																																				
0.60	76.0	76.9	75.7																																																				
0.66	75.9	77.0	76.3																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.12</td><td>65.9</td><td>62.2</td><td>53.3</td></tr> <tr><td>0.24</td><td>73.3</td><td>71.7</td><td>66.0</td></tr> <tr><td>0.36</td><td>75.5</td><td>75.1</td><td>71.3</td></tr> <tr><td>0.48</td><td>76.2</td><td>76.3</td><td>74.2</td></tr> <tr><td>0.60</td><td>76.0</td><td>76.9</td><td>75.7</td></tr> <tr><td>0.66</td><td>75.9</td><td>77.0</td><td>76.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-	-	-	0.12	65.9	62.2	53.3	0.24	73.3	71.7	66.0	0.36	75.5	75.1	71.3	0.48	76.2	76.3	74.2	0.60	76.0	76.9	75.7	0.66	75.9	77.0	76.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																				
0.00	-	-	-																																																				
0.12	65.9	62.2	53.3																																																				
0.24	73.3	71.7	66.0																																																				
0.36	75.5	75.1	71.3																																																				
0.48	76.2	76.3	74.2																																																				
0.60	76.0	76.9	75.7																																																				
0.66	75.9	77.0	76.3																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
		<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+3.3V0.6A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>3.309</td> <td>3.307</td> </tr> <tr> <td>9</td> <td>3.309</td> <td>3.307</td> </tr> <tr> <td>10</td> <td>3.309</td> <td>3.307</td> </tr> <tr> <td>12</td> <td>3.309</td> <td>3.308</td> </tr> <tr> <td>15</td> <td>3.309</td> <td>3.308</td> </tr> <tr> <td>18</td> <td>3.309</td> <td>3.308</td> </tr> <tr> <td>20</td> <td>3.309</td> <td>3.308</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8	3.309	3.307	9	3.309	3.307	10	3.309	3.307	12	3.309	3.308	15	3.309	3.308	18	3.309	3.308	20	3.309	3.308	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8	3.309	3.307																																
9	3.309	3.307																																
10	3.309	3.307																																
12	3.309	3.308																																
15	3.309	3.308																																
18	3.309	3.308																																
20	3.309	3.308																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Load Regulation																																																			
Object	+3.3V0.6A																																																			
1.Graph	<p>—△— Input Volt. 9V - - - □ - - Input Volt. 12V - - - ○ - - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V Output [V]</th> <th>12V Output [V]</th> <th>18V Output [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.311</td><td>3.311</td><td>3.311</td></tr> <tr><td>0.12</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>0.24</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>0.36</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>0.48</td><td>3.308</td><td>3.308</td><td>3.308</td></tr> <tr><td>0.60</td><td>3.307</td><td>3.307</td><td>3.307</td></tr> <tr><td>0.66</td><td>3.307</td><td>3.307</td><td>3.307</td></tr> </tbody> </table>	Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]	0.0	3.311	3.311	3.311	0.12	3.310	3.310	3.310	0.24	3.309	3.309	3.309	0.36	3.309	3.309	3.309	0.48	3.308	3.308	3.308	0.60	3.307	3.307	3.307	0.66	3.307	3.307	3.307																			
Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]																																																	
0.0	3.311	3.311	3.311																																																	
0.12	3.310	3.310	3.310																																																	
0.24	3.309	3.309	3.309																																																	
0.36	3.309	3.309	3.309																																																	
0.48	3.308	3.308	3.308																																																	
0.60	3.307	3.307	3.307																																																	
0.66	3.307	3.307	3.307																																																	
2.Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.311</td><td>3.311</td><td>3.311</td></tr> <tr><td>0.12</td><td>3.310</td><td>3.310</td><td>3.310</td></tr> <tr><td>0.24</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>0.36</td><td>3.309</td><td>3.309</td><td>3.309</td></tr> <tr><td>0.48</td><td>3.308</td><td>3.308</td><td>3.308</td></tr> <tr><td>0.60</td><td>3.307</td><td>3.307</td><td>3.307</td></tr> <tr><td>0.66</td><td>3.307</td><td>3.307</td><td>3.307</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	3.311	3.311	3.311	0.12	3.310	3.310	3.310	0.24	3.309	3.309	3.309	0.36	3.309	3.309	3.309	0.48	3.308	3.308	3.308	0.60	3.307	3.307	3.307	0.66	3.307	3.307	3.307	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																			
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																	
0.00	3.311	3.311	3.311																																																	
0.12	3.310	3.310	3.310																																																	
0.24	3.309	3.309	3.309																																																	
0.36	3.309	3.309	3.309																																																	
0.48	3.308	3.308	3.308																																																	
0.60	3.307	3.307	3.307																																																	
0.66	3.307	3.307	3.307																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.


COSEL



Model	SUTS3123R3
Item	Ripple Voltage (by Load Current)
Object	+3.3V0.6A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	3	3
0.12	3	3
0.24	6	6
0.36	8	6
0.48	11	7
0.60	16	8
0.66	19	9
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS3123R3
Item	Ripple-Noise
Object	+3.3V0.6A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	7	6
0.12	10	8
0.24	14	10
0.36	18	13
0.48	22	17
0.60	29	20
0.66	33	21
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS3123R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V0.6A

1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	11	19
-40	11	19
-20	10	19
0	8	17
25	7	15
55	6	11
60	6	11
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS3123R3
Item	Ambient Temperature Drift
Object	+3.3V0.6A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	3.265	3.266	3.267
-40	3.278	3.279	3.279
-20	3.288	3.289	3.289
0	3.298	3.298	3.298
25	3.307	3.307	3.307
55	3.312	3.312	3.312
60	3.313	3.313	3.313
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS3123R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V0.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current : 0 - 0.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	9	0	3.317	±20	±0.6
Minimum Voltage	-40	9	0.6	3.278		

COSEL

Model	SUTS3123R3
Item	Time Lapse Drift
Object	+3.3V0.6A

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values


Time since start [H]	Output Voltage [V]
0.0	3.288
0.5	3.291
1.0	3.291
2.0	3.291
3.0	3.291
4.0	3.291
5.0	3.291
6.0	3.291
7.0	3.291
8.0	3.291

COSEL

Model	SUTS3123R3
Item	Rise and Fall Time
Object	+3.3V0.6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	1.0	1.1	0.1	1.3
100 %		0.1	1.0	1.1	0.1	0.7



Model	SUTS3123R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V0.6A

Testing Circuitry Figure A


1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.0	5.2
-40	3.0	5.3
-20	3.1	5.4
0	3.2	5.7
25	3.4	5.9
55	3.7	6.2
60	3.7	6.2
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS3123R3	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+3.3V0.6A																																																								
1.Graph	<p>— Input Volt. 9V — Input Volt. 12V — Input Volt. 18V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>0.60</td><td>0.60</td><td>0.60</td></tr> <tr><td>3.14</td><td>0.90</td><td>0.98</td><td>0.91</td></tr> <tr><td>2.97</td><td>0.91</td><td>0.99</td><td>0.92</td></tr> <tr><td>2.64</td><td>0.95</td><td>1.02</td><td>0.94</td></tr> <tr><td>2.31</td><td>0.98</td><td>1.05</td><td>0.96</td></tr> <tr><td>1.98</td><td>1.02</td><td>1.07</td><td>0.97</td></tr> <tr><td>1.65</td><td>1.05</td><td>1.09</td><td>0.98</td></tr> <tr><td>1.32</td><td>1.08</td><td>1.10</td><td>0.98</td></tr> <tr><td>0.99</td><td>1.08</td><td>1.09</td><td>0.96</td></tr> <tr><td>0.66</td><td>1.06</td><td>1.05</td><td>0.92</td></tr> <tr><td>0.33</td><td>1.00</td><td>0.99</td><td>0.87</td></tr> <tr><td>0.00</td><td>1.11</td><td>1.05</td><td>0.89</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	3.30	0.60	0.60	0.60	3.14	0.90	0.98	0.91	2.97	0.91	0.99	0.92	2.64	0.95	1.02	0.94	2.31	0.98	1.05	0.96	1.98	1.02	1.07	0.97	1.65	1.05	1.09	0.98	1.32	1.08	1.10	0.98	0.99	1.08	1.09	0.96	0.66	1.06	1.05	0.92	0.33	1.00	0.99	0.87	0.00	1.11	1.05	0.89
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
3.30	0.60	0.60	0.60																																																						
3.14	0.90	0.98	0.91																																																						
2.97	0.91	0.99	0.92																																																						
2.64	0.95	1.02	0.94																																																						
2.31	0.98	1.05	0.96																																																						
1.98	1.02	1.07	0.97																																																						
1.65	1.05	1.09	0.98																																																						
1.32	1.08	1.10	0.98																																																						
0.99	1.08	1.09	0.96																																																						
0.66	1.06	1.05	0.92																																																						
0.33	1.00	0.99	0.87																																																						
0.00	1.11	1.05	0.89																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)