

# TEST DATA OF SUTW102412

Regulated DC Power Supply  
February 24, 2009

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Sho Saito  
Sho Saito Design Engineer

**COSEL CO.,LTD.**


## CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW102412	Temperature Testing Circuitry      25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100%        - - -□- - Load 50%        - -○--- Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>12.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>16.0</td><td>0.028</td><td>0.404</td><td>0.002</td></tr> <tr><td>16.4</td><td>0.028</td><td>0.395</td><td>0.806</td></tr> <tr><td>18.0</td><td>0.026</td><td>0.361</td><td>0.730</td></tr> <tr><td>20.0</td><td>0.025</td><td>0.325</td><td>0.652</td></tr> <tr><td>24.0</td><td>0.024</td><td>0.273</td><td>0.543</td></tr> <tr><td>28.0</td><td>0.024</td><td>0.235</td><td>0.463</td></tr> <tr><td>32.0</td><td>0.022</td><td>0.205</td><td>0.407</td></tr> <tr><td>36.0</td><td>0.022</td><td>0.185</td><td>0.363</td></tr> <tr><td>40.0</td><td>0.021</td><td>0.170</td><td>0.328</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.001	0.001	0.001	12.0	0.001	0.001	0.001	16.0	0.028	0.404	0.002	16.4	0.028	0.395	0.806	18.0	0.026	0.361	0.730	20.0	0.025	0.325	0.652	24.0	0.024	0.273	0.543	28.0	0.024	0.235	0.463	32.0	0.022	0.205	0.407	36.0	0.022	0.185	0.363	40.0	0.021	0.170	0.328	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
8.0	0.001	0.001	0.001																																																																																
12.0	0.001	0.001	0.001																																																																																
16.0	0.028	0.404	0.002																																																																																
16.4	0.028	0.395	0.806																																																																																
18.0	0.026	0.361	0.730																																																																																
20.0	0.025	0.325	0.652																																																																																
24.0	0.024	0.273	0.543																																																																																
28.0	0.024	0.235	0.463																																																																																
32.0	0.022	0.205	0.407																																																																																
36.0	0.022	0.185	0.363																																																																																
40.0	0.021	0.170	0.328																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW102412
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Ration [%]	Input Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	0.026	0.024	0.022
20	0.160	0.121	0.090
40	0.294	0.221	0.156
60	0.431	0.325	0.221
80	0.571	0.428	0.289
100	0.723	0.534	0.357
110	0.795	0.588	0.392
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model	SUTW102412	Temperature Testing Circuitry 25°C Figure A																																														
Item	Input Power (by Load Current)																																															
Object	_____																																															
1.Graph		2.Values																																														
<p>—△— Input Volt. 18V        - - -□--- Input Volt. 24V        - - ○--- Input Volt. 36V</p> <p>The graph plots Input Power [W] on the Y-axis (0.0 to 20.0) against Load Ration [%] on the X-axis (0 to 120). Three data series are shown for input voltages of 18V, 24V, and 36V. The curves are nearly identical, showing a linear increase from (0,0) to approximately (110, 14W).</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V] [W]</th> <th>24[V] [W]</th> <th>36[V] [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.47</td><td>0.59</td><td>0.79</td></tr> <tr><td>20</td><td>2.87</td><td>2.91</td><td>3.23</td></tr> <tr><td>40</td><td>5.27</td><td>5.29</td><td>5.61</td></tr> <tr><td>60</td><td>7.74</td><td>7.79</td><td>7.95</td></tr> <tr><td>80</td><td>10.27</td><td>10.25</td><td>10.40</td></tr> <tr><td>100</td><td>12.91</td><td>12.78</td><td>12.84</td></tr> <tr><td>110</td><td>14.27</td><td>14.07</td><td>14.10</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	18[V] [W]	24[V] [W]	36[V] [W]	0	0.47	0.59	0.79	20	2.87	2.91	3.23	40	5.27	5.29	5.61	60	7.74	7.79	7.95	80	10.27	10.25	10.40	100	12.91	12.78	12.84	110	14.27	14.07	14.10	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	18[V] [W]	24[V] [W]	36[V] [W]																																													
0	0.47	0.59	0.79																																													
20	2.87	2.91	3.23																																													
40	5.27	5.29	5.61																																													
60	7.74	7.79	7.95																																													
80	10.27	10.25	10.40																																													
100	12.91	12.78	12.84																																													
110	14.27	14.07	14.10																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													


Model	SUTW102412	Temperature Testing Circuitry 25°C Figure A																							
Item	Efficiency (by Input Voltage)																								
Object	—																								
1. Graph		2. Values																							
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (10 to 50). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency decreasing slightly as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>84.7</td><td>84.1</td></tr> <tr><td>18</td><td>84.6</td><td>84.9</td></tr> <tr><td>20</td><td>84.3</td><td>85.3</td></tr> <tr><td>24</td><td>83.6</td><td>85.8</td></tr> <tr><td>30</td><td>83.2</td><td>85.9</td></tr> <tr><td>36</td><td>82.5</td><td>85.4</td></tr> <tr><td>40</td><td>80.7</td><td>85.0</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	84.7	84.1	18	84.6	84.9	20	84.3	85.3	24	83.6	85.8	30	83.2	85.9	36	82.5	85.4	40	80.7	85.0
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																							
16	84.7	84.1																							
18	84.6	84.9																							
20	84.3	85.3																							
24	83.6	85.8																							
30	83.2	85.9																							
36	82.5	85.4																							
40	80.7	85.0																							
<p>Note: Slanted line shows the range of the rated input voltage.</p>																									

Model	SUTW102412	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 18V        - - - □ - - Input Volt. 24V        - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [Efficiency %]</th> <th>24V [Efficiency %]</th> <th>36V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>76.3</td><td>75.3</td><td>67.9</td></tr> <tr><td>40</td><td>83.4</td><td>83.1</td><td>78.2</td></tr> <tr><td>60</td><td>85.2</td><td>84.6</td><td>82.9</td></tr> <tr><td>80</td><td>85.4</td><td>85.6</td><td>84.4</td></tr> <tr><td>100</td><td>85.0</td><td>85.9</td><td>85.5</td></tr> <tr><td>110</td><td>84.6</td><td>85.8</td><td>85.6</td></tr> </tbody> </table>		Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]	20	76.3	75.3	67.9	40	83.4	83.1	78.2	60	85.2	84.6	82.9	80	85.4	85.6	84.4	100	85.0	85.9	85.5	110	84.6	85.8	85.6																									
Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]																																																			
20	76.3	75.3	67.9																																																			
40	83.4	83.1	78.2																																																			
60	85.2	84.6	82.9																																																			
80	85.4	85.6	84.4																																																			
100	85.0	85.9	85.5																																																			
110	84.6	85.8	85.6																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>76.3</td><td>75.3</td><td>67.9</td></tr> <tr><td>40</td><td>83.4</td><td>83.1</td><td>78.2</td></tr> <tr><td>60</td><td>85.2</td><td>84.6</td><td>82.9</td></tr> <tr><td>80</td><td>85.4</td><td>85.6</td><td>84.4</td></tr> <tr><td>100</td><td>85.0</td><td>85.9</td><td>85.5</td></tr> <tr><td>110</td><td>84.6</td><td>85.8</td><td>85.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	76.3	75.3	67.9	40	83.4	83.1	78.2	60	85.2	84.6	82.9	80	85.4	85.6	84.4	100	85.0	85.9	85.5	110	84.6	85.8	85.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	-	-	-																																																			
20	76.3	75.3	67.9																																																			
40	83.4	83.1	78.2																																																			
60	85.2	84.6	82.9																																																			
80	85.4	85.6	84.4																																																			
100	85.0	85.9	85.5																																																			
110	84.6	85.8	85.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW102412
Item	Line Regulation
Object	+12V0.45A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	12.275	12.195
18	12.272	12.195
20	12.269	12.196
24	12.264	12.196
30	12.261	12.197
36	12.259	12.197
40	12.258	12.197
--	-	-
--	-	-

## Object -12V0.45A

## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-12.279	-12.197
18	-12.275	-12.197
20	-12.272	-12.198
24	-12.267	-12.197
30	-12.263	-12.197
36	-12.261	-12.198
40	-12.260	-12.198
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	SUTW102412	Temperature Testing Circuitry 25°C Figure A
Item	Load Regulation	
Object	+12V0.45A	

1.Graph

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	12.637	12.625	12.614
0.090	12.328	12.321	12.320
0.180	12.289	12.282	12.277
0.270	12.256	12.251	12.247
0.360	12.225	12.223	12.221
0.450	12.195	12.196	12.196
0.495	12.180	12.182	12.185
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Object


1.Graph

2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	-12.642	-12.622	-12.617
0.090	-12.331	-12.323	-12.321
0.180	-12.292	-12.283	-12.277
0.270	-12.259	-12.253	-12.247
0.360	-12.227	-12.224	-12.221
0.450	-12.197	-12.197	-12.197
0.495	-12.182	-12.183	-12.185
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**




**COSEL**



Model	SUTW102412
Item	Ripple Voltage (by Load Current)
Object	+12V0.45A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	6	7
0.090	6	7
0.180	6	7
0.270	8	9
0.360	9	9
0.450	10	9
0.495	10	10
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW102412
Item	Ripple Voltage (by Load Current)
Object	-12V0.45A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	8	9
0.090	10	9
0.180	11	9
0.270	11	10
0.360	12	10
0.450	14	11
0.495	16	12
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW102412
Item	Ripple-Noise
Object	+12V0.45A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	6	7
0.090	6	7
0.180	8	7
0.270	9	9
0.360	10	10
0.450	13	10
0.495	13	11
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW102412
Item	Ripple-Noise
Object	-12V0.45A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	10	9
0.090	10	9
0.180	11	11
0.270	12	13
0.360	13	14
0.450	16	15
0.495	18	16
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW102412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.45A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	6	9
-40	6	9
-20	6	9
0	6	9
25	6	9
55	4	4
60	4	4
--	-	-
--	-	-
--	-	-
--	-	-

## 1.Graph



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	10
-40	9	10
-20	9	10
0	7	10
25	5	10
55	5	7
60	5	6
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW102412
Item	Ambient Temperature Drift
Object	+12V0.45A

Testing Circuitry Figure A



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	12.123	12.124	12.126
-40	12.146	12.148	12.149
-20	12.166	12.166	12.167
0	12.180	12.181	12.182
25	12.194	12.194	12.195
55	12.204	12.204	12.205
60	12.204	12.205	12.206
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-12.122	-12.123	-12.125
-40	-12.146	-12.147	-12.148
-20	-12.164	-12.166	-12.166
0	-12.179	-12.180	-12.181
25	-12.193	-12.194	-12.194
55	-12.204	-12.204	-12.204
60	-12.205	-12.205	-12.205
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW102412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.45A (AVR 2) : 0 - 0.45A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object		+12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	12.649	±462	±3.9	
Minimum Voltage	-40	18	0.45	11.726			

Object		-12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	-12.653	±463	±3.9	
Minimum Voltage	-40	18	0.45	-11.727			

**COSEL**


Model	SUTW102412	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+12V0.45A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.185</td></tr> <tr><td>0.5</td><td>12.194</td></tr> <tr><td>1.0</td><td>12.194</td></tr> <tr><td>2.0</td><td>12.194</td></tr> <tr><td>3.0</td><td>12.194</td></tr> <tr><td>4.0</td><td>12.194</td></tr> <tr><td>5.0</td><td>12.194</td></tr> <tr><td>6.0</td><td>12.194</td></tr> <tr><td>7.0</td><td>12.194</td></tr> <tr><td>8.0</td><td>12.194</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.185	0.5	12.194	1.0	12.194	2.0	12.194	3.0	12.194	4.0	12.194	5.0	12.194	6.0	12.194	7.0	12.194	8.0	12.194
Time since start [H]	Output Voltage [V]																								
0.0	12.185																								
0.5	12.194																								
1.0	12.194																								
2.0	12.194																								
3.0	12.194																								
4.0	12.194																								
5.0	12.194																								
6.0	12.194																								
7.0	12.194																								
8.0	12.194																								
Object			2.Values																						
1.Graph			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.193</td></tr> <tr><td>0.5</td><td>-12.204</td></tr> <tr><td>1.0</td><td>-12.204</td></tr> <tr><td>2.0</td><td>-12.204</td></tr> <tr><td>3.0</td><td>-12.204</td></tr> <tr><td>4.0</td><td>-12.204</td></tr> <tr><td>5.0</td><td>-12.204</td></tr> <tr><td>6.0</td><td>-12.204</td></tr> <tr><td>7.0</td><td>-12.204</td></tr> <tr><td>8.0</td><td>-12.204</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.193	0.5	-12.204	1.0	-12.204	2.0	-12.204	3.0	-12.204	4.0	-12.204	5.0	-12.204	6.0	-12.204	7.0	-12.204	8.0	-12.204
Time since start [H]	Output Voltage [V]																								
0.0	-12.193																								
0.5	-12.204																								
1.0	-12.204																								
2.0	-12.204																								
3.0	-12.204																								
4.0	-12.204																								
5.0	-12.204																								
6.0	-12.204																								
7.0	-12.204																								
8.0	-12.204																								
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>																									

**COSEL**

Model	SUTW102412
Item	Rise and Fall Time
Object	+12V0.45A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		8.8	2.3	11.1	0.1	3.3	
100 %		8.8	2.3	11.1	0.1	1.7	




**COSEL**

Model	SUTW102412
Item	Rise and Fall Time
Object	-12V0.45A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		8.8	2.4	11.2	0.1	3.5	
100 %		8.8	2.4	11.2	0.1	1.7	





<p>Model      SUTW102412</p> <p>Item      Minimum Input Voltage for Regulated Output Voltage</p> <p>Object    +12V0.45A</p>	Testing Circuitry   Figure A																																							
	2.Values																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.9</td><td>13.1</td></tr> <tr><td>-40</td><td>12.9</td><td>12.8</td></tr> <tr><td>-20</td><td>12.7</td><td>12.6</td></tr> <tr><td>0</td><td>12.5</td><td>12.4</td></tr> <tr><td>25</td><td>12.3</td><td>12.4</td></tr> <tr><td>55</td><td>12.1</td><td>12.2</td></tr> <tr><td>60</td><td>12.1</td><td>12.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	12.9	13.1	-40	12.9	12.8	-20	12.7	12.6	0	12.5	12.4	25	12.3	12.4	55	12.1	12.2	60	12.1	12.2	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	12.9	13.1																																						
-40	12.9	12.8																																						
-20	12.7	12.6																																						
0	12.5	12.4																																						
25	12.3	12.4																																						
55	12.1	12.2																																						
60	12.1	12.2																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
1.Graph	<p>---□--- Load 50%</p> <p>—△— Load 100%</p>																																							
Object    -12V0.45A	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.8</td><td>13.0</td></tr> <tr><td>-40</td><td>12.8</td><td>12.8</td></tr> <tr><td>-20</td><td>12.6</td><td>12.5</td></tr> <tr><td>0</td><td>12.4</td><td>12.5</td></tr> <tr><td>25</td><td>12.2</td><td>12.3</td></tr> <tr><td>55</td><td>12.0</td><td>12.1</td></tr> <tr><td>60</td><td>12.0</td><td>12.1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	12.8	13.0	-40	12.8	12.8	-20	12.6	12.5	0	12.4	12.5	25	12.2	12.3	55	12.0	12.1	60	12.0	12.1	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	12.8	13.0																																						
-40	12.8	12.8																																						
-20	12.6	12.5																																						
0	12.4	12.5																																						
25	12.2	12.3																																						
55	12.0	12.1																																						
60	12.0	12.1																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
1.Graph	<p>---□--- Load 50%</p> <p>—△— Load 100%</p>																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								

Model	SUTW102412			Temperature Testing Circuitry      25°C Figure A																																																						
Item	Overcurrent Protection																																																									
Object	+12V0.45A																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.46</td><td>0.46</td><td>0.46</td></tr> <tr><td>11.4</td><td>0.72</td><td>0.82</td><td>0.87</td></tr> <tr><td>10.8</td><td>0.78</td><td>0.88</td><td>0.93</td></tr> <tr><td>9.6</td><td>0.91</td><td>1.02</td><td>1.09</td></tr> <tr><td>8.4</td><td>1.04</td><td>1.15</td><td>1.21</td></tr> <tr><td>7.2</td><td>1.13</td><td>1.22</td><td>1.26</td></tr> <tr><td>6.0</td><td>1.21</td><td>1.29</td><td>1.29</td></tr> <tr><td>4.8</td><td>1.29</td><td>1.35</td><td>1.31</td></tr> <tr><td>3.6</td><td>1.40</td><td>1.42</td><td>1.29</td></tr> <tr><td>2.4</td><td>1.51</td><td>1.45</td><td>1.25</td></tr> <tr><td>1.2</td><td>1.61</td><td>1.50</td><td>1.22</td></tr> <tr><td>0.0</td><td>1.63</td><td>1.49</td><td>1.70</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.0	0.46	0.46	0.46	11.4	0.72	0.82	0.87	10.8	0.78	0.88	0.93	9.6	0.91	1.02	1.09	8.4	1.04	1.15	1.21	7.2	1.13	1.22	1.26	6.0	1.21	1.29	1.29	4.8	1.29	1.35	1.31	3.6	1.40	1.42	1.29	2.4	1.51	1.45	1.25	1.2	1.61	1.50	1.22	0.0	1.63	1.49	1.70
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
12.0	0.46	0.46	0.46																																																							
11.4	0.72	0.82	0.87																																																							
10.8	0.78	0.88	0.93																																																							
9.6	0.91	1.02	1.09																																																							
8.4	1.04	1.15	1.21																																																							
7.2	1.13	1.22	1.26																																																							
6.0	1.21	1.29	1.29																																																							
4.8	1.29	1.35	1.31																																																							
3.6	1.40	1.42	1.29																																																							
2.4	1.51	1.45	1.25																																																							
1.2	1.61	1.50	1.22																																																							
0.0	1.63	1.49	1.70																																																							
Object	-12V0.45A																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.46</td><td>0.46</td><td>0.46</td></tr> <tr><td>-11.4</td><td>0.71</td><td>0.82</td><td>0.87</td></tr> <tr><td>-10.8</td><td>0.77</td><td>0.88</td><td>0.93</td></tr> <tr><td>-9.6</td><td>0.90</td><td>1.02</td><td>1.09</td></tr> <tr><td>-8.4</td><td>1.04</td><td>1.15</td><td>1.21</td></tr> <tr><td>-7.2</td><td>1.13</td><td>1.22</td><td>1.26</td></tr> <tr><td>-6.0</td><td>1.20</td><td>1.29</td><td>1.29</td></tr> <tr><td>-4.8</td><td>1.29</td><td>1.35</td><td>1.31</td></tr> <tr><td>-3.6</td><td>1.39</td><td>1.42</td><td>1.28</td></tr> <tr><td>-2.4</td><td>1.51</td><td>1.46</td><td>1.25</td></tr> <tr><td>-1.2</td><td>1.61</td><td>1.50</td><td>1.22</td></tr> <tr><td>0.0</td><td>1.63</td><td>1.49</td><td>1.69</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-12.0	0.46	0.46	0.46	-11.4	0.71	0.82	0.87	-10.8	0.77	0.88	0.93	-9.6	0.90	1.02	1.09	-8.4	1.04	1.15	1.21	-7.2	1.13	1.22	1.26	-6.0	1.20	1.29	1.29	-4.8	1.29	1.35	1.31	-3.6	1.39	1.42	1.28	-2.4	1.51	1.46	1.25	-1.2	1.61	1.50	1.22	0.0	1.63	1.49	1.69
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
-12.0	0.46	0.46	0.46																																																							
-11.4	0.71	0.82	0.87																																																							
-10.8	0.77	0.88	0.93																																																							
-9.6	0.90	1.02	1.09																																																							
-8.4	1.04	1.15	1.21																																																							
-7.2	1.13	1.22	1.26																																																							
-6.0	1.20	1.29	1.29																																																							
-4.8	1.29	1.35	1.31																																																							
-3.6	1.39	1.42	1.28																																																							
-2.4	1.51	1.46	1.25																																																							
-1.2	1.61	1.50	1.22																																																							
0.0	1.63	1.49	1.69																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)