

# TEST DATA OF SUTW102415

Regulated DC Power Supply  
February 24, 2009

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Sho Saito  
Sho Saito Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW102415	Temperature Testing Circuitry      25°C Figure A																																														
Item	Input Current (by Input Voltage)																																															
Object	_____	2.Values																																														
1.Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Load 100%  <span style="color: black;">□</span> Load 50%  <span style="color: black;">○</span> Load 0%     </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>14.8</td><td>0.031</td><td>0.413</td><td>0.849</td></tr> <tr><td>15.2</td><td>0.033</td><td>0.404</td><td>0.825</td></tr> <tr><td>16.0</td><td>0.033</td><td>0.384</td><td>0.778</td></tr> <tr><td>18.0</td><td>0.031</td><td>0.349</td><td>0.686</td></tr> <tr><td>20.0</td><td>0.029</td><td>0.310</td><td>0.614</td></tr> <tr><td>24.0</td><td>0.026</td><td>0.261</td><td>0.509</td></tr> <tr><td>28.0</td><td>0.024</td><td>0.225</td><td>0.437</td></tr> <tr><td>32.0</td><td>0.024</td><td>0.196</td><td>0.384</td></tr> <tr><td>36.0</td><td>0.024</td><td>0.176</td><td>0.343</td></tr> <tr><td>40.0</td><td>0.024</td><td>0.162</td><td>0.311</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	14.8	0.031	0.413	0.849	15.2	0.033	0.404	0.825	16.0	0.033	0.384	0.778	18.0	0.031	0.349	0.686	20.0	0.029	0.310	0.614	24.0	0.026	0.261	0.509	28.0	0.024	0.225	0.437	32.0	0.024	0.196	0.384	36.0	0.024	0.176	0.343	40.0	0.024	0.162	0.311			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																													
14.8	0.031	0.413	0.849																																													
15.2	0.033	0.404	0.825																																													
16.0	0.033	0.384	0.778																																													
18.0	0.031	0.349	0.686																																													
20.0	0.029	0.310	0.614																																													
24.0	0.026	0.261	0.509																																													
28.0	0.024	0.225	0.437																																													
32.0	0.024	0.196	0.384																																													
36.0	0.024	0.176	0.343																																													
40.0	0.024	0.162	0.311																																													
1. Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Load 100%  <span style="color: black;">□</span> Load 50%  <span style="color: black;">○</span> Load 0%     </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>14.8</td><td>0.031</td><td>0.413</td><td>0.849</td></tr> <tr><td>15.2</td><td>0.033</td><td>0.404</td><td>0.825</td></tr> <tr><td>16.0</td><td>0.033</td><td>0.384</td><td>0.778</td></tr> <tr><td>18.0</td><td>0.031</td><td>0.349</td><td>0.686</td></tr> <tr><td>20.0</td><td>0.029</td><td>0.310</td><td>0.614</td></tr> <tr><td>24.0</td><td>0.026</td><td>0.261</td><td>0.509</td></tr> <tr><td>28.0</td><td>0.024</td><td>0.225</td><td>0.437</td></tr> <tr><td>32.0</td><td>0.024</td><td>0.196</td><td>0.384</td></tr> <tr><td>36.0</td><td>0.024</td><td>0.176</td><td>0.343</td></tr> <tr><td>40.0</td><td>0.024</td><td>0.162</td><td>0.311</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	14.8	0.031	0.413	0.849	15.2	0.033	0.404	0.825	16.0	0.033	0.384	0.778	18.0	0.031	0.349	0.686	20.0	0.029	0.310	0.614	24.0	0.026	0.261	0.509	28.0	0.024	0.225	0.437	32.0	0.024	0.196	0.384	36.0	0.024	0.176	0.343	40.0	0.024	0.162	0.311	2.Values		
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																													
14.8	0.031	0.413	0.849																																													
15.2	0.033	0.404	0.825																																													
16.0	0.033	0.384	0.778																																													
18.0	0.031	0.349	0.686																																													
20.0	0.029	0.310	0.614																																													
24.0	0.026	0.261	0.509																																													
28.0	0.024	0.225	0.437																																													
32.0	0.024	0.196	0.384																																													
36.0	0.024	0.176	0.343																																													
40.0	0.024	0.162	0.311																																													
Note:	Slanted line shows the range of the rated input voltage.																																															

Model	SUTW102415																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 18V        - - -□--- Input Volt. 24V        - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (18V)</th> <th>Input Current [A] (24V)</th> <th>Input Current [A] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.031</td><td>0.027</td><td>0.024</td></tr> <tr><td>20</td><td>0.155</td><td>0.117</td><td>0.088</td></tr> <tr><td>40</td><td>0.282</td><td>0.212</td><td>0.150</td></tr> <tr><td>60</td><td>0.411</td><td>0.310</td><td>0.212</td></tr> <tr><td>80</td><td>0.545</td><td>0.407</td><td>0.276</td></tr> <tr><td>100</td><td>0.679</td><td>0.506</td><td>0.340</td></tr> <tr><td>110</td><td>0.755</td><td>0.557</td><td>0.373</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)	0	0.031	0.027	0.024	20	0.155	0.117	0.088	40	0.282	0.212	0.150	60	0.411	0.310	0.212	80	0.545	0.407	0.276	100	0.679	0.506	0.340	110	0.755	0.557	0.373																			
Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)																																																			
0	0.031	0.027	0.024																																																			
20	0.155	0.117	0.088																																																			
40	0.282	0.212	0.150																																																			
60	0.411	0.310	0.212																																																			
80	0.545	0.407	0.276																																																			
100	0.679	0.506	0.340																																																			
110	0.755	0.557	0.373																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.031</td><td>0.027</td><td>0.024</td></tr> <tr><td>20</td><td>0.155</td><td>0.117</td><td>0.088</td></tr> <tr><td>40</td><td>0.282</td><td>0.212</td><td>0.150</td></tr> <tr><td>60</td><td>0.411</td><td>0.310</td><td>0.212</td></tr> <tr><td>80</td><td>0.545</td><td>0.407</td><td>0.276</td></tr> <tr><td>100</td><td>0.679</td><td>0.506</td><td>0.340</td></tr> <tr><td>110</td><td>0.755</td><td>0.557</td><td>0.373</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.031	0.027	0.024	20	0.155	0.117	0.088	40	0.282	0.212	0.150	60	0.411	0.310	0.212	80	0.545	0.407	0.276	100	0.679	0.506	0.340	110	0.755	0.557	0.373	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	0.031	0.027	0.024																																																			
20	0.155	0.117	0.088																																																			
40	0.282	0.212	0.150																																																			
60	0.411	0.310	0.212																																																			
80	0.545	0.407	0.276																																																			
100	0.679	0.506	0.340																																																			
110	0.755	0.557	0.373																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW102415																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—△— Input Volt. 18V        - - -□--- Input Volt. 24V        - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (18V)</th> <th>Input Power [W] (24V)</th> <th>Input Power [W] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.56</td><td>0.64</td><td>0.87</td></tr> <tr><td>20</td><td>2.79</td><td>2.81</td><td>3.16</td></tr> <tr><td>40</td><td>5.05</td><td>5.07</td><td>5.40</td></tr> <tr><td>60</td><td>7.36</td><td>7.43</td><td>7.62</td></tr> <tr><td>80</td><td>9.75</td><td>9.75</td><td>9.93</td></tr> <tr><td>100</td><td>12.22</td><td>12.11</td><td>12.22</td></tr> <tr><td>110</td><td>13.48</td><td>13.32</td><td>13.39</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)	0	0.56	0.64	0.87	20	2.79	2.81	3.16	40	5.05	5.07	5.40	60	7.36	7.43	7.62	80	9.75	9.75	9.93	100	12.22	12.11	12.22	110	13.48	13.32	13.39																			
Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)																																																			
0	0.56	0.64	0.87																																																			
20	2.79	2.81	3.16																																																			
40	5.05	5.07	5.40																																																			
60	7.36	7.43	7.62																																																			
80	9.75	9.75	9.93																																																			
100	12.22	12.11	12.22																																																			
110	13.48	13.32	13.39																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.56</td><td>0.64</td><td>0.87</td></tr> <tr><td>20</td><td>2.79</td><td>2.81</td><td>3.16</td></tr> <tr><td>40</td><td>5.05</td><td>5.07</td><td>5.40</td></tr> <tr><td>60</td><td>7.36</td><td>7.43</td><td>7.62</td></tr> <tr><td>80</td><td>9.75</td><td>9.75</td><td>9.93</td></tr> <tr><td>100</td><td>12.22</td><td>12.11</td><td>12.22</td></tr> <tr><td>110</td><td>13.48</td><td>13.32</td><td>13.39</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.56	0.64	0.87	20	2.79	2.81	3.16	40	5.05	5.07	5.40	60	7.36	7.43	7.62	80	9.75	9.75	9.93	100	12.22	12.11	12.22	110	13.48	13.32	13.39	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	0.56	0.64	0.87																																																			
20	2.79	2.81	3.16																																																			
40	5.05	5.07	5.40																																																			
60	7.36	7.43	7.62																																																			
80	9.75	9.75	9.93																																																			
100	12.22	12.11	12.22																																																			
110	13.48	13.32	13.39																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	SUTW102415	Temperature Testing Circuitry 25°C Figure A																							
Item	Efficiency (by Input Voltage)																								
Object	—																								
1. Graph		2. Values																							
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (10 to 50). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency decreasing slightly as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>84.4</td><td>84.7</td></tr> <tr><td>18</td><td>84.2</td><td>85.4</td></tr> <tr><td>20</td><td>83.8</td><td>85.8</td></tr> <tr><td>24</td><td>83.0</td><td>86.1</td></tr> <tr><td>30</td><td>82.5</td><td>85.9</td></tr> <tr><td>36</td><td>82.0</td><td>85.3</td></tr> <tr><td>40</td><td>80.1</td><td>84.8</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	84.4	84.7	18	84.2	85.4	20	83.8	85.8	24	83.0	86.1	30	82.5	85.9	36	82.0	85.3	40	80.1	84.8
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																							
16	84.4	84.7																							
18	84.2	85.4																							
20	83.8	85.8																							
24	83.0	86.1																							
30	82.5	85.9																							
36	82.0	85.3																							
40	80.1	84.8																							
<p>Note: Slanted line shows the range of the rated input voltage.</p>																									

Model	SUTW102415	Temperature Testing Circuitry 25°C Figure A																																										
Item	Efficiency (by Load Current)																																											
Object	_____																																											
1.Graph		2.Values																																										
<p>—△— Input Volt. 18V        - - -□- - Input Volt. 24V        - - ○- - Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 18[V] (%)</th> <th>Input Volt. 24[V] (%)</th> <th>Input Volt. 36[V] (%)</th> </tr> </thead> <tbody> <tr><td>20</td><td>74.8</td><td>74.4</td><td>66.0</td></tr> <tr><td>40</td><td>82.7</td><td>82.2</td><td>77.3</td></tr> <tr><td>60</td><td>85.0</td><td>84.2</td><td>82.2</td></tr> <tr><td>80</td><td>85.6</td><td>85.6</td><td>84.0</td></tr> <tr><td>100</td><td>85.4</td><td>86.1</td><td>85.3</td></tr> <tr><td>110</td><td>85.1</td><td>86.1</td><td>85.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 18[V] (%)	Input Volt. 24[V] (%)	Input Volt. 36[V] (%)	20	74.8	74.4	66.0	40	82.7	82.2	77.3	60	85.0	84.2	82.2	80	85.6	85.6	84.0	100	85.4	86.1	85.3	110	85.1	86.1	85.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Volt. 18[V] (%)	Input Volt. 24[V] (%)	Input Volt. 36[V] (%)																																									
20	74.8	74.4	66.0																																									
40	82.7	82.2	77.3																																									
60	85.0	84.2	82.2																																									
80	85.6	85.6	84.0																																									
100	85.4	86.1	85.3																																									
110	85.1	86.1	85.6																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									

Model	SUTW102415
Item	Line Regulation
Object	+15V0.35A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	14.992	14.882
18	14.986	14.882
20	14.982	14.883
24	14.976	14.883
30	14.969	14.883
36	14.966	14.883
40	14.965	14.883
--	-	-
--	-	-

## Object -15V0.35A

## 1.Graph





## 2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-14.989	-14.880
18	-14.984	-14.880
20	-14.978	-14.880
24	-14.972	-14.880
30	-14.966	-14.880
36	-14.964	-14.880
40	-14.963	-14.880
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


**COSEL**

Model	SUTW102415																																																					
Item	Load Regulation																																																					
Object	+15V0.35A																																																					
1. Graph <div style="display: flex; justify-content: space-between; align-items: center;"> <span style="margin-right: 20px;">—△— Input Volt. 18V</span> <span style="margin-right: 20px;">- -□- - Input Volt. 24V</span> <span style="margin-right: 20px;">- -○- - Input Volt. 36V</span> </div>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																						
2. Values <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.267</td><td>15.255</td><td>15.241</td></tr> <tr><td>0.070</td><td>15.059</td><td>15.048</td><td>15.045</td></tr> <tr><td>0.140</td><td>15.008</td><td>14.996</td><td>14.988</td></tr> <tr><td>0.210</td><td>14.965</td><td>14.956</td><td>14.948</td></tr> <tr><td>0.280</td><td>14.923</td><td>14.918</td><td>14.914</td></tr> <tr><td>0.350</td><td>14.882</td><td>14.883</td><td>14.883</td></tr> <tr><td>0.385</td><td>14.861</td><td>14.864</td><td>14.867</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	15.267	15.255	15.241	0.070	15.059	15.048	15.045	0.140	15.008	14.996	14.988	0.210	14.965	14.956	14.948	0.280	14.923	14.918	14.914	0.350	14.882	14.883	14.883	0.385	14.861	14.864	14.867	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	15.267	15.255	15.241																																																			
0.070	15.059	15.048	15.045																																																			
0.140	15.008	14.996	14.988																																																			
0.210	14.965	14.956	14.948																																																			
0.280	14.923	14.918	14.914																																																			
0.350	14.882	14.883	14.883																																																			
0.385	14.861	14.864	14.867																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object <td colspan="3">-15V0.35A</td>				-15V0.35A																																																		
1. Graph <div style="display: flex; justify-content: space-between; align-items: center;"> <span style="margin-right: 20px;">—△— Input Volt. 18V</span> <span style="margin-right: 20px;">- -□- - Input Volt. 24V</span> <span style="margin-right: 20px;">- -○- - Input Volt. 36V</span> </div>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																						
2. Values <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.266</td><td>-15.259</td><td>-15.267</td></tr> <tr><td>0.070</td><td>-15.055</td><td>-15.045</td><td>-15.043</td></tr> <tr><td>0.140</td><td>-15.005</td><td>-14.992</td><td>-14.985</td></tr> <tr><td>0.210</td><td>-14.962</td><td>-14.953</td><td>-14.944</td></tr> <tr><td>0.280</td><td>-14.920</td><td>-14.916</td><td>-14.911</td></tr> <tr><td>0.350</td><td>-14.880</td><td>-14.880</td><td>-14.880</td></tr> <tr><td>0.385</td><td>-14.860</td><td>-14.862</td><td>-14.864</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-15.266	-15.259	-15.267	0.070	-15.055	-15.045	-15.043	0.140	-15.005	-14.992	-14.985	0.210	-14.962	-14.953	-14.944	0.280	-14.920	-14.916	-14.911	0.350	-14.880	-14.880	-14.880	0.385	-14.860	-14.862	-14.864	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-15.266	-15.259	-15.267																																																			
0.070	-15.055	-15.045	-15.043																																																			
0.140	-15.005	-14.992	-14.985																																																			
0.210	-14.962	-14.953	-14.944																																																			
0.280	-14.920	-14.916	-14.911																																																			
0.350	-14.880	-14.880	-14.880																																																			
0.385	-14.860	-14.862	-14.864																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**




**COSEL**



Model	SUTW102415
Item	Ripple Voltage (by Load Current)
Object	+15V0.35A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	3	3
0.070	3	3
0.140	4	4
0.210	5	5
0.280	6	6
0.350	8	7
0.385	8	7
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW102415
Item	Ripple Voltage (by Load Current)
Object	-15V0.35A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	4	6
0.070	5	6
0.140	6	8
0.210	6	8
0.280	8	9
0.350	8	9
0.385	8	9
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW102415																																							
Item	Ripple-Noise	Temperature Testing Circuitry      25°C Figure B																																						
Object	+15V0.35A																																							
1.Graph																																								
		2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>5</td></tr> <tr><td>0.070</td><td>4</td><td>5</td></tr> <tr><td>0.140</td><td>6</td><td>6</td></tr> <tr><td>0.210</td><td>7</td><td>8</td></tr> <tr><td>0.280</td><td>8</td><td>8</td></tr> <tr><td>0.350</td><td>10</td><td>9</td></tr> <tr><td>0.385</td><td>10</td><td>9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.000	4	5	0.070	4	5	0.140	6	6	0.210	7	8	0.280	8	8	0.350	10	9	0.385	10	9	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.000	4	5																																						
0.070	4	5																																						
0.140	6	6																																						
0.210	7	8																																						
0.280	8	8																																						
0.350	10	9																																						
0.385	10	9																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.      Ripple-Noise is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

Model	SUTW102415
Item	Ripple-Noise
Object	-15V0.35A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	5	6
0.070	6	7
0.140	8	10
0.210	9	10
0.280	10	10
0.350	10	11
0.385	11	11
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW102415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.35A

## 1.Graph

--□-- Load 50%  
—△— Load 100%



Input Volt. 24V


Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	11
-40	7	10
-20	7	10
0	5	9
25	5	8
55	5	8
60	5	8
--	-	-
--	-	-
--	-	-
--	-	-

## 1.Graph

--□-- Load 50%  
—△— Load 100%



Input Volt. 24V

## 2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	10
-40	9	10
-20	9	10
0	8	9
25	6	9
55	6	9
60	6	9
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW102415
Item	Ambient Temperature Drift
Object	+15V0.35A

Testing Circuitry Figure A



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	14.850	14.852	14.853
-40	14.868	14.869	14.869
-20	14.879	14.880	14.880
0	14.884	14.885	14.885
25	14.884	14.884	14.884
55	14.874	14.874	14.874
60	14.871	14.871	14.871
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-14.847	-14.848	-14.849
-40	-14.865	-14.865	-14.865
-20	-14.876	-14.876	-14.876
0	-14.882	-14.882	-14.881
25	-14.881	-14.881	-14.881
55	-14.871	-14.871	-14.870
60	-14.868	-14.868	-14.867
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW102415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.35A (AVR 2) : 0 - 0.35A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object		+15V0.35A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	15.268			
Minimum Voltage	55	36	0.35	14.478	±395	±2.6	

Object		-15V0.35A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	36	0	-15.271			
Minimum Voltage	55	18	0.35	-14.482	±395	±2.6	

**COSEL**


Model	SUTW102415	Temperature Testing Circuitry	25°C Figure A																							
Item	Time Lapse Drift																									
Object	+15V0.35A																									
1.Graph			2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.882</td></tr> <tr><td>0.5</td><td>14.878</td></tr> <tr><td>1.0</td><td>14.878</td></tr> <tr><td>2.0</td><td>14.878</td></tr> <tr><td>3.0</td><td>14.878</td></tr> <tr><td>4.0</td><td>14.878</td></tr> <tr><td>5.0</td><td>14.878</td></tr> <tr><td>6.0</td><td>14.878</td></tr> <tr><td>7.0</td><td>14.878</td></tr> <tr><td>8.0</td><td>14.878</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.882	0.5	14.878	1.0	14.878	2.0	14.878	3.0	14.878	4.0	14.878	5.0	14.878	6.0	14.878	7.0	14.878	8.0	14.878	
Time since start [H]	Output Voltage [V]																									
0.0	14.882																									
0.5	14.878																									
1.0	14.878																									
2.0	14.878																									
3.0	14.878																									
4.0	14.878																									
5.0	14.878																									
6.0	14.878																									
7.0	14.878																									
8.0	14.878																									
Object			2.Values																							
1.Graph			 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.887</td></tr> <tr><td>0.5</td><td>-14.885</td></tr> <tr><td>1.0</td><td>-14.884</td></tr> <tr><td>2.0</td><td>-14.884</td></tr> <tr><td>3.0</td><td>-14.884</td></tr> <tr><td>4.0</td><td>-14.885</td></tr> <tr><td>5.0</td><td>-14.884</td></tr> <tr><td>6.0</td><td>-14.884</td></tr> <tr><td>7.0</td><td>-14.884</td></tr> <tr><td>8.0</td><td>-14.884</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-14.887	0.5	-14.885	1.0	-14.884	2.0	-14.884	3.0	-14.884	4.0	-14.885	5.0	-14.884	6.0	-14.884	7.0	-14.884	8.0	-14.884
Time since start [H]	Output Voltage [V]																									
0.0	-14.887																									
0.5	-14.885																									
1.0	-14.884																									
2.0	-14.884																									
3.0	-14.884																									
4.0	-14.885																									
5.0	-14.884																									
6.0	-14.884																									
7.0	-14.884																									
8.0	-14.884																									

**COSEL**

Model	SUTW102415
Item	Rise and Fall Time
Object	+15V0.35A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		9.2	3.8	13.0	0.1	3.5
100 %		9.2	3.9	13.1	0.1	1.7




**COSEL**

Model	SUTW102415
Item	Rise and Fall Time
Object	-15V0.35A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.2	4.0	13.2	0.1	3.7	
100 %		9.2	4.0	13.2	0.1	1.9	




**COSEL**

Model	SUTW102415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.35A

## 1.Graph

---□--- Load 50%  
—△— Load 100%



Testing Circuitry Figure A


## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	12.9	13.0
-40	12.9	12.8
-20	12.7	12.6
0	12.5	12.6
25	12.3	12.4
55	12.1	12.2
60	12.1	12.2
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.35A
--------	-----------

## 1.Graph



---□--- Load 50%  
—△— Load 100%



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	12.8	12.9
-40	12.8	12.7
-20	12.6	12.5
0	12.4	12.5
25	12.2	12.3
55	12.0	12.1
60	11.9	12.1
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

		Temperature Testing Circuitry      25°C Figure A					
Model	SUTW102415						
Item	Overcurrent Protection						
Object	+15V0.35A						
1.Graph	<p>— Input Volt. 18V            — Input Volt. 24V            — Input Volt. 36V</p> 	2.Values					
2.Values							
Object	-15V0.35A	2.Values					
1.Graph	<p>— Input Volt. 18V            — Input Volt. 24V            — Input Volt. 36V</p> 						
2.Values							
Note: Slanted line shows the range of the rated load current.							

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)