

TEST DATA OF SUTW31215

Regulated DC Power Supply

Approved by : Kazunari Asano Kazunari Asano Design Manager

Prepared by : Sho Saito Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW31215	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	_____	<p>The graph plots Input Current [A] on the y-axis (0.0 to 1.0) against Input Voltage [V] on the x-axis (0 to 28). Three data series are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). All series show a sharp increase in current from 0V to approximately 3V, followed by a gradual decrease. A slanted line is drawn through the data points, representing the rated input voltage range.</p>																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>2.6</td><td>0.124</td><td>0.782</td><td>0.771</td></tr> <tr><td>4.0</td><td>0.071</td><td>0.627</td><td>0.802</td></tr> <tr><td>4.6</td><td>0.062</td><td>0.500</td><td>0.822</td></tr> <tr><td>5.0</td><td>0.059</td><td>0.441</td><td>0.820</td></tr> <tr><td>6.0</td><td>0.051</td><td>0.345</td><td>0.708</td></tr> <tr><td>8.0</td><td>0.042</td><td>0.257</td><td>0.488</td></tr> <tr><td>9.0</td><td>0.039</td><td>0.228</td><td>0.429</td></tr> <tr><td>10.0</td><td>0.037</td><td>0.205</td><td>0.382</td></tr> <tr><td>12.0</td><td>0.033</td><td>0.172</td><td>0.316</td></tr> <tr><td>14.0</td><td>0.030</td><td>0.149</td><td>0.272</td></tr> <tr><td>16.0</td><td>0.027</td><td>0.131</td><td>0.239</td></tr> <tr><td>18.0</td><td>0.026</td><td>0.118</td><td>0.212</td></tr> <tr><td>20.0</td><td>0.024</td><td>0.108</td><td>0.193</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.009	0.009	0.009	2.6	0.124	0.782	0.771	4.0	0.071	0.627	0.802	4.6	0.062	0.500	0.822	5.0	0.059	0.441	0.820	6.0	0.051	0.345	0.708	8.0	0.042	0.257	0.488	9.0	0.039	0.228	0.429	10.0	0.037	0.205	0.382	12.0	0.033	0.172	0.316	14.0	0.030	0.149	0.272	16.0	0.027	0.131	0.239	18.0	0.026	0.118	0.212	20.0	0.024	0.108	0.193	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	0.009	0.009	0.009																																																																																
2.6	0.124	0.782	0.771																																																																																
4.0	0.071	0.627	0.802																																																																																
4.6	0.062	0.500	0.822																																																																																
5.0	0.059	0.441	0.820																																																																																
6.0	0.051	0.345	0.708																																																																																
8.0	0.042	0.257	0.488																																																																																
9.0	0.039	0.228	0.429																																																																																
10.0	0.037	0.205	0.382																																																																																
12.0	0.033	0.172	0.316																																																																																
14.0	0.030	0.149	0.272																																																																																
16.0	0.027	0.131	0.239																																																																																
18.0	0.026	0.118	0.212																																																																																
20.0	0.024	0.108	0.193																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Note: Slanted line shows the range of the rated input voltage.

Model	SUTW31215	Temperature Testing Circuitry 25°C Figure A																																																																																																			
Item	Input Current (by Load Current)																																																																																																				
Object	_____																																																																																																				
1.Graph		2.Values																																																																																																			
<p style="text-align: center;"> —△— Input Volt. 9V ---□--- Input Volt. 12V ---○--- Input Volt. 18V </p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (9V)</th> <th>Input Current [A] (12V)</th> <th>Input Current [A] (18V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.039</td><td>0.033</td><td>0.025</td></tr> <tr><td>20</td><td>0.113</td><td>0.088</td><td>0.062</td></tr> <tr><td>40</td><td>0.188</td><td>0.142</td><td>0.099</td></tr> <tr><td>60</td><td>0.266</td><td>0.198</td><td>0.136</td></tr> <tr><td>80</td><td>0.345</td><td>0.255</td><td>0.173</td></tr> <tr><td>100</td><td>0.422</td><td>0.312</td><td>0.210</td></tr> <tr><td>110</td><td>0.463</td><td>0.342</td><td>0.229</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A] (9V)	Input Current [A] (12V)	Input Current [A] (18V)	0	0.039	0.033	0.025	20	0.113	0.088	0.062	40	0.188	0.142	0.099	60	0.266	0.198	0.136	80	0.345	0.255	0.173	100	0.422	0.312	0.210	110	0.463	0.342	0.229	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.039</td><td>0.033</td><td>0.025</td></tr> <tr><td>20</td><td>0.113</td><td>0.088</td><td>0.062</td></tr> <tr><td>40</td><td>0.188</td><td>0.142</td><td>0.099</td></tr> <tr><td>60</td><td>0.266</td><td>0.198</td><td>0.136</td></tr> <tr><td>80</td><td>0.345</td><td>0.255</td><td>0.173</td></tr> <tr><td>100</td><td>0.422</td><td>0.312</td><td>0.210</td></tr> <tr><td>110</td><td>0.463</td><td>0.342</td><td>0.229</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.039	0.033	0.025	20	0.113	0.088	0.062	40	0.188	0.142	0.099	60	0.266	0.198	0.136	80	0.345	0.255	0.173	100	0.422	0.312	0.210	110	0.463	0.342	0.229	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A] (9V)	Input Current [A] (12V)	Input Current [A] (18V)																																																																																																		
0	0.039	0.033	0.025																																																																																																		
20	0.113	0.088	0.062																																																																																																		
40	0.188	0.142	0.099																																																																																																		
60	0.266	0.198	0.136																																																																																																		
80	0.345	0.255	0.173																																																																																																		
100	0.422	0.312	0.210																																																																																																		
110	0.463	0.342	0.229																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
Load Ration [%]	Input Current [A]																																																																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																																																																		
0	0.039	0.033	0.025																																																																																																		
20	0.113	0.088	0.062																																																																																																		
40	0.188	0.142	0.099																																																																																																		
60	0.266	0.198	0.136																																																																																																		
80	0.345	0.255	0.173																																																																																																		
100	0.422	0.312	0.210																																																																																																		
110	0.463	0.342	0.229																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		

Model	SUTW31215																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - ○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (9V)</th> <th>Input Power [W] (12V)</th> <th>Input Power [W] (18V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.34</td><td>0.38</td><td>0.45</td></tr> <tr><td>20</td><td>1.01</td><td>1.05</td><td>1.12</td></tr> <tr><td>40</td><td>1.68</td><td>1.71</td><td>1.79</td></tr> <tr><td>60</td><td>2.37</td><td>2.39</td><td>2.46</td></tr> <tr><td>80</td><td>3.07</td><td>3.07</td><td>3.12</td></tr> <tr><td>100</td><td>3.79</td><td>3.76</td><td>3.80</td></tr> <tr><td>110</td><td>4.16</td><td>4.11</td><td>4.13</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (9V)	Input Power [W] (12V)	Input Power [W] (18V)	0	0.34	0.38	0.45	20	1.01	1.05	1.12	40	1.68	1.71	1.79	60	2.37	2.39	2.46	80	3.07	3.07	3.12	100	3.79	3.76	3.80	110	4.16	4.11	4.13																			
Load Ration [%]	Input Power [W] (9V)	Input Power [W] (12V)	Input Power [W] (18V)																																																			
0	0.34	0.38	0.45																																																			
20	1.01	1.05	1.12																																																			
40	1.68	1.71	1.79																																																			
60	2.37	2.39	2.46																																																			
80	3.07	3.07	3.12																																																			
100	3.79	3.76	3.80																																																			
110	4.16	4.11	4.13																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.34</td><td>0.38</td><td>0.45</td></tr> <tr><td>20</td><td>1.01</td><td>1.05</td><td>1.12</td></tr> <tr><td>40</td><td>1.68</td><td>1.71</td><td>1.79</td></tr> <tr><td>60</td><td>2.37</td><td>2.39</td><td>2.46</td></tr> <tr><td>80</td><td>3.07</td><td>3.07</td><td>3.12</td></tr> <tr><td>100</td><td>3.79</td><td>3.76</td><td>3.80</td></tr> <tr><td>110</td><td>4.16</td><td>4.11</td><td>4.13</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.34	0.38	0.45	20	1.01	1.05	1.12	40	1.68	1.71	1.79	60	2.37	2.39	2.46	80	3.07	3.07	3.12	100	3.79	3.76	3.80	110	4.16	4.11	4.13	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.34	0.38	0.45																																																			
20	1.01	1.05	1.12																																																			
40	1.68	1.71	1.79																																																			
60	2.37	2.39	2.46																																																			
80	3.07	3.07	3.12																																																			
100	3.79	3.76	3.80																																																			
110	4.16	4.11	4.13																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	SUTW31215	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1.Graph		2.Values																													
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (6 to 22). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>8</td><td>73.8</td><td>78.2</td></tr> <tr><td>9</td><td>73.8</td><td>78.9</td></tr> <tr><td>10</td><td>73.6</td><td>79.2</td></tr> <tr><td>12</td><td>73.3</td><td>79.4</td></tr> <tr><td>15</td><td>71.5</td><td>79.5</td></tr> <tr><td>18</td><td>70.4</td><td>78.8</td></tr> <tr><td>20</td><td>69.3</td><td>78.0</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	8	73.8	78.2	9	73.8	78.9	10	73.6	79.2	12	73.3	79.4	15	71.5	79.5	18	70.4	78.8	20	69.3	78.0	--	-	-	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
8	73.8	78.2																													
9	73.8	78.9																													
10	73.6	79.2																													
12	73.3	79.4																													
15	71.5	79.5																													
18	70.4	78.8																													
20	69.3	78.0																													
--	-	-																													
--	-	-																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTW31215	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - ○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [Efficiency %]</th> <th>12V [Efficiency %]</th> <th>18V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>58</td><td>55</td><td>53</td></tr> <tr><td>40</td><td>70</td><td>68</td><td>65</td></tr> <tr><td>60</td><td>75</td><td>73</td><td>70</td></tr> <tr><td>80</td><td>78</td><td>76</td><td>74</td></tr> <tr><td>100</td><td>78.8</td><td>79.6</td><td>78.7</td></tr> <tr><td>110</td><td>79.1</td><td>80.0</td><td>79.6</td></tr> </tbody> </table>	Load Ration [%]	9V [Efficiency %]	12V [Efficiency %]	18V [Efficiency %]	20	58	55	53	40	70	68	65	60	75	73	70	80	78	76	74	100	78.8	79.6	78.7	110	79.1	80.0	79.6																								
Load Ration [%]	9V [Efficiency %]	12V [Efficiency %]	18V [Efficiency %]																																																		
20	58	55	53																																																		
40	70	68	65																																																		
60	75	73	70																																																		
80	78	76	74																																																		
100	78.8	79.6	78.7																																																		
110	79.1	80.0	79.6																																																		
2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>59.0</td><td>57.2</td><td>53.4</td></tr> <tr><td>40</td><td>71.0</td><td>69.7</td><td>66.8</td></tr> <tr><td>60</td><td>75.6</td><td>75.2</td><td>73.0</td></tr> <tr><td>80</td><td>77.8</td><td>77.9</td><td>76.5</td></tr> <tr><td>100</td><td>78.8</td><td>79.6</td><td>78.7</td></tr> <tr><td>110</td><td>79.1</td><td>80.0</td><td>79.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	59.0	57.2	53.4	40	71.0	69.7	66.8	60	75.6	75.2	73.0	80	77.8	77.9	76.5	100	78.8	79.6	78.7	110	79.1	80.0	79.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0	-	-	-																																																		
20	59.0	57.2	53.4																																																		
40	71.0	69.7	66.8																																																		
60	75.6	75.2	73.0																																																		
80	77.8	77.9	76.5																																																		
100	78.8	79.6	78.7																																																		
110	79.1	80.0	79.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Model	SUTW31215
Item	Line Regulation
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	15.005	14.936
9	15.002	14.937
10	15.000	14.937
12	14.996	14.937
15	14.994	14.937
18	14.991	14.937
20	14.991	14.936
--	-	-
--	-	-

Object -15V0.1A

1.Graph




2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	-15.000	-14.931
9	-14.997	-14.932
10	-14.994	-14.931
12	-14.991	-14.931
15	-14.989	-14.931
18	-14.987	-14.931
20	-14.986	-14.931
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUTW31215	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+15V0.1A																																																					
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	2.Values																																																				
	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																					
Object	-15V0.1A	2.Values																																																				
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.174</td><td>15.166</td><td>15.149</td></tr> <tr><td>0.02</td><td>15.063</td><td>15.056</td><td>15.048</td></tr> <tr><td>0.04</td><td>15.019</td><td>15.012</td><td>15.006</td></tr> <tr><td>0.06</td><td>14.987</td><td>14.982</td><td>14.978</td></tr> <tr><td>0.08</td><td>14.960</td><td>14.957</td><td>14.955</td></tr> <tr><td>0.10</td><td>14.936</td><td>14.936</td><td>14.936</td></tr> <tr><td>0.11</td><td>14.924</td><td>14.926</td><td>14.927</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	15.174	15.166	15.149	0.02	15.063	15.056	15.048	0.04	15.019	15.012	15.006	0.06	14.987	14.982	14.978	0.08	14.960	14.957	14.955	0.10	14.936	14.936	14.936	0.11	14.924	14.926	14.927	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	15.174	15.166	15.149																																																			
0.02	15.063	15.056	15.048																																																			
0.04	15.019	15.012	15.006																																																			
0.06	14.987	14.982	14.978																																																			
0.08	14.960	14.957	14.955																																																			
0.10	14.936	14.936	14.936																																																			
0.11	14.924	14.926	14.927																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.1A	2.Values																																																				
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																					
	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																					
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


COSEL

COSEL

Model	SUTW31215
Item	Ripple Voltage (by Load Current)
Object	+15V0.1A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	2	2
0.02	2	2
0.04	3	2
0.06	4	3
0.08	6	3
0.10	12	4
0.11	14	5
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW31215
Item	Ripple Voltage (by Load Current)
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	2	2
0.02	2	2
0.04	2	2
0.06	4	3
0.08	7	3
0.10	11	3
0.11	-	3
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW31215
Item	Ripple-Noise
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	8	5
0.02	8	9
0.04	10	9
0.06	13	10
0.08	16	10
0.10	24	11
0.11	27	12
--	-	-
--	-	-
--	-	-
--	-	-



Model	SUTW31215
Item	Ripple-Noise
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	10	8
0.02	10	10
0.04	11	10
0.06	11	10
0.08	11	10
0.10	16	11
0.11	19	11
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form


Model SUTW31215

Item Ripple Voltage (by Ambient Temp.)

Object +15V0.1A

1.Graph

---□--- Load 50%
—△— Load 100%



Input Volt. 48V


Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	15
-40	7	15
-20	7	12
0	5	10
25	3	9
55	3	9
60	3	9
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph

---□--- Load 50%
—△— Load 100%



Input Volt. 48V

2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	8
-40	4	8
-20	4	9
0	3	10
25	3	10
55	3	7
60	3	7
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW31215
Item	Ambient Temperature Drift
Object	+15V0.1A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	14.894	14.894	14.894
-40	14.914	14.914	14.914
-20	14.928	14.928	14.927
0	14.936	14.936	14.935
25	14.939	14.938	14.938
55	14.932	14.932	14.931
60	14.931	14.930	14.930
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-14.885	-14.886	-14.888
-40	-14.905	-14.907	-14.908
-20	-14.920	-14.921	-14.922
0	-14.929	-14.929	-14.930
25	-14.932	-14.932	-14.932
55	-14.926	-14.926	-14.925
60	-14.924	-14.924	-14.923
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW31215	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object	+15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	9		0	15.175	
Minimum Voltage	-40	9	0.1	14.677	±249	±1.7

Object	-15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	9		0	-15.180	
Minimum Voltage	-40	9	0.1	-14.682	±249	±1.7

COSEL

Model	SUTW31215
Item	Time Lapse Drift
Object	+15V0.1A

1.Graph




Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	14.934
0.5	14.934
1.0	14.934
2.0	14.934
3.0	14.934
4.0	14.934
5.0	14.934
6.0	14.934
7.0	14.934
8.0	14.934

Object	-15V0.1A
--------	----------

1.Graph



2.Values

Time since start [H]	Output Voltage [V]
0.0	-14.933
0.5	-14.933
1.0	-14.933
2.0	-14.933
3.0	-14.933
4.0	-14.933
5.0	-14.933
6.0	-14.933
7.0	-14.933
8.0	-14.933


Input Volt.	12V
Load	100%

COSEL

Model	SUTW31215
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	3.0	3.1	0.5	2.4	
100 %		0.1	3.2	3.3	0.3	1.2	




COSEL

Model	SUTW31215
Item	Rise and Fall Time
Object	-15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.1	3.2	0.5	3.1
100 %		0.1	3.2	3.3	0.3	1.5




COSEL

Model	SUTW31215
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.1A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.3	4.9
-40	3.3	4.9
-20	3.5	4.9
0	3.5	5.1
25	3.5	5.3
55	3.7	5.5
60	3.7	5.5
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.1A
--------	----------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.3	4.9
-40	3.3	4.9
-20	3.5	4.9
0	3.5	5.1
25	3.5	5.3
55	3.7	5.5
60	3.7	5.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW31215																																																										
Item	Overcurrent Protection		Temperature Testing Circuitry	25°C Figure A																																																							
Object	+15V0.1A																																																										
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>14.3</td><td>0.27</td><td>0.28</td><td>0.28</td></tr> <tr><td>13.5</td><td>0.28</td><td>0.30</td><td>0.29</td></tr> <tr><td>12.0</td><td>0.32</td><td>0.33</td><td>0.32</td></tr> <tr><td>10.5</td><td>0.36</td><td>0.37</td><td>0.35</td></tr> <tr><td>9.0</td><td>0.40</td><td>0.40</td><td>0.38</td></tr> <tr><td>7.5</td><td>0.44</td><td>0.44</td><td>0.41</td></tr> <tr><td>6.0</td><td>0.48</td><td>0.47</td><td>0.43</td></tr> <tr><td>4.5</td><td>0.53</td><td>0.50</td><td>0.45</td></tr> <tr><td>3.0</td><td>0.55</td><td>0.51</td><td>0.46</td></tr> <tr><td>1.5</td><td>0.54</td><td>0.49</td><td>0.44</td></tr> <tr><td>0.0</td><td>0.47</td><td>0.43</td><td>0.41</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	15.0	0.10	0.10	0.10	14.3	0.27	0.28	0.28	13.5	0.28	0.30	0.29	12.0	0.32	0.33	0.32	10.5	0.36	0.37	0.35	9.0	0.40	0.40	0.38	7.5	0.44	0.44	0.41	6.0	0.48	0.47	0.43	4.5	0.53	0.50	0.45	3.0	0.55	0.51	0.46	1.5	0.54	0.49	0.44	0.0	0.47	0.43	0.41
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																								
15.0	0.10	0.10	0.10																																																								
14.3	0.27	0.28	0.28																																																								
13.5	0.28	0.30	0.29																																																								
12.0	0.32	0.33	0.32																																																								
10.5	0.36	0.37	0.35																																																								
9.0	0.40	0.40	0.38																																																								
7.5	0.44	0.44	0.41																																																								
6.0	0.48	0.47	0.43																																																								
4.5	0.53	0.50	0.45																																																								
3.0	0.55	0.51	0.46																																																								
1.5	0.54	0.49	0.44																																																								
0.0	0.47	0.43	0.41																																																								
Object		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>-14.25</td><td>0.27</td><td>0.29</td><td>0.28</td></tr> <tr><td>-13.50</td><td>0.28</td><td>0.30</td><td>0.29</td></tr> <tr><td>-12.00</td><td>0.32</td><td>0.33</td><td>0.32</td></tr> <tr><td>-10.50</td><td>0.36</td><td>0.37</td><td>0.35</td></tr> <tr><td>-9.00</td><td>0.40</td><td>0.40</td><td>0.38</td></tr> <tr><td>-7.50</td><td>0.44</td><td>0.44</td><td>0.41</td></tr> <tr><td>-6.00</td><td>0.48</td><td>0.47</td><td>0.43</td></tr> <tr><td>-4.50</td><td>0.53</td><td>0.50</td><td>0.45</td></tr> <tr><td>-3.00</td><td>0.55</td><td>0.51</td><td>0.46</td></tr> <tr><td>-1.50</td><td>0.54</td><td>0.49</td><td>0.44</td></tr> <tr><td>0.00</td><td>0.47</td><td>0.43</td><td>0.41</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-15.00	0.10	0.10	0.10	-14.25	0.27	0.29	0.28	-13.50	0.28	0.30	0.29	-12.00	0.32	0.33	0.32	-10.50	0.36	0.37	0.35	-9.00	0.40	0.40	0.38	-7.50	0.44	0.44	0.41	-6.00	0.48	0.47	0.43	-4.50	0.53	0.50	0.45	-3.00	0.55	0.51	0.46	-1.50	0.54	0.49	0.44	0.00	0.47	0.43	0.41
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																								
-15.00	0.10	0.10	0.10																																																								
-14.25	0.27	0.29	0.28																																																								
-13.50	0.28	0.30	0.29																																																								
-12.00	0.32	0.33	0.32																																																								
-10.50	0.36	0.37	0.35																																																								
-9.00	0.40	0.40	0.38																																																								
-7.50	0.44	0.44	0.41																																																								
-6.00	0.48	0.47	0.43																																																								
-4.50	0.53	0.50	0.45																																																								
-3.00	0.55	0.51	0.46																																																								
-1.50	0.54	0.49	0.44																																																								
0.00	0.47	0.43	0.41																																																								
<p>Note: Slanted line shows the range of the rated load current.</p>																																																											

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)