

TEST DATA OF SUTW32412

Regulated DC Power Supply
March 10, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

Model	SUTW32412	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□- - Load 50% - -○- - Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.008</td><td>0.008</td><td>0.007</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>8.8</td><td>0.030</td><td>0.008</td><td>0.008</td></tr> <tr><td>9.2</td><td>0.029</td><td>0.242</td><td>0.473</td></tr> <tr><td>12.0</td><td>0.023</td><td>0.180</td><td>0.352</td></tr> <tr><td>16.0</td><td>0.019</td><td>0.134</td><td>0.257</td></tr> <tr><td>18.0</td><td>0.017</td><td>0.119</td><td>0.226</td></tr> <tr><td>20.0</td><td>0.018</td><td>0.108</td><td>0.204</td></tr> <tr><td>24.0</td><td>0.015</td><td>0.091</td><td>0.169</td></tr> <tr><td>28.0</td><td>0.013</td><td>0.078</td><td>0.145</td></tr> <tr><td>32.0</td><td>0.013</td><td>0.069</td><td>0.129</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.064</td><td>0.114</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.060</td><td>0.104</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.008	0.008	0.007	8.0	0.007	0.007	0.007	8.8	0.030	0.008	0.008	9.2	0.029	0.242	0.473	12.0	0.023	0.180	0.352	16.0	0.019	0.134	0.257	18.0	0.017	0.119	0.226	20.0	0.018	0.108	0.204	24.0	0.015	0.091	0.169	28.0	0.013	0.078	0.145	32.0	0.013	0.069	0.129	36.0	0.015	0.064	0.114	40.0	0.015	0.060	0.104	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.008	0.008	0.007																																																																																
8.0	0.007	0.007	0.007																																																																																
8.8	0.030	0.008	0.008																																																																																
9.2	0.029	0.242	0.473																																																																																
12.0	0.023	0.180	0.352																																																																																
16.0	0.019	0.134	0.257																																																																																
18.0	0.017	0.119	0.226																																																																																
20.0	0.018	0.108	0.204																																																																																
24.0	0.015	0.091	0.169																																																																																
28.0	0.013	0.078	0.145																																																																																
32.0	0.013	0.069	0.129																																																																																
36.0	0.015	0.064	0.114																																																																																
40.0	0.015	0.060	0.104																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW32412																																																				
Item	Input Current (by Load Current)	Temperature Testing Circuitry																																																			
Object	_____	25°C Figure A																																																			
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (18V)</th> <th>Input Current [A] (24V)</th> <th>Input Current [A] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.018</td><td>0.015</td><td>0.014</td></tr> <tr><td>20</td><td>0.058</td><td>0.045</td><td>0.034</td></tr> <tr><td>40</td><td>0.098</td><td>0.075</td><td>0.054</td></tr> <tr><td>60</td><td>0.140</td><td>0.105</td><td>0.074</td></tr> <tr><td>80</td><td>0.182</td><td>0.136</td><td>0.094</td></tr> <tr><td>100</td><td>0.224</td><td>0.167</td><td>0.114</td></tr> <tr><td>110</td><td>0.246</td><td>0.182</td><td>0.124</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)	0	0.018	0.015	0.014	20	0.058	0.045	0.034	40	0.098	0.075	0.054	60	0.140	0.105	0.074	80	0.182	0.136	0.094	100	0.224	0.167	0.114	110	0.246	0.182	0.124																			
Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)																																																		
0	0.018	0.015	0.014																																																		
20	0.058	0.045	0.034																																																		
40	0.098	0.075	0.054																																																		
60	0.140	0.105	0.074																																																		
80	0.182	0.136	0.094																																																		
100	0.224	0.167	0.114																																																		
110	0.246	0.182	0.124																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.018</td><td>0.015</td><td>0.014</td></tr> <tr><td>20</td><td>0.058</td><td>0.045</td><td>0.034</td></tr> <tr><td>40</td><td>0.098</td><td>0.075</td><td>0.054</td></tr> <tr><td>60</td><td>0.140</td><td>0.105</td><td>0.074</td></tr> <tr><td>80</td><td>0.182</td><td>0.136</td><td>0.094</td></tr> <tr><td>100</td><td>0.224</td><td>0.167</td><td>0.114</td></tr> <tr><td>110</td><td>0.246</td><td>0.182</td><td>0.124</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.018	0.015	0.014	20	0.058	0.045	0.034	40	0.098	0.075	0.054	60	0.140	0.105	0.074	80	0.182	0.136	0.094	100	0.224	0.167	0.114	110	0.246	0.182	0.124	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	0.018	0.015	0.014																																																		
20	0.058	0.045	0.034																																																		
40	0.098	0.075	0.054																																																		
60	0.140	0.105	0.074																																																		
80	0.182	0.136	0.094																																																		
100	0.224	0.167	0.114																																																		
110	0.246	0.182	0.124																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Model	SUTW32412	Temperature Testing Circuitry 25°C Figure A																																														
Item	Input Power (by Load Current)																																															
Object	_____																																															
1.Graph		2.Values																																														
<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [W]</th> <th>24V [W]</th> <th>36V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.31</td><td>0.34</td><td>0.46</td></tr> <tr><td>20</td><td>1.04</td><td>1.08</td><td>1.20</td></tr> <tr><td>40</td><td>1.77</td><td>1.80</td><td>1.92</td></tr> <tr><td>60</td><td>2.50</td><td>2.53</td><td>2.65</td></tr> <tr><td>80</td><td>3.27</td><td>3.27</td><td>3.37</td></tr> <tr><td>100</td><td>4.03</td><td>4.02</td><td>4.10</td></tr> <tr><td>110</td><td>4.42</td><td>4.40</td><td>4.47</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	18V [W]	24V [W]	36V [W]	0	0.31	0.34	0.46	20	1.04	1.08	1.20	40	1.77	1.80	1.92	60	2.50	2.53	2.65	80	3.27	3.27	3.37	100	4.03	4.02	4.10	110	4.42	4.40	4.47	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	18V [W]	24V [W]	36V [W]																																													
0	0.31	0.34	0.46																																													
20	1.04	1.08	1.20																																													
40	1.77	1.80	1.92																																													
60	2.50	2.53	2.65																																													
80	3.27	3.27	3.37																																													
100	4.03	4.02	4.10																																													
110	4.42	4.40	4.47																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													


Model	SUTW32412																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (10 to 50). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>74.2</td><td>78.0</td></tr> <tr><td>18</td><td>74.0</td><td>78.7</td></tr> <tr><td>20</td><td>73.8</td><td>78.9</td></tr> <tr><td>24</td><td>73.2</td><td>78.8</td></tr> <tr><td>30</td><td>71.8</td><td>78.2</td></tr> <tr><td>36</td><td>69.5</td><td>77.1</td></tr> <tr><td>40</td><td>67.4</td><td>75.8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	74.2	78.0	18	74.0	78.7	20	73.8	78.9	24	73.2	78.8	30	71.8	78.2	36	69.5	77.1	40	67.4	75.8	--	-	-	--	-	-		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
16	74.2	78.0																																
18	74.0	78.7																																
20	73.8	78.9																																
24	73.2	78.8																																
30	71.8	78.2																																
36	69.5	77.1																																
40	67.4	75.8																																
--	-	-																																
--	-	-																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>74.2</td><td>78.0</td></tr> <tr><td>18</td><td>74.0</td><td>78.7</td></tr> <tr><td>20</td><td>73.8</td><td>78.9</td></tr> <tr><td>24</td><td>73.2</td><td>78.8</td></tr> <tr><td>30</td><td>71.8</td><td>78.2</td></tr> <tr><td>36</td><td>69.5</td><td>77.1</td></tr> <tr><td>40</td><td>67.4</td><td>75.8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	74.2	78.0	18	74.0	78.7	20	73.8	78.9	24	73.2	78.8	30	71.8	78.2	36	69.5	77.1	40	67.4	75.8	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
16	74.2	78.0																																
18	74.0	78.7																																
20	73.8	78.9																																
24	73.2	78.8																																
30	71.8	78.2																																
36	69.5	77.1																																
40	67.4	75.8																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	SUTW32412	Temperature Testing Circuitry 25°C Figure A																																										
Item	Efficiency (by Load Current)																																											
Object	_____																																											
1.Graph		2.Values																																										
<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>20</td><td>61.1</td><td>59.0</td><td>52.9</td></tr> <tr><td>40</td><td>71.7</td><td>70.5</td><td>66.0</td></tr> <tr><td>60</td><td>76.0</td><td>75.2</td><td>71.9</td></tr> <tr><td>80</td><td>77.5</td><td>77.6</td><td>75.3</td></tr> <tr><td>100</td><td>78.7</td><td>78.9</td><td>77.3</td></tr> <tr><td>110</td><td>78.9</td><td>79.3</td><td>78.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	20	61.1	59.0	52.9	40	71.7	70.5	66.0	60	76.0	75.2	71.9	80	77.5	77.6	75.3	100	78.7	78.9	77.3	110	78.9	79.3	78.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																									
20	61.1	59.0	52.9																																									
40	71.7	70.5	66.0																																									
60	76.0	75.2	71.9																																									
80	77.5	77.6	75.3																																									
100	78.7	78.9	77.3																																									
110	78.9	79.3	78.0																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									

Model	SUTW32412
Item	Line Regulation
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	12.249	12.181
18	12.247	12.182
20	12.245	12.183
24	12.242	12.184
30	12.240	12.184
36	12.238	12.184
40	12.238	12.184
--	-	-
--	-	-

Object	-12V0.13A
--------	-----------

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-12.259	-12.190
18	-12.255	-12.191
20	-12.253	-12.191
24	-12.249	-12.191
30	-12.247	-12.191
36	-12.245	-12.191
40	-12.245	-12.191
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW32412																																																					
Item	Load Regulation																																																					
Object	+12V0.13A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — △ — Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.419</td><td>12.411</td><td>12.404</td></tr> <tr><td>0.026</td><td>12.306</td><td>12.300</td><td>12.297</td></tr> <tr><td>0.052</td><td>12.262</td><td>12.258</td><td>12.254</td></tr> <tr><td>0.078</td><td>12.231</td><td>12.228</td><td>12.225</td></tr> <tr><td>0.104</td><td>12.205</td><td>12.204</td><td>12.202</td></tr> <tr><td>0.130</td><td>12.180</td><td>12.181</td><td>12.182</td></tr> <tr><td>0.143</td><td>12.168</td><td>12.171</td><td>12.173</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	12.419	12.411	12.404	0.026	12.306	12.300	12.297	0.052	12.262	12.258	12.254	0.078	12.231	12.228	12.225	0.104	12.205	12.204	12.202	0.130	12.180	12.181	12.182	0.143	12.168	12.171	12.173	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	12.419	12.411	12.404																																																			
0.026	12.306	12.300	12.297																																																			
0.052	12.262	12.258	12.254																																																			
0.078	12.231	12.228	12.225																																																			
0.104	12.205	12.204	12.202																																																			
0.130	12.180	12.181	12.182																																																			
0.143	12.168	12.171	12.173																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.13A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — △ — Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.424</td><td>-12.415</td><td>-12.407</td></tr> <tr><td>0.026</td><td>-12.313</td><td>-12.306</td><td>-12.302</td></tr> <tr><td>0.052</td><td>-12.270</td><td>-12.264</td><td>-12.260</td></tr> <tr><td>0.078</td><td>-12.239</td><td>-12.235</td><td>-12.232</td></tr> <tr><td>0.104</td><td>-12.213</td><td>-12.210</td><td>-12.209</td></tr> <tr><td>0.130</td><td>-12.188</td><td>-12.188</td><td>-12.188</td></tr> <tr><td>0.143</td><td>-12.176</td><td>-12.178</td><td>-12.180</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-12.424	-12.415	-12.407	0.026	-12.313	-12.306	-12.302	0.052	-12.270	-12.264	-12.260	0.078	-12.239	-12.235	-12.232	0.104	-12.213	-12.210	-12.209	0.130	-12.188	-12.188	-12.188	0.143	-12.176	-12.178	-12.180	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-12.424	-12.415	-12.407																																																			
0.026	-12.313	-12.306	-12.302																																																			
0.052	-12.270	-12.264	-12.260																																																			
0.078	-12.239	-12.235	-12.232																																																			
0.104	-12.213	-12.210	-12.209																																																			
0.130	-12.188	-12.188	-12.188																																																			
0.143	-12.176	-12.178	-12.180																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL




COSEL



Model	SUTW32412
Item	Ripple Voltage (by Load Current)
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	2	2
0.026	2	2
0.052	3	2
0.078	4	2
0.104	5	2
0.130	7	3
0.143	10	3
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW32412
Item	Ripple Voltage (by Load Current)
Object	-12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	2	2
0.026	2	2
0.052	2	2
0.078	2	2
0.104	5	2
0.130	7	2
0.143	9	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW32412
Item	Ripple-Noise
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	4	4
0.026	6	5
0.052	7	6
0.078	10	7
0.104	12	8
0.130	17	9
0.143	20	10
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW32412
Item	Ripple-Noise
Object	-12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	5	5
0.026	8	8
0.052	9	9
0.078	12	10
0.104	13	11
0.130	17	12
0.143	19	13
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW32412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.13A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	9
-20	4	9
0	3	9
25	3	5
55	2	5
60	2	5
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	8
-40	4	8
-20	4	7
0	4	7
25	4	7
55	4	5
60	3	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW32412
Item	Ambient Temperature Drift
Object	+12V0.13A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	12.059	12.062	12.064
-40	12.097	12.099	12.100
-20	12.130	12.131	12.132
0	12.156	12.157	12.158
25	12.181	12.182	12.183
55	12.200	12.200	12.201
60	12.202	12.202	12.203
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-12.062	-12.066	-12.068
-40	-12.101	-12.103	-12.105
-20	-12.133	-12.135	-12.137
0	-12.161	-12.162	-12.163
25	-12.186	-12.187	-12.188
55	-12.205	-12.205	-12.206
60	-12.207	-12.207	-12.208
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW32412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.13A (AVR 2) : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	12.444	± 280	± 2.3	
Minimum Voltage	-40	18	0.13	11.884			

Object		-12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	-12.448	± 283	± 2.4	
Minimum Voltage	-40	18	0.13	-11.883			

COSEL


Model	SUTW32412	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+12V0.13A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.169</td></tr> <tr><td>0.5</td><td>12.184</td></tr> <tr><td>1.0</td><td>12.184</td></tr> <tr><td>2.0</td><td>12.184</td></tr> <tr><td>3.0</td><td>12.184</td></tr> <tr><td>4.0</td><td>12.184</td></tr> <tr><td>5.0</td><td>12.184</td></tr> <tr><td>6.0</td><td>12.184</td></tr> <tr><td>7.0</td><td>12.184</td></tr> <tr><td>8.0</td><td>12.184</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.169	0.5	12.184	1.0	12.184	2.0	12.184	3.0	12.184	4.0	12.184	5.0	12.184	6.0	12.184	7.0	12.184	8.0	12.184
Time since start [H]	Output Voltage [V]																							
0.0	12.169																							
0.5	12.184																							
1.0	12.184																							
2.0	12.184																							
3.0	12.184																							
4.0	12.184																							
5.0	12.184																							
6.0	12.184																							
7.0	12.184																							
8.0	12.184																							
Object -12V0.13A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.180</td></tr> <tr><td>0.5</td><td>-12.194</td></tr> <tr><td>1.0</td><td>-12.194</td></tr> <tr><td>2.0</td><td>-12.194</td></tr> <tr><td>3.0</td><td>-12.194</td></tr> <tr><td>4.0</td><td>-12.194</td></tr> <tr><td>5.0</td><td>-12.194</td></tr> <tr><td>6.0</td><td>-12.194</td></tr> <tr><td>7.0</td><td>-12.194</td></tr> <tr><td>8.0</td><td>-12.194</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.180	0.5	-12.194	1.0	-12.194	2.0	-12.194	3.0	-12.194	4.0	-12.194	5.0	-12.194	6.0	-12.194	7.0	-12.194	8.0	-12.194
Time since start [H]	Output Voltage [V]																							
0.0	-12.180																							
0.5	-12.194																							
1.0	-12.194																							
2.0	-12.194																							
3.0	-12.194																							
4.0	-12.194																							
5.0	-12.194																							
6.0	-12.194																							
7.0	-12.194																							
8.0	-12.194																							

COSEL

Model	SUTW32412
Item	Rise and Fall Time
Object	+12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	2.1	2.2	1.5	2.3
100 %		0.1	2.3	2.4	0.7	1.2




COSEL

Model	SUTW32412
Item	Rise and Fall Time
Object	-12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	2.3	2.4	1.5	2.7
100 %		0.1	2.6	2.7	0.7	1.4



COSEL

Model	SUTW32412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.13A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.2	9.4
-40	6.2	9.0
-20	6.1	8.9
0	6.1	9.1
25	6.3	9.4
55	6.6	10.0
60	6.6	10.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.13A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.2	9.4
-40	6.2	8.8
-20	6.1	8.9
0	6.1	9.1
25	6.1	9.4
55	6.6	10.0
60	6.6	10.0
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW32412			Temperature Testing Circuitry 25°C Figure A																																																						
Item	Overcurrent Protection																																																									
Object	+12V0.13A																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>11.4</td><td>0.31</td><td>0.31</td><td>0.32</td></tr> <tr><td>10.8</td><td>0.32</td><td>0.33</td><td>0.33</td></tr> <tr><td>9.6</td><td>0.36</td><td>0.35</td><td>0.36</td></tr> <tr><td>8.4</td><td>0.39</td><td>0.38</td><td>0.38</td></tr> <tr><td>7.2</td><td>0.42</td><td>0.41</td><td>0.41</td></tr> <tr><td>6.0</td><td>0.46</td><td>0.44</td><td>0.43</td></tr> <tr><td>4.8</td><td>0.49</td><td>0.46</td><td>0.45</td></tr> <tr><td>3.6</td><td>0.51</td><td>0.48</td><td>0.46</td></tr> <tr><td>2.4</td><td>0.52</td><td>0.48</td><td>0.46</td></tr> <tr><td>1.2</td><td>0.50</td><td>0.46</td><td>0.45</td></tr> <tr><td>0.0</td><td>0.57</td><td>0.53</td><td>0.58</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.0	0.13	0.13	0.13	11.4	0.31	0.31	0.32	10.8	0.32	0.33	0.33	9.6	0.36	0.35	0.36	8.4	0.39	0.38	0.38	7.2	0.42	0.41	0.41	6.0	0.46	0.44	0.43	4.8	0.49	0.46	0.45	3.6	0.51	0.48	0.46	2.4	0.52	0.48	0.46	1.2	0.50	0.46	0.45	0.0	0.57	0.53	0.58
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
12.0	0.13	0.13	0.13																																																							
11.4	0.31	0.31	0.32																																																							
10.8	0.32	0.33	0.33																																																							
9.6	0.36	0.35	0.36																																																							
8.4	0.39	0.38	0.38																																																							
7.2	0.42	0.41	0.41																																																							
6.0	0.46	0.44	0.43																																																							
4.8	0.49	0.46	0.45																																																							
3.6	0.51	0.48	0.46																																																							
2.4	0.52	0.48	0.46																																																							
1.2	0.50	0.46	0.45																																																							
0.0	0.57	0.53	0.58																																																							
Object	-12V0.13A																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>-11.4</td><td>0.31</td><td>0.31</td><td>0.32</td></tr> <tr><td>-10.8</td><td>0.32</td><td>0.32</td><td>0.33</td></tr> <tr><td>-9.6</td><td>0.35</td><td>0.35</td><td>0.36</td></tr> <tr><td>-8.4</td><td>0.39</td><td>0.38</td><td>0.38</td></tr> <tr><td>-7.2</td><td>0.42</td><td>0.41</td><td>0.41</td></tr> <tr><td>-6.0</td><td>0.46</td><td>0.44</td><td>0.43</td></tr> <tr><td>-4.8</td><td>0.48</td><td>0.46</td><td>0.45</td></tr> <tr><td>-3.6</td><td>0.51</td><td>0.48</td><td>0.46</td></tr> <tr><td>-2.4</td><td>0.52</td><td>0.48</td><td>0.46</td></tr> <tr><td>-1.2</td><td>0.50</td><td>0.46</td><td>0.45</td></tr> <tr><td>0.0</td><td>0.57</td><td>0.53</td><td>0.57</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-12.0	0.13	0.13	0.13	-11.4	0.31	0.31	0.32	-10.8	0.32	0.32	0.33	-9.6	0.35	0.35	0.36	-8.4	0.39	0.38	0.38	-7.2	0.42	0.41	0.41	-6.0	0.46	0.44	0.43	-4.8	0.48	0.46	0.45	-3.6	0.51	0.48	0.46	-2.4	0.52	0.48	0.46	-1.2	0.50	0.46	0.45	0.0	0.57	0.53	0.57
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
-12.0	0.13	0.13	0.13																																																							
-11.4	0.31	0.31	0.32																																																							
-10.8	0.32	0.32	0.33																																																							
-9.6	0.35	0.35	0.36																																																							
-8.4	0.39	0.38	0.38																																																							
-7.2	0.42	0.41	0.41																																																							
-6.0	0.46	0.44	0.43																																																							
-4.8	0.48	0.46	0.45																																																							
-3.6	0.51	0.48	0.46																																																							
-2.4	0.52	0.48	0.46																																																							
-1.2	0.50	0.46	0.45																																																							
0.0	0.57	0.53	0.57																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										




Figure A




Figure B (Ripple and Ripple noise Characteristic)