

TEST DATA OF SUTW32415

Regulated DC Power Supply
March 10, 2009

Approved by : Kazunari Asano Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW32415	Temperature Testing Circuitry 25°C Figure A																																																																											
Item	Input Current (by Input Voltage)																																																																												
Object	_____	2.Values																																																																											
1.Graph	<p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- - ○- - Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.008</td><td>0.007</td><td>0.008</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>9.2</td><td>0.034</td><td>0.232</td><td>0.436</td></tr> <tr><td>12.0</td><td>0.029</td><td>0.173</td><td>0.330</td></tr> <tr><td>16.0</td><td>0.024</td><td>0.130</td><td>0.243</td></tr> <tr><td>18.0</td><td>0.022</td><td>0.116</td><td>0.215</td></tr> <tr><td>20.0</td><td>0.021</td><td>0.105</td><td>0.193</td></tr> <tr><td>24.0</td><td>0.019</td><td>0.089</td><td>0.161</td></tr> <tr><td>28.0</td><td>0.017</td><td>0.077</td><td>0.139</td></tr> <tr><td>32.0</td><td>0.016</td><td>0.069</td><td>0.123</td></tr> <tr><td>36.0</td><td>0.016</td><td>0.062</td><td>0.110</td></tr> <tr><td>40.0</td><td>0.016</td><td>0.058</td><td>0.101</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	4.0	0.008	0.007	0.008	8.0	0.007	0.007	0.007	9.2	0.034	0.232	0.436	12.0	0.029	0.173	0.330	16.0	0.024	0.130	0.243	18.0	0.022	0.116	0.215	20.0	0.021	0.105	0.193	24.0	0.019	0.089	0.161	28.0	0.017	0.077	0.139	32.0	0.016	0.069	0.123	36.0	0.016	0.062	0.110	40.0	0.016	0.058	0.101	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																										
0.0	0.000	0.000	0.000																																																																										
4.0	0.008	0.007	0.008																																																																										
8.0	0.007	0.007	0.007																																																																										
9.2	0.034	0.232	0.436																																																																										
12.0	0.029	0.173	0.330																																																																										
16.0	0.024	0.130	0.243																																																																										
18.0	0.022	0.116	0.215																																																																										
20.0	0.021	0.105	0.193																																																																										
24.0	0.019	0.089	0.161																																																																										
28.0	0.017	0.077	0.139																																																																										
32.0	0.016	0.069	0.123																																																																										
36.0	0.016	0.062	0.110																																																																										
40.0	0.016	0.058	0.101																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										

Note: Slanted line shows the range of the rated input voltage.

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
4.0	0.008	0.007	0.008
8.0	0.007	0.007	0.007
9.2	0.034	0.232	0.436
12.0	0.029	0.173	0.330
16.0	0.024	0.130	0.243
18.0	0.022	0.116	0.215
20.0	0.021	0.105	0.193
24.0	0.019	0.089	0.161
28.0	0.017	0.077	0.139
32.0	0.016	0.069	0.123
36.0	0.016	0.062	0.110
40.0	0.016	0.058	0.101
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model	SUTW32415																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.022</td><td>0.019</td><td>0.016</td></tr> <tr><td>20</td><td>0.059</td><td>0.047</td><td>0.035</td></tr> <tr><td>40</td><td>0.097</td><td>0.074</td><td>0.053</td></tr> <tr><td>60</td><td>0.135</td><td>0.102</td><td>0.072</td></tr> <tr><td>80</td><td>0.174</td><td>0.131</td><td>0.091</td></tr> <tr><td>100</td><td>0.213</td><td>0.159</td><td>0.109</td></tr> <tr><td>110</td><td>0.233</td><td>0.174</td><td>0.119</td></tr> </tbody> </table>	Load Ration [%]	18V [A]	24V [A]	36V [A]	0	0.022	0.019	0.016	20	0.059	0.047	0.035	40	0.097	0.074	0.053	60	0.135	0.102	0.072	80	0.174	0.131	0.091	100	0.213	0.159	0.109	110	0.233	0.174	0.119																						
Load Ration [%]	18V [A]	24V [A]	36V [A]																																																				
0	0.022	0.019	0.016																																																				
20	0.059	0.047	0.035																																																				
40	0.097	0.074	0.053																																																				
60	0.135	0.102	0.072																																																				
80	0.174	0.131	0.091																																																				
100	0.213	0.159	0.109																																																				
110	0.233	0.174	0.119																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.022</td><td>0.019</td><td>0.016</td></tr> <tr><td>20</td><td>0.059</td><td>0.047</td><td>0.035</td></tr> <tr><td>40</td><td>0.097</td><td>0.074</td><td>0.053</td></tr> <tr><td>60</td><td>0.135</td><td>0.102</td><td>0.072</td></tr> <tr><td>80</td><td>0.174</td><td>0.131</td><td>0.091</td></tr> <tr><td>100</td><td>0.213</td><td>0.159</td><td>0.109</td></tr> <tr><td>110</td><td>0.233</td><td>0.174</td><td>0.119</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.022	0.019	0.016	20	0.059	0.047	0.035	40	0.097	0.074	0.053	60	0.135	0.102	0.072	80	0.174	0.131	0.091	100	0.213	0.159	0.109	110	0.233	0.174	0.119	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0	0.022	0.019	0.016																																																				
20	0.059	0.047	0.035																																																				
40	0.097	0.074	0.053																																																				
60	0.135	0.102	0.072																																																				
80	0.174	0.131	0.091																																																				
100	0.213	0.159	0.109																																																				
110	0.233	0.174	0.119																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	SUTW32415	Temperature Testing Circuitry 25°C Figure A																																															
Item	Input Power (by Load Current)																																																
Object	_____																																																
1.Graph		2.Values																																															
<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [W]</th> <th>24V [W]</th> <th>36V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.39</td><td>0.43</td><td>0.55</td></tr> <tr><td>20</td><td>1.06</td><td>1.11</td><td>1.24</td></tr> <tr><td>40</td><td>1.74</td><td>1.79</td><td>1.91</td></tr> <tr><td>60</td><td>2.42</td><td>2.46</td><td>2.59</td></tr> <tr><td>80</td><td>3.12</td><td>3.14</td><td>3.26</td></tr> <tr><td>100</td><td>3.83</td><td>3.84</td><td>3.94</td></tr> <tr><td>110</td><td>4.18</td><td>4.19</td><td>4.28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	18V [W]	24V [W]	36V [W]	0	0.39	0.43	0.55	20	1.06	1.11	1.24	40	1.74	1.79	1.91	60	2.42	2.46	2.59	80	3.12	3.14	3.26	100	3.83	3.84	3.94	110	4.18	4.19	4.28	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	18V [W]	24V [W]	36V [W]																																														
0	0.39	0.43	0.55																																														
20	1.06	1.11	1.24																																														
40	1.74	1.79	1.91																																														
60	2.42	2.46	2.59																																														
80	3.12	3.14	3.26																																														
100	3.83	3.84	3.94																																														
110	4.18	4.19	4.28																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														


Model	SUTW32415	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (10 to 50). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>72.2</td><td>77.9</td></tr> <tr><td>18</td><td>72.0</td><td>78.3</td></tr> <tr><td>20</td><td>71.8</td><td>78.3</td></tr> <tr><td>24</td><td>70.6</td><td>78.3</td></tr> <tr><td>30</td><td>69.0</td><td>77.6</td></tr> <tr><td>36</td><td>66.9</td><td>76.4</td></tr> <tr><td>40</td><td>64.8</td><td>75.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	72.2	77.9	18	72.0	78.3	20	71.8	78.3	24	70.6	78.3	30	69.0	77.6	36	66.9	76.4	40	64.8	75.2	--	-	-	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
16	72.2	77.9																													
18	72.0	78.3																													
20	71.8	78.3																													
24	70.6	78.3																													
30	69.0	77.6																													
36	66.9	76.4																													
40	64.8	75.2																													
--	-	-																													
--	-	-																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTW32415	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Efficiency (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 18V - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [Efficiency %]</th> <th>24V [Efficiency %]</th> <th>36V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>56.7</td><td>54.2</td><td>48.6</td></tr> <tr><td>40</td><td>69.1</td><td>67.3</td><td>62.9</td></tr> <tr><td>60</td><td>74.3</td><td>73.2</td><td>69.6</td></tr> <tr><td>80</td><td>77.0</td><td>76.4</td><td>73.7</td></tr> <tr><td>100</td><td>78.4</td><td>78.3</td><td>76.2</td></tr> <tr><td>110</td><td>79.0</td><td>78.9</td><td>77.2</td></tr> </tbody> </table>		Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]	20	56.7	54.2	48.6	40	69.1	67.3	62.9	60	74.3	73.2	69.6	80	77.0	76.4	73.7	100	78.4	78.3	76.2	110	79.0	78.9	77.2																							
Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]																																																	
20	56.7	54.2	48.6																																																	
40	69.1	67.3	62.9																																																	
60	74.3	73.2	69.6																																																	
80	77.0	76.4	73.7																																																	
100	78.4	78.3	76.2																																																	
110	79.0	78.9	77.2																																																	
<table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [Efficiency %]</th> <th>24V [Efficiency %]</th> <th>36V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>56.7</td><td>54.2</td><td>48.6</td></tr> <tr><td>40</td><td>69.1</td><td>67.3</td><td>62.9</td></tr> <tr><td>60</td><td>74.3</td><td>73.2</td><td>69.6</td></tr> <tr><td>80</td><td>77.0</td><td>76.4</td><td>73.7</td></tr> <tr><td>100</td><td>78.4</td><td>78.3</td><td>76.2</td></tr> <tr><td>110</td><td>79.0</td><td>78.9</td><td>77.2</td></tr> </tbody> </table>		Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]	20	56.7	54.2	48.6	40	69.1	67.3	62.9	60	74.3	73.2	69.6	80	77.0	76.4	73.7	100	78.4	78.3	76.2	110	79.0	78.9	77.2																							
Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]																																																	
20	56.7	54.2	48.6																																																	
40	69.1	67.3	62.9																																																	
60	74.3	73.2	69.6																																																	
80	77.0	76.4	73.7																																																	
100	78.4	78.3	76.2																																																	
110	79.0	78.9	77.2																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>56.7</td><td>54.2</td><td>48.6</td></tr> <tr><td>40</td><td>69.1</td><td>67.3</td><td>62.9</td></tr> <tr><td>60</td><td>74.3</td><td>73.2</td><td>69.6</td></tr> <tr><td>80</td><td>77.0</td><td>76.4</td><td>73.7</td></tr> <tr><td>100</td><td>78.4</td><td>78.3</td><td>76.2</td></tr> <tr><td>110</td><td>79.0</td><td>78.9</td><td>77.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	56.7	54.2	48.6	40	69.1	67.3	62.9	60	74.3	73.2	69.6	80	77.0	76.4	73.7	100	78.4	78.3	76.2	110	79.0	78.9	77.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																			
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																	
0	-	-	-																																																	
20	56.7	54.2	48.6																																																	
40	69.1	67.3	62.9																																																	
60	74.3	73.2	69.6																																																	
80	77.0	76.4	73.7																																																	
100	78.4	78.3	76.2																																																	
110	79.0	78.9	77.2																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Model	SUTW32415
Item	Line Regulation
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	15.078	15.012
18	15.076	15.012
20	15.074	15.012
24	15.071	15.012
30	15.068	15.012
36	15.068	15.012
40	15.067	15.013
--	-	-
--	-	-

Object -15V0.1A

1.Graph





2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-15.061	-14.994
18	-15.058	-14.994
20	-15.056	-14.994
24	-15.053	-14.994
30	-15.051	-14.994
36	-15.050	-14.994
40	-15.049	-14.994
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW32415	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.1A																																																					
1.Graph	—△— Input Volt. 18V - - □ - - Input Volt. 24V - · ○ - - Input Volt. 36V																																																					
																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.247</td><td>15.237</td><td>15.227</td></tr> <tr><td>0.02</td><td>15.135</td><td>15.130</td><td>15.125</td></tr> <tr><td>0.04</td><td>15.093</td><td>15.086</td><td>15.083</td></tr> <tr><td>0.06</td><td>15.061</td><td>15.057</td><td>15.055</td></tr> <tr><td>0.08</td><td>15.034</td><td>15.032</td><td>15.031</td></tr> <tr><td>0.10</td><td>15.011</td><td>15.011</td><td>15.011</td></tr> <tr><td>0.11</td><td>15.000</td><td>15.001</td><td>15.002</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	15.247	15.237	15.227	0.02	15.135	15.130	15.125	0.04	15.093	15.086	15.083	0.06	15.061	15.057	15.055	0.08	15.034	15.032	15.031	0.10	15.011	15.011	15.011	0.11	15.000	15.001	15.002	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	15.247	15.237	15.227																																																			
0.02	15.135	15.130	15.125																																																			
0.04	15.093	15.086	15.083																																																			
0.06	15.061	15.057	15.055																																																			
0.08	15.034	15.032	15.031																																																			
0.10	15.011	15.011	15.011																																																			
0.11	15.000	15.001	15.002																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.1A																																																					
1.Graph	—△— Input Volt. 18V - - □ - - Input Volt. 24V - · ○ - - Input Volt. 36V																																																					
																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.232</td><td>-15.222</td><td>-15.210</td></tr> <tr><td>0.02</td><td>-15.118</td><td>-15.112</td><td>-15.107</td></tr> <tr><td>0.04</td><td>-15.074</td><td>-15.069</td><td>-15.065</td></tr> <tr><td>0.06</td><td>-15.043</td><td>-15.039</td><td>-15.036</td></tr> <tr><td>0.08</td><td>-15.017</td><td>-15.015</td><td>-15.013</td></tr> <tr><td>0.10</td><td>-14.994</td><td>-14.993</td><td>-14.994</td></tr> <tr><td>0.11</td><td>-14.982</td><td>-14.983</td><td>-14.985</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-15.232	-15.222	-15.210	0.02	-15.118	-15.112	-15.107	0.04	-15.074	-15.069	-15.065	0.06	-15.043	-15.039	-15.036	0.08	-15.017	-15.015	-15.013	0.10	-14.994	-14.993	-14.994	0.11	-14.982	-14.983	-14.985	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-15.232	-15.222	-15.210																																																			
0.02	-15.118	-15.112	-15.107																																																			
0.04	-15.074	-15.069	-15.065																																																			
0.06	-15.043	-15.039	-15.036																																																			
0.08	-15.017	-15.015	-15.013																																																			
0.10	-14.994	-14.993	-14.994																																																			
0.11	-14.982	-14.983	-14.985																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						
		- 7 -																																																				
		BC-10255																																																				

COSEL




COSEL



Model	SUTW32415
Item	Ripple Voltage (by Load Current)
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	1	1
0.02	2	1
0.04	2	2
0.06	2	2
0.08	4	2
0.10	6	2
0.11	8	3
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW32415
Item	Ripple Voltage (by Load Current)
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	1	1
0.02	1	1
0.04	2	2
0.06	2	2
0.08	3	2
0.10	5	2
0.11	6	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW32415
Item	Ripple-Noise
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	4	4
0.02	7	6
0.04	7	7
0.06	9	7
0.08	12	9
0.10	15	9
0.11	17	10
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW32415
Item	Ripple-Noise
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	10	10
0.02	12	13
0.04	13	14
0.06	13	14
0.08	13	14
0.10	14	15
0.11	14	15
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form


Model	SUTW32415
-------	-----------

Item	Ripple Voltage (by Ambient Temp.)
------	-----------------------------------

Object	+15V0.1A
--------	----------

1.Graph

--- □--- Load 50%
 —△— Load 100%



Input Volt. 24V


Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	4	10
-20	4	9
0	4	6
25	3	6
55	3	5
60	3	5
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph

--- □--- Load 50%
 —△— Load 100%



Input Volt. 24V

2.Values



Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	6	7
-40	7	8
-20	6	7
0	6	7
25	6	6
55	5	6
60	5	6
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW32415
Item	Ambient Temperature Drift
Object	+15V0.1A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	14.949	14.949	14.950
-40	14.973	14.973	14.973
-20	14.990	14.990	14.991
0	15.004	15.003	15.003
25	15.012	15.011	15.011
55	15.012	15.011	15.011
60	15.011	15.010	15.010
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-14.927	-14.929	-14.930
-40	-14.951	-14.953	-14.954
-20	-14.970	-14.971	-14.972
0	-14.984	-14.984	-14.984
25	-14.993	-14.993	-14.993
55	-14.993	-14.993	-14.993
60	-14.992	-14.992	-14.992
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW32415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object	+15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	18		0	15.251	
Minimum Voltage	-40	18	0.1	14.755	±248	±1.7

Object	-15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	18		0	-15.236	
Minimum Voltage	-40	18	0.1	-14.739	±249	±1.7

COSEL

Model	SUTW32415
Item	Time Lapse Drift
Object	+15V0.1A


1.Graph



Input Volt. 24V
Load 100%

Object	-15V0.1A
--------	----------

1.Graph



Input Volt. 24V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.007
0.5	15.010
1.0	15.010
2.0	15.010
3.0	15.010
4.0	15.010
5.0	15.010
6.0	15.010
7.0	15.010
8.0	15.010

2.Values


Time since start [H]	Output Voltage [V]
0.0	-14.994
0.5	-14.996
1.0	-14.996
2.0	-14.996
3.0	-14.996
4.0	-14.996
5.0	-14.996
6.0	-14.996
7.0	-14.996
8.0	-14.996

COSEL

Model	SUTW32415
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	2.8	2.9	1.6	2.4	
100 %		0.2	2.9	3.1	0.8	1.3	




COSEL

Model	SUTW32415
Item	Rise and Fall Time
Object	-15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	2.8	3.0	1.6	3.1
100 %		0.2	3.0	3.2	0.8	1.6



COSEL

Model	SUTW32415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.1A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.0	9.0
-40	5.9	8.9
-20	6.2	8.7
0	6.2	8.9
25	6.2	9.3
55	6.4	9.6
60	6.4	9.6
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.1A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.0	9.0
-40	6.1	8.7
-20	6.2	8.7
0	6.2	8.9
25	6.2	9.1
55	6.4	9.4
60	6.4	9.6
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

		Temperature Testing Circuitry 25°C Figure A		
Model	SUTW32415			
Item	Overcurrent Protection			
Object	+15V0.1A			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>	2.Values		
2.Values				
Object	-15V0.1A	2.Values		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>			
2.Values				
Note: Slanted line shows the range of the rated load current.				




Figure A




Figure B (Ripple and Ripple noise Characteristic)