

TEST DATA OF SUTW34812

Regulated DC Power Supply
March 12, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>16.0</td><td>0.005</td><td>0.006</td><td>0.006</td></tr> <tr><td>19.2</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>21.6</td><td>0.013</td><td>0.099</td><td>0.187</td></tr> <tr><td>24.0</td><td>0.013</td><td>0.089</td><td>0.171</td></tr> <tr><td>33.0</td><td>0.012</td><td>0.065</td><td>0.123</td></tr> <tr><td>36.0</td><td>0.011</td><td>0.060</td><td>0.113</td></tr> <tr><td>40.0</td><td>0.010</td><td>0.055</td><td>0.102</td></tr> <tr><td>48.0</td><td>0.010</td><td>0.045</td><td>0.085</td></tr> <tr><td>60.0</td><td>0.010</td><td>0.038</td><td>0.068</td></tr> <tr><td>70.0</td><td>0.010</td><td>0.033</td><td>0.060</td></tr> <tr><td>76.0</td><td>0.010</td><td>0.031</td><td>0.056</td></tr> <tr><td>80.0</td><td>0.011</td><td>0.031</td><td>0.054</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.007	0.007	0.007	16.0	0.005	0.006	0.006	19.2	0.005	0.005	0.005	21.6	0.013	0.099	0.187	24.0	0.013	0.089	0.171	33.0	0.012	0.065	0.123	36.0	0.011	0.060	0.113	40.0	0.010	0.055	0.102	48.0	0.010	0.045	0.085	60.0	0.010	0.038	0.068	70.0	0.010	0.033	0.060	76.0	0.010	0.031	0.056	80.0	0.011	0.031	0.054	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.007	0.007	0.007																																																																																
16.0	0.005	0.006	0.006																																																																																
19.2	0.005	0.005	0.005																																																																																
21.6	0.013	0.099	0.187																																																																																
24.0	0.013	0.089	0.171																																																																																
33.0	0.012	0.065	0.123																																																																																
36.0	0.011	0.060	0.113																																																																																
40.0	0.010	0.055	0.102																																																																																
48.0	0.010	0.045	0.085																																																																																
60.0	0.010	0.038	0.068																																																																																
70.0	0.010	0.033	0.060																																																																																
76.0	0.010	0.031	0.056																																																																																
80.0	0.011	0.031	0.054																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW34812																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 36V ---□--- Input Volt. 48V ---○--- Input Volt. 76V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [A]</th> <th>48V [A]</th> <th>76V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.011</td><td>0.010</td><td>0.010</td></tr> <tr><td>20</td><td>0.030</td><td>0.024</td><td>0.019</td></tr> <tr><td>40</td><td>0.050</td><td>0.038</td><td>0.027</td></tr> <tr><td>60</td><td>0.070</td><td>0.053</td><td>0.037</td></tr> <tr><td>80</td><td>0.090</td><td>0.068</td><td>0.046</td></tr> <tr><td>100</td><td>0.111</td><td>0.084</td><td>0.055</td></tr> <tr><td>110</td><td>0.122</td><td>0.092</td><td>0.060</td></tr> </tbody> </table>			Load Ration [%]	36V [A]	48V [A]	76V [A]	0	0.011	0.010	0.010	20	0.030	0.024	0.019	40	0.050	0.038	0.027	60	0.070	0.053	0.037	80	0.090	0.068	0.046	100	0.111	0.084	0.055	110	0.122	0.092	0.060																			
Load Ration [%]	36V [A]	48V [A]	76V [A]																																																			
0	0.011	0.010	0.010																																																			
20	0.030	0.024	0.019																																																			
40	0.050	0.038	0.027																																																			
60	0.070	0.053	0.037																																																			
80	0.090	0.068	0.046																																																			
100	0.111	0.084	0.055																																																			
110	0.122	0.092	0.060																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.011</td><td>0.010</td><td>0.010</td></tr> <tr><td>20</td><td>0.030</td><td>0.024</td><td>0.019</td></tr> <tr><td>40</td><td>0.050</td><td>0.038</td><td>0.027</td></tr> <tr><td>60</td><td>0.070</td><td>0.053</td><td>0.037</td></tr> <tr><td>80</td><td>0.090</td><td>0.068</td><td>0.046</td></tr> <tr><td>100</td><td>0.111</td><td>0.084</td><td>0.055</td></tr> <tr><td>110</td><td>0.122</td><td>0.092</td><td>0.060</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.011	0.010	0.010	20	0.030	0.024	0.019	40	0.050	0.038	0.027	60	0.070	0.053	0.037	80	0.090	0.068	0.046	100	0.111	0.084	0.055	110	0.122	0.092	0.060	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.011	0.010	0.010																																																			
20	0.030	0.024	0.019																																																			
40	0.050	0.038	0.027																																																			
60	0.070	0.053	0.037																																																			
80	0.090	0.068	0.046																																																			
100	0.111	0.084	0.055																																																			
110	0.122	0.092	0.060																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																																															
Item	Input Power (by Load Current)																																																
Object	_____																																																
1.Graph		2.Values																																															
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.33</td><td>0.37</td><td>0.57</td></tr> <tr><td>20</td><td>1.05</td><td>1.09</td><td>1.29</td></tr> <tr><td>40</td><td>1.77</td><td>1.81</td><td>1.99</td></tr> <tr><td>60</td><td>2.51</td><td>2.52</td><td>2.71</td></tr> <tr><td>80</td><td>3.25</td><td>3.27</td><td>3.43</td></tr> <tr><td>100</td><td>4.01</td><td>4.01</td><td>4.16</td></tr> <tr><td>110</td><td>4.40</td><td>4.38</td><td>4.51</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0	0.33	0.37	0.57	20	1.05	1.09	1.29	40	1.77	1.81	1.99	60	2.51	2.52	2.71	80	3.25	3.27	3.43	100	4.01	4.01	4.16	110	4.40	4.38	4.51	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																														
0	0.33	0.37	0.57																																														
20	1.05	1.09	1.29																																														
40	1.77	1.81	1.99																																														
60	2.51	2.52	2.71																																														
80	3.25	3.27	3.43																																														
100	4.01	4.01	4.16																																														
110	4.40	4.38	4.51																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														

Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1.Graph		2.Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>74.2</td><td>78.3</td></tr> <tr><td>36</td><td>74.2</td><td>78.8</td></tr> <tr><td>40</td><td>73.9</td><td>78.9</td></tr> <tr><td>48</td><td>72.8</td><td>79.0</td></tr> <tr><td>55</td><td>72.2</td><td>78.7</td></tr> <tr><td>60</td><td>71.2</td><td>78.1</td></tr> <tr><td>70</td><td>68.7</td><td>76.8</td></tr> <tr><td>76</td><td>67.2</td><td>76.3</td></tr> <tr><td>80</td><td>65.6</td><td>74.8</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	74.2	78.3	36	74.2	78.8	40	73.9	78.9	48	72.8	79.0	55	72.2	78.7	60	71.2	78.1	70	68.7	76.8	76	67.2	76.3	80	65.6	74.8
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
33	74.2	78.3																													
36	74.2	78.8																													
40	73.9	78.9																													
48	72.8	79.0																													
55	72.2	78.7																													
60	71.2	78.1																													
70	68.7	76.8																													
76	67.2	76.3																													
80	65.6	74.8																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [Efficiency %]</th> <th>48V [Efficiency %]</th> <th>76V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>60.3</td><td>57.7</td><td>49.0</td></tr> <tr><td>40</td><td>71.3</td><td>69.8</td><td>63.5</td></tr> <tr><td>60</td><td>75.4</td><td>75.0</td><td>70.0</td></tr> <tr><td>80</td><td>77.7</td><td>77.3</td><td>73.7</td></tr> <tr><td>100</td><td>78.7</td><td>78.8</td><td>75.9</td></tr> <tr><td>110</td><td>78.9</td><td>79.3</td><td>76.9</td></tr> </tbody> </table>	Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]	20	60.3	57.7	49.0	40	71.3	69.8	63.5	60	75.4	75.0	70.0	80	77.7	77.3	73.7	100	78.7	78.8	75.9	110	78.9	79.3	76.9																								
Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]																																																		
20	60.3	57.7	49.0																																																		
40	71.3	69.8	63.5																																																		
60	75.4	75.0	70.0																																																		
80	77.7	77.3	73.7																																																		
100	78.7	78.8	75.9																																																		
110	78.9	79.3	76.9																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>60.3</td><td>57.7</td><td>49.0</td></tr> <tr><td>40</td><td>71.3</td><td>69.8</td><td>63.5</td></tr> <tr><td>60</td><td>75.4</td><td>75.0</td><td>70.0</td></tr> <tr><td>80</td><td>77.7</td><td>77.3</td><td>73.7</td></tr> <tr><td>100</td><td>78.7</td><td>78.8</td><td>75.9</td></tr> <tr><td>110</td><td>78.9</td><td>79.3</td><td>76.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	60.3	57.7	49.0	40	71.3	69.8	63.5	60	75.4	75.0	70.0	80	77.7	77.3	73.7	100	78.7	78.8	75.9	110	78.9	79.3	76.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	60.3	57.7	49.0																																																		
40	71.3	69.8	63.5																																																		
60	75.4	75.0	70.0																																																		
80	77.7	77.3	73.7																																																		
100	78.7	78.8	75.9																																																		
110	78.9	79.3	76.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		


Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+12V0.13A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>12.205</td><td>12.131</td></tr> <tr><td>36</td><td>12.202</td><td>12.131</td></tr> <tr><td>40</td><td>12.199</td><td>12.132</td></tr> <tr><td>48</td><td>12.195</td><td>12.132</td></tr> <tr><td>55</td><td>12.192</td><td>12.132</td></tr> <tr><td>60</td><td>12.191</td><td>12.132</td></tr> <tr><td>70</td><td>12.189</td><td>12.132</td></tr> <tr><td>76</td><td>12.189</td><td>12.132</td></tr> <tr><td>80</td><td>12.188</td><td>12.132</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	12.205	12.131	36	12.202	12.131	40	12.199	12.132	48	12.195	12.132	55	12.192	12.132	60	12.191	12.132	70	12.189	12.132	76	12.189	12.132	80	12.188	12.132
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	12.205	12.131																																
36	12.202	12.131																																
40	12.199	12.132																																
48	12.195	12.132																																
55	12.192	12.132																																
60	12.191	12.132																																
70	12.189	12.132																																
76	12.189	12.132																																
80	12.188	12.132																																
Object -12V0.13A		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-12.210</td><td>-12.134</td></tr> <tr><td>36</td><td>-12.207</td><td>-12.134</td></tr> <tr><td>40</td><td>-12.204</td><td>-12.134</td></tr> <tr><td>48</td><td>-12.200</td><td>-12.135</td></tr> <tr><td>55</td><td>-12.198</td><td>-12.135</td></tr> <tr><td>60</td><td>-12.197</td><td>-12.135</td></tr> <tr><td>70</td><td>-12.196</td><td>-12.135</td></tr> <tr><td>76</td><td>-12.195</td><td>-12.135</td></tr> <tr><td>80</td><td>-12.195</td><td>-12.136</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-12.210	-12.134	36	-12.207	-12.134	40	-12.204	-12.134	48	-12.200	-12.135	55	-12.198	-12.135	60	-12.197	-12.135	70	-12.196	-12.135	76	-12.195	-12.135	80	-12.195	-12.136
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	-12.210	-12.134																																
36	-12.207	-12.134																																
40	-12.204	-12.134																																
48	-12.200	-12.135																																
55	-12.198	-12.135																																
60	-12.197	-12.135																																
70	-12.196	-12.135																																
76	-12.195	-12.135																																
80	-12.195	-12.136																																
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL


Model	SUTW34812	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V0.13A																																																					
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>	2.Values																																																				
	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.374</td><td>12.365</td><td>12.357</td></tr> <tr><td>0.026</td><td>12.263</td><td>12.255</td><td>12.247</td></tr> <tr><td>0.052</td><td>12.220</td><td>12.212</td><td>12.205</td></tr> <tr><td>0.078</td><td>12.186</td><td>12.180</td><td>12.175</td></tr> <tr><td>0.104</td><td>12.158</td><td>12.154</td><td>12.151</td></tr> <tr><td>0.130</td><td>12.130</td><td>12.130</td><td>12.130</td></tr> <tr><td>0.143</td><td>12.116</td><td>12.118</td><td>12.120</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.374	12.365	12.357	0.026	12.263	12.255	12.247	0.052	12.220	12.212	12.205	0.078	12.186	12.180	12.175	0.104	12.158	12.154	12.151	0.130	12.130	12.130	12.130	0.143	12.116	12.118	12.120	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	12.374	12.365	12.357																																																			
0.026	12.263	12.255	12.247																																																			
0.052	12.220	12.212	12.205																																																			
0.078	12.186	12.180	12.175																																																			
0.104	12.158	12.154	12.151																																																			
0.130	12.130	12.130	12.130																																																			
0.143	12.116	12.118	12.120																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.13A	2.Values																																																				
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.389</td><td>-12.380</td><td>-12.372</td></tr> <tr><td>0.026</td><td>-12.269</td><td>-12.261</td><td>-12.256</td></tr> <tr><td>0.052</td><td>-12.224</td><td>-12.216</td><td>-12.211</td></tr> <tr><td>0.078</td><td>-12.190</td><td>-12.184</td><td>-12.181</td></tr> <tr><td>0.104</td><td>-12.161</td><td>-12.157</td><td>-12.156</td></tr> <tr><td>0.130</td><td>-12.132</td><td>-12.132</td><td>-12.134</td></tr> <tr><td>0.143</td><td>-12.119</td><td>-12.121</td><td>-12.124</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.389	-12.380	-12.372	0.026	-12.269	-12.261	-12.256	0.052	-12.224	-12.216	-12.211	0.078	-12.190	-12.184	-12.181	0.104	-12.161	-12.157	-12.156	0.130	-12.132	-12.132	-12.134	0.143	-12.119	-12.121	-12.124	--	-	-	-	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	-12.389	-12.380	-12.372																																																			
0.026	-12.269	-12.261	-12.256																																																			
0.052	-12.224	-12.216	-12.211																																																			
0.078	-12.190	-12.184	-12.181																																																			
0.104	-12.161	-12.157	-12.156																																																			
0.130	-12.132	-12.132	-12.134																																																			
0.143	-12.119	-12.121	-12.124																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL




COSEL



Model	SUTW34812
Item	Ripple Voltage (by Load Current)
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	1	1
0.026	1	1
0.052	2	1
0.078	4	2
0.104	8	2
0.130	12	2
0.143	15	2
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW34812
Item	Ripple Voltage (by Load Current)
Object	-12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	2	1
0.026	2	1
0.052	2	2
0.078	4	2
0.104	5	2
0.130	10	2
0.143	12	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW34812
Item	Ripple-Noise
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	4	4
0.026	6	7
0.052	8	8
0.078	11	8
0.104	15	9
0.130	20	11
0.143	24	12
--	-	-
--	-	-
--	-	-
--	-	-



Model	SUTW34812
Item	Ripple-Noise
Object	-12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	11	11
0.026	14	15
0.052	14	16
0.078	14	16
0.104	14	16
0.130	16	16
0.143	20	16
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW34812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.13A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	6	12
-40	6	12
-20	5	9
0	5	8
25	4	7
55	4	7
60	4	7
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	6	8
-40	6	8
-20	5	8
0	5	7
25	5	6
55	4	6
60	4	6
--	-	-
--	-	-
--	-	-
--	-	-


Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW34812
Item	Ambient Temperature Drift
Object	+12V0.13A

Testing Circuitry Figure A


- 1.Graph
- △— Input Volt. 36V
 - - - □ - - Input Volt. 48V
 - · ○ - - Input Volt. 76V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	12.054	12.055	12.055
-40	12.081	12.082	12.082
-20	12.102	12.103	12.103
0	12.119	12.119	12.119
25	12.131	12.131	12.131
55	12.136	12.135	12.135
60	12.136	12.135	12.135
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

- 1.Graph
- △— Input Volt. 36V
 - - - □ - - Input Volt. 48V
 - · ○ - - Input Volt. 76V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-12.052	-12.056	-12.058
-40	-12.081	-12.083	-12.085
-20	-12.102	-12.105	-12.106
0	-12.119	-12.121	-12.122
25	-12.132	-12.133	-12.134
55	-12.137	-12.138	-12.139
60	-12.137	-12.138	-12.138
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW34812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.13A (AVR 2) : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	36	0	12.386	± 273	± 2.3	
Minimum Voltage	-40	36	0.13	11.841			

Object		-12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	36	0	-12.402	± 271	± 2.3	
Minimum Voltage	-40	36	0.13	-11.861			

COSEL


Model	SUTW34812	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+12V0.13A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.123</td></tr> <tr><td>0.5</td><td>12.131</td></tr> <tr><td>1.0</td><td>12.131</td></tr> <tr><td>2.0</td><td>12.131</td></tr> <tr><td>3.0</td><td>12.131</td></tr> <tr><td>4.0</td><td>12.131</td></tr> <tr><td>5.0</td><td>12.131</td></tr> <tr><td>6.0</td><td>12.131</td></tr> <tr><td>7.0</td><td>12.131</td></tr> <tr><td>8.0</td><td>12.131</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.123	0.5	12.131	1.0	12.131	2.0	12.131	3.0	12.131	4.0	12.131	5.0	12.131	6.0	12.131	7.0	12.131	8.0	12.131
Time since start [H]	Output Voltage [V]																							
0.0	12.123																							
0.5	12.131																							
1.0	12.131																							
2.0	12.131																							
3.0	12.131																							
4.0	12.131																							
5.0	12.131																							
6.0	12.131																							
7.0	12.131																							
8.0	12.131																							
Object -12V0.13A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.131</td></tr> <tr><td>0.5</td><td>-12.137</td></tr> <tr><td>1.0</td><td>-12.137</td></tr> <tr><td>2.0</td><td>-12.137</td></tr> <tr><td>3.0</td><td>-12.137</td></tr> <tr><td>4.0</td><td>-12.137</td></tr> <tr><td>5.0</td><td>-12.137</td></tr> <tr><td>6.0</td><td>-12.137</td></tr> <tr><td>7.0</td><td>-12.137</td></tr> <tr><td>8.0</td><td>-12.137</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.131	0.5	-12.137	1.0	-12.137	2.0	-12.137	3.0	-12.137	4.0	-12.137	5.0	-12.137	6.0	-12.137	7.0	-12.137	8.0	-12.137
Time since start [H]	Output Voltage [V]																							
0.0	-12.131																							
0.5	-12.137																							
1.0	-12.137																							
2.0	-12.137																							
3.0	-12.137																							
4.0	-12.137																							
5.0	-12.137																							
6.0	-12.137																							
7.0	-12.137																							
8.0	-12.137																							

COSEL

Model	SUTW34812
Item	Rise and Fall Time
Object	+12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	1.8	2.0	5.7	2.5
100 %		0.2	1.9	2.1	2.8	1.5




COSEL

Model	SUTW34812
Item	Rise and Fall Time
Object	-12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.2	2.0	2.2	5.7	2.8	
100 %		0.2	2.2	2.4	2.7	1.7	



COSEL

Model	SUTW34812																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry	Figure A																																						
Object	+12V0.13A																																								
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>-60</td><td>14.1</td><td>20.1</td></tr> <tr><td>-40</td><td>13.7</td><td>19.7</td></tr> <tr><td>-20</td><td>13.7</td><td>20.1</td></tr> <tr><td>0</td><td>13.7</td><td>20.5</td></tr> <tr><td>25</td><td>14.1</td><td>21.3</td></tr> <tr><td>55</td><td>14.5</td><td>22.5</td></tr> <tr><td>60</td><td>14.5</td><td>22.5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	14.1	20.1	-40	13.7	19.7	-20	13.7	20.1	0	13.7	20.5	25	14.1	21.3	55	14.5	22.5	60	14.5	22.5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	14.1	20.1																																							
-40	13.7	19.7																																							
-20	13.7	20.1																																							
0	13.7	20.5																																							
25	14.1	21.3																																							
55	14.5	22.5																																							
60	14.5	22.5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>-60</td><td>14.1</td><td>19.7</td></tr> <tr><td>-40</td><td>13.7</td><td>19.7</td></tr> <tr><td>-20</td><td>13.7</td><td>20.1</td></tr> <tr><td>0</td><td>13.7</td><td>20.5</td></tr> <tr><td>25</td><td>14.1</td><td>21.3</td></tr> <tr><td>55</td><td>14.5</td><td>22.5</td></tr> <tr><td>60</td><td>14.5</td><td>22.5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	14.1	19.7	-40	13.7	19.7	-20	13.7	20.1	0	13.7	20.5	25	14.1	21.3	55	14.5	22.5	60	14.5	22.5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	14.1	19.7																																							
-40	13.7	19.7																																							
-20	13.7	20.1																																							
0	13.7	20.5																																							
25	14.1	21.3																																							
55	14.5	22.5																																							
60	14.5	22.5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

Model	SUTW34812																																																										
Item	Overcurrent Protection		Temperature Testing Circuitry	25°C Figure A																																																							
Object	+12V0.13A																																																										
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>11.4</td><td>0.28</td><td>0.29</td><td>0.32</td></tr> <tr><td>10.8</td><td>0.29</td><td>0.31</td><td>0.33</td></tr> <tr><td>9.6</td><td>0.33</td><td>0.34</td><td>0.37</td></tr> <tr><td>8.4</td><td>0.37</td><td>0.37</td><td>0.39</td></tr> <tr><td>7.2</td><td>0.40</td><td>0.41</td><td>0.42</td></tr> <tr><td>6.0</td><td>0.44</td><td>0.44</td><td>0.45</td></tr> <tr><td>4.8</td><td>0.48</td><td>0.47</td><td>0.47</td></tr> <tr><td>3.6</td><td>0.51</td><td>0.49</td><td>0.48</td></tr> <tr><td>2.4</td><td>0.53</td><td>0.49</td><td>0.48</td></tr> <tr><td>1.2</td><td>0.51</td><td>0.47</td><td>0.46</td></tr> <tr><td>0.0</td><td>0.43</td><td>0.41</td><td>0.45</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.13	0.13	0.13	11.4	0.28	0.29	0.32	10.8	0.29	0.31	0.33	9.6	0.33	0.34	0.37	8.4	0.37	0.37	0.39	7.2	0.40	0.41	0.42	6.0	0.44	0.44	0.45	4.8	0.48	0.47	0.47	3.6	0.51	0.49	0.48	2.4	0.53	0.49	0.48	1.2	0.51	0.47	0.46	0.0	0.43	0.41	0.45
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																								
12.0	0.13	0.13	0.13																																																								
11.4	0.28	0.29	0.32																																																								
10.8	0.29	0.31	0.33																																																								
9.6	0.33	0.34	0.37																																																								
8.4	0.37	0.37	0.39																																																								
7.2	0.40	0.41	0.42																																																								
6.0	0.44	0.44	0.45																																																								
4.8	0.48	0.47	0.47																																																								
3.6	0.51	0.49	0.48																																																								
2.4	0.53	0.49	0.48																																																								
1.2	0.51	0.47	0.46																																																								
0.0	0.43	0.41	0.45																																																								
Object		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>-11.4</td><td>0.27</td><td>0.29</td><td>0.32</td></tr> <tr><td>-10.8</td><td>0.29</td><td>0.31</td><td>0.34</td></tr> <tr><td>-9.6</td><td>0.32</td><td>0.34</td><td>0.36</td></tr> <tr><td>-8.4</td><td>0.36</td><td>0.37</td><td>0.39</td></tr> <tr><td>-7.2</td><td>0.40</td><td>0.41</td><td>0.42</td></tr> <tr><td>-6.0</td><td>0.44</td><td>0.44</td><td>0.44</td></tr> <tr><td>-4.8</td><td>0.48</td><td>0.47</td><td>0.47</td></tr> <tr><td>-3.6</td><td>0.51</td><td>0.49</td><td>0.48</td></tr> <tr><td>-2.4</td><td>0.53</td><td>0.49</td><td>0.48</td></tr> <tr><td>-1.2</td><td>0.51</td><td>0.47</td><td>0.46</td></tr> <tr><td>0.0</td><td>0.43</td><td>0.42</td><td>0.45</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-12.0	0.13	0.13	0.13	-11.4	0.27	0.29	0.32	-10.8	0.29	0.31	0.34	-9.6	0.32	0.34	0.36	-8.4	0.36	0.37	0.39	-7.2	0.40	0.41	0.42	-6.0	0.44	0.44	0.44	-4.8	0.48	0.47	0.47	-3.6	0.51	0.49	0.48	-2.4	0.53	0.49	0.48	-1.2	0.51	0.47	0.46	0.0	0.43	0.42	0.45
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																								
-12.0	0.13	0.13	0.13																																																								
-11.4	0.27	0.29	0.32																																																								
-10.8	0.29	0.31	0.34																																																								
-9.6	0.32	0.34	0.36																																																								
-8.4	0.36	0.37	0.39																																																								
-7.2	0.40	0.41	0.42																																																								
-6.0	0.44	0.44	0.44																																																								
-4.8	0.48	0.47	0.47																																																								
-3.6	0.51	0.49	0.48																																																								
-2.4	0.53	0.49	0.48																																																								
-1.2	0.51	0.47	0.46																																																								
0.0	0.43	0.42	0.45																																																								
<p>Note: Slanted line shows the range of the rated load current.</p>																																																											

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)