

TEST DATA OF SUTW34815

Regulated DC Power Supply
March 12, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager


Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.


CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW34815	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>16.0</td><td>0.006</td><td>0.006</td><td>0.006</td></tr> <tr><td>19.2</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>21.6</td><td>0.015</td><td>0.095</td><td>0.167</td></tr> <tr><td>22.4</td><td>0.015</td><td>0.092</td><td>0.167</td></tr> <tr><td>24.0</td><td>0.015</td><td>0.087</td><td>0.160</td></tr> <tr><td>33.0</td><td>0.013</td><td>0.063</td><td>0.118</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.059</td><td>0.108</td></tr> <tr><td>40.0</td><td>0.011</td><td>0.053</td><td>0.097</td></tr> <tr><td>48.0</td><td>0.011</td><td>0.045</td><td>0.081</td></tr> <tr><td>60.0</td><td>0.011</td><td>0.037</td><td>0.066</td></tr> <tr><td>70.0</td><td>0.011</td><td>0.033</td><td>0.058</td></tr> <tr><td>76.0</td><td>0.012</td><td>0.032</td><td>0.055</td></tr> <tr><td>80.0</td><td>0.012</td><td>0.031</td><td>0.052</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.007	0.007	0.007	16.0	0.006	0.006	0.006	19.2	0.005	0.005	0.005	21.6	0.015	0.095	0.167	22.4	0.015	0.092	0.167	24.0	0.015	0.087	0.160	33.0	0.013	0.063	0.118	36.0	0.012	0.059	0.108	40.0	0.011	0.053	0.097	48.0	0.011	0.045	0.081	60.0	0.011	0.037	0.066	70.0	0.011	0.033	0.058	76.0	0.012	0.032	0.055	80.0	0.012	0.031	0.052	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.007	0.007	0.007																																																																																
16.0	0.006	0.006	0.006																																																																																
19.2	0.005	0.005	0.005																																																																																
21.6	0.015	0.095	0.167																																																																																
22.4	0.015	0.092	0.167																																																																																
24.0	0.015	0.087	0.160																																																																																
33.0	0.013	0.063	0.118																																																																																
36.0	0.012	0.059	0.108																																																																																
40.0	0.011	0.053	0.097																																																																																
48.0	0.011	0.045	0.081																																																																																
60.0	0.011	0.037	0.066																																																																																
70.0	0.011	0.033	0.058																																																																																
76.0	0.012	0.032	0.055																																																																																
80.0	0.012	0.031	0.052																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW34815																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 36V ---□--- Input Volt. 48V ---○--- Input Volt. 76V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [A]</th> <th>48V [A]</th> <th>76V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.012</td><td>0.011</td><td>0.011</td></tr> <tr><td>20</td><td>0.030</td><td>0.024</td><td>0.020</td></tr> <tr><td>40</td><td>0.049</td><td>0.039</td><td>0.028</td></tr> <tr><td>60</td><td>0.068</td><td>0.052</td><td>0.036</td></tr> <tr><td>80</td><td>0.088</td><td>0.066</td><td>0.045</td></tr> <tr><td>100</td><td>0.107</td><td>0.081</td><td>0.054</td></tr> <tr><td>110</td><td>0.117</td><td>0.088</td><td>0.058</td></tr> </tbody> </table>			Load Ration [%]	36V [A]	48V [A]	76V [A]	0	0.012	0.011	0.011	20	0.030	0.024	0.020	40	0.049	0.039	0.028	60	0.068	0.052	0.036	80	0.088	0.066	0.045	100	0.107	0.081	0.054	110	0.117	0.088	0.058																			
Load Ration [%]	36V [A]	48V [A]	76V [A]																																																			
0	0.012	0.011	0.011																																																			
20	0.030	0.024	0.020																																																			
40	0.049	0.039	0.028																																																			
60	0.068	0.052	0.036																																																			
80	0.088	0.066	0.045																																																			
100	0.107	0.081	0.054																																																			
110	0.117	0.088	0.058																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.012</td><td>0.011</td><td>0.011</td></tr> <tr><td>20</td><td>0.030</td><td>0.024</td><td>0.020</td></tr> <tr><td>40</td><td>0.049</td><td>0.039</td><td>0.028</td></tr> <tr><td>60</td><td>0.068</td><td>0.052</td><td>0.036</td></tr> <tr><td>80</td><td>0.088</td><td>0.066</td><td>0.045</td></tr> <tr><td>100</td><td>0.107</td><td>0.081</td><td>0.054</td></tr> <tr><td>110</td><td>0.117</td><td>0.088</td><td>0.058</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.012	0.011	0.011	20	0.030	0.024	0.020	40	0.049	0.039	0.028	60	0.068	0.052	0.036	80	0.088	0.066	0.045	100	0.107	0.081	0.054	110	0.117	0.088	0.058	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.012	0.011	0.011																																																			
20	0.030	0.024	0.020																																																			
40	0.049	0.039	0.028																																																			
60	0.068	0.052	0.036																																																			
80	0.088	0.066	0.045																																																			
100	0.107	0.081	0.054																																																			
110	0.117	0.088	0.058																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW34815	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Input Power (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p>  <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.39</td><td>0.45</td><td>0.69</td></tr> <tr><td>20</td><td>1.08</td><td>1.13</td><td>1.36</td></tr> <tr><td>40</td><td>1.75</td><td>1.81</td><td>2.02</td></tr> <tr><td>60</td><td>2.45</td><td>2.48</td><td>2.69</td></tr> <tr><td>80</td><td>3.14</td><td>3.17</td><td>3.37</td></tr> <tr><td>100</td><td>3.85</td><td>3.87</td><td>4.04</td></tr> <tr><td>110</td><td>4.21</td><td>4.22</td><td>4.38</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0	0.39	0.45	0.69	20	1.08	1.13	1.36	40	1.75	1.81	2.02	60	2.45	2.48	2.69	80	3.14	3.17	3.37	100	3.85	3.87	4.04	110	4.21	4.22	4.38																			
Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																	
0	0.39	0.45	0.69																																																	
20	1.08	1.13	1.36																																																	
40	1.75	1.81	2.02																																																	
60	2.45	2.48	2.69																																																	
80	3.14	3.17	3.37																																																	
100	3.85	3.87	4.04																																																	
110	4.21	4.22	4.38																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.39</td><td>0.45</td><td>0.69</td></tr> <tr><td>20</td><td>1.08</td><td>1.13</td><td>1.36</td></tr> <tr><td>40</td><td>1.75</td><td>1.81</td><td>2.02</td></tr> <tr><td>60</td><td>2.45</td><td>2.48</td><td>2.69</td></tr> <tr><td>80</td><td>3.14</td><td>3.17</td><td>3.37</td></tr> <tr><td>100</td><td>3.85</td><td>3.87</td><td>4.04</td></tr> <tr><td>110</td><td>4.21</td><td>4.22</td><td>4.38</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.39	0.45	0.69	20	1.08	1.13	1.36	40	1.75	1.81	2.02	60	2.45	2.48	2.69	80	3.14	3.17	3.37	100	3.85	3.87	4.04	110	4.21	4.22	4.38	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																	
0	0.39	0.45	0.69																																																	
20	1.08	1.13	1.36																																																	
40	1.75	1.81	2.02																																																	
60	2.45	2.48	2.69																																																	
80	3.14	3.17	3.37																																																	
100	3.85	3.87	4.04																																																	
110	4.21	4.22	4.38																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Model	SUTW34815																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line at approximately 45 degrees across the plot area indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>72.7</td><td>77.8</td></tr> <tr><td>36</td><td>72.1</td><td>77.9</td></tr> <tr><td>40</td><td>71.7</td><td>78.8</td></tr> <tr><td>48</td><td>70.7</td><td>78.2</td></tr> <tr><td>55</td><td>69.6</td><td>77.5</td></tr> <tr><td>60</td><td>68.4</td><td>76.8</td></tr> <tr><td>70</td><td>65.9</td><td>75.3</td></tr> <tr><td>76</td><td>63.8</td><td>74.2</td></tr> <tr><td>80</td><td>63.0</td><td>74.4</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	72.7	77.8	36	72.1	77.9	40	71.7	78.8	48	70.7	78.2	55	69.6	77.5	60	68.4	76.8	70	65.9	75.3	76	63.8	74.2	80	63.0	74.4		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
33	72.7	77.8																																
36	72.1	77.9																																
40	71.7	78.8																																
48	70.7	78.2																																
55	69.6	77.5																																
60	68.4	76.8																																
70	65.9	75.3																																
76	63.8	74.2																																
80	63.0	74.4																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>72.7</td><td>77.8</td></tr> <tr><td>36</td><td>72.1</td><td>77.9</td></tr> <tr><td>40</td><td>71.7</td><td>78.8</td></tr> <tr><td>48</td><td>70.7</td><td>78.2</td></tr> <tr><td>55</td><td>69.6</td><td>77.5</td></tr> <tr><td>60</td><td>68.4</td><td>76.8</td></tr> <tr><td>70</td><td>65.9</td><td>75.3</td></tr> <tr><td>76</td><td>63.8</td><td>74.2</td></tr> <tr><td>80</td><td>63.0</td><td>74.4</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	72.7	77.8	36	72.1	77.9	40	71.7	78.8	48	70.7	78.2	55	69.6	77.5	60	68.4	76.8	70	65.9	75.3	76	63.8	74.2	80	63.0	74.4
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
33	72.7	77.8																																
36	72.1	77.9																																
40	71.7	78.8																																
48	70.7	78.2																																
55	69.6	77.5																																
60	68.4	76.8																																
70	65.9	75.3																																
76	63.8	74.2																																
80	63.0	74.4																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		


Model	SUTW34815	Temperature Testing Circuitry 25°C Figure A																																												
Item	Efficiency (by Load Current)																																													
Object	_____																																													
1.Graph		2.Values																																												
<p>—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>20</td><td>55.8</td><td>53.4</td><td>44.3</td></tr> <tr><td>40</td><td>68.7</td><td>66.6</td><td>59.6</td></tr> <tr><td>60</td><td>73.7</td><td>72.7</td><td>67.2</td></tr> <tr><td>80</td><td>76.6</td><td>75.9</td><td>71.5</td></tr> <tr><td>100</td><td>78.1</td><td>77.8</td><td>74.6</td></tr> <tr><td>110</td><td>78.6</td><td>78.5</td><td>75.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	20	55.8	53.4	44.3	40	68.7	66.6	59.6	60	73.7	72.7	67.2	80	76.6	75.9	71.5	100	78.1	77.8	74.6	110	78.6	78.5	75.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																											
20	55.8	53.4	44.3																																											
40	68.7	66.6	59.6																																											
60	73.7	72.7	67.2																																											
80	76.6	75.9	71.5																																											
100	78.1	77.8	74.6																																											
110	78.6	78.5	75.6																																											
--	-	-	-																																											
--	-	-	-																																											
--	-	-	-																																											
--	-	-	-																																											

Model	SUTW34815	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+15V0.1A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>15.117</td><td>15.043</td></tr> <tr><td>36</td><td>15.115</td><td>15.044</td></tr> <tr><td>40</td><td>15.113</td><td>15.045</td></tr> <tr><td>48</td><td>15.109</td><td>15.045</td></tr> <tr><td>55</td><td>15.107</td><td>15.045</td></tr> <tr><td>60</td><td>15.106</td><td>15.045</td></tr> <tr><td>70</td><td>15.104</td><td>15.046</td></tr> <tr><td>76</td><td>15.104</td><td>15.045</td></tr> <tr><td>80</td><td>15.103</td><td>15.046</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	15.117	15.043	36	15.115	15.044	40	15.113	15.045	48	15.109	15.045	55	15.107	15.045	60	15.106	15.045	70	15.104	15.046	76	15.104	15.045	80	15.103	15.046
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	15.117	15.043																																
36	15.115	15.044																																
40	15.113	15.045																																
48	15.109	15.045																																
55	15.107	15.045																																
60	15.106	15.045																																
70	15.104	15.046																																
76	15.104	15.045																																
80	15.103	15.046																																
Object -15V0.1A		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-15.101</td><td>-15.029</td></tr> <tr><td>36</td><td>-15.098</td><td>-15.029</td></tr> <tr><td>40</td><td>-15.095</td><td>-15.029</td></tr> <tr><td>48</td><td>-15.091</td><td>-15.028</td></tr> <tr><td>55</td><td>-15.088</td><td>-15.027</td></tr> <tr><td>60</td><td>-15.087</td><td>-15.027</td></tr> <tr><td>70</td><td>-15.085</td><td>-15.027</td></tr> <tr><td>76</td><td>-15.085</td><td>-15.027</td></tr> <tr><td>80</td><td>-15.085</td><td>-15.028</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-15.101	-15.029	36	-15.098	-15.029	40	-15.095	-15.029	48	-15.091	-15.028	55	-15.088	-15.027	60	-15.087	-15.027	70	-15.085	-15.027	76	-15.085	-15.027	80	-15.085	-15.028
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	-15.101	-15.029																																
36	-15.098	-15.029																																
40	-15.095	-15.029																																
48	-15.091	-15.028																																
55	-15.088	-15.027																																
60	-15.087	-15.027																																
70	-15.085	-15.027																																
76	-15.085	-15.027																																
80	-15.085	-15.028																																
Note: Slanted line shows the range of the rated input voltage.																																		




Model	SUTW34815	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.1A																																																					
1.Graph	—△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ - - Input Volt. 76V																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.291</td><td>15.281</td><td>15.272</td></tr> <tr><td>0.02</td><td>15.179</td><td>15.172</td><td>15.167</td></tr> <tr><td>0.04</td><td>15.132</td><td>15.125</td><td>15.119</td></tr> <tr><td>0.06</td><td>15.099</td><td>15.094</td><td>15.089</td></tr> <tr><td>0.08</td><td>15.070</td><td>15.068</td><td>15.065</td></tr> <tr><td>0.10</td><td>15.044</td><td>15.044</td><td>15.044</td></tr> <tr><td>0.11</td><td>15.031</td><td>15.033</td><td>15.035</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	15.291	15.281	15.272	0.02	15.179	15.172	15.167	0.04	15.132	15.125	15.119	0.06	15.099	15.094	15.089	0.08	15.070	15.068	15.065	0.10	15.044	15.044	15.044	0.11	15.031	15.033	15.035	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	15.291	15.281	15.272																																																			
0.02	15.179	15.172	15.167																																																			
0.04	15.132	15.125	15.119																																																			
0.06	15.099	15.094	15.089																																																			
0.08	15.070	15.068	15.065																																																			
0.10	15.044	15.044	15.044																																																			
0.11	15.031	15.033	15.035																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.1A																																																					
1.Graph	—△— Input Volt. 36V - - □ - - Input Volt. 48V - · ○ - - Input Volt. 76V																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.266</td><td>-15.256</td><td>-15.246</td></tr> <tr><td>0.02</td><td>-15.159</td><td>-15.151</td><td>-15.145</td></tr> <tr><td>0.04</td><td>-15.114</td><td>-15.107</td><td>-15.100</td></tr> <tr><td>0.06</td><td>-15.082</td><td>-15.075</td><td>-15.071</td></tr> <tr><td>0.08</td><td>-15.054</td><td>-15.050</td><td>-15.047</td></tr> <tr><td>0.10</td><td>-15.028</td><td>-15.027</td><td>-15.026</td></tr> <tr><td>0.11</td><td>-15.015</td><td>-15.016</td><td>-15.017</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-15.266	-15.256	-15.246	0.02	-15.159	-15.151	-15.145	0.04	-15.114	-15.107	-15.100	0.06	-15.082	-15.075	-15.071	0.08	-15.054	-15.050	-15.047	0.10	-15.028	-15.027	-15.026	0.11	-15.015	-15.016	-15.017	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	-15.266	-15.256	-15.246																																																			
0.02	-15.159	-15.151	-15.145																																																			
0.04	-15.114	-15.107	-15.100																																																			
0.06	-15.082	-15.075	-15.071																																																			
0.08	-15.054	-15.050	-15.047																																																			
0.10	-15.028	-15.027	-15.026																																																			
0.11	-15.015	-15.016	-15.017																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL




COSEL



Model	SUTW34815
Item	Ripple Voltage (by Load Current)
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	2	2
0.02	2	2
0.04	2	2
0.06	2	2
0.08	5	2
0.10	9	2
0.11	13	2
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW34815
Item	Ripple Voltage (by Load Current)
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	2	2
0.02	2	2
0.04	2	2
0.06	2	2
0.08	4	2
0.10	8	2
0.11	11	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW34815
Item	Ripple-Noise
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	8	5
0.02	8	9
0.04	10	9
0.06	13	10
0.08	16	10
0.10	24	11
0.11	27	12
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW34815
Item	Ripple-Noise
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	10	8
0.02	10	10
0.04	11	10
0.06	11	10
0.08	11	10
0.10	16	11
0.11	19	11
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW34815
-------	-----------

| Item | Ripple Voltage (by Ambient Temp.) |
| Object | +15V0.1A |

1.Graph

---□--- Load 50%
—△— Load 100%



Input Volt. 48V


Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	15
-40	7	15
-20	7	12
0	5	10
25	3	9
55	3	9
60	3	9
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph

---□--- Load 50%
—△— Load 100%



Input Volt. 48V

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	8
-40	4	8
-20	4	9
0	3	10
25	3	10
55	3	7
60	3	7
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW34815
Item	Ambient Temperature Drift
Object	+15V0.1A

Testing Circuitry Figure A

1.Graph

- △— Input Volt. 36V
- - - □ - - Input Volt. 48V
- · ○ - - Input Volt. 76V




2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.937	14.939	14.941
-40	14.972	14.974	14.975
-20	15.000	15.002	15.002
0	15.023	15.024	15.025
25	15.042	15.043	15.044
55	15.053	15.053	15.053
60	15.053	15.054	15.054
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

1.Graph

- △— Input Volt. 36V
- - - □ - - Input Volt. 48V
- · ○ - - Input Volt. 76V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-14.920	-14.921	-14.921
-40	-14.955	-14.956	-14.955
-20	-14.983	-14.983	-14.983
0	-15.006	-15.006	-15.005
25	-15.025	-15.025	-15.024
55	-15.036	-15.035	-15.034
60	-15.036	-15.036	-15.035
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW34815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object	+15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36		0	15.305	
Minimum Voltage	-40	36	0.1	14.760	±273	±1.8

Object	-15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36		0	-15.281	
Minimum Voltage	-40	36	0.1	-14.732	±275	±1.8

COSEL


Model	SUTW34815
Item	Time Lapse Drift
Object	+15V0.1A

1.Graph



Object	-15V0.1A
--------	----------

1.Graph



Temperature	25°C
Testing Circuitry	Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.035
0.5	15.043
1.0	15.043
2.0	15.043
3.0	15.043
4.0	15.044
5.0	15.043
6.0	15.043
7.0	15.044
8.0	15.043

2.Values


Time since start [H]	Output Voltage [V]
0.0	-15.022
0.5	-15.030
1.0	-15.030
2.0	-15.030
3.0	-15.030
4.0	-15.030
5.0	-15.030
6.0	-15.030
7.0	-15.030
8.0	-15.030

COSEL

Model	SUTW34815
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	7.9	8.0	5.9	2.7	
100 %		0.1	8.1	8.2	2.8	2.0	




COSEL

Model	SUTW34815
Item	Rise and Fall Time
Object	-15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph





2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	8.0	8.1	5.9	3.2
100 %		0.1	8.2	8.3	2.8	2.2



COSEL

Model	SUTW34815																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry	Figure A																																						
Object	+15V0.1A																																								
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>-60</td><td>14.1</td><td>20.9</td></tr> <tr><td>-40</td><td>14.1</td><td>21.3</td></tr> <tr><td>-20</td><td>14.1</td><td>21.7</td></tr> <tr><td>0</td><td>14.5</td><td>22.1</td></tr> <tr><td>25</td><td>14.9</td><td>22.9</td></tr> <tr><td>55</td><td>15.7</td><td>23.7</td></tr> <tr><td>60</td><td>15.7</td><td>23.7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	14.1	20.9	-40	14.1	21.3	-20	14.1	21.7	0	14.5	22.1	25	14.9	22.9	55	15.7	23.7	60	15.7	23.7	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	14.1	20.9																																							
-40	14.1	21.3																																							
-20	14.1	21.7																																							
0	14.5	22.1																																							
25	14.9	22.9																																							
55	15.7	23.7																																							
60	15.7	23.7																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr> <tr> <th>Load 50%</th><th>Load 100%</th></tr> </thead> <tbody> <tr><td>-60</td><td>14.1</td><td>20.9</td></tr> <tr><td>-40</td><td>14.1</td><td>21.3</td></tr> <tr><td>-20</td><td>14.1</td><td>21.7</td></tr> <tr><td>0</td><td>14.5</td><td>22.1</td></tr> <tr><td>25</td><td>14.9</td><td>22.9</td></tr> <tr><td>55</td><td>15.7</td><td>23.7</td></tr> <tr><td>60</td><td>15.7</td><td>23.7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	14.1	20.9	-40	14.1	21.3	-20	14.1	21.7	0	14.5	22.1	25	14.9	22.9	55	15.7	23.7	60	15.7	23.7	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	14.1	20.9																																							
-40	14.1	21.3																																							
-20	14.1	21.7																																							
0	14.5	22.1																																							
25	14.9	22.9																																							
55	15.7	23.7																																							
60	15.7	23.7																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

Model	SUTW34815	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+15V0.1A																																																								
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values																																																							
Object	-15V0.1A	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>14.3</td><td>0.21</td><td>0.22</td><td>0.22</td></tr> <tr><td>13.5</td><td>0.23</td><td>0.24</td><td>0.23</td></tr> <tr><td>12.0</td><td>0.26</td><td>0.27</td><td>0.26</td></tr> <tr><td>10.5</td><td>0.30</td><td>0.30</td><td>0.29</td></tr> <tr><td>9.0</td><td>0.33</td><td>0.33</td><td>0.31</td></tr> <tr><td>7.5</td><td>0.37</td><td>0.37</td><td>0.34</td></tr> <tr><td>6.0</td><td>0.41</td><td>0.40</td><td>0.37</td></tr> <tr><td>4.5</td><td>0.45</td><td>0.42</td><td>0.39</td></tr> <tr><td>3.0</td><td>0.47</td><td>0.44</td><td>0.40</td></tr> <tr><td>1.5</td><td>0.46</td><td>0.42</td><td>0.40</td></tr> <tr><td>0.0</td><td>0.40</td><td>0.38</td><td>0.41</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	15.0	0.10	0.10	0.10	14.3	0.21	0.22	0.22	13.5	0.23	0.24	0.23	12.0	0.26	0.27	0.26	10.5	0.30	0.30	0.29	9.0	0.33	0.33	0.31	7.5	0.37	0.37	0.34	6.0	0.41	0.40	0.37	4.5	0.45	0.42	0.39	3.0	0.47	0.44	0.40	1.5	0.46	0.42	0.40	0.0	0.40	0.38	0.41
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
15.0	0.10	0.10	0.10																																																						
14.3	0.21	0.22	0.22																																																						
13.5	0.23	0.24	0.23																																																						
12.0	0.26	0.27	0.26																																																						
10.5	0.30	0.30	0.29																																																						
9.0	0.33	0.33	0.31																																																						
7.5	0.37	0.37	0.34																																																						
6.0	0.41	0.40	0.37																																																						
4.5	0.45	0.42	0.39																																																						
3.0	0.47	0.44	0.40																																																						
1.5	0.46	0.42	0.40																																																						
0.0	0.40	0.38	0.41																																																						
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values																																																							
Note: Slanted line shows the range of the rated load current.		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>-14.25</td><td>0.21</td><td>0.22</td><td>0.22</td></tr> <tr><td>-13.50</td><td>0.23</td><td>0.24</td><td>0.23</td></tr> <tr><td>-12.00</td><td>0.26</td><td>0.27</td><td>0.26</td></tr> <tr><td>-10.50</td><td>0.30</td><td>0.30</td><td>0.29</td></tr> <tr><td>-9.00</td><td>0.33</td><td>0.33</td><td>0.31</td></tr> <tr><td>-7.50</td><td>0.37</td><td>0.37</td><td>0.34</td></tr> <tr><td>-6.00</td><td>0.41</td><td>0.40</td><td>0.37</td></tr> <tr><td>-4.50</td><td>0.45</td><td>0.42</td><td>0.39</td></tr> <tr><td>-3.00</td><td>0.47</td><td>0.44</td><td>0.40</td></tr> <tr><td>-1.50</td><td>0.46</td><td>0.42</td><td>0.40</td></tr> <tr><td>0.00</td><td>0.39</td><td>0.38</td><td>0.41</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-15.00	0.10	0.10	0.10	-14.25	0.21	0.22	0.22	-13.50	0.23	0.24	0.23	-12.00	0.26	0.27	0.26	-10.50	0.30	0.30	0.29	-9.00	0.33	0.33	0.31	-7.50	0.37	0.37	0.34	-6.00	0.41	0.40	0.37	-4.50	0.45	0.42	0.39	-3.00	0.47	0.44	0.40	-1.50	0.46	0.42	0.40	0.00	0.39	0.38	0.41
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
-15.00	0.10	0.10	0.10																																																						
-14.25	0.21	0.22	0.22																																																						
-13.50	0.23	0.24	0.23																																																						
-12.00	0.26	0.27	0.26																																																						
-10.50	0.30	0.30	0.29																																																						
-9.00	0.33	0.33	0.31																																																						
-7.50	0.37	0.37	0.34																																																						
-6.00	0.41	0.40	0.37																																																						
-4.50	0.45	0.42	0.39																																																						
-3.00	0.47	0.44	0.40																																																						
-1.50	0.46	0.42	0.40																																																						
0.00	0.39	0.38	0.41																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)