

TEST DATA OF SUTW60512

Regulated DC Power Supply
March 16, 2009

Approved by : *Kazunari Asano*
Kazunari Asano Design Manager

Prepared by : *Sho Saito*
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS


1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)



Model	SUTW60512
Item	Input Current (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.00	0.000	0.000	0.000
1.70	0.009	0.009	0.010
2.00	0.010	0.010	0.010
3.00	0.010	0.010	0.010
3.66	0.126	0.285	0.264
4.00	0.119	0.932	1.995
4.17	0.114	1.064	1.859
4.50	0.109	0.895	1.701
5.00	0.102	0.795	1.519
6.00	0.091	0.657	1.247
7.00	0.084	0.569	1.058
8.00	0.081	0.501	0.928
9.00	0.079	0.450	0.852
10.00	0.079	0.417	0.759
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



COSEL																																																						
Model	SUTW60512	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - - - ○ - - - Input Volt. 9V </p> <p style="text-align: center;">Input Current [A]</p> <p style="text-align: center;">Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.108</td><td>0.100</td><td>0.078</td></tr> <tr><td>20</td><td>0.402</td><td>0.363</td><td>0.225</td></tr> <tr><td>40</td><td>0.699</td><td>0.625</td><td>0.371</td></tr> <tr><td>60</td><td>1.017</td><td>0.900</td><td>0.520</td></tr> <tr><td>80</td><td>1.343</td><td>1.227</td><td>0.667</td></tr> <tr><td>100</td><td>1.708</td><td>1.527</td><td>0.815</td></tr> <tr><td>110</td><td>1.907</td><td>1.661</td><td>0.895</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.108	0.100	0.078	20	0.402	0.363	0.225	40	0.699	0.625	0.371	60	1.017	0.900	0.520	80	1.343	1.227	0.667	100	1.708	1.527	0.815	110	1.907	1.661	0.895	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	0.108	0.100	0.078																																																			
20	0.402	0.363	0.225																																																			
40	0.699	0.625	0.371																																																			
60	1.017	0.900	0.520																																																			
80	1.343	1.227	0.667																																																			
100	1.708	1.527	0.815																																																			
110	1.907	1.661	0.895																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



COSEL																																																						
Model	SUTW60512	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> </p> <p> △ Input Volt. 4.5V □ Input Volt. 5V ○ Input Volt. 9V </p>		<p>2.Values</p>																																																				
<p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Ration [%]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.48</td><td>0.48</td><td>0.70</td></tr> <tr><td>20</td><td>1.78</td><td>1.81</td><td>2.04</td></tr> <tr><td>40</td><td>3.14</td><td>3.15</td><td>3.34</td></tr> <tr><td>60</td><td>4.56</td><td>4.54</td><td>4.64</td></tr> <tr><td>80</td><td>6.04</td><td>5.99</td><td>5.96</td></tr> <tr><td>100</td><td>7.59</td><td>7.49</td><td>7.33</td></tr> <tr><td>110</td><td>8.39</td><td>8.25</td><td>8.01</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.48	0.48	0.70	20	1.78	1.81	2.04	40	3.14	3.15	3.34	60	4.56	4.54	4.64	80	6.04	5.99	5.96	100	7.59	7.49	7.33	110	8.39	8.25	8.01	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	0.48	0.48	0.70																																																			
20	1.78	1.81	2.04																																																			
40	3.14	3.15	3.34																																																			
60	4.56	4.54	4.64																																																			
80	6.04	5.99	5.96																																																			
100	7.59	7.49	7.33																																																			
110	8.39	8.25	8.01																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



COSEL																																			
Model	SUTW60512	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>77.7</td><td>78.2</td></tr> <tr><td>4.5</td><td>79.0</td><td>79.9</td></tr> <tr><td>5.0</td><td>79.5</td><td>81.3</td></tr> <tr><td>6.0</td><td>79.5</td><td>82.7</td></tr> <tr><td>7.0</td><td>79.0</td><td>83.4</td></tr> <tr><td>8.0</td><td>77.9</td><td>83.3</td></tr> <tr><td>9.0</td><td>76.4</td><td>83.2</td></tr> <tr><td>9.5</td><td>75.6</td><td>82.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	77.7	78.2	4.5	79.0	79.9	5.0	79.5	81.3	6.0	79.5	82.7	7.0	79.0	83.4	8.0	77.9	83.3	9.0	76.4	83.2	9.5	75.6	82.9	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
4.0	77.7	78.2																																	
4.5	79.0	79.9																																	
5.0	79.5	81.3																																	
6.0	79.5	82.7																																	
7.0	79.0	83.4																																	
8.0	77.9	83.3																																	
9.0	76.4	83.2																																	
9.5	75.6	82.9																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model SUTW60512</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V </p> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>68.3</td><td>67.2</td><td>59.7</td></tr> <tr><td>40</td><td>77.5</td><td>77.3</td><td>72.9</td></tr> <tr><td>60</td><td>80.0</td><td>80.3</td><td>78.5</td></tr> <tr><td>80</td><td>80.5</td><td>81.2</td><td>81.6</td></tr> <tr><td>100</td><td>80.1</td><td>81.2</td><td>83.0</td></tr> <tr><td>110</td><td>79.7</td><td>81.1</td><td>83.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	68.3	67.2	59.7	40	77.5	77.3	72.9	60	80.0	80.3	78.5	80	80.5	81.2	81.6	100	80.1	81.2	83.0	110	79.7	81.1	83.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0	-	-	-																																																		
20	68.3	67.2	59.7																																																		
40	77.5	77.3	72.9																																																		
60	80.0	80.3	78.5																																																		
80	80.5	81.2	81.6																																																		
100	80.1	81.2	83.0																																																		
110	79.7	81.1	83.5																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




COSEL																																			
Model	SUTW60512	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V0.25A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.210</td><td>12.143</td></tr> <tr><td>4.5</td><td>12.209</td><td>12.145</td></tr> <tr><td>5.0</td><td>12.207</td><td>12.145</td></tr> <tr><td>6.0</td><td>12.205</td><td>12.146</td></tr> <tr><td>7.0</td><td>12.203</td><td>12.147</td></tr> <tr><td>8.0</td><td>12.202</td><td>12.147</td></tr> <tr><td>9.0</td><td>12.201</td><td>12.147</td></tr> <tr><td>9.5</td><td>12.201</td><td>12.148</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	12.210	12.143	4.5	12.209	12.145	5.0	12.207	12.145	6.0	12.205	12.146	7.0	12.203	12.147	8.0	12.202	12.147	9.0	12.201	12.147	9.5	12.201	12.148	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	12.210	12.143																																	
4.5	12.209	12.145																																	
5.0	12.207	12.145																																	
6.0	12.205	12.146																																	
7.0	12.203	12.147																																	
8.0	12.202	12.147																																	
9.0	12.201	12.147																																	
9.5	12.201	12.148																																	
--	-	-																																	
Object	-12V0.25A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.213</td><td>-12.147</td></tr> <tr><td>4.5</td><td>-12.211</td><td>-12.147</td></tr> <tr><td>5.0</td><td>-12.208</td><td>-12.147</td></tr> <tr><td>6.0</td><td>-12.205</td><td>-12.147</td></tr> <tr><td>7.0</td><td>-12.202</td><td>-12.146</td></tr> <tr><td>8.0</td><td>-12.200</td><td>-12.145</td></tr> <tr><td>9.0</td><td>-12.200</td><td>-12.145</td></tr> <tr><td>9.5</td><td>-12.199</td><td>-12.145</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-12.213	-12.147	4.5	-12.211	-12.147	5.0	-12.208	-12.147	6.0	-12.205	-12.147	7.0	-12.202	-12.146	8.0	-12.200	-12.145	9.0	-12.200	-12.145	9.5	-12.199	-12.145	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	-12.213	-12.147																																	
4.5	-12.211	-12.147																																	
5.0	-12.208	-12.147																																	
6.0	-12.205	-12.147																																	
7.0	-12.202	-12.146																																	
8.0	-12.200	-12.145																																	
9.0	-12.200	-12.145																																	
9.5	-12.199	-12.145																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model	SUTW60512
Item	Load Regulation
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure A

1.Graph
 —△— Input Volt. 4.5V
 ---□--- Input Volt. 5V
 -·-○-·- Input Volt. 9V




2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	12.420	12.415	12.387
0.050	12.270	12.270	12.262
0.100	12.224	12.223	12.217
0.150	12.194	12.193	12.189
0.200	12.168	12.168	12.167
0.250	12.144	12.146	12.147
0.275	12.133	12.135	12.138
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Object	-12V0.25A
--------	-----------

1.Graph
 —△— Input Volt. 4.5V
 ---□--- Input Volt. 5V
 -·-○-·- Input Volt. 9V



2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	-12.438	-12.430	-12.399
0.050	-12.275	-12.274	-12.264
0.100	-12.226	-12.223	-12.215
0.150	-12.195	-12.193	-12.186
0.200	-12.170	-12.169	-12.163
0.250	-12.147	-12.147	-12.145
0.275	-12.136	-12.136	-12.136
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.




Model	SUTW60512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.25A		

Input Volt. 48 V
 Cycle 100 mS




Min. Load (0A) ←→
 Load 100% (0.25A)

500mV/div




500µs/div




500µs/div

Min. Load (0A) ←→
 Load 50% (0.125A)

500mV/div




500µs/div



500µs/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

500mV/div



500µs/div



500µs/div




Model	SUTW60512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.25A		

Input Volt. 48 V
 Cycle 100 mS



Min. Load (0A) ←→
 Load 100% (0.25A)

500mV/div




500µs/div




500µs/div

Min. Load (0A) ←→
 Load 50% (0.125A)

500mV/div




500µs/div



500µs/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

500mV/div



500µs/div



500µs/div

<p>Model SUTW60512</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+12V0.25A																																							
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 9V</p> <p>-·-○-·- Input Volt. 18V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>4</td></tr> <tr><td>0.050</td><td>4</td><td>4</td></tr> <tr><td>0.100</td><td>5</td><td>4</td></tr> <tr><td>0.150</td><td>6</td><td>4</td></tr> <tr><td>0.200</td><td>9</td><td>5</td></tr> <tr><td>0.250</td><td>12</td><td>6</td></tr> <tr><td>0.275</td><td>15</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	4	4	0.050	4	4	0.100	5	4	0.150	6	4	0.200	9	5	0.250	12	6	0.275	15	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	4	4																																						
0.050	4	4																																						
0.100	5	4																																						
0.150	6	4																																						
0.200	9	5																																						
0.250	12	6																																						
0.275	15	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

<p>Model SUTW60512</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	-12V0.25A																																							
<p>1.Graph</p> <p> —△— Input Volt. 9V - - ○ - - Input Volt. 18V </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>3</td></tr> <tr><td>0.050</td><td>4</td><td>3</td></tr> <tr><td>0.100</td><td>5</td><td>3</td></tr> <tr><td>0.150</td><td>5</td><td>4</td></tr> <tr><td>0.200</td><td>8</td><td>6</td></tr> <tr><td>0.250</td><td>10</td><td>7</td></tr> <tr><td>0.275</td><td>13</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	4	3	0.050	4	3	0.100	5	3	0.150	5	4	0.200	8	6	0.250	10	7	0.275	13	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	4	3																																						
0.050	4	3																																						
0.100	5	3																																						
0.150	5	4																																						
0.200	8	6																																						
0.250	10	7																																						
0.275	13	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

<p>Model SUTW60512</p> <p>Item Ripple-Noise</p> <p>Object +12V0.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p> —△— Input Volt. 9V - - ○ - - Input Volt. 18V </p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>4</td></tr> <tr><td>0.050</td><td>4</td><td>4</td></tr> <tr><td>0.100</td><td>5</td><td>4</td></tr> <tr><td>0.150</td><td>6</td><td>4</td></tr> <tr><td>0.200</td><td>9</td><td>5</td></tr> <tr><td>0.250</td><td>12</td><td>6</td></tr> <tr><td>0.275</td><td>15</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	4	4	0.050	4	4	0.100	5	4	0.150	6	4	0.200	9	5	0.250	12	6	0.275	15	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	4	4																																						
0.050	4	4																																						
0.100	5	4																																						
0.150	6	4																																						
0.200	9	5																																						
0.250	12	6																																						
0.275	15	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

<p>Model SUTW60512</p> <p>Item Ripple-Noise</p> <p>Object -12V0.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p> —△— Input Volt. 9V - - ○ - - Input Volt. 18V </p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>3</td></tr> <tr><td>0.050</td><td>4</td><td>3</td></tr> <tr><td>0.100</td><td>4</td><td>3</td></tr> <tr><td>0.150</td><td>6</td><td>4</td></tr> <tr><td>0.200</td><td>8</td><td>5</td></tr> <tr><td>0.250</td><td>11</td><td>6</td></tr> <tr><td>0.275</td><td>14</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	4	3	0.050	4	3	0.100	4	3	0.150	6	4	0.200	8	5	0.250	11	6	0.275	14	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	4	3																																						
0.050	4	3																																						
0.100	4	3																																						
0.150	6	4																																						
0.200	8	5																																						
0.250	11	6																																						
0.275	14	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



COSEL																																								
Model	SUTW60512																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+12V0.25A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 12V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>10</td></tr> <tr><td>-40</td><td>5</td><td>9</td></tr> <tr><td>-20</td><td>5</td><td>9</td></tr> <tr><td>0</td><td>4</td><td>8</td></tr> <tr><td>25</td><td>4</td><td>7</td></tr> <tr><td>55</td><td>3</td><td>6</td></tr> <tr><td>60</td><td>3</td><td>6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	10	-40	5	9	-20	5	9	0	4	8	25	4	7	55	3	6	60	3	6	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	5	10																																						
-40	5	9																																						
-20	5	9																																						
0	4	8																																						
25	4	7																																						
55	3	6																																						
60	3	6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Object	-12V0.25A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 12V</p> <p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3</td><td>5</td></tr> <tr><td>-40</td><td>3</td><td>5</td></tr> <tr><td>-20</td><td>3</td><td>5</td></tr> <tr><td>0</td><td>3</td><td>5</td></tr> <tr><td>25</td><td>2</td><td>4</td></tr> <tr><td>55</td><td>2</td><td>3</td></tr> <tr><td>60</td><td>2</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	3	5	-40	3	5	-20	3	5	0	3	5	25	2	4	55	2	3	60	2	3	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	3	5																																						
-40	3	5																																						
-20	3	5																																						
0	3	5																																						
25	2	4																																						
55	2	3																																						
60	2	3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



COSEL																																																						
Model	SUTW60512																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+12V0.25A																																																					
<p>1.Graph</p> <p style="text-align: right;"> —△— Input Volt. 4.5V ---□--- Input Volt. 5V -·-○-·- Input Volt. 9V </p> <p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.087</td><td>12.088</td><td>12.090</td></tr> <tr><td>-40</td><td>12.109</td><td>12.110</td><td>12.112</td></tr> <tr><td>-20</td><td>12.125</td><td>12.127</td><td>12.128</td></tr> <tr><td>0</td><td>12.137</td><td>12.138</td><td>12.140</td></tr> <tr><td>25</td><td>12.144</td><td>12.145</td><td>12.147</td></tr> <tr><td>55</td><td>12.145</td><td>12.145</td><td>12.147</td></tr> <tr><td>60</td><td>12.144</td><td>12.144</td><td>12.146</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.087	12.088	12.090	-40	12.109	12.110	12.112	-20	12.125	12.127	12.128	0	12.137	12.138	12.140	25	12.144	12.145	12.147	55	12.145	12.145	12.147	60	12.144	12.144	12.146	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	12.087	12.088	12.090																																																			
-40	12.109	12.110	12.112																																																			
-20	12.125	12.127	12.128																																																			
0	12.137	12.138	12.140																																																			
25	12.144	12.145	12.147																																																			
55	12.145	12.145	12.147																																																			
60	12.144	12.144	12.146																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object		-12V0.25A																																																				
<p>1.Graph</p> <p style="text-align: right;"> —△— Input Volt. 4.5V ---□--- Input Volt. 5V -·-○-·- Input Volt. 9V </p> <p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.086</td><td>-12.086</td><td>-12.086</td></tr> <tr><td>-40</td><td>-12.109</td><td>-12.109</td><td>-12.108</td></tr> <tr><td>-20</td><td>-12.126</td><td>-12.126</td><td>-12.125</td></tr> <tr><td>0</td><td>-12.138</td><td>-12.138</td><td>-12.136</td></tr> <tr><td>25</td><td>-12.146</td><td>-12.146</td><td>-12.144</td></tr> <tr><td>55</td><td>-12.147</td><td>-12.147</td><td>-12.145</td></tr> <tr><td>60</td><td>-12.147</td><td>-12.146</td><td>-12.144</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.086	-12.086	-12.086	-40	-12.109	-12.109	-12.108	-20	-12.126	-12.126	-12.125	0	-12.138	-12.138	-12.136	25	-12.146	-12.146	-12.144	55	-12.147	-12.147	-12.145	60	-12.147	-12.146	-12.144	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	-12.086	-12.086	-12.086																																																			
-40	-12.109	-12.109	-12.108																																																			
-20	-12.126	-12.126	-12.125																																																			
0	-12.138	-12.138	-12.136																																																			
25	-12.146	-12.146	-12.144																																																			
55	-12.147	-12.147	-12.145																																																			
60	-12.147	-12.146	-12.144																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		
Model	SUTW60512	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.25A (AVR 2) : 0 - 0.25A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+12V0.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	12.427	±287	±2.4
Minimum Voltage	55	4.5	0.25	11.854		

Object		-12V0.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	-12.445	±286	±2.4
Minimum Voltage	55	4.5	0.25	-11.873		




COSEL																									
Model	SUTW60512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.140</td></tr> <tr><td>0.5</td><td>12.143</td></tr> <tr><td>1.0</td><td>12.143</td></tr> <tr><td>2.0</td><td>12.143</td></tr> <tr><td>3.0</td><td>12.143</td></tr> <tr><td>4.0</td><td>12.143</td></tr> <tr><td>5.0</td><td>12.143</td></tr> <tr><td>6.0</td><td>12.143</td></tr> <tr><td>7.0</td><td>12.143</td></tr> <tr><td>8.0</td><td>12.143</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.140	0.5	12.143	1.0	12.143	2.0	12.143	3.0	12.143	4.0	12.143	5.0	12.143	6.0	12.143	7.0	12.143	8.0	12.143
Time since start [H]	Output Voltage [V]																								
0.0	12.140																								
0.5	12.143																								
1.0	12.143																								
2.0	12.143																								
3.0	12.143																								
4.0	12.143																								
5.0	12.143																								
6.0	12.143																								
7.0	12.143																								
8.0	12.143																								
Object	-12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.146</td></tr> <tr><td>0.5</td><td>-12.150</td></tr> <tr><td>1.0</td><td>-12.150</td></tr> <tr><td>2.0</td><td>-12.150</td></tr> <tr><td>3.0</td><td>-12.150</td></tr> <tr><td>4.0</td><td>-12.150</td></tr> <tr><td>5.0</td><td>-12.150</td></tr> <tr><td>6.0</td><td>-12.151</td></tr> <tr><td>7.0</td><td>-12.151</td></tr> <tr><td>8.0</td><td>-12.151</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.146	0.5	-12.150	1.0	-12.150	2.0	-12.150	3.0	-12.150	4.0	-12.150	5.0	-12.150	6.0	-12.151	7.0	-12.151	8.0	-12.151
Time since start [H]	Output Voltage [V]																								
0.0	-12.146																								
0.5	-12.150																								
1.0	-12.150																								
2.0	-12.150																								
3.0	-12.150																								
4.0	-12.150																								
5.0	-12.150																								
6.0	-12.151																								
7.0	-12.151																								
8.0	-12.151																								



Model		SUTW60512	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		+12V0.25A	

1. Graph


Input Volt. 5 V



2. Values

[mS]


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.2	2.0	2.2	0.1	2.7
100 %	0.2	2.1	2.3	0.1	1.3






Model		SUTW60512	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		-12V0.25A	Input Volt. 5 V	

1. Graph



2. Values

		[mS]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	2.3	2.5	0.1	2.9
100 %		0.2	2.3	2.5	0.1	1.5






Model	SUTW60512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.1	2.7
-20	2.3	2.7
0	2.2	2.7
25	2.2	3.1
55	2.2	2.9
60	2.3	3.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.0	2.7
-20	2.0	2.7
0	2.2	2.7
25	2.2	2.9
55	2.2	2.9
60	2.2	2.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL																																																										
Model	SUTW60512	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V0.25A																																																									
1.Graph		2.Values																																																								
	<p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p>																																																									
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.26</td><td>0.26</td><td>0.26</td></tr> <tr><td>11.4</td><td>0.46</td><td>0.50</td><td>0.60</td></tr> <tr><td>10.8</td><td>0.48</td><td>0.52</td><td>0.61</td></tr> <tr><td>9.6</td><td>0.53</td><td>0.57</td><td>0.65</td></tr> <tr><td>8.4</td><td>0.59</td><td>0.63</td><td>0.69</td></tr> <tr><td>7.2</td><td>0.66</td><td>0.69</td><td>0.73</td></tr> <tr><td>6.0</td><td>0.70</td><td>0.75</td><td>0.77</td></tr> <tr><td>4.8</td><td>0.76</td><td>0.80</td><td>0.80</td></tr> <tr><td>3.6</td><td>0.80</td><td>0.83</td><td>0.83</td></tr> <tr><td>2.4</td><td>0.82</td><td>0.84</td><td>0.83</td></tr> <tr><td>1.2</td><td>0.78</td><td>0.80</td><td>0.79</td></tr> <tr><td>0.0</td><td>0.93</td><td>0.97</td><td>1.12</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	12.0	0.26	0.26	0.26	11.4	0.46	0.50	0.60	10.8	0.48	0.52	0.61	9.6	0.53	0.57	0.65	8.4	0.59	0.63	0.69	7.2	0.66	0.69	0.73	6.0	0.70	0.75	0.77	4.8	0.76	0.80	0.80	3.6	0.80	0.83	0.83	2.4	0.82	0.84	0.83	1.2	0.78	0.80	0.79	0.0	0.93	0.97	1.12
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
12.0	0.26	0.26	0.26																																																							
11.4	0.46	0.50	0.60																																																							
10.8	0.48	0.52	0.61																																																							
9.6	0.53	0.57	0.65																																																							
8.4	0.59	0.63	0.69																																																							
7.2	0.66	0.69	0.73																																																							
6.0	0.70	0.75	0.77																																																							
4.8	0.76	0.80	0.80																																																							
3.6	0.80	0.83	0.83																																																							
2.4	0.82	0.84	0.83																																																							
1.2	0.78	0.80	0.79																																																							
0.0	0.93	0.97	1.12																																																							
Object	-12V0.25A																																																									
1.Graph		2.Values																																																								
	<p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p>																																																									
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.26</td><td>0.26</td><td>0.26</td></tr> <tr><td>-11.4</td><td>0.45</td><td>0.50</td><td>0.60</td></tr> <tr><td>-10.8</td><td>0.47</td><td>0.52</td><td>0.61</td></tr> <tr><td>-9.6</td><td>0.53</td><td>0.57</td><td>0.65</td></tr> <tr><td>-8.4</td><td>0.58</td><td>0.63</td><td>0.69</td></tr> <tr><td>-7.2</td><td>0.65</td><td>0.69</td><td>0.73</td></tr> <tr><td>-6.0</td><td>0.72</td><td>0.75</td><td>0.77</td></tr> <tr><td>-4.8</td><td>0.76</td><td>0.79</td><td>0.81</td></tr> <tr><td>-3.6</td><td>0.81</td><td>0.83</td><td>0.83</td></tr> <tr><td>-2.4</td><td>0.82</td><td>0.84</td><td>0.83</td></tr> <tr><td>-1.2</td><td>0.79</td><td>0.80</td><td>0.79</td></tr> <tr><td>0.0</td><td>0.86</td><td>0.92</td><td>1.05</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-12.0	0.26	0.26	0.26	-11.4	0.45	0.50	0.60	-10.8	0.47	0.52	0.61	-9.6	0.53	0.57	0.65	-8.4	0.58	0.63	0.69	-7.2	0.65	0.69	0.73	-6.0	0.72	0.75	0.77	-4.8	0.76	0.79	0.81	-3.6	0.81	0.83	0.83	-2.4	0.82	0.84	0.83	-1.2	0.79	0.80	0.79	0.0	0.86	0.92	1.05
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
-12.0	0.26	0.26	0.26																																																							
-11.4	0.45	0.50	0.60																																																							
-10.8	0.47	0.52	0.61																																																							
-9.6	0.53	0.57	0.65																																																							
-8.4	0.58	0.63	0.69																																																							
-7.2	0.65	0.69	0.73																																																							
-6.0	0.72	0.75	0.77																																																							
-4.8	0.76	0.79	0.81																																																							
-3.6	0.81	0.83	0.83																																																							
-2.4	0.82	0.84	0.83																																																							
-1.2	0.79	0.80	0.79																																																							
0.0	0.86	0.92	1.05																																																							
	Note: Slanted line shows the range of the rated load current.																																																									




Figure A




Figure B (Ripple and Ripple noise Characteristic)