

# TEST DATA OF SUTW60515

Regulated DC Power Supply  
March 16, 2009

Approved by : *Kazunari Asano*  
Kazunari Asano Design Manager

Prepared by : *Sho Saito*  
Sho Saito Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	10
10. Ripple-Noise . . . . .	12
11. Ripple Voltage (by Ambient Temperature) . . . . .	14
12. Ambient Temperature Drift . . . . .	15
13. Output Voltage Accuracy . . . . .	16
14. Time Lapse Drift . . . . .	17
15. Rise and Fall Time . . . . .	18
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17. Overcurrent Protection . . . . .	21
18. Figure of Testing Circuitry . . . . .	22

(Final Page 22)



<b>COSEL</b>																																																																																		
Model	SUTW60515	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> </div> <div style="width: 35%;"> <p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- · -○- · - Load 0%</p> </div> </div>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>2.00</td><td>0.010</td><td>0.010</td><td>0.010</td></tr> <tr><td>3.00</td><td>0.010</td><td>0.011</td><td>0.011</td></tr> <tr><td>3.49</td><td>0.015</td><td>0.033</td><td>0.041</td></tr> <tr><td>3.83</td><td>0.135</td><td>0.993</td><td>1.966</td></tr> <tr><td>4.00</td><td>0.135</td><td>0.964</td><td>1.898</td></tr> <tr><td>4.50</td><td>0.124</td><td>0.878</td><td>1.680</td></tr> <tr><td>5.00</td><td>0.116</td><td>0.774</td><td>1.473</td></tr> <tr><td>6.00</td><td>0.100</td><td>0.651</td><td>1.220</td></tr> <tr><td>7.00</td><td>0.096</td><td>0.556</td><td>1.029</td></tr> <tr><td>8.00</td><td>0.090</td><td>0.489</td><td>0.919</td></tr> <tr><td>9.00</td><td>0.087</td><td>0.444</td><td>0.813</td></tr> <tr><td>10.00</td><td>0.086</td><td>0.407</td><td>0.743</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.010	0.010	0.010	2.00	0.010	0.010	0.010	3.00	0.010	0.011	0.011	3.49	0.015	0.033	0.041	3.83	0.135	0.993	1.966	4.00	0.135	0.964	1.898	4.50	0.124	0.878	1.680	5.00	0.116	0.774	1.473	6.00	0.100	0.651	1.220	7.00	0.096	0.556	1.029	8.00	0.090	0.489	0.919	9.00	0.087	0.444	0.813	10.00	0.086	0.407	0.743	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.00	0.000	0.000	0.000																																																																															
1.70	0.010	0.010	0.010																																																																															
2.00	0.010	0.010	0.010																																																																															
3.00	0.010	0.011	0.011																																																																															
3.49	0.015	0.033	0.041																																																																															
3.83	0.135	0.993	1.966																																																																															
4.00	0.135	0.964	1.898																																																																															
4.50	0.124	0.878	1.680																																																																															
5.00	0.116	0.774	1.473																																																																															
6.00	0.100	0.651	1.220																																																																															
7.00	0.096	0.556	1.029																																																																															
8.00	0.090	0.489	0.919																																																																															
9.00	0.087	0.444	0.813																																																																															
10.00	0.086	0.407	0.743																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		



<b>COSEL</b>																																																						
Model	SUTW60515	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 4.5V                      - - - □ - - - Input Volt. 5V                      - - - ○ - - - Input Volt. 9V                 </p> <p>Input Current [A]</p> <p>Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.121</td><td>0.115</td><td>0.086</td></tr> <tr><td>20</td><td>0.405</td><td>0.364</td><td>0.232</td></tr> <tr><td>40</td><td>0.699</td><td>0.625</td><td>0.368</td></tr> <tr><td>60</td><td>0.986</td><td>0.892</td><td>0.513</td></tr> <tr><td>80</td><td>1.324</td><td>1.141</td><td>0.653</td></tr> <tr><td>100</td><td>1.631</td><td>1.435</td><td>0.799</td></tr> <tr><td>110</td><td>1.810</td><td>1.590</td><td>0.874</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.121	0.115	0.086	20	0.405	0.364	0.232	40	0.699	0.625	0.368	60	0.986	0.892	0.513	80	1.324	1.141	0.653	100	1.631	1.435	0.799	110	1.810	1.590	0.874	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	0.121	0.115	0.086																																																			
20	0.405	0.364	0.232																																																			
40	0.699	0.625	0.368																																																			
60	0.986	0.892	0.513																																																			
80	1.324	1.141	0.653																																																			
100	1.631	1.435	0.799																																																			
110	1.810	1.590	0.874																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



<b>COSEL</b>																																																						
Model	SUTW60515	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> <span style="display: inline-block; width: 100px; border-bottom: 1px solid black; margin-right: 5px;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; border-radius: 50%; margin-right: 5px;"></span> Input Volt. 4.5V  <span style="display: inline-block; width: 100px; border-bottom: 1px dashed black; margin-right: 5px;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; border-radius: 50%; margin-right: 5px;"></span> Input Volt. 5V  <span style="display: inline-block; width: 100px; border-bottom: 1px dash-dot black; margin-right: 5px;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; border-radius: 50%; margin-right: 5px;"></span> Input Volt. 9V                 </p> <p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Ration [%]</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.53</td><td>0.55</td><td>0.79</td></tr> <tr><td>20</td><td>1.80</td><td>1.82</td><td>2.06</td></tr> <tr><td>40</td><td>3.10</td><td>3.11</td><td>3.31</td></tr> <tr><td>60</td><td>4.48</td><td>4.44</td><td>4.58</td></tr> <tr><td>80</td><td>5.89</td><td>5.83</td><td>5.87</td></tr> <tr><td>100</td><td>7.36</td><td>7.25</td><td>7.15</td></tr> <tr><td>110</td><td>8.12</td><td>7.98</td><td>7.80</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.53	0.55	0.79	20	1.80	1.82	2.06	40	3.10	3.11	3.31	60	4.48	4.44	4.58	80	5.89	5.83	5.87	100	7.36	7.25	7.15	110	8.12	7.98	7.80	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	0.53	0.55	0.79																																																			
20	1.80	1.82	2.06																																																			
40	3.10	3.11	3.31																																																			
60	4.48	4.44	4.58																																																			
80	5.89	5.83	5.87																																																			
100	7.36	7.25	7.15																																																			
110	8.12	7.98	7.80																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



<p>Model SUTW60515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item</p>	<p>Efficiency (by Input Voltage)</p>																																	
<p>Object</p>	<p>_____</p>																																	
<p>1.Graph</p>		<p>2.Values</p>																																
<p>---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>78.8</td><td>80.1</td></tr> <tr><td>4.5</td><td>79.4</td><td>81.4</td></tr> <tr><td>5.0</td><td>79.7</td><td>82.6</td></tr> <tr><td>6.0</td><td>79.5</td><td>83.8</td></tr> <tr><td>7.0</td><td>78.8</td><td>84.2</td></tr> <tr><td>8.0</td><td>77.6</td><td>84.5</td></tr> <tr><td>9.0</td><td>76.1</td><td>83.8</td></tr> <tr><td>9.5</td><td>75.2</td><td>83.6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	78.8	80.1	4.5	79.4	81.4	5.0	79.7	82.6	6.0	79.5	83.8	7.0	78.8	84.2	8.0	77.6	84.5	9.0	76.1	83.8	9.5	75.2	83.6	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.0	78.8	80.1																																
4.5	79.4	81.4																																
5.0	79.7	82.6																																
6.0	79.5	83.8																																
7.0	78.8	84.2																																
8.0	77.6	84.5																																
9.0	76.1	83.8																																
9.5	75.2	83.6																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model SUTW60515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p>                     —△— Input Volt. 4.5V                      - - - □ - - - Input Volt. 5V                      - · - ○ - · - - Input Volt. 9V                 </p> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>66.7</td> <td>66.2</td> <td>58.4</td> </tr> <tr> <td>40</td> <td>77.5</td> <td>77.3</td> <td>72.6</td> </tr> <tr> <td>60</td> <td>80.4</td> <td>81.2</td> <td>78.6</td> </tr> <tr> <td>80</td> <td>81.5</td> <td>82.4</td> <td>81.9</td> </tr> <tr> <td>100</td> <td>81.5</td> <td>82.8</td> <td>84.0</td> </tr> <tr> <td>110</td> <td>81.3</td> <td>82.8</td> <td>84.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	66.7	66.2	58.4	40	77.5	77.3	72.6	60	80.4	81.2	78.6	80	81.5	82.4	81.9	100	81.5	82.8	84.0	110	81.3	82.8	84.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0	-	-	-																																																		
20	66.7	66.2	58.4																																																		
40	77.5	77.3	72.6																																																		
60	80.4	81.2	78.6																																																		
80	81.5	82.4	81.9																																																		
100	81.5	82.8	84.0																																																		
110	81.3	82.8	84.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




<b>COSEL</b>																																			
Model	SUTW60515	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V0.2A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>15.052</td><td>14.991</td></tr> <tr><td>4.5</td><td>15.050</td><td>14.992</td></tr> <tr><td>5.0</td><td>15.048</td><td>14.992</td></tr> <tr><td>6.0</td><td>15.046</td><td>14.993</td></tr> <tr><td>7.0</td><td>15.044</td><td>14.993</td></tr> <tr><td>8.0</td><td>15.043</td><td>14.994</td></tr> <tr><td>9.0</td><td>15.042</td><td>14.993</td></tr> <tr><td>9.5</td><td>15.041</td><td>14.994</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	15.052	14.991	4.5	15.050	14.992	5.0	15.048	14.992	6.0	15.046	14.993	7.0	15.044	14.993	8.0	15.043	14.994	9.0	15.042	14.993	9.5	15.041	14.994	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	15.052	14.991																																	
4.5	15.050	14.992																																	
5.0	15.048	14.992																																	
6.0	15.046	14.993																																	
7.0	15.044	14.993																																	
8.0	15.043	14.994																																	
9.0	15.042	14.993																																	
9.5	15.041	14.994																																	
--	-	-																																	
Object	-15V0.2A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-15.053</td><td>-14.994</td></tr> <tr><td>4.5</td><td>-15.051</td><td>-14.994</td></tr> <tr><td>5.0</td><td>-15.048</td><td>-14.994</td></tr> <tr><td>6.0</td><td>-15.045</td><td>-14.993</td></tr> <tr><td>7.0</td><td>-15.043</td><td>-14.992</td></tr> <tr><td>8.0</td><td>-15.041</td><td>-14.992</td></tr> <tr><td>9.0</td><td>-15.041</td><td>-14.992</td></tr> <tr><td>9.5</td><td>-15.040</td><td>-14.992</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-15.053	-14.994	4.5	-15.051	-14.994	5.0	-15.048	-14.994	6.0	-15.045	-14.993	7.0	-15.043	-14.992	8.0	-15.041	-14.992	9.0	-15.041	-14.992	9.5	-15.040	-14.992	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	-15.053	-14.994																																	
4.5	-15.051	-14.994																																	
5.0	-15.048	-14.994																																	
6.0	-15.045	-14.993																																	
7.0	-15.043	-14.992																																	
8.0	-15.041	-14.992																																	
9.0	-15.041	-14.992																																	
9.5	-15.040	-14.992																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model	SUTW60515
Item	Load Regulation
Object	+15V0.2A

Temperature 25°C  
Testing Circuitry Figure A

1.Graph  
 —△— Input Volt. 4.5V  
 ---□--- Input Volt. 5V  
 -·-○-·- Input Volt. 9V




2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	15.225	15.219	15.196
0.04	15.104	15.102	15.092
0.08	15.064	15.062	15.055
0.12	15.037	15.036	15.031
0.16	15.014	15.013	15.011
0.20	14.992	14.993	14.993
0.22	14.981	14.982	14.985
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Object	-15V0.2A
--------	----------

1.Graph  
 —△— Input Volt. 4.5V  
 ---□--- Input Volt. 5V  
 -·-○-·- Input Volt. 9V



2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	-15.249	-15.238	-15.210
0.04	-15.108	-15.106	-15.095
0.08	-15.065	-15.062	-15.054
0.12	-15.037	-15.036	-15.029
0.16	-15.015	-15.014	-15.009
0.20	-14.994	-14.994	-14.992
0.22	-14.984	-14.984	-14.983
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.




Model	SUTW60515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.2A		

Input Volt. 48 V  
 Cycle 100 mS



Min. Load (0A)  $\longleftrightarrow$   
 Load 100% (0.2A)

500mV/div




500µs/div




500µs/div

Min. Load (0A)  $\longleftrightarrow$   
 Load 50% (0.1A)

500mV/div




500µs/div



500µs/div

Load 50% (0.1A)  $\longleftrightarrow$   
 Load 100% (0.2A)

500mV/div



500µs/div



500µs/div




Model	SUTW60515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V0.2A		

Input Volt. 48 V  
 Cycle 100 mS




Min. Load (0A)  $\longleftrightarrow$   
 Load 100% (0.2A)

500mV/div




500µs/div



500µs/div

Min. Load (0A)  $\longleftrightarrow$   
 Load 50% (0.1A)

500mV/div




500µs/div



500µs/div

Load 50% (0.1A)  $\longleftrightarrow$   
 Load 100% (0.2A)

500mV/div



500µs/div



500µs/div

<p>Model SUTW60515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+15V0.2A																																							
<p>1.Graph</p> <p>             —△— Input Volt. 9V              - - -○- - - Input Volt. 18V         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>3</td></tr> <tr><td>0.04</td><td>4</td><td>3</td></tr> <tr><td>0.08</td><td>5</td><td>3</td></tr> <tr><td>0.12</td><td>5</td><td>4</td></tr> <tr><td>0.16</td><td>8</td><td>6</td></tr> <tr><td>0.20</td><td>10</td><td>7</td></tr> <tr><td>0.22</td><td>13</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	4	3	0.04	4	3	0.08	5	3	0.12	5	4	0.16	8	6	0.20	10	7	0.22	13	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	4	3																																						
0.04	4	3																																						
0.08	5	3																																						
0.12	5	4																																						
0.16	8	6																																						
0.20	10	7																																						
0.22	13	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

<p>Model SUTW60515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	-15V0.2A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 9V - - -○- - - Input Volt. 18V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>4</td></tr> <tr><td>0.04</td><td>4</td><td>4</td></tr> <tr><td>0.08</td><td>4</td><td>4</td></tr> <tr><td>0.12</td><td>6</td><td>5</td></tr> <tr><td>0.16</td><td>7</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>6</td></tr> <tr><td>0.22</td><td>12</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	4	4	0.04	4	4	0.08	4	4	0.12	6	5	0.16	7	5	0.20	10	6	0.22	12	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	4	4																																						
0.04	4	4																																						
0.08	4	4																																						
0.12	6	5																																						
0.16	7	5																																						
0.20	10	6																																						
0.22	12	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

<p>Model SUTW60515</p> <p>Item Ripple-Noise</p> <p>Object +15V0.2A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 9V</p> <p>- - -○- - - Input Volt. 18V</p> </div> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>3</td></tr> <tr><td>0.04</td><td>4</td><td>3</td></tr> <tr><td>0.08</td><td>5</td><td>3</td></tr> <tr><td>0.12</td><td>5</td><td>4</td></tr> <tr><td>0.16</td><td>8</td><td>6</td></tr> <tr><td>0.20</td><td>10</td><td>7</td></tr> <tr><td>0.22</td><td>13</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	4	3	0.04	4	3	0.08	5	3	0.12	5	4	0.16	8	6	0.20	10	7	0.22	13	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	4	3																																						
0.04	4	3																																						
0.08	5	3																																						
0.12	5	4																																						
0.16	8	6																																						
0.20	10	7																																						
0.22	13	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

<p>Model SUTW60515</p> <p>Item Ripple-Noise</p> <p>Object -15V0.2A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>             —△— Input Volt. 9V              - - ○ - - Input Volt. 18V         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>4</td></tr> <tr><td>0.04</td><td>4</td><td>4</td></tr> <tr><td>0.08</td><td>4</td><td>4</td></tr> <tr><td>0.12</td><td>6</td><td>5</td></tr> <tr><td>0.16</td><td>7</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>6</td></tr> <tr><td>0.22</td><td>12</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	4	4	0.04	4	4	0.08	4	4	0.12	6	5	0.16	7	5	0.20	10	6	0.22	12	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	4	4																																						
0.04	4	4																																						
0.08	4	4																																						
0.12	6	5																																						
0.16	7	5																																						
0.20	10	6																																						
0.22	12	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.                  Ripple-Noise is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



<b>Model</b> SUTW60515		Testing Circuitry Figure B																																							
<b>Item</b> Ripple Voltage (by Ambient Temp.)																																									
<b>Object</b> +15V0.2A																																									
<p>1.Graph</p> <div style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 12V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>9</td></tr> <tr><td>-40</td><td>5</td><td>9</td></tr> <tr><td>-20</td><td>5</td><td>9</td></tr> <tr><td>0</td><td>5</td><td>8</td></tr> <tr><td>25</td><td>4</td><td>8</td></tr> <tr><td>55</td><td>4</td><td>8</td></tr> <tr><td>60</td><td>4</td><td>8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	9	-40	5	9	-20	5	9	0	5	8	25	4	8	55	4	8	60	4	8	--	-	-	--	-	-	--	-	-	--	-	-	
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-60	5	9																																							
-40	5	9																																							
-20	5	9																																							
0	5	8																																							
25	4	8																																							
55	4	8																																							
60	4	8																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<b>Object</b> -15V0.2A		Testing Circuitry Figure B																																							
<p>1.Graph</p> <div style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 12V</p> <p>Measured by 100 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>			<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>4</td><td>6</td></tr> <tr><td>-40</td><td>4</td><td>6</td></tr> <tr><td>-20</td><td>4</td><td>6</td></tr> <tr><td>0</td><td>4</td><td>6</td></tr> <tr><td>25</td><td>4</td><td>5</td></tr> <tr><td>55</td><td>4</td><td>5</td></tr> <tr><td>60</td><td>4</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	4	6	-40	4	6	-20	4	6	0	4	6	25	4	5	55	4	5	60	4	5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-60	4	6																																							
-40	4	6																																							
-20	4	6																																							
0	4	6																																							
25	4	5																																							
55	4	5																																							
60	4	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							



<b>COSEL</b>																																																					
Model	SUTW60515																																																				
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																			
Object	+15V0.2A																																																				
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 50%;"> <p>—△— Input Volt. 4.5V                  ---□--- Input Volt. 5V                  -·-○-·- Input Volt. 9V</p> </div> </div>	<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.920</td><td>14.921</td><td>14.922</td></tr> <tr><td>-40</td><td>14.947</td><td>14.948</td><td>14.948</td></tr> <tr><td>-20</td><td>14.966</td><td>14.967</td><td>14.968</td></tr> <tr><td>0</td><td>14.981</td><td>14.982</td><td>14.983</td></tr> <tr><td>25</td><td>14.991</td><td>14.992</td><td>14.993</td></tr> <tr><td>55</td><td>14.993</td><td>14.993</td><td>14.994</td></tr> <tr><td>60</td><td>14.992</td><td>14.993</td><td>14.993</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	14.920	14.921	14.922	-40	14.947	14.948	14.948	-20	14.966	14.967	14.968	0	14.981	14.982	14.983	25	14.991	14.992	14.993	55	14.993	14.993	14.994	60	14.992	14.993	14.993	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
-60	14.920	14.921	14.922																																																		
-40	14.947	14.948	14.948																																																		
-20	14.966	14.967	14.968																																																		
0	14.981	14.982	14.983																																																		
25	14.991	14.992	14.993																																																		
55	14.993	14.993	14.994																																																		
60	14.992	14.993	14.993																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Object	-15V0.2A																																																				
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 50%;"> <p>—△— Input Volt. 4.5V                  ---□--- Input Volt. 5V                  -·-○-·- Input Volt. 9V</p> </div> </div>	<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.920</td><td>-14.920</td><td>-14.919</td></tr> <tr><td>-40</td><td>-14.946</td><td>-14.947</td><td>-14.946</td></tr> <tr><td>-20</td><td>-14.967</td><td>-14.967</td><td>-14.966</td></tr> <tr><td>0</td><td>-14.982</td><td>-14.982</td><td>-14.981</td></tr> <tr><td>25</td><td>-14.993</td><td>-14.993</td><td>-14.991</td></tr> <tr><td>55</td><td>-14.995</td><td>-14.995</td><td>-14.993</td></tr> <tr><td>60</td><td>-14.995</td><td>-14.995</td><td>-14.992</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-14.920	-14.920	-14.919	-40	-14.946	-14.947	-14.946	-20	-14.967	-14.967	-14.966	0	-14.982	-14.982	-14.981	25	-14.993	-14.993	-14.991	55	-14.995	-14.995	-14.993	60	-14.995	-14.995	-14.992	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
-60	-14.920	-14.920	-14.919																																																		
-40	-14.946	-14.947	-14.946																																																		
-20	-14.967	-14.967	-14.966																																																		
0	-14.982	-14.982	-14.981																																																		
25	-14.993	-14.993	-14.991																																																		
55	-14.995	-14.995	-14.993																																																		
60	-14.995	-14.995	-14.992																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					



<b>COSEL</b>		
Model	SUTW60515	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.2A (AVR 2) : 0 - 0.2A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+15V0.2A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	15.231	±254	±1.7
Minimum Voltage	-40	4.5	0.2	14.724		

Object		-15V0.2A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	-15.255	±253	±1.7
Minimum Voltage	-40	4.5	0.2	-14.750		




<b>COSEL</b>																									
Model	SUTW60515	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.2A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt.     5V Load                100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.986</td></tr> <tr><td>0.5</td><td>14.990</td></tr> <tr><td>1.0</td><td>14.990</td></tr> <tr><td>2.0</td><td>14.990</td></tr> <tr><td>3.0</td><td>14.990</td></tr> <tr><td>4.0</td><td>14.990</td></tr> <tr><td>5.0</td><td>14.990</td></tr> <tr><td>6.0</td><td>14.990</td></tr> <tr><td>7.0</td><td>14.990</td></tr> <tr><td>8.0</td><td>14.990</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	14.986	0.5	14.990	1.0	14.990	2.0	14.990	3.0	14.990	4.0	14.990	5.0	14.990	6.0	14.990	7.0	14.990	8.0	14.990
Time since start [H]	Output Voltage [V]																								
0.0	14.986																								
0.5	14.990																								
1.0	14.990																								
2.0	14.990																								
3.0	14.990																								
4.0	14.990																								
5.0	14.990																								
6.0	14.990																								
7.0	14.990																								
8.0	14.990																								
Object	-15V0.2A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt.     5V Load                100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.992</td></tr> <tr><td>0.5</td><td>-14.996</td></tr> <tr><td>1.0</td><td>-14.996</td></tr> <tr><td>2.0</td><td>-14.996</td></tr> <tr><td>3.0</td><td>-14.996</td></tr> <tr><td>4.0</td><td>-14.996</td></tr> <tr><td>5.0</td><td>-14.996</td></tr> <tr><td>6.0</td><td>-14.996</td></tr> <tr><td>7.0</td><td>-14.996</td></tr> <tr><td>8.0</td><td>-14.996</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-14.992	0.5	-14.996	1.0	-14.996	2.0	-14.996	3.0	-14.996	4.0	-14.996	5.0	-14.996	6.0	-14.996	7.0	-14.996	8.0	-14.996
Time since start [H]	Output Voltage [V]																								
0.0	-14.992																								
0.5	-14.996																								
1.0	-14.996																								
2.0	-14.996																								
3.0	-14.996																								
4.0	-14.996																								
5.0	-14.996																								
6.0	-14.996																								
7.0	-14.996																								
8.0	-14.996																								



<b>COSEL</b>			
Model	SUTW60515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.2A		

1. Graph


Input Volt. 5 V



2. Values

[mS]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.2	3.5	3.7	0.1	3.9
100 %	0.2	3.6	3.8	0.1	2.0






Model		SUTW60515	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		-15V0.2A		

1. Graph


Input Volt. 5 V



2. Values

[mS]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.2	3.5	3.7	0.1	4.2
100 %	0.2	3.7	3.9	0.1	2.1






Model	SUTW60515
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.1	2.7
-20	2.3	2.7
0	2.2	2.7
25	2.2	2.8
55	2.2	2.9
60	2.3	3.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.0	2.7
-20	2.0	2.7
0	2.2	2.7
25	2.2	2.8
55	2.2	2.9
60	2.2	2.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<b>COSEL</b>																																																										
Model	SUTW60515	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+15V0.2A																																																									
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>14.3</td><td>0.33</td><td>0.36</td><td>0.37</td></tr> <tr><td>13.5</td><td>0.35</td><td>0.38</td><td>0.38</td></tr> <tr><td>12.0</td><td>0.39</td><td>0.42</td><td>0.41</td></tr> <tr><td>10.5</td><td>0.43</td><td>0.46</td><td>0.43</td></tr> <tr><td>9.0</td><td>0.48</td><td>0.50</td><td>0.46</td></tr> <tr><td>7.5</td><td>0.52</td><td>0.54</td><td>0.48</td></tr> <tr><td>6.0</td><td>0.56</td><td>0.57</td><td>0.51</td></tr> <tr><td>4.5</td><td>0.58</td><td>0.59</td><td>0.52</td></tr> <tr><td>3.0</td><td>0.58</td><td>0.59</td><td>0.53</td></tr> <tr><td>1.5</td><td>0.55</td><td>0.55</td><td>0.50</td></tr> <tr><td>0.0</td><td>0.55</td><td>0.59</td><td>0.62</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	15.0	0.20	0.20	0.20	14.3	0.33	0.36	0.37	13.5	0.35	0.38	0.38	12.0	0.39	0.42	0.41	10.5	0.43	0.46	0.43	9.0	0.48	0.50	0.46	7.5	0.52	0.54	0.48	6.0	0.56	0.57	0.51	4.5	0.58	0.59	0.52	3.0	0.58	0.59	0.53	1.5	0.55	0.55	0.50	0.0	0.55	0.59	0.62
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
15.0	0.20	0.20	0.20																																																							
14.3	0.33	0.36	0.37																																																							
13.5	0.35	0.38	0.38																																																							
12.0	0.39	0.42	0.41																																																							
10.5	0.43	0.46	0.43																																																							
9.0	0.48	0.50	0.46																																																							
7.5	0.52	0.54	0.48																																																							
6.0	0.56	0.57	0.51																																																							
4.5	0.58	0.59	0.52																																																							
3.0	0.58	0.59	0.53																																																							
1.5	0.55	0.55	0.50																																																							
0.0	0.55	0.59	0.62																																																							
Object	-15V0.2A																																																									
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.21</td><td>0.21</td><td>0.21</td></tr> <tr><td>-14.25</td><td>0.33</td><td>0.36</td><td>0.37</td></tr> <tr><td>-13.50</td><td>0.35</td><td>0.38</td><td>0.38</td></tr> <tr><td>-12.00</td><td>0.39</td><td>0.42</td><td>0.41</td></tr> <tr><td>-10.50</td><td>0.43</td><td>0.46</td><td>0.43</td></tr> <tr><td>-9.00</td><td>0.48</td><td>0.50</td><td>0.46</td></tr> <tr><td>-7.50</td><td>0.52</td><td>0.54</td><td>0.48</td></tr> <tr><td>-6.00</td><td>0.56</td><td>0.57</td><td>0.51</td></tr> <tr><td>-4.50</td><td>0.58</td><td>0.59</td><td>0.53</td></tr> <tr><td>-3.00</td><td>0.58</td><td>0.59</td><td>0.53</td></tr> <tr><td>-1.50</td><td>0.55</td><td>0.55</td><td>0.50</td></tr> <tr><td>0.00</td><td>0.53</td><td>0.56</td><td>0.59</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-15.00	0.21	0.21	0.21	-14.25	0.33	0.36	0.37	-13.50	0.35	0.38	0.38	-12.00	0.39	0.42	0.41	-10.50	0.43	0.46	0.43	-9.00	0.48	0.50	0.46	-7.50	0.52	0.54	0.48	-6.00	0.56	0.57	0.51	-4.50	0.58	0.59	0.53	-3.00	0.58	0.59	0.53	-1.50	0.55	0.55	0.50	0.00	0.53	0.56	0.59
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
-15.00	0.21	0.21	0.21																																																							
-14.25	0.33	0.36	0.37																																																							
-13.50	0.35	0.38	0.38																																																							
-12.00	0.39	0.42	0.41																																																							
-10.50	0.43	0.46	0.43																																																							
-9.00	0.48	0.50	0.46																																																							
-7.50	0.52	0.54	0.48																																																							
-6.00	0.56	0.57	0.51																																																							
-4.50	0.58	0.59	0.53																																																							
-3.00	0.58	0.59	0.53																																																							
-1.50	0.55	0.55	0.50																																																							
0.00	0.53	0.56	0.59																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										




Figure A




Figure B (Ripple and Ripple noise Characteristic)