

TEST DATA OF SUTW62412

Regulated DC Power Supply
March 17, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)


Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>8.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>12.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>14.0</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>14.8</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>15.6</td><td>0.029</td><td>0.238</td><td>0.466</td></tr> <tr><td>16.0</td><td>0.028</td><td>0.233</td><td>0.453</td></tr> <tr><td>18.0</td><td>0.026</td><td>0.206</td><td>0.401</td></tr> <tr><td>20.0</td><td>0.025</td><td>0.187</td><td>0.359</td></tr> <tr><td>24.0</td><td>0.023</td><td>0.158</td><td>0.300</td></tr> <tr><td>28.0</td><td>0.023</td><td>0.139</td><td>0.259</td></tr> <tr><td>32.0</td><td>0.024</td><td>0.124</td><td>0.229</td></tr> <tr><td>36.0</td><td>0.025</td><td>0.114</td><td>0.205</td></tr> <tr><td>40.0</td><td>0.026</td><td>0.105</td><td>0.188</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.009	0.009	0.009	8.0	0.008	0.008	0.008	12.0	0.009	0.009	0.009	14.0	0.008	0.008	0.008	14.8	0.007	0.007	0.007	15.6	0.029	0.238	0.466	16.0	0.028	0.233	0.453	18.0	0.026	0.206	0.401	20.0	0.025	0.187	0.359	24.0	0.023	0.158	0.300	28.0	0.023	0.139	0.259	32.0	0.024	0.124	0.229	36.0	0.025	0.114	0.205	40.0	0.026	0.105	0.188	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.009	0.009	0.009																																																																																
8.0	0.008	0.008	0.008																																																																																
12.0	0.009	0.009	0.009																																																																																
14.0	0.008	0.008	0.008																																																																																
14.8	0.007	0.007	0.007																																																																																
15.6	0.029	0.238	0.466																																																																																
16.0	0.028	0.233	0.453																																																																																
18.0	0.026	0.206	0.401																																																																																
20.0	0.025	0.187	0.359																																																																																
24.0	0.023	0.158	0.300																																																																																
28.0	0.023	0.139	0.259																																																																																
32.0	0.024	0.124	0.229																																																																																
36.0	0.025	0.114	0.205																																																																																
40.0	0.026	0.105	0.188																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Input Current (by Load Current)																																																						
Object	_____	2.Values																																																					
1.Graph	_____	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○- - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.026</td><td>0.023</td><td>0.024</td></tr> <tr><td>20</td><td>0.098</td><td>0.077</td><td>0.061</td></tr> <tr><td>40</td><td>0.171</td><td>0.130</td><td>0.096</td></tr> <tr><td>60</td><td>0.245</td><td>0.185</td><td>0.132</td></tr> <tr><td>80</td><td>0.319</td><td>0.241</td><td>0.168</td></tr> <tr><td>100</td><td>0.395</td><td>0.296</td><td>0.204</td></tr> <tr><td>110</td><td>0.434</td><td>0.326</td><td>0.222</td></tr> </tbody> </table>			Load Ration [%]	18V [A]	24V [A]	36V [A]	0	0.026	0.023	0.024	20	0.098	0.077	0.061	40	0.171	0.130	0.096	60	0.245	0.185	0.132	80	0.319	0.241	0.168	100	0.395	0.296	0.204	110	0.434	0.326	0.222																			
Load Ration [%]	18V [A]	24V [A]	36V [A]																																																				
0	0.026	0.023	0.024																																																				
20	0.098	0.077	0.061																																																				
40	0.171	0.130	0.096																																																				
60	0.245	0.185	0.132																																																				
80	0.319	0.241	0.168																																																				
100	0.395	0.296	0.204																																																				
110	0.434	0.326	0.222																																																				
2.	Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.026</td><td>0.023</td><td>0.024</td></tr> <tr><td>20</td><td>0.098</td><td>0.077</td><td>0.061</td></tr> <tr><td>40</td><td>0.171</td><td>0.130</td><td>0.096</td></tr> <tr><td>60</td><td>0.245</td><td>0.185</td><td>0.132</td></tr> <tr><td>80</td><td>0.319</td><td>0.241</td><td>0.168</td></tr> <tr><td>100</td><td>0.395</td><td>0.296</td><td>0.204</td></tr> <tr><td>110</td><td>0.434</td><td>0.326</td><td>0.222</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.026	0.023	0.024	20	0.098	0.077	0.061	40	0.171	0.130	0.096	60	0.245	0.185	0.132	80	0.319	0.241	0.168	100	0.395	0.296	0.204	110	0.434	0.326	0.222	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0	0.026	0.023	0.024																																																				
20	0.098	0.077	0.061																																																				
40	0.171	0.130	0.096																																																				
60	0.245	0.185	0.132																																																				
80	0.319	0.241	0.168																																																				
100	0.395	0.296	0.204																																																				
110	0.434	0.326	0.222																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Power (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (18V)</th> <th>Input Power [W] (24V)</th> <th>Input Power [W] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.46</td><td>0.53</td><td>0.85</td></tr> <tr><td>40</td><td>1.76</td><td>1.86</td><td>2.20</td></tr> <tr><td>60</td><td>3.07</td><td>3.18</td><td>3.41</td></tr> <tr><td>80</td><td>4.40</td><td>4.44</td><td>4.78</td></tr> <tr><td>100</td><td>5.74</td><td>5.81</td><td>6.01</td></tr> <tr><td>110</td><td>7.12</td><td>7.14</td><td>7.31</td></tr> <tr><td>120</td><td>7.80</td><td>7.78</td><td>7.99</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)	0	0.46	0.53	0.85	40	1.76	1.86	2.20	60	3.07	3.18	3.41	80	4.40	4.44	4.78	100	5.74	5.81	6.01	110	7.12	7.14	7.31	120	7.80	7.78	7.99
Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)																														
0	0.46	0.53	0.85																														
40	1.76	1.86	2.20																														
60	3.07	3.18	3.41																														
80	4.40	4.44	4.78																														
100	5.74	5.81	6.01																														
110	7.12	7.14	7.31																														
120	7.80	7.78	7.99																														
<p>Load Ration [%]</p>		Input Power [W]																															
		Input Volt. 18[V] Input Volt. 24[V] Input Volt. 36[V]																															
0	0.46	0.53	0.85																														
20	1.76	1.86	2.20																														
40	3.07	3.18	3.41																														
60	4.40	4.44	4.78																														
80	5.74	5.81	6.01																														
100	7.12	7.14	7.31																														
110	7.80	7.78	7.99																														
--	-	-	-																														
--	-	-	-																														
--	-	-	-																														
--	-	-	-																														

Model	SUTW62412	Temperature	25°C
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A
Object	—		

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
16	82.2	84.9
18	82.3	86.4
20	81.4	85.8
24	80.6	85.0
30	78.1	84.4
36	74.6	83.9
40	72.5	81.5
--	-	-
--	-	-

Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [Efficiency %]</th> <th>24V [Efficiency %]</th> <th>36V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>69.3</td><td>65.7</td><td>55.4</td></tr> <tr><td>40</td><td>79.6</td><td>76.7</td><td>71.6</td></tr> <tr><td>60</td><td>83.2</td><td>82.5</td><td>76.6</td></tr> <tr><td>80</td><td>85.1</td><td>84.0</td><td>81.2</td></tr> <tr><td>100</td><td>85.7</td><td>85.5</td><td>83.5</td></tr> <tr><td>110</td><td>86.1</td><td>86.3</td><td>84.0</td></tr> </tbody> </table>	Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]	20	69.3	65.7	55.4	40	79.6	76.7	71.6	60	83.2	82.5	76.6	80	85.1	84.0	81.2	100	85.7	85.5	83.5	110	86.1	86.3	84.0																								
Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]																																																		
20	69.3	65.7	55.4																																																		
40	79.6	76.7	71.6																																																		
60	83.2	82.5	76.6																																																		
80	85.1	84.0	81.2																																																		
100	85.7	85.5	83.5																																																		
110	86.1	86.3	84.0																																																		
2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>69.3</td><td>65.7</td><td>55.4</td></tr> <tr><td>40</td><td>79.6</td><td>76.7</td><td>71.6</td></tr> <tr><td>60</td><td>83.2</td><td>82.5</td><td>76.6</td></tr> <tr><td>80</td><td>85.1</td><td>84.0</td><td>81.2</td></tr> <tr><td>100</td><td>85.7</td><td>85.5</td><td>83.5</td></tr> <tr><td>110</td><td>86.1</td><td>86.3</td><td>84.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	69.3	65.7	55.4	40	79.6	76.7	71.6	60	83.2	82.5	76.6	80	85.1	84.0	81.2	100	85.7	85.5	83.5	110	86.1	86.3	84.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	-	-	-																																																		
20	69.3	65.7	55.4																																																		
40	79.6	76.7	71.6																																																		
60	83.2	82.5	76.6																																																		
80	85.1	84.0	81.2																																																		
100	85.7	85.5	83.5																																																		
110	86.1	86.3	84.0																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Model	SUTW62412
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	12.264	12.198
18	12.262	12.199
20	12.261	12.199
24	12.258	12.199
30	12.254	12.199
36	12.253	12.199
40	12.252	12.199
--	-	-
--	-	-

Object -12V0.25A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-12.270	-12.202
18	-12.268	-12.202
20	-12.265	-12.202
24	-12.262	-12.202
30	-12.259	-12.201
36	-12.257	-12.201
40	-12.257	-12.201
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW62412	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V0.25A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V 	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.463</td><td>12.447</td><td>12.424</td></tr> <tr><td>0.050</td><td>12.322</td><td>12.318</td><td>12.310</td></tr> <tr><td>0.100</td><td>12.278</td><td>12.273</td><td>12.267</td></tr> <tr><td>0.150</td><td>12.248</td><td>12.244</td><td>12.241</td></tr> <tr><td>0.200</td><td>12.222</td><td>12.220</td><td>12.218</td></tr> <tr><td>0.250</td><td>12.198</td><td>12.199</td><td>12.199</td></tr> <tr><td>0.275</td><td>12.186</td><td>12.188</td><td>12.189</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	12.463	12.447	12.424	0.050	12.322	12.318	12.310	0.100	12.278	12.273	12.267	0.150	12.248	12.244	12.241	0.200	12.222	12.220	12.218	0.250	12.198	12.199	12.199	0.275	12.186	12.188	12.189	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	12.463	12.447	12.424																																																			
0.050	12.322	12.318	12.310																																																			
0.100	12.278	12.273	12.267																																																			
0.150	12.248	12.244	12.241																																																			
0.200	12.222	12.220	12.218																																																			
0.250	12.198	12.199	12.199																																																			
0.275	12.186	12.188	12.189																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.25A	2.Values																																																				
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V 	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.494</td><td>-12.476</td><td>-12.451</td></tr> <tr><td>0.050</td><td>-12.334</td><td>-12.329</td><td>-12.323</td></tr> <tr><td>0.100</td><td>-12.284</td><td>-12.278</td><td>-12.272</td></tr> <tr><td>0.150</td><td>-12.251</td><td>-12.247</td><td>-12.243</td></tr> <tr><td>0.200</td><td>-12.225</td><td>-12.223</td><td>-12.220</td></tr> <tr><td>0.250</td><td>-12.202</td><td>-12.201</td><td>-12.200</td></tr> <tr><td>0.275</td><td>-12.190</td><td>-12.191</td><td>-12.191</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-12.494	-12.476	-12.451	0.050	-12.334	-12.329	-12.323	0.100	-12.284	-12.278	-12.272	0.150	-12.251	-12.247	-12.243	0.200	-12.225	-12.223	-12.220	0.250	-12.202	-12.201	-12.200	0.275	-12.190	-12.191	-12.191	--	-	-	-	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-12.494	-12.476	-12.451																																																			
0.050	-12.334	-12.329	-12.323																																																			
0.100	-12.284	-12.278	-12.272																																																			
0.150	-12.251	-12.247	-12.243																																																			
0.200	-12.225	-12.223	-12.220																																																			
0.250	-12.202	-12.201	-12.200																																																			
0.275	-12.190	-12.191	-12.191																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL




COSEL



Model	SUTW62412
Item	Ripple Voltage (by Load Current)
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	3	4
0.050	3	4
0.100	4	4
0.150	7	4
0.200	8	5
0.250	12	5
0.275	13	6
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW62412
Item	Ripple Voltage (by Load Current)
Object	-12V0.25A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	5	3
0.050	5	3
0.100	5	3
0.150	8	5
0.200	8	5
0.250	11	5
0.275	14	6
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW62412
Item	Ripple-Noise
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	4	5
0.050	4	5
0.100	5	5
0.150	7	5
0.200	9	7
0.250	13	8
0.275	15	8
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW62412
Item	Ripple-Noise
Object	-12V0.25A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	5	8
0.050	5	8
0.100	5	8
0.150	8	8
0.200	8	10
0.250	12	10
0.275	14	10
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SUTW62412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	9
-20	5	9
0	4	8
25	4	7
55	3	6
60	3	6
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	5
-40	3	5
-20	3	5
0	3	5
25	2	4
55	2	3
60	2	3
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW62412
Item	Ambient Temperature Drift
Object	+12V0.25A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	12.121	12.122	12.121
-40	12.146	12.146	12.146
-20	12.167	12.167	12.167
0	12.183	12.184	12.183
25	12.197	12.198	12.197
55	12.205	12.206	12.205
60	12.206	12.206	12.206
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-12.122	-12.122	-12.122
-40	-12.147	-12.147	-12.147
-20	-12.168	-12.168	-12.168
0	-12.185	-12.185	-12.185
25	-12.200	-12.199	-12.199
55	-12.208	-12.207	-12.207
60	-12.209	-12.208	-12.207
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW62412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.25A (AVR 2) : 0 - 0.25A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	12.480	± 295	± 2.5	
Minimum Voltage	-40	18	0.25	11.890			

Object		-12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	18	0	-12.509	± 293	± 2.4	
Minimum Voltage	-40	18	0.25	-11.924			

COSEL


Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+12V0.25A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.192</td></tr> <tr><td>0.5</td><td>12.198</td></tr> <tr><td>1.0</td><td>12.198</td></tr> <tr><td>2.0</td><td>12.198</td></tr> <tr><td>3.0</td><td>12.198</td></tr> <tr><td>4.0</td><td>12.198</td></tr> <tr><td>5.0</td><td>12.198</td></tr> <tr><td>6.0</td><td>12.198</td></tr> <tr><td>7.0</td><td>12.198</td></tr> <tr><td>8.0</td><td>12.198</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.192	0.5	12.198	1.0	12.198	2.0	12.198	3.0	12.198	4.0	12.198	5.0	12.198	6.0	12.198	7.0	12.198	8.0	12.198
Time since start [H]	Output Voltage [V]																							
0.0	12.192																							
0.5	12.198																							
1.0	12.198																							
2.0	12.198																							
3.0	12.198																							
4.0	12.198																							
5.0	12.198																							
6.0	12.198																							
7.0	12.198																							
8.0	12.198																							
Object -12V0.25A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.198</td></tr> <tr><td>0.5</td><td>-12.204</td></tr> <tr><td>1.0</td><td>-12.204</td></tr> <tr><td>2.0</td><td>-12.204</td></tr> <tr><td>3.0</td><td>-12.204</td></tr> <tr><td>4.0</td><td>-12.204</td></tr> <tr><td>5.0</td><td>-12.204</td></tr> <tr><td>6.0</td><td>-12.204</td></tr> <tr><td>7.0</td><td>-12.205</td></tr> <tr><td>8.0</td><td>-12.205</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.198	0.5	-12.204	1.0	-12.204	2.0	-12.204	3.0	-12.204	4.0	-12.204	5.0	-12.204	6.0	-12.204	7.0	-12.205	8.0	-12.205
Time since start [H]	Output Voltage [V]																							
0.0	-12.198																							
0.5	-12.204																							
1.0	-12.204																							
2.0	-12.204																							
3.0	-12.204																							
4.0	-12.204																							
5.0	-12.204																							
6.0	-12.204																							
7.0	-12.205																							
8.0	-12.205																							

COSEL

Model	SUTW62412
Item	Rise and Fall Time
Object	+12V0.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.3	1.9	2.2	0.7	2.8	
100 %		0.3	2.1	2.4	0.4	1.4	




COSEL

Model	SUTW62412
Item	Rise and Fall Time
Object	-12V0.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.3	2.2	2.5	0.7	3.0
100 %		0.3	2.3	2.6	0.4	1.5




COSEL

Model	SUTW62412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.4	15.5
-40	15.0	15.2
-20	15.0	15.1
0	14.6	15.2
25	14.6	15.0
55	14.4	14.6
60	14.6	14.7
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.2	15.4
-40	15.0	15.2
-20	14.8	15.0
0	14.6	15.0
25	14.6	14.8
55	14.4	14.6
60	14.4	14.6
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW62412	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.25A																																																								
1.Graph	<p>— Input Volt. 18V — Input Volt. 24V — Input Volt. 36V</p>	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.26</td><td>0.26</td><td>0.26</td></tr> <tr><td>11.4</td><td>0.49</td><td>0.52</td><td>0.50</td></tr> <tr><td>10.8</td><td>0.51</td><td>0.54</td><td>0.51</td></tr> <tr><td>9.6</td><td>0.59</td><td>0.60</td><td>0.55</td></tr> <tr><td>8.4</td><td>0.66</td><td>0.67</td><td>0.61</td></tr> <tr><td>7.2</td><td>0.73</td><td>0.72</td><td>0.65</td></tr> <tr><td>6.0</td><td>0.78</td><td>0.77</td><td>0.69</td></tr> <tr><td>4.8</td><td>0.82</td><td>0.80</td><td>0.72</td></tr> <tr><td>3.6</td><td>0.85</td><td>0.81</td><td>0.74</td></tr> <tr><td>2.4</td><td>0.84</td><td>0.79</td><td>0.73</td></tr> <tr><td>1.2</td><td>0.79</td><td>0.73</td><td>0.69</td></tr> <tr><td>0.0</td><td>0.97</td><td>0.91</td><td>0.88</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.0	0.26	0.26	0.26	11.4	0.49	0.52	0.50	10.8	0.51	0.54	0.51	9.6	0.59	0.60	0.55	8.4	0.66	0.67	0.61	7.2	0.73	0.72	0.65	6.0	0.78	0.77	0.69	4.8	0.82	0.80	0.72	3.6	0.85	0.81	0.74	2.4	0.84	0.79	0.73	1.2	0.79	0.73	0.69	0.0	0.97	0.91	0.88
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
12.0	0.26	0.26	0.26																																																						
11.4	0.49	0.52	0.50																																																						
10.8	0.51	0.54	0.51																																																						
9.6	0.59	0.60	0.55																																																						
8.4	0.66	0.67	0.61																																																						
7.2	0.73	0.72	0.65																																																						
6.0	0.78	0.77	0.69																																																						
4.8	0.82	0.80	0.72																																																						
3.6	0.85	0.81	0.74																																																						
2.4	0.84	0.79	0.73																																																						
1.2	0.79	0.73	0.69																																																						
0.0	0.97	0.91	0.88																																																						
Object	-12V0.25A	2.Values																																																							
1.Graph	<p>— Input Volt. 18V — Input Volt. 24V — Input Volt. 36V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.26</td><td>0.26</td><td>0.26</td></tr> <tr><td>-11.4</td><td>0.49</td><td>0.52</td><td>0.50</td></tr> <tr><td>-10.8</td><td>0.51</td><td>0.54</td><td>0.51</td></tr> <tr><td>-9.6</td><td>0.59</td><td>0.60</td><td>0.55</td></tr> <tr><td>-8.4</td><td>0.66</td><td>0.67</td><td>0.61</td></tr> <tr><td>-7.2</td><td>0.73</td><td>0.73</td><td>0.66</td></tr> <tr><td>-6.0</td><td>0.78</td><td>0.77</td><td>0.70</td></tr> <tr><td>-4.8</td><td>0.82</td><td>0.80</td><td>0.73</td></tr> <tr><td>-3.6</td><td>0.85</td><td>0.81</td><td>0.74</td></tr> <tr><td>-2.4</td><td>0.85</td><td>0.79</td><td>0.73</td></tr> <tr><td>-1.2</td><td>0.79</td><td>0.74</td><td>0.69</td></tr> <tr><td>0.0</td><td>0.91</td><td>0.85</td><td>0.83</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-12.0	0.26	0.26	0.26	-11.4	0.49	0.52	0.50	-10.8	0.51	0.54	0.51	-9.6	0.59	0.60	0.55	-8.4	0.66	0.67	0.61	-7.2	0.73	0.73	0.66	-6.0	0.78	0.77	0.70	-4.8	0.82	0.80	0.73	-3.6	0.85	0.81	0.74	-2.4	0.85	0.79	0.73	-1.2	0.79	0.74	0.69	0.0	0.91	0.85	0.83
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
-12.0	0.26	0.26	0.26																																																						
-11.4	0.49	0.52	0.50																																																						
-10.8	0.51	0.54	0.51																																																						
-9.6	0.59	0.60	0.55																																																						
-8.4	0.66	0.67	0.61																																																						
-7.2	0.73	0.73	0.66																																																						
-6.0	0.78	0.77	0.70																																																						
-4.8	0.82	0.80	0.73																																																						
-3.6	0.85	0.81	0.74																																																						
-2.4	0.85	0.79	0.73																																																						
-1.2	0.79	0.74	0.69																																																						
0.0	0.91	0.85	0.83																																																						

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)