

# TEST DATA OF SUTW64815

Regulated DC Power Supply  
March 17, 2009

Approved by : Kazunari Asano  
Kazunari Asano                      Design Manager

COSEL CO.,LTD.

## CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	SUTW64815	Temperature Testing Circuitry      25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Load 100%  <span style="color: black;">□</span> Load 50%  <span style="color: black;">○</span> Load 0%     </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>10</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>20</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>30</td><td>0.000</td><td>0.000</td><td>0.220</td></tr> <tr><td>35</td><td>0.000</td><td>0.010</td><td>0.180</td></tr> <tr><td>40</td><td>0.000</td><td>0.010</td><td>0.160</td></tr> <tr><td>45</td><td>0.000</td><td>0.008</td><td>0.140</td></tr> <tr><td>50</td><td>0.000</td><td>0.005</td><td>0.130</td></tr> <tr><td>60</td><td>0.000</td><td>0.005</td><td>0.110</td></tr> <tr><td>70</td><td>0.000</td><td>0.005</td><td>0.090</td></tr> <tr><td>80</td><td>0.000</td><td>0.005</td><td>0.090</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	10	0.000	0.000	0.000	20	0.000	0.000	0.000	30	0.000	0.000	0.220	35	0.000	0.010	0.180	40	0.000	0.010	0.160	45	0.000	0.008	0.140	50	0.000	0.005	0.130	60	0.000	0.005	0.110	70	0.000	0.005	0.090	80	0.000	0.005	0.090																																		
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																																
0	0.000	0.000	0.000																																																																																
10	0.000	0.000	0.000																																																																																
20	0.000	0.000	0.000																																																																																
30	0.000	0.000	0.220																																																																																
35	0.000	0.010	0.180																																																																																
40	0.000	0.010	0.160																																																																																
45	0.000	0.008	0.140																																																																																
50	0.000	0.005	0.130																																																																																
60	0.000	0.005	0.110																																																																																
70	0.000	0.005	0.090																																																																																
80	0.000	0.005	0.090																																																																																
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>16.0</td><td>0.006</td><td>0.006</td><td>0.006</td></tr> <tr><td>24.0</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>28.2</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>29.8</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>31.4</td><td>0.015</td><td>0.116</td><td>0.224</td></tr> <tr><td>33.0</td><td>0.015</td><td>0.111</td><td>0.213</td></tr> <tr><td>36.0</td><td>0.014</td><td>0.102</td><td>0.195</td></tr> <tr><td>40.0</td><td>0.013</td><td>0.092</td><td>0.174</td></tr> <tr><td>48.0</td><td>0.013</td><td>0.076</td><td>0.146</td></tr> <tr><td>60.0</td><td>0.011</td><td>0.063</td><td>0.117</td></tr> <tr><td>70.0</td><td>0.011</td><td>0.055</td><td>0.103</td></tr> <tr><td>76.0</td><td>0.012</td><td>0.052</td><td>0.094</td></tr> <tr><td>80.0</td><td>0.012</td><td>0.050</td><td>0.092</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.007	0.007	0.007	16.0	0.006	0.006	0.006	24.0	0.005	0.005	0.005	28.2	0.005	0.005	0.005	29.8	0.005	0.005	0.005	31.4	0.015	0.116	0.224	33.0	0.015	0.111	0.213	36.0	0.014	0.102	0.195	40.0	0.013	0.092	0.174	48.0	0.013	0.076	0.146	60.0	0.011	0.063	0.117	70.0	0.011	0.055	0.103	76.0	0.012	0.052	0.094	80.0	0.012	0.050	0.092	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.007	0.007	0.007																																																																																
16.0	0.006	0.006	0.006																																																																																
24.0	0.005	0.005	0.005																																																																																
28.2	0.005	0.005	0.005																																																																																
29.8	0.005	0.005	0.005																																																																																
31.4	0.015	0.116	0.224																																																																																
33.0	0.015	0.111	0.213																																																																																
36.0	0.014	0.102	0.195																																																																																
40.0	0.013	0.092	0.174																																																																																
48.0	0.013	0.076	0.146																																																																																
60.0	0.011	0.063	0.117																																																																																
70.0	0.011	0.055	0.103																																																																																
76.0	0.012	0.052	0.094																																																																																
80.0	0.012	0.050	0.092																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Note: Slanted line shows the range of the rated input voltage.

Model	SUTW64815	Temperature Testing Circuitry      25°C Figure A																																																					
Item	Input Current (by Load Current)																																																						
Object	_____	2.Values																																																					
1.Graph	<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (36V)</th> <th>Input Current [A] (48V)</th> <th>Input Current [A] (76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.014</td><td>0.012</td><td>0.012</td></tr> <tr><td>20</td><td>0.048</td><td>0.037</td><td>0.028</td></tr> <tr><td>40</td><td>0.083</td><td>0.063</td><td>0.045</td></tr> <tr><td>60</td><td>0.121</td><td>0.092</td><td>0.061</td></tr> <tr><td>80</td><td>0.157</td><td>0.117</td><td>0.077</td></tr> <tr><td>100</td><td>0.193</td><td>0.143</td><td>0.094</td></tr> <tr><td>110</td><td>0.210</td><td>0.160</td><td>0.103</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)	0	0.014	0.012	0.012	20	0.048	0.037	0.028	40	0.083	0.063	0.045	60	0.121	0.092	0.061	80	0.157	0.117	0.077	100	0.193	0.143	0.094	110	0.210	0.160	0.103																						
Load Ration [%]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)																																																				
0	0.014	0.012	0.012																																																				
20	0.048	0.037	0.028																																																				
40	0.083	0.063	0.045																																																				
60	0.121	0.092	0.061																																																				
80	0.157	0.117	0.077																																																				
100	0.193	0.143	0.094																																																				
110	0.210	0.160	0.103																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.014</td><td>0.012</td><td>0.012</td></tr> <tr><td>20</td><td>0.048</td><td>0.037</td><td>0.028</td></tr> <tr><td>40</td><td>0.083</td><td>0.063</td><td>0.045</td></tr> <tr><td>60</td><td>0.121</td><td>0.092</td><td>0.061</td></tr> <tr><td>80</td><td>0.157</td><td>0.117</td><td>0.077</td></tr> <tr><td>100</td><td>0.193</td><td>0.143</td><td>0.094</td></tr> <tr><td>110</td><td>0.210</td><td>0.160</td><td>0.103</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.014	0.012	0.012	20	0.048	0.037	0.028	40	0.083	0.063	0.045	60	0.121	0.092	0.061	80	0.157	0.117	0.077	100	0.193	0.143	0.094	110	0.210	0.160	0.103	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0	0.014	0.012	0.012																																																				
20	0.048	0.037	0.028																																																				
40	0.083	0.063	0.045																																																				
60	0.121	0.092	0.061																																																				
80	0.157	0.117	0.077																																																				
100	0.193	0.143	0.094																																																				
110	0.210	0.160	0.103																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	SUTW64815																																																		
Item	Input Power (by Load Current)																																																		
Object	_____																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 36V</li> <li>- -□-- Input Volt. 48V</li> <li>- -○-- Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.45</td><td>0.49</td><td>0.80</td></tr> <tr><td>20</td><td>1.71</td><td>1.78</td><td>2.05</td></tr> <tr><td>40</td><td>3.03</td><td>3.09</td><td>3.33</td></tr> <tr><td>60</td><td>4.23</td><td>4.28</td><td>4.58</td></tr> <tr><td>80</td><td>5.67</td><td>5.61</td><td>5.89</td></tr> <tr><td>100</td><td>6.90</td><td>7.02</td><td>7.08</td></tr> <tr><td>110</td><td>7.67</td><td>7.52</td><td>7.74</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0	0.45	0.49	0.80	20	1.71	1.78	2.05	40	3.03	3.09	3.33	60	4.23	4.28	4.58	80	5.67	5.61	5.89	100	6.90	7.02	7.08	110	7.67	7.52	7.74	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																
0	0.45	0.49	0.80																																																
20	1.71	1.78	2.05																																																
40	3.03	3.09	3.33																																																
60	4.23	4.28	4.58																																																
80	5.67	5.61	5.89																																																
100	6.90	7.02	7.08																																																
110	7.67	7.52	7.74																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
2.Values																																																			

Load Ration [%]	Input Power [W]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0	0.45	0.49	0.80
20	1.71	1.78	2.05
40	3.03	3.09	3.33
60	4.23	4.28	4.58
80	5.67	5.61	5.89
100	6.90	7.02	7.08
110	7.67	7.52	7.74
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model	SUTW64815	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>82.5</td><td>87.1</td></tr> <tr><td>36</td><td>81.5</td><td>87.5</td></tr> <tr><td>40</td><td>80.5</td><td>87.5</td></tr> <tr><td>48</td><td>78.5</td><td>87.5</td></tr> <tr><td>55</td><td>76.5</td><td>87.1</td></tr> <tr><td>60</td><td>75.5</td><td>86.6</td></tr> <tr><td>70</td><td>73.5</td><td>85.2</td></tr> <tr><td>76</td><td>72.5</td><td>84.5</td></tr> <tr><td>80</td><td>72.0</td><td>83.8</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	82.5	87.1	36	81.5	87.5	40	80.5	87.5	48	78.5	87.5	55	76.5	87.1	60	75.5	86.6	70	73.5	85.2	76	72.5	84.5	80	72.0	83.8
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
33	82.5	87.1																													
36	81.5	87.5																													
40	80.5	87.5																													
48	78.5	87.5																													
55	76.5	87.1																													
60	75.5	86.6																													
70	73.5	85.2																													
76	72.5	84.5																													
80	72.0	83.8																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTW64815	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [Efficiency %]</th> <th>48V [Efficiency %]</th> <th>76V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>70.5</td><td>67.9</td><td>58.9</td></tr> <tr><td>40</td><td>79.5</td><td>78.2</td><td>72.5</td></tr> <tr><td>60</td><td>85.5</td><td>84.5</td><td>79.0</td></tr> <tr><td>80</td><td>85.1</td><td>86.0</td><td>81.9</td></tr> <tr><td>100</td><td>87.3</td><td>85.9</td><td>85.1</td></tr> <tr><td>110</td><td>86.5</td><td>88.2</td><td>85.7</td></tr> </tbody> </table>		Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]	20	70.5	67.9	58.9	40	79.5	78.2	72.5	60	85.5	84.5	79.0	80	85.1	86.0	81.9	100	87.3	85.9	85.1	110	86.5	88.2	85.7																							
Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]																																																		
20	70.5	67.9	58.9																																																		
40	79.5	78.2	72.5																																																		
60	85.5	84.5	79.0																																																		
80	85.1	86.0	81.9																																																		
100	87.3	85.9	85.1																																																		
110	86.5	88.2	85.7																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>70.5</td><td>67.9</td><td>58.9</td></tr> <tr><td>40</td><td>79.5</td><td>78.2</td><td>72.5</td></tr> <tr><td>60</td><td>85.5</td><td>84.5</td><td>79.0</td></tr> <tr><td>80</td><td>85.1</td><td>86.0</td><td>81.9</td></tr> <tr><td>100</td><td>87.3</td><td>85.9</td><td>85.1</td></tr> <tr><td>110</td><td>86.5</td><td>88.2</td><td>85.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	70.5	67.9	58.9	40	79.5	78.2	72.5	60	85.5	84.5	79.0	80	85.1	86.0	81.9	100	87.3	85.9	85.1	110	86.5	88.2	85.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	70.5	67.9	58.9																																																		
40	79.5	78.2	72.5																																																		
60	85.5	84.5	79.0																																																		
80	85.1	86.0	81.9																																																		
100	87.3	85.9	85.1																																																		
110	86.5	88.2	85.7																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		


Model	SUTW64815	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+15V0.2A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>15.119</td><td>15.052</td></tr> <tr><td>36</td><td>15.117</td><td>15.053</td></tr> <tr><td>40</td><td>15.116</td><td>15.053</td></tr> <tr><td>48</td><td>15.113</td><td>15.054</td></tr> <tr><td>55</td><td>15.112</td><td>15.054</td></tr> <tr><td>60</td><td>15.110</td><td>15.054</td></tr> <tr><td>70</td><td>15.109</td><td>15.054</td></tr> <tr><td>76</td><td>15.108</td><td>15.054</td></tr> <tr><td>80</td><td>15.108</td><td>15.054</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	15.119	15.052	36	15.117	15.053	40	15.116	15.053	48	15.113	15.054	55	15.112	15.054	60	15.110	15.054	70	15.109	15.054	76	15.108	15.054	80	15.108	15.054
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	15.119	15.052																																
36	15.117	15.053																																
40	15.116	15.053																																
48	15.113	15.054																																
55	15.112	15.054																																
60	15.110	15.054																																
70	15.109	15.054																																
76	15.108	15.054																																
80	15.108	15.054																																
Object -15V0.2A		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-15.125</td><td>-15.060</td></tr> <tr><td>36</td><td>-15.123</td><td>-15.060</td></tr> <tr><td>40</td><td>-15.121</td><td>-15.060</td></tr> <tr><td>48</td><td>-15.118</td><td>-15.059</td></tr> <tr><td>55</td><td>-15.115</td><td>-15.059</td></tr> <tr><td>60</td><td>-15.114</td><td>-15.058</td></tr> <tr><td>70</td><td>-15.112</td><td>-15.058</td></tr> <tr><td>76</td><td>-15.112</td><td>-15.058</td></tr> <tr><td>80</td><td>-15.111</td><td>-15.058</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-15.125	-15.060	36	-15.123	-15.060	40	-15.121	-15.060	48	-15.118	-15.059	55	-15.115	-15.059	60	-15.114	-15.058	70	-15.112	-15.058	76	-15.112	-15.058	80	-15.111	-15.058
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	-15.125	-15.060																																
36	-15.123	-15.060																																
40	-15.121	-15.060																																
48	-15.118	-15.059																																
55	-15.115	-15.059																																
60	-15.114	-15.058																																
70	-15.112	-15.058																																
76	-15.112	-15.058																																
80	-15.111	-15.058																																

Note: Slanted line shows the range of the rated input voltage.


**COSEL**

Model	SUTW64815	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+15V0.2A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.315</td><td>15.297</td><td>15.283</td></tr> <tr><td>0.04</td><td>15.176</td><td>15.170</td><td>15.165</td></tr> <tr><td>0.08</td><td>15.133</td><td>15.128</td><td>15.123</td></tr> <tr><td>0.12</td><td>15.103</td><td>15.099</td><td>15.096</td></tr> <tr><td>0.16</td><td>15.077</td><td>15.075</td><td>15.073</td></tr> <tr><td>0.20</td><td>15.053</td><td>15.053</td><td>15.054</td></tr> <tr><td>0.22</td><td>15.041</td><td>15.043</td><td>15.044</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	15.315	15.297	15.283	0.04	15.176	15.170	15.165	0.08	15.133	15.128	15.123	0.12	15.103	15.099	15.096	0.16	15.077	15.075	15.073	0.20	15.053	15.053	15.054	0.22	15.041	15.043	15.044	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	15.315	15.297	15.283																																																			
0.04	15.176	15.170	15.165																																																			
0.08	15.133	15.128	15.123																																																			
0.12	15.103	15.099	15.096																																																			
0.16	15.077	15.075	15.073																																																			
0.20	15.053	15.053	15.054																																																			
0.22	15.041	15.043	15.044																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.2A	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.326</td><td>-15.308</td><td>-15.292</td></tr> <tr><td>0.04</td><td>-15.182</td><td>-15.175</td><td>-15.169</td></tr> <tr><td>0.08</td><td>-15.138</td><td>-15.132</td><td>-15.126</td></tr> <tr><td>0.12</td><td>-15.108</td><td>-15.104</td><td>-15.099</td></tr> <tr><td>0.16</td><td>-15.083</td><td>-15.080</td><td>-15.077</td></tr> <tr><td>0.20</td><td>-15.060</td><td>-15.059</td><td>-15.057</td></tr> <tr><td>0.22</td><td>-15.049</td><td>-15.049</td><td>-15.048</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-15.326	-15.308	-15.292	0.04	-15.182	-15.175	-15.169	0.08	-15.138	-15.132	-15.126	0.12	-15.108	-15.104	-15.099	0.16	-15.083	-15.080	-15.077	0.20	-15.060	-15.059	-15.057	0.22	-15.049	-15.049	-15.048	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	-15.326	-15.308	-15.292																																																			
0.04	-15.182	-15.175	-15.169																																																			
0.08	-15.138	-15.132	-15.126																																																			
0.12	-15.108	-15.104	-15.099																																																			
0.16	-15.083	-15.080	-15.077																																																			
0.20	-15.060	-15.059	-15.057																																																			
0.22	-15.049	-15.049	-15.048																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
		Note: Slanted line shows the range of the rated load current.																																																				

**COSEL**




**COSEL**



Model	SUTW64815
Item	Ripple Voltage (by Load Current)
Object	+15V0.2A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	5	3
0.04	5	4
0.08	5	5
0.12	6	5
0.16	9	6
0.20	14	7
0.22	16	8
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW64815
Item	Ripple Voltage (by Load Current)
Object	-15V0.2A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	4	5
0.04	5	5
0.08	5	5
0.12	5	5
0.16	7	5
0.20	9	5
0.22	10	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW64815
Item	Ripple-Noise
Object	+15V0.2A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	5	3
0.04	5	4
0.08	6	5
0.12	8	6
0.16	10	7
0.20	15	8
0.22	17	9
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW64815
Item	Ripple-Noise
Object	-15V0.2A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	7	7
0.04	8	7
0.08	9	11
0.12	9	11
0.16	10	12
0.20	12	13
0.22	13	13
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW64815
-------	-----------

| Item | Ripple Voltage (by Ambient Temp.) |
| Object | +15V0.2A |

## 1.Graph

---□--- Load 50%  
—△— Load 100%




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	12
-40	8	11
-20	7	9
0	6	9
25	6	9
55	5	8
60	5	8
--	-	-
--	-	-
--	-	-
--	-	-

## 1.Graph

---□--- Load 50%  
—△— Load 100%



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	14
-40	9	14
-20	9	11
0	9	11
25	9	11
55	7	10
60	7	10
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW64815
Item	Ambient Temperature Drift
Object	+15V0.2A

Testing Circuitry Figure A

1.Graph

- △— Input Volt. 36V
- - - □ - - Input Volt. 48V
- · ○ - - Input Volt. 76V




## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.947	14.949	14.949
-40	14.981	14.983	14.983
-20	15.007	15.008	15.009
0	15.030	15.031	15.031
25	15.051	15.051	15.052
55	15.064	15.065	15.066
60	15.066	15.066	15.067
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

1.Graph

- △— Input Volt. 36V
- - - □ - - Input Volt. 48V
- · ○ - - Input Volt. 76V



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-14.951	-14.952	-14.951
-40	-14.986	-14.986	-14.985
-20	-15.013	-15.012	-15.012
0	-15.036	-15.035	-15.034
25	-15.057	-15.057	-15.055
55	-15.072	-15.071	-15.070
60	-15.074	-15.072	-15.071
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW64815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.2A (AVR 2) : 0 - 0.2A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36		0	15.332	
Minimum Voltage	-40	36	0.2	14.751	±291	±1.9

Object	-15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36		0	-15.345	
Minimum Voltage	-40	36	0.2	-14.764	±291	±1.9

**COSEL**


Model	SUTW64815	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+15V0.2A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.043</td></tr> <tr><td>0.5</td><td>15.051</td></tr> <tr><td>1.0</td><td>15.051</td></tr> <tr><td>2.0</td><td>15.051</td></tr> <tr><td>3.0</td><td>15.051</td></tr> <tr><td>4.0</td><td>15.051</td></tr> <tr><td>5.0</td><td>15.051</td></tr> <tr><td>6.0</td><td>15.051</td></tr> <tr><td>7.0</td><td>15.051</td></tr> <tr><td>8.0</td><td>15.051</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.043	0.5	15.051	1.0	15.051	2.0	15.051	3.0	15.051	4.0	15.051	5.0	15.051	6.0	15.051	7.0	15.051	8.0	15.051
Time since start [H]	Output Voltage [V]																							
0.0	15.043																							
0.5	15.051																							
1.0	15.051																							
2.0	15.051																							
3.0	15.051																							
4.0	15.051																							
5.0	15.051																							
6.0	15.051																							
7.0	15.051																							
8.0	15.051																							
Object -15V0.2A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.053</td></tr> <tr><td>0.5</td><td>-15.061</td></tr> <tr><td>1.0</td><td>-15.061</td></tr> <tr><td>2.0</td><td>-15.061</td></tr> <tr><td>3.0</td><td>-15.061</td></tr> <tr><td>4.0</td><td>-15.062</td></tr> <tr><td>5.0</td><td>-15.061</td></tr> <tr><td>6.0</td><td>-15.061</td></tr> <tr><td>7.0</td><td>-15.061</td></tr> <tr><td>8.0</td><td>-15.061</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-15.053	0.5	-15.061	1.0	-15.061	2.0	-15.061	3.0	-15.061	4.0	-15.062	5.0	-15.061	6.0	-15.061	7.0	-15.061	8.0	-15.061
Time since start [H]	Output Voltage [V]																							
0.0	-15.053																							
0.5	-15.061																							
1.0	-15.061																							
2.0	-15.061																							
3.0	-15.061																							
4.0	-15.062																							
5.0	-15.061																							
6.0	-15.061																							
7.0	-15.061																							
8.0	-15.061																							

**COSEL**

Model	SUTW64815
Item	Rise and Fall Time
Object	+15V0.2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.3	3.3	3.6	2.3	4.0
100 %		0.3	3.4	3.7	1.2	2.0




**COSEL**

Model	SUTW64815
Item	Rise and Fall Time
Object	-15V0.2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.3	3.4	3.7	2.3	4.3
100 %		0.3	3.5	3.8	1.2	2.2




**COSEL**

Model	SUTW64815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

## 1.Graph

---□--- Load 50%  
—△— Load 100%



Testing Circuitry Figure A


## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.1	30.5
-40	30.1	30.1
-20	30.1	30.1
0	30.1	30.1
25	30.1	30.5
55	30.5	30.5
60	30.5	30.5
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

## 1.Graph

---□--- Load 50%  
—△— Load 100%



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.1	30.5
-40	30.1	30.1
-20	30.1	30.1
0	30.1	30.1
25	30.5	30.5
55	30.5	30.5
60	30.5	30.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW64815																																																										
Item	Overcurrent Protection		Temperature Testing Circuitry	25°C Figure A																																																							
Object	+15V0.2A																																																										
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.21</td><td>0.21</td><td>0.21</td></tr> <tr><td>14.3</td><td>0.36</td><td>0.38</td><td>0.37</td></tr> <tr><td>13.5</td><td>0.38</td><td>0.40</td><td>0.38</td></tr> <tr><td>12.0</td><td>0.48</td><td>0.50</td><td>0.46</td></tr> <tr><td>10.5</td><td>0.55</td><td>0.57</td><td>0.53</td></tr> <tr><td>9.0</td><td>0.60</td><td>0.62</td><td>0.58</td></tr> <tr><td>7.5</td><td>0.66</td><td>0.66</td><td>0.62</td></tr> <tr><td>6.0</td><td>0.70</td><td>0.70</td><td>0.66</td></tr> <tr><td>4.5</td><td>0.74</td><td>0.72</td><td>0.69</td></tr> <tr><td>3.0</td><td>0.74</td><td>0.72</td><td>0.70</td></tr> <tr><td>1.5</td><td>0.71</td><td>0.69</td><td>0.67</td></tr> <tr><td>0.0</td><td>1.12</td><td>1.09</td><td>1.10</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	15.0	0.21	0.21	0.21	14.3	0.36	0.38	0.37	13.5	0.38	0.40	0.38	12.0	0.48	0.50	0.46	10.5	0.55	0.57	0.53	9.0	0.60	0.62	0.58	7.5	0.66	0.66	0.62	6.0	0.70	0.70	0.66	4.5	0.74	0.72	0.69	3.0	0.74	0.72	0.70	1.5	0.71	0.69	0.67	0.0	1.12	1.09	1.10
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																								
15.0	0.21	0.21	0.21																																																								
14.3	0.36	0.38	0.37																																																								
13.5	0.38	0.40	0.38																																																								
12.0	0.48	0.50	0.46																																																								
10.5	0.55	0.57	0.53																																																								
9.0	0.60	0.62	0.58																																																								
7.5	0.66	0.66	0.62																																																								
6.0	0.70	0.70	0.66																																																								
4.5	0.74	0.72	0.69																																																								
3.0	0.74	0.72	0.70																																																								
1.5	0.71	0.69	0.67																																																								
0.0	1.12	1.09	1.10																																																								
Object		-15V0.2A																																																									
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>																																																									
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.21</td><td>0.21</td><td>0.21</td></tr> <tr><td>-14.25</td><td>0.36</td><td>0.38</td><td>0.37</td></tr> <tr><td>-13.50</td><td>0.38</td><td>0.40</td><td>0.38</td></tr> <tr><td>-12.00</td><td>0.47</td><td>0.50</td><td>0.46</td></tr> <tr><td>-10.50</td><td>0.54</td><td>0.57</td><td>0.53</td></tr> <tr><td>-9.00</td><td>0.60</td><td>0.62</td><td>0.58</td></tr> <tr><td>-7.50</td><td>0.66</td><td>0.66</td><td>0.63</td></tr> <tr><td>-6.00</td><td>0.70</td><td>0.70</td><td>0.66</td></tr> <tr><td>-4.50</td><td>0.74</td><td>0.72</td><td>0.69</td></tr> <tr><td>-3.00</td><td>0.75</td><td>0.73</td><td>0.70</td></tr> <tr><td>-1.50</td><td>0.71</td><td>0.69</td><td>0.68</td></tr> <tr><td>0.00</td><td>1.10</td><td>1.08</td><td>1.08</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-15.00	0.21	0.21	0.21	-14.25	0.36	0.38	0.37	-13.50	0.38	0.40	0.38	-12.00	0.47	0.50	0.46	-10.50	0.54	0.57	0.53	-9.00	0.60	0.62	0.58	-7.50	0.66	0.66	0.63	-6.00	0.70	0.70	0.66	-4.50	0.74	0.72	0.69	-3.00	0.75	0.73	0.70	-1.50	0.71	0.69	0.68	0.00	1.10	1.08	1.08
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																								
-15.00	0.21	0.21	0.21																																																								
-14.25	0.36	0.38	0.37																																																								
-13.50	0.38	0.40	0.38																																																								
-12.00	0.47	0.50	0.46																																																								
-10.50	0.54	0.57	0.53																																																								
-9.00	0.60	0.62	0.58																																																								
-7.50	0.66	0.66	0.63																																																								
-6.00	0.70	0.70	0.66																																																								
-4.50	0.74	0.72	0.69																																																								
-3.00	0.75	0.73	0.70																																																								
-1.50	0.71	0.69	0.68																																																								
0.00	1.10	1.08	1.08																																																								
Note: Slanted line shows the range of the rated load current.																																																											




Figure A




Figure B (Ripple and Ripple noise Characteristic)