



TEST DATA OF SUW100512 SUCW100512

Regulated DC Power Supply
Mar 28, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshimichi Hirokawa
Yoshimichi Hirokawa Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

coSEL

Model	SUW100512/SUCW100512																																																																													
Item	Input Current (by Input Voltage)																																																																													
Object	<u> </u>																																																																													
1.Graph	<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 100% (▲) Load 50% (□) Load 0% (○) <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																													
Temperature	25°C																																																																													
Testing Circuitry	Figure A																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.16</td><td>0.111</td><td>1.530</td><td>3.006</td></tr> <tr><td>4.50</td><td>0.109</td><td>1.447</td><td>2.903</td></tr> <tr><td>5.00</td><td>0.096</td><td>1.292</td><td>2.569</td></tr> <tr><td>6.00</td><td>0.078</td><td>1.071</td><td>2.122</td></tr> <tr><td>7.00</td><td>0.069</td><td>0.922</td><td>1.791</td></tr> <tr><td>8.00</td><td>0.064</td><td>0.817</td><td>1.587</td></tr> <tr><td>9.00</td><td>0.061</td><td>0.718</td><td>1.405</td></tr> <tr><td>10.00</td><td>0.061</td><td>0.645</td><td>1.265</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.000	0.000	0.000	2.00	0.000	0.000	0.000	3.00	0.000	0.000	0.000	4.00	0.000	0.000	0.000	4.16	0.111	1.530	3.006	4.50	0.109	1.447	2.903	5.00	0.096	1.292	2.569	6.00	0.078	1.071	2.122	7.00	0.069	0.922	1.791	8.00	0.064	0.817	1.587	9.00	0.061	0.718	1.405	10.00	0.061	0.645	1.265	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																													
	Load 0%	Load 50%	Load 100%																																																																											
0.00	0.000	0.000	0.000																																																																											
1.70	0.000	0.000	0.000																																																																											
2.00	0.000	0.000	0.000																																																																											
3.00	0.000	0.000	0.000																																																																											
4.00	0.000	0.000	0.000																																																																											
4.16	0.111	1.530	3.006																																																																											
4.50	0.109	1.447	2.903																																																																											
5.00	0.096	1.292	2.569																																																																											
6.00	0.078	1.071	2.122																																																																											
7.00	0.069	0.922	1.791																																																																											
8.00	0.064	0.817	1.587																																																																											
9.00	0.061	0.718	1.405																																																																											
10.00	0.061	0.645	1.265																																																																											
-	-	-	-																																																																											
-	-	-	-																																																																											
-	-	-	-																																																																											
-	-	-	-																																																																											

COSEL

Model	SUW100512/SUCW100512																																																				
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object																																																					
1.Graph	<p style="text-align: center;">—△— Input Volt. 4.5V - - □ - - Input Volt. 5V - - ○ - - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [A]</th> <th>5V [A]</th> <th>9V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.105</td><td>0.093</td><td>0.061</td></tr> <tr><td>20</td><td>0.637</td><td>0.565</td><td>0.317</td></tr> <tr><td>40</td><td>1.176</td><td>1.048</td><td>0.571</td></tr> <tr><td>60</td><td>1.713</td><td>1.556</td><td>0.858</td></tr> <tr><td>80</td><td>2.242</td><td>2.035</td><td>1.120</td></tr> <tr><td>100</td><td>2.886</td><td>2.548</td><td>1.394</td></tr> <tr><td>110</td><td>3.148</td><td>2.844</td><td>1.513</td></tr> </tbody> </table>	Load Ration [%]	4.5V [A]	5V [A]	9V [A]	0	0.105	0.093	0.061	20	0.637	0.565	0.317	40	1.176	1.048	0.571	60	1.713	1.556	0.858	80	2.242	2.035	1.120	100	2.886	2.548	1.394	110	3.148	2.844	1.513																				
Load Ration [%]	4.5V [A]	5V [A]	9V [A]																																																		
0	0.105	0.093	0.061																																																		
20	0.637	0.565	0.317																																																		
40	1.176	1.048	0.571																																																		
60	1.713	1.556	0.858																																																		
80	2.242	2.035	1.120																																																		
100	2.886	2.548	1.394																																																		
110	3.148	2.844	1.513																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.105</td><td>0.093</td><td>0.061</td></tr> <tr><td>20</td><td>0.637</td><td>0.565</td><td>0.317</td></tr> <tr><td>40</td><td>1.176</td><td>1.048</td><td>0.571</td></tr> <tr><td>60</td><td>1.713</td><td>1.556</td><td>0.858</td></tr> <tr><td>80</td><td>2.242</td><td>2.035</td><td>1.120</td></tr> <tr><td>100</td><td>2.886</td><td>2.548</td><td>1.394</td></tr> <tr><td>110</td><td>3.148</td><td>2.844</td><td>1.513</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.105	0.093	0.061	20	0.637	0.565	0.317	40	1.176	1.048	0.571	60	1.713	1.556	0.858	80	2.242	2.035	1.120	100	2.886	2.548	1.394	110	3.148	2.844	1.513	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0	0.105	0.093	0.061																																																		
20	0.637	0.565	0.317																																																		
40	1.176	1.048	0.571																																																		
60	1.713	1.556	0.858																																																		
80	2.242	2.035	1.120																																																		
100	2.886	2.548	1.394																																																		
110	3.148	2.844	1.513																																																		
-	-	-	-																																																		
-	-	-	-																																																		
-	-	-	-																																																		
-	-	-	-																																																		

COSEL


Model	SUW100512/SUCW100512																																		
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																
Object																																			
1.Graph	<p>—△— Input Volt. 4.5V - -□-- Input Volt. 5V - -○-- Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (4.5V)</th> <th>Input Power [W] (5V)</th> <th>Input Power [W] (9V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.48</td><td>0.47</td><td>0.56</td></tr> <tr><td>20</td><td>2.82</td><td>2.81</td><td>2.87</td></tr> <tr><td>40</td><td>5.24</td><td>5.24</td><td>5.16</td></tr> <tr><td>60</td><td>7.67</td><td>7.64</td><td>7.71</td></tr> <tr><td>80</td><td>10.13</td><td>10.09</td><td>10.04</td></tr> <tr><td>100</td><td>12.70</td><td>12.61</td><td>12.45</td></tr> <tr><td>110</td><td>14.04</td><td>13.91</td><td>13.64</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)	0	0.48	0.47	0.56	20	2.82	2.81	2.87	40	5.24	5.24	5.16	60	7.67	7.64	7.71	80	10.13	10.09	10.04	100	12.70	12.61	12.45	110	14.04	13.91	13.64
Load Ration [%]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)																																
0	0.48	0.47	0.56																																
20	2.82	2.81	2.87																																
40	5.24	5.24	5.16																																
60	7.67	7.64	7.71																																
80	10.13	10.09	10.04																																
100	12.70	12.61	12.45																																
110	14.04	13.91	13.64																																
2.Values	Load Ration [%]	Input Power [W]																																	
		Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																															
0		0.48	0.47	0.56																															
20		2.82	2.81	2.87																															
40		5.24	5.24	5.16																															
60		7.67	7.64	7.71																															
80		10.13	10.09	10.04																															
100		12.70	12.61	12.45																															
110		14.04	13.91	13.64																															
--		-	-	-																															
--		-	-	-																															
--		-	-	-																															
--		-	-	-																															

COSEL

Model	SUW100512/SUCW100512																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	<hr/>																																	
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>84.4</td> <td>84.3</td> </tr> <tr> <td>4.5</td> <td>84.5</td> <td>85.7</td> </tr> <tr> <td>5.0</td> <td>84.7</td> <td>86.3</td> </tr> <tr> <td>6.0</td> <td>84.6</td> <td>87.1</td> </tr> <tr> <td>7.0</td> <td>84.3</td> <td>87.6</td> </tr> <tr> <td>8.0</td> <td>83.8</td> <td>87.7</td> </tr> <tr> <td>9.0</td> <td>84.1</td> <td>87.7</td> </tr> <tr> <td>10.0</td> <td>84.9</td> <td>87.4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	84.4	84.3	4.5	84.5	85.7	5.0	84.7	86.3	6.0	84.6	87.1	7.0	84.3	87.6	8.0	83.8	87.7	9.0	84.1	87.7	10.0	84.9	87.4	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.0	84.4	84.3																																
4.5	84.5	85.7																																
5.0	84.7	86.3																																
6.0	84.6	87.1																																
7.0	84.3	87.6																																
8.0	83.8	87.7																																
9.0	84.1	87.7																																
10.0	84.9	87.4																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL


Model	SUW100512/SUCW100512																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 4.5V - -□-- Input Volt. 5V - -○-- Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [%]</th> <th>5V [%]</th> <th>9V [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>78</td><td>80</td><td>82</td></tr> <tr><td>40</td><td>82</td><td>84</td><td>85</td></tr> <tr><td>60</td><td>84</td><td>86</td><td>87</td></tr> <tr><td>80</td><td>85</td><td>87</td><td>88</td></tr> <tr><td>100</td><td>85</td><td>87</td><td>88</td></tr> <tr><td>110</td><td>84</td><td>86</td><td>87</td></tr> </tbody> </table>			Load Ration [%]	4.5V [%]	5V [%]	9V [%]	20	78	80	82	40	82	84	85	60	84	86	87	80	85	87	88	100	85	87	88	110	84	86	87																							
Load Ration [%]	4.5V [%]	5V [%]	9V [%]																																																			
20	78	80	82																																																			
40	82	84	85																																																			
60	84	86	87																																																			
80	85	87	88																																																			
100	85	87	88																																																			
110	84	86	87																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>77.4</td><td>77.9</td><td>76.1</td></tr> <tr><td>40</td><td>83.2</td><td>83.2</td><td>84.5</td></tr> <tr><td>60</td><td>85.3</td><td>85.6</td><td>84.9</td></tr> <tr><td>80</td><td>86.0</td><td>86.3</td><td>86.7</td></tr> <tr><td>100</td><td>85.8</td><td>86.3</td><td>87.5</td></tr> <tr><td>110</td><td>85.3</td><td>86.1</td><td>87.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	77.4	77.9	76.1	40	83.2	83.2	84.5	60	85.3	85.6	84.9	80	86.0	86.3	86.7	100	85.8	86.3	87.5	110	85.3	86.1	87.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	-	-	-																																																			
20	77.4	77.9	76.1																																																			
40	83.2	83.2	84.5																																																			
60	85.3	85.6	84.9																																																			
80	86.0	86.3	86.7																																																			
100	85.8	86.3	87.5																																																			
110	85.3	86.1	87.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	12.165	12.093
4.5	12.160	12.093
5.0	12.157	12.093
6.0	12.152	12.093
7.0	12.149	12.093
8.0	12.147	12.092
9.0	12.145	12.093
10.0	12.144	12.092
--	-	-



2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	-12.170	-12.096
4.5	-12.165	-12.096
5.0	-12.163	-12.097
6.0	-12.158	-12.097
7.0	-12.155	-12.097
8.0	-12.152	-12.097
9.0	-12.151	-12.097
10.0	-12.149	-12.097
--	-	-


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUW100512/SUCW100512	Temperature Testing Circuitry 25°C Figure A																															
Item	Load Regulation																																
Object	+12V0.45A																																
1.Graph	<p>—△— Input Volt. 4.5V - - -□- Input Volt. 5V - · -○- Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.410</td><td>12.400</td><td>12.423</td></tr> <tr><td>0.10</td><td>12.208</td><td>12.204</td><td>12.192</td></tr> <tr><td>0.20</td><td>12.175</td><td>12.171</td><td>12.159</td></tr> <tr><td>0.30</td><td>12.147</td><td>12.144</td><td>12.134</td></tr> <tr><td>0.40</td><td>12.119</td><td>12.118</td><td>12.113</td></tr> <tr><td>0.450</td><td>12.093</td><td>12.092</td><td>12.092</td></tr> <tr><td>0.495</td><td>12.080</td><td>12.080</td><td>12.082</td></tr> </tbody> </table>	Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.00	12.410	12.400	12.423	0.10	12.208	12.204	12.192	0.20	12.175	12.171	12.159	0.30	12.147	12.144	12.134	0.40	12.119	12.118	12.113	0.450	12.093	12.092	12.092	0.495	12.080	12.080	12.082
Load Current [A]	4.5V [V]	5V [V]	9V [V]																														
0.00	12.410	12.400	12.423																														
0.10	12.208	12.204	12.192																														
0.20	12.175	12.171	12.159																														
0.30	12.147	12.144	12.134																														
0.40	12.119	12.118	12.113																														
0.450	12.093	12.092	12.092																														
0.495	12.080	12.080	12.082																														
2.Values																																	
Object	-12V0.45A																																
1.Graph	<p>—△— Input Volt. 4.5V - - -□- Input Volt. 5V - · -○- Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph 2</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-12.413</td><td>-12.402</td><td>-12.390</td></tr> <tr><td>0.10</td><td>-12.214</td><td>-12.210</td><td>-12.196</td></tr> <tr><td>0.20</td><td>-12.181</td><td>-12.177</td><td>-12.164</td></tr> <tr><td>0.30</td><td>-12.151</td><td>-12.149</td><td>-12.139</td></tr> <tr><td>0.40</td><td>-12.124</td><td>-12.122</td><td>-12.117</td></tr> <tr><td>0.450</td><td>-12.097</td><td>-12.096</td><td>-12.097</td></tr> <tr><td>0.495</td><td>-12.083</td><td>-12.084</td><td>-12.087</td></tr> </tbody> </table>	Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.00	-12.413	-12.402	-12.390	0.10	-12.214	-12.210	-12.196	0.20	-12.181	-12.177	-12.164	0.30	-12.151	-12.149	-12.139	0.40	-12.124	-12.122	-12.117	0.450	-12.097	-12.096	-12.097	0.495	-12.083	-12.084	-12.087
Load Current [A]	4.5V [V]	5V [V]	9V [V]																														
0.00	-12.413	-12.402	-12.390																														
0.10	-12.214	-12.210	-12.196																														
0.20	-12.181	-12.177	-12.164																														
0.30	-12.151	-12.149	-12.139																														
0.40	-12.124	-12.122	-12.117																														
0.450	-12.097	-12.096	-12.097																														
0.495	-12.083	-12.084	-12.087																														
2.Values																																	

Note: Slanted line shows the range of the rated load current.

COSEL

COSEL

COSEL

Model	SUW100512/SUCW100512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.45A																																							
1. Graph																																								
<p style="text-align: center;"> Input Volt. 4.5V Input Volt. 9V </p>																																								
2. Values																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>2</td></tr> <tr><td>0.090</td><td>2</td><td>2</td></tr> <tr><td>0.180</td><td>3</td><td>2</td></tr> <tr><td>0.270</td><td>4</td><td>3</td></tr> <tr><td>0.360</td><td>5</td><td>4</td></tr> <tr><td>0.450</td><td>6</td><td>5</td></tr> <tr><td>0.495</td><td>6</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	2	2	0.090	2	2	0.180	3	2	0.270	4	3	0.360	5	4	0.450	6	5	0.495	6	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	2	2																																						
0.090	2	2																																						
0.180	3	2																																						
0.270	4	3																																						
0.360	5	4																																						
0.450	6	5																																						
0.495	6	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	SUW100512/SUCW100512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-12V0.45A																																							
1. Graph																																								
		2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>2</td></tr> <tr><td>0.090</td><td>3</td><td>3</td></tr> <tr><td>0.180</td><td>3</td><td>3</td></tr> <tr><td>0.270</td><td>5</td><td>4</td></tr> <tr><td>0.360</td><td>5</td><td>5</td></tr> <tr><td>0.450</td><td>7</td><td>5</td></tr> <tr><td>0.495</td><td>7</td><td>6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	2	2	0.090	3	3	0.180	3	3	0.270	5	4	0.360	5	5	0.450	7	5	0.495	7	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	2	2																																						
0.090	3	3																																						
0.180	3	3																																						
0.270	5	4																																						
0.360	5	5																																						
0.450	7	5																																						
0.495	7	6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	SUW100512/SUCW100512	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple-Noise																																							
Object	+12V0.45A																																							
1. Graph		2. Values																																						
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 80 mV with major grid lines every 20 units. The X-axis ranges from 0.00 to 0.50 A with major grid lines every 0.10 units. Two data series are plotted: Input Volt. 4.5V (solid line with open circles) and Input Volt. 9V (dashed line with open circles). Both series show a slight increase in noise as load current increases. A slanted line indicates the rated load current range.</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>4</td><td>4</td></tr> <tr><td>0.090</td><td>4</td><td>4</td></tr> <tr><td>0.180</td><td>6</td><td>4</td></tr> <tr><td>0.270</td><td>6</td><td>6</td></tr> <tr><td>0.360</td><td>7</td><td>6</td></tr> <tr><td>0.450</td><td>8</td><td>6</td></tr> <tr><td>0.495</td><td>9</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	4	4	0.090	4	4	0.180	6	4	0.270	6	6	0.360	7	6	0.450	8	6	0.495	9	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	4	4																																						
0.090	4	4																																						
0.180	6	4																																						
0.270	6	6																																						
0.360	7	6																																						
0.450	8	6																																						
0.495	9	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

COSEL


Model SUW100512/SUCW100512

Item Ripple-Noise

Object -12V0.45A

1. Graph

—▲— Input Volt. 4.5V
 -·○-·- Input Volt. 9V



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	4	4
0.090	5	6
0.180	6	6
0.270	7	8
0.360	8	8
0.450	9	8
0.495	9	8
--	-	-
--	-	-
--	-	-
--	-	-




Fig.Complex Ripple Noise Wave Form

COSEL


Model SUW100512/SUCW100512

Item Ripple Voltage (by Ambient Temp.)

Object +12V0.45A

1. Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure B


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	6
-40	3	6
-20	3	5
0	2	4
25	2	3
55	2	3
60	1	3
--	-	-
--	-	-
--	-	-
--	-	-

Object -12V0.45A

1. Graph

---□--- Load 50%
—△— Load 100%



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	14
-40	9	14
-20	8	12
0	6	10
25	5	8
55	4	5
60	4	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

<p>Model SUW100512/SUCW100512</p> <p>Item Ambient Temperature Drift</p> <p>Object +12V0.45A</p>	Testing Circuitry Figure A																																																					
	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.071</td><td>12.071</td><td>12.071</td></tr> <tr><td>-40</td><td>12.085</td><td>12.086</td><td>12.086</td></tr> <tr><td>-20</td><td>12.094</td><td>12.094</td><td>12.094</td></tr> <tr><td>0</td><td>12.097</td><td>12.097</td><td>12.097</td></tr> <tr><td>25</td><td>12.093</td><td>12.093</td><td>12.092</td></tr> <tr><td>55</td><td>12.080</td><td>12.079</td><td>12.079</td></tr> <tr><td>60</td><td>12.077</td><td>12.076</td><td>12.076</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.071	12.071	12.071	-40	12.085	12.086	12.086	-20	12.094	12.094	12.094	0	12.097	12.097	12.097	25	12.093	12.093	12.092	55	12.080	12.079	12.079	60	12.077	12.076	12.076	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	12.071	12.071	12.071																																																			
-40	12.085	12.086	12.086																																																			
-20	12.094	12.094	12.094																																																			
0	12.097	12.097	12.097																																																			
25	12.093	12.093	12.092																																																			
55	12.080	12.079	12.079																																																			
60	12.077	12.076	12.076																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Object -12V0.45A</p> <p>1.Graph</p> <p>—△— Input Volt. 4.5V - - -□-- Input Volt. 5V - - -○-- Input Volt. 9V</p>	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.072</td><td>-12.074</td><td>-12.075</td></tr> <tr><td>-40</td><td>-12.088</td><td>-12.089</td><td>-12.089</td></tr> <tr><td>-20</td><td>-12.097</td><td>-12.098</td><td>-12.098</td></tr> <tr><td>0</td><td>-12.100</td><td>-12.100</td><td>-12.101</td></tr> <tr><td>25</td><td>-12.096</td><td>-12.097</td><td>-12.097</td></tr> <tr><td>55</td><td>-12.084</td><td>-12.084</td><td>-12.084</td></tr> <tr><td>60</td><td>-12.081</td><td>-12.080</td><td>-12.081</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.072	-12.074	-12.075	-40	-12.088	-12.089	-12.089	-20	-12.097	-12.098	-12.098	0	-12.100	-12.100	-12.101	25	-12.096	-12.097	-12.097	55	-12.084	-12.084	-12.084	60	-12.081	-12.080	-12.081	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	-12.072	-12.074	-12.075																																																			
-40	-12.088	-12.089	-12.089																																																			
-20	-12.097	-12.098	-12.098																																																			
0	-12.100	-12.100	-12.101																																																			
25	-12.096	-12.097	-12.097																																																			
55	-12.084	-12.084	-12.084																																																			
60	-12.081	-12.080	-12.081																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



Model	SUW100512/SUCW100512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.45A (AVR 2) : 0 - 0.45A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	0	9	0	12.427	±174	±1.5	
Minimum Voltage	55	9	0.45	12.079			

Object		-12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	0	4.5	0	-12.415	±166	±1.4	
Minimum Voltage	55	9	0.45	-12.084			


COSEL

Model	SUW100512/SUCW1001512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.45A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>12.094</td></tr> <tr><td>0.5</td><td>12.087</td></tr> <tr><td>1.0</td><td>12.087</td></tr> <tr><td>2.0</td><td>12.087</td></tr> <tr><td>3.0</td><td>12.087</td></tr> <tr><td>4.0</td><td>12.087</td></tr> <tr><td>5.0</td><td>12.087</td></tr> <tr><td>6.0</td><td>12.087</td></tr> <tr><td>7.0</td><td>12.087</td></tr> <tr><td>8.0</td><td>12.087</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.094	0.5	12.087	1.0	12.087	2.0	12.087	3.0	12.087	4.0	12.087	5.0	12.087	6.0	12.087	7.0	12.087	8.0	12.087
Time since start [H]	Output Voltage [V]																								
0.0	12.094																								
0.5	12.087																								
1.0	12.087																								
2.0	12.087																								
3.0	12.087																								
4.0	12.087																								
5.0	12.087																								
6.0	12.087																								
7.0	12.087																								
8.0	12.087																								
Object -12V0.45A		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-12.102</td></tr> <tr><td>0.5</td><td>-12.098</td></tr> <tr><td>1.0</td><td>-12.098</td></tr> <tr><td>2.0</td><td>-12.098</td></tr> <tr><td>3.0</td><td>-12.098</td></tr> <tr><td>4.0</td><td>-12.098</td></tr> <tr><td>5.0</td><td>-12.098</td></tr> <tr><td>6.0</td><td>-12.097</td></tr> <tr><td>7.0</td><td>-12.098</td></tr> <tr><td>8.0</td><td>-12.098</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.102	0.5	-12.098	1.0	-12.098	2.0	-12.098	3.0	-12.098	4.0	-12.098	5.0	-12.098	6.0	-12.097	7.0	-12.098	8.0	-12.098
Time since start [H]	Output Voltage [V]																								
0.0	-12.102																								
0.5	-12.098																								
1.0	-12.098																								
2.0	-12.098																								
3.0	-12.098																								
4.0	-12.098																								
5.0	-12.098																								
6.0	-12.097																								
7.0	-12.098																								
8.0	-12.098																								

COSEL


Model	SUW100512/SUCW100512	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.45A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.6	3.1	3.7	0.2	2.3	
100 %		0.6	3.5	4.1	0.2	1.2	



COSEL


Model	SUW100512/SUCW100512	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.45A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.6	3.3	3.9	0.2	2.4	
100 %		0.6	3.7	4.3	0.2	1.2	




COSEL

Model SUW100512/SUCW100512

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V0.45A

1.Graph

 --- □--- Load 50%
 —△— Load 100%



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.4	3.0
-40	2.3	3.2
-20	2.5	3.2
0	2.5	3.2
25	2.8	3.4
55	2.7	3.4
60	2.8	3.4
--	-	-
--	-	-
--	-	-
--	-	-

Object -12V0.45A

1.Graph

 --- □--- Load 50%
 —△— Load 100%


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.3	2.9
-40	2.2	3.1
-20	2.4	3.1
0	2.5	3.2
25	2.7	3.3
55	2.7	3.4
60	2.7	3.4
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SUW100512/SUCW100512	Temperature	25°C																																																
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																
Object	+12V0.45A																																																		
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p> <table border="1"> <caption>Estimated data points for +12V0.45A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.0</td><td>12.0</td><td>12.0</td></tr> <tr><td>0.74</td><td>12.0</td><td>11.4</td><td>10.8</td></tr> <tr><td>1.0</td><td>11.4</td><td>10.8</td><td>9.6</td></tr> <tr><td>1.14</td><td>10.8</td><td>9.6</td><td>8.4</td></tr> <tr><td>1.2</td><td>10.8</td><td>9.6</td><td>7.2</td></tr> <tr><td>1.36</td><td>10.8</td><td>9.6</td><td>6.0</td></tr> <tr><td>1.45</td><td>10.8</td><td>9.6</td><td>4.8</td></tr> <tr><td>1.45</td><td>10.8</td><td>9.6</td><td>3.6</td></tr> <tr><td>1.46</td><td>10.8</td><td>9.6</td><td>2.4</td></tr> <tr><td>1.45</td><td>10.8</td><td>9.6</td><td>1.2</td></tr> <tr><td>1.71</td><td>12.0</td><td>12.0</td><td>0.0</td></tr> </tbody> </table>	Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.0	12.0	12.0	12.0	0.74	12.0	11.4	10.8	1.0	11.4	10.8	9.6	1.14	10.8	9.6	8.4	1.2	10.8	9.6	7.2	1.36	10.8	9.6	6.0	1.45	10.8	9.6	4.8	1.45	10.8	9.6	3.6	1.46	10.8	9.6	2.4	1.45	10.8	9.6	1.2	1.71	12.0	12.0	0.0	2.Values	
Load Current [A]	4.5V [V]	5V [V]	9V [V]																																																
0.0	12.0	12.0	12.0																																																
0.74	12.0	11.4	10.8																																																
1.0	11.4	10.8	9.6																																																
1.14	10.8	9.6	8.4																																																
1.2	10.8	9.6	7.2																																																
1.36	10.8	9.6	6.0																																																
1.45	10.8	9.6	4.8																																																
1.45	10.8	9.6	3.6																																																
1.46	10.8	9.6	2.4																																																
1.45	10.8	9.6	1.2																																																
1.71	12.0	12.0	0.0																																																
Object	-12V0.45A																																																		
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p> <table border="1"> <caption>Estimated data points for -12V0.45A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.0</td><td>-12.0</td><td>-12.0</td></tr> <tr><td>0.76</td><td>-12.0</td><td>-11.4</td><td>-10.8</td></tr> <tr><td>1.0</td><td>-11.4</td><td>-10.8</td><td>-9.6</td></tr> <tr><td>1.13</td><td>-10.8</td><td>-9.6</td><td>-8.4</td></tr> <tr><td>1.19</td><td>-10.8</td><td>-9.6</td><td>-7.2</td></tr> <tr><td>1.27</td><td>-10.8</td><td>-9.6</td><td>-6.0</td></tr> <tr><td>1.36</td><td>-10.8</td><td>-9.6</td><td>-4.8</td></tr> <tr><td>1.44</td><td>-10.8</td><td>-9.6</td><td>-3.6</td></tr> <tr><td>1.43</td><td>-10.8</td><td>-9.6</td><td>-2.4</td></tr> <tr><td>1.42</td><td>-10.8</td><td>-9.6</td><td>-1.2</td></tr> <tr><td>1.69</td><td>-12.0</td><td>-12.0</td><td>0.0</td></tr> </tbody> </table>	Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.0	-12.0	-12.0	-12.0	0.76	-12.0	-11.4	-10.8	1.0	-11.4	-10.8	-9.6	1.13	-10.8	-9.6	-8.4	1.19	-10.8	-9.6	-7.2	1.27	-10.8	-9.6	-6.0	1.36	-10.8	-9.6	-4.8	1.44	-10.8	-9.6	-3.6	1.43	-10.8	-9.6	-2.4	1.42	-10.8	-9.6	-1.2	1.69	-12.0	-12.0	0.0	2.Values	
Load Current [A]	4.5V [V]	5V [V]	9V [V]																																																
0.0	-12.0	-12.0	-12.0																																																
0.76	-12.0	-11.4	-10.8																																																
1.0	-11.4	-10.8	-9.6																																																
1.13	-10.8	-9.6	-8.4																																																
1.19	-10.8	-9.6	-7.2																																																
1.27	-10.8	-9.6	-6.0																																																
1.36	-10.8	-9.6	-4.8																																																
1.44	-10.8	-9.6	-3.6																																																
1.43	-10.8	-9.6	-2.4																																																
1.42	-10.8	-9.6	-1.2																																																
1.69	-12.0	-12.0	0.0																																																

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B(Ripple and Ripple noise Characteristic)