

# TEST DATA OF SUW1R50515

Regulated DC Power Supply  
Sep 14, 2004

Approved by : Tetsuo Sugimori  
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima  
Masahiro Shima Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Figure of Testing Circuitry . . . . .	22

(Final Page 22)



<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure A																																																																							
<b>Item</b>	Input Current (by Input Voltage)																																																																								
<b>Object</b>																																																																									
<p>1.Graph</p> <p>—△— Load 100%          - - □ - - Load 50%          - - ○ - - Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.7</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.3</td><td>0.098</td><td>0.779</td><td>0.751</td></tr> <tr><td>3.0</td><td>0.085</td><td>0.419</td><td>0.772</td></tr> <tr><td>3.2</td><td>0.081</td><td>0.379</td><td>0.769</td></tr> <tr><td>4.0</td><td>0.070</td><td>0.287</td><td>0.562</td></tr> <tr><td>4.5</td><td>0.066</td><td>0.254</td><td>0.481</td></tr> <tr><td>5.0</td><td>0.062</td><td>0.230</td><td>0.422</td></tr> <tr><td>6.0</td><td>0.056</td><td>0.193</td><td>0.343</td></tr> <tr><td>7.0</td><td>0.051</td><td>0.166</td><td>0.294</td></tr> <tr><td>8.0</td><td>0.047</td><td>0.148</td><td>0.258</td></tr> <tr><td>9.0</td><td>0.044</td><td>0.136</td><td>0.230</td></tr> <tr><td>10.0</td><td>0.043</td><td>0.126</td><td>0.209</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	1.7	0.000	0.000	0.000	2.0	0.000	0.000	0.000	2.3	0.098	0.779	0.751	3.0	0.085	0.419	0.772	3.2	0.081	0.379	0.769	4.0	0.070	0.287	0.562	4.5	0.066	0.254	0.481	5.0	0.062	0.230	0.422	6.0	0.056	0.193	0.343	7.0	0.051	0.166	0.294	8.0	0.047	0.148	0.258	9.0	0.044	0.136	0.230	10.0	0.043	0.126	0.209	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																								
	Load 0%	Load 50%	Load 100%																																																																						
0	0.000	0.000	0.000																																																																						
1.7	0.000	0.000	0.000																																																																						
2.0	0.000	0.000	0.000																																																																						
2.3	0.098	0.779	0.751																																																																						
3.0	0.085	0.419	0.772																																																																						
3.2	0.081	0.379	0.769																																																																						
4.0	0.070	0.287	0.562																																																																						
4.5	0.066	0.254	0.481																																																																						
5.0	0.062	0.230	0.422																																																																						
6.0	0.056	0.193	0.343																																																																						
7.0	0.051	0.166	0.294																																																																						
8.0	0.047	0.148	0.258																																																																						
9.0	0.044	0.136	0.230																																																																						
10.0	0.043	0.126	0.209																																																																						
-	-	-	-																																																																						
-	-	-	-																																																																						




Model	SUW1R50515
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

1.Graph

- △— Input Volt. 4.5V
- - -□- - - Input Volt. 5V
- - -○- - - Input Volt. 9V



2.Values

Load Ration [%]	Input Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0	0.064	0.061	0.044
20	0.137	0.126	0.082
40	0.214	0.194	0.119
60	0.297	0.266	0.155
80	0.376	0.335	0.192
100	0.470	0.414	0.230
110	0.509	0.444	0.249
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Model		SUW1R50515		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.29</td><td>0.30</td><td>0.40</td></tr> <tr><td>20</td><td>0.62</td><td>0.64</td><td>0.73</td></tr> <tr><td>40</td><td>0.96</td><td>0.97</td><td>1.06</td></tr> <tr><td>60</td><td>1.32</td><td>1.31</td><td>1.39</td></tr> <tr><td>80</td><td>1.68</td><td>1.67</td><td>1.72</td></tr> <tr><td>100</td><td>2.07</td><td>2.04</td><td>2.06</td></tr> <tr><td>110</td><td>2.27</td><td>2.23</td><td>2.22</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.29	0.30	0.40	20	0.62	0.64	0.73	40	0.96	0.97	1.06	60	1.32	1.31	1.39	80	1.68	1.67	1.72	100	2.07	2.04	2.06	110	2.27	2.23	2.22	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.29	0.30	0.40																																																					
20	0.62	0.64	0.73																																																					
40	0.96	0.97	1.06																																																					
60	1.32	1.31	1.39																																																					
80	1.68	1.67	1.72																																																					
100	2.07	2.04	2.06																																																					
110	2.27	2.23	2.22																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					



<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure A																																
<b>Item</b>	<b>Efficiency (by Input Voltage)</b>																																	
<b>Object</b>	_____																																	
<b>1.Graph</b> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<b>2.Values</b> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>66.6</td><td>68.4</td></tr> <tr><td>4.5</td><td>66.6</td><td>72.0</td></tr> <tr><td>5.0</td><td>66.1</td><td>73.5</td></tr> <tr><td>6.0</td><td>65.3</td><td>74.0</td></tr> <tr><td>7.0</td><td>64.4</td><td>74.1</td></tr> <tr><td>8.0</td><td>63.2</td><td>73.7</td></tr> <tr><td>9.0</td><td>61.7</td><td>72.8</td></tr> <tr><td>9.5</td><td>60.7</td><td>72.3</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	66.6	68.4	4.5	66.6	72.0	5.0	66.1	73.5	6.0	65.3	74.0	7.0	64.4	74.1	8.0	63.2	73.7	9.0	61.7	72.8	9.5	60.7	72.3	—	—	—
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.0	66.6	68.4																																
4.5	66.6	72.0																																
5.0	66.1	73.5																																
6.0	65.3	74.0																																
7.0	64.4	74.1																																
8.0	63.2	73.7																																
9.0	61.7	72.8																																
9.5	60.7	72.3																																
—	—	—																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model		SUW1R50515		Temperature		25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry		Figure A																																																				
Object		_____																																																								
1.Graph				2.Values																																																						
<p>                 —△— Input Volt. 4.5V                  - - □ - - Input Volt. 5V                  - · ○ · - Input Volt. 9V             </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>49.9</td><td>48.8</td><td>42.2</td></tr> <tr><td>40</td><td>62.9</td><td>62.5</td><td>57.0</td></tr> <tr><td>60</td><td>68.7</td><td>68.8</td><td>64.8</td></tr> <tr><td>80</td><td>71.4</td><td>71.8</td><td>69.7</td></tr> <tr><td>100</td><td>72.2</td><td>73.4</td><td>72.7</td></tr> <tr><td>110</td><td>72.4</td><td>73.8</td><td>74.0</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	49.9	48.8	42.2	40	62.9	62.5	57.0	60	68.7	68.8	64.8	80	71.4	71.8	69.7	100	72.2	73.4	72.7	110	72.4	73.8	74.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
0	-	-	-																																																							
20	49.9	48.8	42.2																																																							
40	62.9	62.5	57.0																																																							
60	68.7	68.8	64.8																																																							
80	71.4	71.8	69.7																																																							
100	72.2	73.4	72.7																																																							
110	72.4	73.8	74.0																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							
-	-	-	-																																																							



<b>COSEL</b>																																			
Model	SUW1R50515	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V0.05A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>14.932</td><td>14.814</td></tr> <tr><td>4.5</td><td>14.920</td><td>14.814</td></tr> <tr><td>5.0</td><td>14.913</td><td>14.815</td></tr> <tr><td>6.0</td><td>14.905</td><td>14.814</td></tr> <tr><td>7.0</td><td>14.899</td><td>14.814</td></tr> <tr><td>8.0</td><td>14.895</td><td>14.814</td></tr> <tr><td>9.0</td><td>14.892</td><td>14.814</td></tr> <tr><td>9.5</td><td>14.891</td><td>14.814</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	14.932	14.814	4.5	14.920	14.814	5.0	14.913	14.815	6.0	14.905	14.814	7.0	14.899	14.814	8.0	14.895	14.814	9.0	14.892	14.814	9.5	14.891	14.814	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	14.932	14.814																																	
4.5	14.920	14.814																																	
5.0	14.913	14.815																																	
6.0	14.905	14.814																																	
7.0	14.899	14.814																																	
8.0	14.895	14.814																																	
9.0	14.892	14.814																																	
9.5	14.891	14.814																																	
-	-	-																																	
Object	-15V0.05A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-14.974</td><td>-14.859</td></tr> <tr><td>4.5</td><td>-14.965</td><td>-14.859</td></tr> <tr><td>5.0</td><td>-14.957</td><td>-14.858</td></tr> <tr><td>6.0</td><td>-14.949</td><td>-14.859</td></tr> <tr><td>7.0</td><td>-14.944</td><td>-14.859</td></tr> <tr><td>8.0</td><td>-14.940</td><td>-14.858</td></tr> <tr><td>9.0</td><td>-14.937</td><td>-14.858</td></tr> <tr><td>9.5</td><td>-14.936</td><td>-14.858</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-14.974	-14.859	4.5	-14.965	-14.859	5.0	-14.957	-14.858	6.0	-14.949	-14.859	7.0	-14.944	-14.859	8.0	-14.940	-14.858	9.0	-14.937	-14.858	9.5	-14.936	-14.858	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.0	-14.974	-14.859																																	
4.5	-14.965	-14.859																																	
5.0	-14.957	-14.858																																	
6.0	-14.949	-14.859																																	
7.0	-14.944	-14.859																																	
8.0	-14.940	-14.858																																	
9.0	-14.937	-14.858																																	
9.5	-14.936	-14.858																																	
-	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			




<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure A																																																			
<b>Item</b>	Load Regulation																																																				
<b>Object</b>	+15V0.05A																																																				
<b>1.Graph</b> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="flex: 1;"> </div> <div style="flex: 0.5;"> <p>—△— Input Volt. 4.5V              ---□--- Input Volt. 5V              -·-○-·- Input Volt. 9V</p> </div> </div>		<b>2.Values</b> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.117</td><td>15.118</td><td>15.119</td></tr> <tr><td>0.008</td><td>15.000</td><td>14.992</td><td>14.972</td></tr> <tr><td>0.016</td><td>14.959</td><td>14.951</td><td>14.928</td></tr> <tr><td>0.024</td><td>14.925</td><td>14.917</td><td>14.896</td></tr> <tr><td>0.032</td><td>14.892</td><td>14.886</td><td>14.869</td></tr> <tr><td>0.040</td><td>14.859</td><td>14.856</td><td>14.844</td></tr> <tr><td>0.048</td><td>14.824</td><td>14.824</td><td>14.821</td></tr> <tr><td>0.050</td><td>14.816</td><td>14.816</td><td>14.815</td></tr> <tr><td>0.055</td><td>14.792</td><td>14.795</td><td>14.801</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	15.117	15.118	15.119	0.008	15.000	14.992	14.972	0.016	14.959	14.951	14.928	0.024	14.925	14.917	14.896	0.032	14.892	14.886	14.869	0.040	14.859	14.856	14.844	0.048	14.824	14.824	14.821	0.050	14.816	14.816	14.815	0.055	14.792	14.795	14.801	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	15.117	15.118	15.119																																																		
0.008	15.000	14.992	14.972																																																		
0.016	14.959	14.951	14.928																																																		
0.024	14.925	14.917	14.896																																																		
0.032	14.892	14.886	14.869																																																		
0.040	14.859	14.856	14.844																																																		
0.048	14.824	14.824	14.821																																																		
0.050	14.816	14.816	14.815																																																		
0.055	14.792	14.795	14.801																																																		
-	-	-	-																																																		
-	-	-	-																																																		
<b>Object</b> -15V0.05A																																																					
<b>1.Graph</b> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="flex: 1;"> </div> <div style="flex: 0.5;"> <p>—△— Input Volt. 4.5V              ---□--- Input Volt. 5V              -·-○-·- Input Volt. 9V</p> </div> </div>		<b>2.Values</b> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.173</td><td>-15.173</td><td>-15.179</td></tr> <tr><td>0.008</td><td>-15.046</td><td>-15.037</td><td>-15.018</td></tr> <tr><td>0.016</td><td>-15.004</td><td>-14.995</td><td>-14.973</td></tr> <tr><td>0.024</td><td>-14.970</td><td>-14.962</td><td>-14.941</td></tr> <tr><td>0.032</td><td>-14.937</td><td>-14.931</td><td>-14.913</td></tr> <tr><td>0.040</td><td>-14.904</td><td>-14.900</td><td>-14.888</td></tr> <tr><td>0.048</td><td>-14.868</td><td>-14.868</td><td>-14.865</td></tr> <tr><td>0.050</td><td>-14.860</td><td>-14.860</td><td>-14.859</td></tr> <tr><td>0.055</td><td>-14.836</td><td>-14.840</td><td>-14.845</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-15.173	-15.173	-15.179	0.008	-15.046	-15.037	-15.018	0.016	-15.004	-14.995	-14.973	0.024	-14.970	-14.962	-14.941	0.032	-14.937	-14.931	-14.913	0.040	-14.904	-14.900	-14.888	0.048	-14.868	-14.868	-14.865	0.050	-14.860	-14.860	-14.859	0.055	-14.836	-14.840	-14.845	--	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	-15.173	-15.173	-15.179																																																		
0.008	-15.046	-15.037	-15.018																																																		
0.016	-15.004	-14.995	-14.973																																																		
0.024	-14.970	-14.962	-14.941																																																		
0.032	-14.937	-14.931	-14.913																																																		
0.040	-14.904	-14.900	-14.888																																																		
0.048	-14.868	-14.868	-14.865																																																		
0.050	-14.860	-14.860	-14.859																																																		
0.055	-14.836	-14.840	-14.845																																																		
--	-	-	-																																																		
-	-	-	-																																																		
<p><b>Note:</b> Slanted line shows the range of the rated load current.</p>																																																					




<b>Model</b>		SUW1R50515	
<b>Item</b>		Dynamic Load Response	
<b>Object</b>		+15V0.05A	
		<b>Temperature</b>	25°C
		<b>Testing Circuitry</b>	Figure A


Input Volt. 5 V  
Cycle 100 mS



Min. Load (0A) ←→  
Load 100% (0.05A)




2ms/div




2ms/div

Min. Load (0A) ←→  
Load 50% (0.025A)




2ms/div




2ms/div

Load 50% (0.025A) ←→  
Load 100% (0.05A)



2ms/div




2ms/div



Model		SUW1R50515	Temperature 25°C Testing Circuitry Figure A
Item		Dynamic Load Response	
Object		-15V0.05A	


Input Volt. 5 V  
Cycle 100 mS



Min. Load (0A) ←→  
Load 100% (0.05A)



2ms/div




2ms/div

Min. Load (0A) ←→  
Load 50% (0.025A)




2ms/div




2ms/div

Load 50% (0.025A) ←→  
Load 100% (0.05A)



2ms/div



2ms/div



<p><b>Model</b> SUW1R50515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p><b>Item</b> Ripple Voltage (by Load Current)</p>																																								
<p><b>Object</b> +15V0.05A</p>																																								
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p> <div style="text-align: center;"> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p> </div>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>2</td></tr> <tr><td>20</td><td>2</td><td>2</td></tr> <tr><td>40</td><td>2</td><td>2</td></tr> <tr><td>60</td><td>2</td><td>2</td></tr> <tr><td>80</td><td>2</td><td>2</td></tr> <tr><td>100</td><td>4</td><td>2</td></tr> <tr><td>110</td><td>6</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0	2	2	20	2	2	40	2	2	60	2	2	80	2	2	100	4	2	110	6	2	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0	2	2																																						
20	2	2																																						
40	2	2																																						
60	2	2																																						
80	2	2																																						
100	4	2																																						
110	6	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						



<p><b>Model</b> SUW1R50515</p> <p><b>Item</b> Ripple Voltage (by Load Current)</p> <p><b>Object</b> -15V0.05A</p>		<p><b>Temperature</b> 25°C</p> <p><b>Testing Circuitry</b> Figure B</p>																																					
<p><b>1.Graph</b></p> <p>—△— Input Volt. 4.5V -·-○-·- Input Volt. 9V</p> <p><b>2.Values</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>2</td></tr> <tr><td>20</td><td>2</td><td>2</td></tr> <tr><td>40</td><td>2</td><td>2</td></tr> <tr><td>60</td><td>2</td><td>2</td></tr> <tr><td>80</td><td>3</td><td>2</td></tr> <tr><td>100</td><td>5</td><td>3</td></tr> <tr><td>110</td><td>7</td><td>3</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0	2	2	20	2	2	40	2	2	60	2	2	80	3	2	100	5	3	110	7	3	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple Voltage [mV]																																						
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																					
0	2	2																																					
20	2	2																																					
40	2	2																																					
60	2	2																																					
80	3	2																																					
100	5	3																																					
110	7	3																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p>																																							
<p>Ripple [mVp-p]</p> <p><b>Fig. Complex Ripple Wave Form</b></p>																																							



<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure B																																						
<b>Item</b>	Ripple-Noise																																							
<b>Object</b>	+15V0.05A																																							
<p>1. Graph</p> <p>—△— Input Volt. 4.5V - - -○- - - Input Volt. 9V</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <p>Fig. Complex Ripple Noise Wave Form</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>4</td><td>4</td></tr> <tr><td>20</td><td>4</td><td>4</td></tr> <tr><td>40</td><td>4</td><td>4</td></tr> <tr><td>60</td><td>4</td><td>4</td></tr> <tr><td>80</td><td>5</td><td>5</td></tr> <tr><td>100</td><td>7</td><td>5</td></tr> <tr><td>110</td><td>9</td><td>5</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ratio [%]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0	4	4	20	4	4	40	4	4	60	4	4	80	5	5	100	7	5	110	9	5	-	-	-	-	-	-	-	-	-	-	-	-
Load Ratio [%]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0	4	4																																						
20	4	4																																						
40	4	4																																						
60	4	4																																						
80	5	5																																						
100	7	5																																						
110	9	5																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						




<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure B																																							
<b>Item</b> Ripple-Noise																																									
<b>Object</b> -15V0.05A																																									
<b>1.Graph</b> <div style="text-align: right; margin-right: 50px;">                 —△— Input Volt. 4.5V                  - - -○- - - Input Volt. 9V             </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <div style="text-align: center; margin-top: 20px;"> <p>Fig.Complex Ripple Noise Wave Form</p> </div>		<b>2.Values</b> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>4</td><td>5</td></tr> <tr><td>20</td><td>4</td><td>5</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>6</td></tr> <tr><td>80</td><td>6</td><td>6</td></tr> <tr><td>100</td><td>7</td><td>6</td></tr> <tr><td>110</td><td>9</td><td>6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0	4	5	20	4	5	40	5	5	60	5	6	80	6	6	100	7	6	110	9	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Ration [%]	Ripple-Noise [mV]																																								
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																							
0	4	5																																							
20	4	5																																							
40	5	5																																							
60	5	6																																							
80	6	6																																							
100	7	6																																							
110	9	6																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							



Model	SUW1R50515
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.05A

Testing Circuitry Figure B

1. Graph




2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	2	4
-40	2	5
-20	2	4
0	2	3
25	1	3
55	2	3
60	2	3
-	-	-
-	-	-
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1. Graph




2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	4
-40	3	5
-20	3	5
0	2	4
25	2	3
55	1	3
60	1	3
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	14.838	14.838	14.837
-40	14.844	14.845	14.843
-20	14.843	14.843	14.841
0	14.834	14.833	14.832
25	14.814	14.813	14.812
55	14.782	14.782	14.779
60	14.777	14.776	14.774
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	-14.883	-14.884	-14.882
-40	-14.889	-14.889	-14.888
-20	-14.887	-14.887	-14.886
0	-14.877	-14.877	-14.876
25	-14.857	-14.857	-14.855
55	-14.825	-14.825	-14.823
60	-14.819	-14.819	-14.817
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



<b>COSEL</b>		Testing Circuitry Figure A
Model	SUW1R50515	
Item	Output Voltage Accuracy	

**1. Output Voltage Accuracy**

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.05A (AVR 2): 0 - 0.05A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration) = } \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

**2. Values**

Object		+15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	9	0	15.149	±185	±1.2
Minimum Voltage	55	9	0.05	14.779		

Object		-15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	9	0	-15.212	±195	±1.3
Minimum Voltage	55	9	0.05	-14.823		




<b>Model</b> SUW1R50515		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure A																						
<b>Item</b>	Time Lapse Drift																							
<b>Object</b>	+15V0.05A																							
<b>1.Graph</b>  Input Volt. 5V Load 100%		<b>2.Values</b> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.819</td></tr> <tr><td>0.5</td><td>14.807</td></tr> <tr><td>1.0</td><td>14.807</td></tr> <tr><td>2.0</td><td>14.807</td></tr> <tr><td>3.0</td><td>14.806</td></tr> <tr><td>4.0</td><td>14.805</td></tr> <tr><td>5.0</td><td>14.805</td></tr> <tr><td>6.0</td><td>14.806</td></tr> <tr><td>7.0</td><td>14.806</td></tr> <tr><td>8.0</td><td>14.807</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.819	0.5	14.807	1.0	14.807	2.0	14.807	3.0	14.806	4.0	14.805	5.0	14.805	6.0	14.806	7.0	14.806	8.0	14.807
Time since start [H]	Output Voltage [V]																							
0.0	14.819																							
0.5	14.807																							
1.0	14.807																							
2.0	14.807																							
3.0	14.806																							
4.0	14.805																							
5.0	14.805																							
6.0	14.806																							
7.0	14.806																							
8.0	14.807																							
<b>Object</b> -15V0.05A <b>1.Graph</b>  Input Volt. 5V Load 100%		<b>2.Values</b> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.868</td></tr> <tr><td>0.5</td><td>-14.859</td></tr> <tr><td>1.0</td><td>-14.859</td></tr> <tr><td>2.0</td><td>-14.858</td></tr> <tr><td>3.0</td><td>-14.858</td></tr> <tr><td>4.0</td><td>-14.857</td></tr> <tr><td>5.0</td><td>-14.857</td></tr> <tr><td>6.0</td><td>-14.857</td></tr> <tr><td>7.0</td><td>-14.857</td></tr> <tr><td>8.0</td><td>-14.858</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-14.868	0.5	-14.859	1.0	-14.859	2.0	-14.858	3.0	-14.858	4.0	-14.857	5.0	-14.857	6.0	-14.857	7.0	-14.857	8.0	-14.858
Time since start [H]	Output Voltage [V]																							
0.0	-14.868																							
0.5	-14.859																							
1.0	-14.859																							
2.0	-14.858																							
3.0	-14.858																							
4.0	-14.857																							
5.0	-14.857																							
6.0	-14.857																							
7.0	-14.857																							
8.0	-14.858																							




Model	SUW1R50515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.05A		

1. Graph



2. Values


Load	Time	[mS]				
		Td	Tr	Ts	Th	Tf
50 %		0.1	5.2	5.3	0.1	3.8
100 %		0.1	5.5	5.6	0.0	1.9






Model	SUW1R50515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.05A		

1. Graph



2. Values

		[mS]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	5.2	5.3	0.1	3.8
100 %		0.1	5.5	5.6	0.0	1.9






Model	SUW1R50515
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.05A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.2	2.9
-40	2.2	3.0
-20	2.3	3.0
0	2.3	3.2
25	2.4	3.2
55	2.3	3.4
60	2.4	3.3
-	-	-
-	-	-
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1.Graph



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.2	2.8
-40	2.1	2.9
-20	2.2	3.0
0	2.2	3.1
25	2.2	3.2
55	2.2	3.2
60	2.3	3.2
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUW1R50515
Item	Overcurrent Protection
Object	+15V0.05A


Temperature 25°C  
Testing Circuitry Figure A



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
15.0	0.05	0.05	0.05
14.3	0.10	0.11	0.10
13.5	0.11	0.12	0.10
12.0	0.12	0.13	0.12
10.5	0.14	0.15	0.13
9.0	0.16	0.17	0.14
7.5	0.18	0.19	0.15
6.0	0.20	0.21	0.16
4.5	0.22	0.23	0.17
3.0	0.24	0.24	0.17
1.5	0.24	0.24	0.16
0.0	0.25	0.28	0.20

Object	-15V0.05A
--------	-----------



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-15.00	0.05	0.05	0.05
-14.25	0.10	0.11	0.10
-13.50	0.11	0.12	0.10
-12.00	0.12	0.14	0.12
-10.50	0.14	0.15	0.13
-9.00	0.16	0.17	0.14
-7.50	0.18	0.19	0.15
-6.00	0.20	0.21	0.16
-4.50	0.22	0.23	0.17
-3.00	0.24	0.24	0.17
-1.50	0.24	0.24	0.16
0.00	0.25	0.28	0.20

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)