

TEST DATA OF SUW1R51215

Regulated DC Power Supply
Sep 17, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUW1R51215	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																							
Object	—																																																																									
1. Graph	<p>—△— Load 100% -□--- Load 50% -○--- Load 0%</p>																																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.6</td><td>0.103</td><td>0.294</td><td>0.118</td></tr> <tr><td>3.8</td><td>0.053</td><td>0.334</td><td>0.325</td></tr> <tr><td>4.0</td><td>0.050</td><td>0.327</td><td>0.324</td></tr> <tr><td>6.0</td><td>0.037</td><td>0.183</td><td>0.351</td></tr> <tr><td>8.0</td><td>0.032</td><td>0.135</td><td>0.251</td></tr> <tr><td>9.0</td><td>0.030</td><td>0.121</td><td>0.221</td></tr> <tr><td>10.0</td><td>0.028</td><td>0.110</td><td>0.198</td></tr> <tr><td>12.0</td><td>0.025</td><td>0.093</td><td>0.165</td></tr> <tr><td>14.0</td><td>0.023</td><td>0.082</td><td>0.143</td></tr> <tr><td>16.0</td><td>0.021</td><td>0.073</td><td>0.126</td></tr> <tr><td>18.0</td><td>0.020</td><td>0.067</td><td>0.114</td></tr> <tr><td>20.0</td><td>0.020</td><td>0.061</td><td>0.104</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	2.6	0.103	0.294	0.118	3.8	0.053	0.334	0.325	4.0	0.050	0.327	0.324	6.0	0.037	0.183	0.351	8.0	0.032	0.135	0.251	9.0	0.030	0.121	0.221	10.0	0.028	0.110	0.198	12.0	0.025	0.093	0.165	14.0	0.023	0.082	0.143	16.0	0.021	0.073	0.126	18.0	0.020	0.067	0.114	20.0	0.020	0.061	0.104	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
2.0	0.000	0.000	0.000																																																																							
2.6	0.103	0.294	0.118																																																																							
3.8	0.053	0.334	0.325																																																																							
4.0	0.050	0.327	0.324																																																																							
6.0	0.037	0.183	0.351																																																																							
8.0	0.032	0.135	0.251																																																																							
9.0	0.030	0.121	0.221																																																																							
10.0	0.028	0.110	0.198																																																																							
12.0	0.025	0.093	0.165																																																																							
14.0	0.023	0.082	0.143																																																																							
16.0	0.021	0.073	0.126																																																																							
18.0	0.020	0.067	0.114																																																																							
20.0	0.020	0.061	0.104																																																																							
-	-	-	-																																																																							
-	-	-	-																																																																							

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUW1R51215																																
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																															
Object	—	—																															
1.Graph																																	
<p style="text-align: center;"> △— Input Volt. 9V □— Input Volt. 12V ○— Input Volt. 18V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.030</td><td>0.025</td><td>0.020</td></tr> <tr><td>20</td><td>0.067</td><td>0.053</td><td>0.039</td></tr> <tr><td>40</td><td>0.104</td><td>0.081</td><td>0.058</td></tr> <tr><td>60</td><td>0.142</td><td>0.108</td><td>0.076</td></tr> <tr><td>80</td><td>0.181</td><td>0.136</td><td>0.094</td></tr> <tr><td>100</td><td>0.220</td><td>0.165</td><td>0.113</td></tr> <tr><td>110</td><td>0.241</td><td>0.179</td><td>0.122</td></tr> </tbody> </table>		Load Ration [%]	9V [A]	12V [A]	18V [A]	0	0.030	0.025	0.020	20	0.067	0.053	0.039	40	0.104	0.081	0.058	60	0.142	0.108	0.076	80	0.181	0.136	0.094	100	0.220	0.165	0.113	110	0.241	0.179	0.122
Load Ration [%]	9V [A]	12V [A]	18V [A]																														
0	0.030	0.025	0.020																														
20	0.067	0.053	0.039																														
40	0.104	0.081	0.058																														
60	0.142	0.108	0.076																														
80	0.181	0.136	0.094																														
100	0.220	0.165	0.113																														
110	0.241	0.179	0.122																														
<p style="text-align: center;">Input Current [A]</p> <p style="text-align: center;">Load Ration [%]</p> <p style="text-align: center;">0 40 80 120</p>																																	

2.Values

Load Ration [%]	Input Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0	0.030	0.025	0.020
20	0.067	0.053	0.039
40	0.104	0.081	0.058
60	0.142	0.108	0.076
80	0.181	0.136	0.094
100	0.220	0.165	0.113
110	0.241	0.179	0.122
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	SUW1R51215
Item	Input Power (by Load Current)
Object	

1.Graph

Load Ration [%]	Input Volt. 9V [W]	Input Volt. 12V [W]	Input Volt. 18V [W]
0	0.27	0.31	0.37
20	0.60	0.64	0.71
40	0.93	0.97	1.04
60	1.27	1.29	1.37
80	1.61	1.63	1.70
100	1.96	1.96	2.03
110	2.14	2.14	2.20
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Temperature 25°C
Testing Circuitry Figure A


2.Values

Load Ration [%]	Input Power [W]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0	0.27	0.31	0.37
20	0.60	0.64	0.71
40	0.93	0.97	1.04
60	1.27	1.29	1.37
80	1.61	1.63	1.70
100	1.96	1.96	2.03
110	2.14	2.14	2.20
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	SUW1R51215
Item	Efficiency (by Input Voltage)
Object	—

1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8	68.9	75.6
9	68.5	76.3
10	68.1	76.4
12	66.7	76.0
15	64.8	75.1
18	62.7	73.8
20	60.9	72.5
-	-	-
-	-	-

COSEL


Model	SUW1R51215																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Graph showing Efficiency [%] vs Load Ration [%]. The Y-axis ranges from 30 to 80 in increments of 10. The X-axis ranges from 0 to 120 in increments of 40. Three curves are shown for Input Voltages: 9V (solid line with triangles), 12V (dashed line with squares), and 18V (dash-dot line with circles). All curves show efficiency increasing with load ratio.</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>9V [Efficiency %]</th> <th>12V [Efficiency %]</th> <th>18V [Efficiency %]</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>50.9</td> <td>48.2</td> <td>43.4</td> </tr> <tr> <td>40</td> <td>65.0</td> <td>62.6</td> <td>58.2</td> </tr> <tr> <td>60</td> <td>71.0</td> <td>69.5</td> <td>65.7</td> </tr> <tr> <td>80</td> <td>74.4</td> <td>73.6</td> <td>70.6</td> </tr> <tr> <td>100</td> <td>76.2</td> <td>76.0</td> <td>73.6</td> </tr> <tr> <td>110</td> <td>76.9</td> <td>76.9</td> <td>74.9</td> </tr> </tbody> </table>			Load Ration [%]	9V [Efficiency %]	12V [Efficiency %]	18V [Efficiency %]	20	50.9	48.2	43.4	40	65.0	62.6	58.2	60	71.0	69.5	65.7	80	74.4	73.6	70.6	100	76.2	76.0	73.6	110	76.9	76.9	74.9																							
Load Ration [%]	9V [Efficiency %]	12V [Efficiency %]	18V [Efficiency %]																																																			
20	50.9	48.2	43.4																																																			
40	65.0	62.6	58.2																																																			
60	71.0	69.5	65.7																																																			
80	74.4	73.6	70.6																																																			
100	76.2	76.0	73.6																																																			
110	76.9	76.9	74.9																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>50.9</td> <td>48.2</td> <td>43.4</td> </tr> <tr> <td>40</td> <td>65.0</td> <td>62.6</td> <td>58.2</td> </tr> <tr> <td>60</td> <td>71.0</td> <td>69.5</td> <td>65.7</td> </tr> <tr> <td>80</td> <td>74.4</td> <td>73.6</td> <td>70.6</td> </tr> <tr> <td>100</td> <td>76.2</td> <td>76.0</td> <td>73.6</td> </tr> <tr> <td>110</td> <td>76.9</td> <td>76.9</td> <td>74.9</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	50.9	48.2	43.4	40	65.0	62.6	58.2	60	71.0	69.5	65.7	80	74.4	73.6	70.6	100	76.2	76.0	73.6	110	76.9	76.9	74.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	-	-	-																																																			
20	50.9	48.2	43.4																																																			
40	65.0	62.6	58.2																																																			
60	71.0	69.5	65.7																																																			
80	74.4	73.6	70.6																																																			
100	76.2	76.0	73.6																																																			
110	76.9	76.9	74.9																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			

COSEL

Model	SUW1R51215
Item	Line Regulation
Object	+15V0.05A

1.Graph

---□--- Load 50%
—△— Load 100%



Temperature 25°C
Testing Circuitry Figure A


2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	14.937	14.835
9	14.930	14.836
10	14.926	14.836
12	14.919	14.836
15	14.914	14.836
18	14.911	14.836
20	14.909	14.835
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	-14.935	-14.834
9	-14.928	-14.833
10	-14.923	-14.833
12	-14.916	-14.833
15	-14.911	-14.833
18	-14.909	-14.832
20	-14.907	-14.833
-	-	-
-	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL








Model	SUW1R51215	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.05A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 9V - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.156</td><td>15.156</td><td>15.159</td></tr> <tr><td>0.008</td><td>15.012</td><td>15.001</td><td>14.992</td></tr> <tr><td>0.016</td><td>14.967</td><td>14.955</td><td>14.946</td></tr> <tr><td>0.024</td><td>14.934</td><td>14.923</td><td>14.915</td></tr> <tr><td>0.032</td><td>14.903</td><td>14.894</td><td>14.888</td></tr> <tr><td>0.040</td><td>14.873</td><td>14.868</td><td>14.864</td></tr> <tr><td>0.048</td><td>14.843</td><td>14.843</td><td>14.842</td></tr> <tr><td>0.050</td><td>14.835</td><td>14.837</td><td>14.837</td></tr> <tr><td>0.055</td><td>14.816</td><td>14.821</td><td>14.823</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.000	15.156	15.156	15.159	0.008	15.012	15.001	14.992	0.016	14.967	14.955	14.946	0.024	14.934	14.923	14.915	0.032	14.903	14.894	14.888	0.040	14.873	14.868	14.864	0.048	14.843	14.843	14.842	0.050	14.835	14.837	14.837	0.055	14.816	14.821	14.823	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.000	15.156	15.156	15.159																																																			
0.008	15.012	15.001	14.992																																																			
0.016	14.967	14.955	14.946																																																			
0.024	14.934	14.923	14.915																																																			
0.032	14.903	14.894	14.888																																																			
0.040	14.873	14.868	14.864																																																			
0.048	14.843	14.843	14.842																																																			
0.050	14.835	14.837	14.837																																																			
0.055	14.816	14.821	14.823																																																			
—	—	—	—																																																			
—	—	—	—																																																			
Object		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 9V - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.162</td><td>-15.163</td><td>-15.167</td></tr> <tr><td>0.008</td><td>-15.011</td><td>-14.999</td><td>-14.990</td></tr> <tr><td>0.016</td><td>-14.966</td><td>-14.954</td><td>-14.945</td></tr> <tr><td>0.024</td><td>-14.932</td><td>-14.921</td><td>-14.913</td></tr> <tr><td>0.032</td><td>-14.902</td><td>-14.893</td><td>-14.886</td></tr> <tr><td>0.040</td><td>-14.872</td><td>-14.866</td><td>-14.862</td></tr> <tr><td>0.048</td><td>-14.842</td><td>-14.841</td><td>-14.839</td></tr> <tr><td>0.050</td><td>-14.834</td><td>-14.834</td><td>-14.834</td></tr> <tr><td>0.055</td><td>-14.815</td><td>-14.818</td><td>-14.821</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.000	-15.162	-15.163	-15.167	0.008	-15.011	-14.999	-14.990	0.016	-14.966	-14.954	-14.945	0.024	-14.932	-14.921	-14.913	0.032	-14.902	-14.893	-14.886	0.040	-14.872	-14.866	-14.862	0.048	-14.842	-14.841	-14.839	0.050	-14.834	-14.834	-14.834	0.055	-14.815	-14.818	-14.821	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.000	-15.162	-15.163	-15.167																																																			
0.008	-15.011	-14.999	-14.990																																																			
0.016	-14.966	-14.954	-14.945																																																			
0.024	-14.932	-14.921	-14.913																																																			
0.032	-14.902	-14.893	-14.886																																																			
0.040	-14.872	-14.866	-14.862																																																			
0.048	-14.842	-14.841	-14.839																																																			
0.050	-14.834	-14.834	-14.834																																																			
0.055	-14.815	-14.818	-14.821																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

coSEL

Model SUW1R51215

Item Dynamic Load Response

Object +15V0.05A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 12 V
Cycle 100 mSMin. Load (0A) ↔
Load 100% (0.05A)Min. Load (0A) ↔
Load 50% (0.025A)Load 50% (0.025A) ↔
Load 100% (0.05A)

COSEL

Model SUW1R51215

Item Dynamic Load Response

Object -15V0.05A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 12 V
Cycle 100 mSMin. Load (0A) \longleftrightarrow
Load 100% (0.05A)


200mV/div



2ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (0.025A)


200mV/div



2ms/div

Load 50% (0.025A) \longleftrightarrow
Load 100% (0.05A)

200mV/div




2ms/div

COSEL

Model	SUW1R51215
Item	Ripple Voltage (by Load Current)
Object	+15V0.05A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.




Fig. Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B


2. Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0	2	2
20	2	2
40	2	2
60	2	3
80	2	3
100	3	3
110	3	3
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	SUW1R51215
Item	Ripple Voltage (by Load Current)
Object	-15V0.05A

1. Graph



Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0	2	2
20	2	2
40	2	2
60	2	2
80	2	2
100	3	2
110	3	2
—	—	—
—	—	—
—	—	—
—	—	—

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	SUW1R51215
Item	Ripple-Noise
Object	+15V0.05A

Temperature 25°C
Testing Circuitry Figure B


1.Graph



2.Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0	4	5
20	5	5
40	5	5
60	6	6
80	6	7
100	6	7
110	6	7
-	-	-
-	-	-
-	-	-
-	-	-


Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.



COSEL

Model	SUW1R51215
Item	Ripple-Noise
Object	-15V0.05A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0	5	5
20	5	5
40	5	5
60	5	5
80	6	6
100	6	6
110	6	6
-	-	-
-	-	-
-	-	-
-	-	-




Fig.Complex Ripple Noise Wave Form

COSEL


Model SUW1R51215

Item Ripple Voltage (by Ambient Temp.)

Object +15V0.05A

1.Graph

--- □ --- Load 50%
 —△— Load 100%



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	4
-40	3	3
-20	3	3
0	2	3
25	2	3
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

Object -15V0.05A

1.Graph

--- □ --- Load 50%
 —△— Load 100%



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	3
-40	3	3
-20	3	3
0	2	2
25	2	2
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

<p>Model SUW1R51215</p> <p>Item Ambient Temperature Drift</p> <p>Object +15V0.05A</p>	Testing Circuitry Figure A																																																					
	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.882</td><td>14.881</td><td>14.882</td></tr> <tr><td>-40</td><td>14.880</td><td>14.880</td><td>14.879</td></tr> <tr><td>-20</td><td>14.873</td><td>14.872</td><td>14.871</td></tr> <tr><td>0</td><td>14.859</td><td>14.859</td><td>14.858</td></tr> <tr><td>25</td><td>14.836</td><td>14.835</td><td>14.834</td></tr> <tr><td>55</td><td>14.802</td><td>14.802</td><td>14.800</td></tr> <tr><td>60</td><td>14.796</td><td>14.795</td><td>14.793</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-60	14.882	14.881	14.882	-40	14.880	14.880	14.879	-20	14.873	14.872	14.871	0	14.859	14.859	14.858	25	14.836	14.835	14.834	55	14.802	14.802	14.800	60	14.796	14.795	14.793	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
-60	14.882	14.881	14.882																																																			
-40	14.880	14.880	14.879																																																			
-20	14.873	14.872	14.871																																																			
0	14.859	14.859	14.858																																																			
25	14.836	14.835	14.834																																																			
55	14.802	14.802	14.800																																																			
60	14.796	14.795	14.793																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>Object -15V0.05A</p> <p>1.Graph</p>	2.Values																																																					
<p>Object</p> <p>1.Graph</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.882</td><td>-14.882</td><td>-14.881</td></tr> <tr><td>-40</td><td>-14.880</td><td>-14.880</td><td>-14.879</td></tr> <tr><td>-20</td><td>-14.872</td><td>-14.872</td><td>-14.871</td></tr> <tr><td>0</td><td>-14.858</td><td>-14.857</td><td>-14.856</td></tr> <tr><td>25</td><td>-14.833</td><td>-14.832</td><td>-14.831</td></tr> <tr><td>55</td><td>-14.799</td><td>-14.798</td><td>-14.797</td></tr> <tr><td>60</td><td>-14.792</td><td>-14.791</td><td>-14.789</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-60	-14.882	-14.882	-14.881	-40	-14.880	-14.880	-14.879	-20	-14.872	-14.872	-14.871	0	-14.858	-14.857	-14.856	25	-14.833	-14.832	-14.831	55	-14.799	-14.798	-14.797	60	-14.792	-14.791	-14.789	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
-60	-14.882	-14.882	-14.881																																																			
-40	-14.880	-14.880	-14.879																																																			
-20	-14.872	-14.872	-14.871																																																			
0	-14.858	-14.857	-14.856																																																			
25	-14.833	-14.832	-14.831																																																			
55	-14.799	-14.798	-14.797																																																			
60	-14.792	-14.791	-14.789																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					



Model	SUW1R51215	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.05A (AVR 2) : 0 - 0.05A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.05A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	-40	18	0	15.199	± 200	± 1.3	
Minimum Voltage	55	12	0.05	14.800			

Object	-15V0.05A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	-40	18	0	-15.208	± 206	± 1.4	
Minimum Voltage	55	18	0.05	-14.797			

COSEL

Model	SUW1R51215	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.05A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.844</td></tr> <tr><td>0.5</td><td>14.834</td></tr> <tr><td>1.0</td><td>14.834</td></tr> <tr><td>2.0</td><td>14.834</td></tr> <tr><td>3.0</td><td>14.834</td></tr> <tr><td>4.0</td><td>14.834</td></tr> <tr><td>5.0</td><td>14.834</td></tr> <tr><td>6.0</td><td>14.834</td></tr> <tr><td>7.0</td><td>14.834</td></tr> <tr><td>8.0</td><td>14.833</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.844	0.5	14.834	1.0	14.834	2.0	14.834	3.0	14.834	4.0	14.834	5.0	14.834	6.0	14.834	7.0	14.834	8.0	14.833
Time since start [H]	Output Voltage [V]																								
0.0	14.844																								
0.5	14.834																								
1.0	14.834																								
2.0	14.834																								
3.0	14.834																								
4.0	14.834																								
5.0	14.834																								
6.0	14.834																								
7.0	14.834																								
8.0	14.833																								
Object -15V0.05A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.848</td></tr> <tr><td>0.5</td><td>-14.836</td></tr> <tr><td>1.0</td><td>-14.836</td></tr> <tr><td>2.0</td><td>-14.836</td></tr> <tr><td>3.0</td><td>-14.836</td></tr> <tr><td>4.0</td><td>-14.835</td></tr> <tr><td>5.0</td><td>-14.836</td></tr> <tr><td>6.0</td><td>-14.836</td></tr> <tr><td>7.0</td><td>-14.836</td></tr> <tr><td>8.0</td><td>-14.836</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-14.848	0.5	-14.836	1.0	-14.836	2.0	-14.836	3.0	-14.836	4.0	-14.835	5.0	-14.836	6.0	-14.836	7.0	-14.836	8.0	-14.836
Time since start [H]	Output Voltage [V]																								
0.0	-14.848																								
0.5	-14.836																								
1.0	-14.836																								
2.0	-14.836																								
3.0	-14.836																								
4.0	-14.835																								
5.0	-14.836																								
6.0	-14.836																								
7.0	-14.836																								
8.0	-14.836																								

COSEL


Model SUW1R51215

Item Rise and Fall Time

Object +15V0.05A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	6.3	6.4	0.1	1.9
100 %		0.1	6.5	6.6	0.1	1.0



COSEL


Model SUW1R51215

Item Rise and Fall Time

Object -15V0.05A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	6.3	6.4	0.1	1.9	
100 %		0.1	6.5	6.6	0.1	1.0	



COSEL

Model	SUW1R51215
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.05A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.7	5.4
-40	3.7	5.6
-20	3.8	5.7
0	3.9	5.8
25	4.0	6.1
55	4.2	6.3
60	4.3	6.3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.05A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.6	5.3
-40	3.6	5.5
-20	3.7	5.6
0	3.8	5.7
25	3.9	5.9
55	4.1	6.2
60	4.2	6.2
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SUW1R51215																																																																	
Item	Overcurrent Protection																																																																	
Object	+15V0.05A																																																																	
1.Graph	<p style="text-align: center;"> Input Volt. 9V Input Volt. 12V Input Volt. 18V </p> <table border="1"> <thead> <tr> <th>Output Voltage [V]</th> <th>0.00</th> <th>0.10</th> <th>0.20</th> <th>0.30</th> </tr> </thead> <tbody> <tr> <td>15.0</td> <td>0.08</td> <td>0.05</td> <td>0.09</td> <td></td> </tr> <tr> <td>14.3</td> <td>0.11</td> <td>0.11</td> <td>0.10</td> <td></td> </tr> <tr> <td>13.5</td> <td>0.12</td> <td>0.12</td> <td>0.11</td> <td></td> </tr> <tr> <td>12.0</td> <td>0.13</td> <td>0.13</td> <td>0.12</td> <td></td> </tr> <tr> <td>10.5</td> <td>0.15</td> <td>0.14</td> <td>0.13</td> <td></td> </tr> <tr> <td>9.0</td> <td>0.17</td> <td>0.16</td> <td>0.14</td> <td></td> </tr> <tr> <td>7.5</td> <td>0.18</td> <td>0.17</td> <td>0.16</td> <td></td> </tr> <tr> <td>6.0</td> <td>0.20</td> <td>0.19</td> <td>0.17</td> <td></td> </tr> <tr> <td>4.5</td> <td>0.21</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>3.0</td> <td>0.23</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>1.5</td> <td>0.23</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>0.0</td> <td>0.29</td> <td>0.25</td> <td>0.22</td> <td></td> </tr> </tbody> </table>	Output Voltage [V]	0.00	0.10	0.20	0.30	15.0	0.08	0.05	0.09		14.3	0.11	0.11	0.10		13.5	0.12	0.12	0.11		12.0	0.13	0.13	0.12		10.5	0.15	0.14	0.13		9.0	0.17	0.16	0.14		7.5	0.18	0.17	0.16		6.0	0.20	0.19	0.17		4.5	0.21	0.20	0.18		3.0	0.23	0.20	0.18		1.5	0.23	0.20	0.18		0.0	0.29	0.25	0.22	
Output Voltage [V]	0.00	0.10	0.20	0.30																																																														
15.0	0.08	0.05	0.09																																																															
14.3	0.11	0.11	0.10																																																															
13.5	0.12	0.12	0.11																																																															
12.0	0.13	0.13	0.12																																																															
10.5	0.15	0.14	0.13																																																															
9.0	0.17	0.16	0.14																																																															
7.5	0.18	0.17	0.16																																																															
6.0	0.20	0.19	0.17																																																															
4.5	0.21	0.20	0.18																																																															
3.0	0.23	0.20	0.18																																																															
1.5	0.23	0.20	0.18																																																															
0.0	0.29	0.25	0.22																																																															

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
15.0	0.08	0.05	0.09
14.3	0.11	0.11	0.10
13.5	0.12	0.12	0.11
12.0	0.13	0.13	0.12
10.5	0.15	0.14	0.13
9.0	0.17	0.16	0.14
7.5	0.18	0.17	0.16
6.0	0.20	0.19	0.17
4.5	0.21	0.20	0.18
3.0	0.23	0.20	0.18
1.5	0.23	0.20	0.18
0.0	0.29	0.25	0.22

Object	-15V0.05A																																																																	
1.Graph	<p style="text-align: center;"> Input Volt. 9V Input Volt. 12V Input Volt. 18V </p> <table border="1"> <thead> <tr> <th>Output Voltage [V]</th> <th>0.00</th> <th>0.10</th> <th>0.20</th> <th>0.30</th> </tr> </thead> <tbody> <tr> <td>-15.00</td> <td>0.05</td> <td>0.05</td> <td>0.05</td> <td></td> </tr> <tr> <td>-14.25</td> <td>0.10</td> <td>0.11</td> <td>0.10</td> <td></td> </tr> <tr> <td>-13.50</td> <td>0.11</td> <td>0.12</td> <td>0.11</td> <td></td> </tr> <tr> <td>-12.00</td> <td>0.13</td> <td>0.13</td> <td>0.12</td> <td></td> </tr> <tr> <td>-10.50</td> <td>0.14</td> <td>0.14</td> <td>0.13</td> <td></td> </tr> <tr> <td>-9.00</td> <td>0.16</td> <td>0.16</td> <td>0.14</td> <td></td> </tr> <tr> <td>-7.50</td> <td>0.18</td> <td>0.17</td> <td>0.16</td> <td></td> </tr> <tr> <td>-6.00</td> <td>0.19</td> <td>0.19</td> <td>0.17</td> <td></td> </tr> <tr> <td>-4.50</td> <td>0.21</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>-3.00</td> <td>0.22</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>-1.50</td> <td>0.23</td> <td>0.20</td> <td>0.18</td> <td></td> </tr> <tr> <td>0.00</td> <td>0.29</td> <td>0.25</td> <td>0.22</td> <td></td> </tr> </tbody> </table>	Output Voltage [V]	0.00	0.10	0.20	0.30	-15.00	0.05	0.05	0.05		-14.25	0.10	0.11	0.10		-13.50	0.11	0.12	0.11		-12.00	0.13	0.13	0.12		-10.50	0.14	0.14	0.13		-9.00	0.16	0.16	0.14		-7.50	0.18	0.17	0.16		-6.00	0.19	0.19	0.17		-4.50	0.21	0.20	0.18		-3.00	0.22	0.20	0.18		-1.50	0.23	0.20	0.18		0.00	0.29	0.25	0.22	
Output Voltage [V]	0.00	0.10	0.20	0.30																																																														
-15.00	0.05	0.05	0.05																																																															
-14.25	0.10	0.11	0.10																																																															
-13.50	0.11	0.12	0.11																																																															
-12.00	0.13	0.13	0.12																																																															
-10.50	0.14	0.14	0.13																																																															
-9.00	0.16	0.16	0.14																																																															
-7.50	0.18	0.17	0.16																																																															
-6.00	0.19	0.19	0.17																																																															
-4.50	0.21	0.20	0.18																																																															
-3.00	0.22	0.20	0.18																																																															
-1.50	0.23	0.20	0.18																																																															
0.00	0.29	0.25	0.22																																																															

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-15.00	0.05	0.05	0.05
-14.25	0.10	0.11	0.10
-13.50	0.11	0.12	0.11
-12.00	0.13	0.13	0.12
-10.50	0.14	0.14	0.13
-9.00	0.16	0.16	0.14
-7.50	0.18	0.17	0.16
-6.00	0.19	0.19	0.17
-4.50	0.21	0.20	0.18
-3.00	0.22	0.20	0.18
-1.50	0.23	0.20	0.18
0.00	0.29	0.25	0.22

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)