

TEST DATA OF SUW1R52415

Regulated DC Power Supply
Sep 27, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)



Model		SUW1R52415		Temperature 25°C																																																																								
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																								
Object		_____																																																																										
1.Graph		<p>—△— Load 100%</p> <p>- - □ - - Load 50%</p> <p>- - ○ - - Load 0%</p>		2.Values																																																																								
				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.030</td><td>0.192</td><td>0.170</td></tr> <tr><td>8.4</td><td>0.028</td><td>0.174</td><td>0.200</td></tr> <tr><td>12.0</td><td>0.019</td><td>0.091</td><td>0.168</td></tr> <tr><td>16.0</td><td>0.016</td><td>0.069</td><td>0.124</td></tr> <tr><td>18.0</td><td>0.015</td><td>0.062</td><td>0.110</td></tr> <tr><td>20.0</td><td>0.014</td><td>0.056</td><td>0.100</td></tr> <tr><td>24.0</td><td>0.013</td><td>0.048</td><td>0.085</td></tr> <tr><td>28.0</td><td>0.012</td><td>0.042</td><td>0.073</td></tr> <tr><td>32.0</td><td>0.011</td><td>0.037</td><td>0.065</td></tr> <tr><td>36.0</td><td>0.011</td><td>0.034</td><td>0.059</td></tr> <tr><td>40.0</td><td>0.012</td><td>0.032</td><td>0.054</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.030	0.192	0.170	8.4	0.028	0.174	0.200	12.0	0.019	0.091	0.168	16.0	0.016	0.069	0.124	18.0	0.015	0.062	0.110	20.0	0.014	0.056	0.100	24.0	0.013	0.048	0.085	28.0	0.012	0.042	0.073	32.0	0.011	0.037	0.065	36.0	0.011	0.034	0.059	40.0	0.012	0.032	0.054	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																											
	Load 0%	Load 50%	Load 100%																																																																									
0	0.000	0.000	0.000																																																																									
4.0	0.000	0.000	0.000																																																																									
8.0	0.030	0.192	0.170																																																																									
8.4	0.028	0.174	0.200																																																																									
12.0	0.019	0.091	0.168																																																																									
16.0	0.016	0.069	0.124																																																																									
18.0	0.015	0.062	0.110																																																																									
20.0	0.014	0.056	0.100																																																																									
24.0	0.013	0.048	0.085																																																																									
28.0	0.012	0.042	0.073																																																																									
32.0	0.011	0.037	0.065																																																																									
36.0	0.011	0.034	0.059																																																																									
40.0	0.012	0.032	0.054																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																												



Model		SUW1R52415		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 18V</p> <p>- - -□- - - Input Volt. 24V</p> <p>- - -○- - - Input Volt. 36V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.015</td><td>0.013</td><td>0.011</td></tr> <tr><td>20</td><td>0.034</td><td>0.027</td><td>0.021</td></tr> <tr><td>40</td><td>0.053</td><td>0.041</td><td>0.030</td></tr> <tr><td>60</td><td>0.072</td><td>0.055</td><td>0.040</td></tr> <tr><td>80</td><td>0.091</td><td>0.070</td><td>0.049</td></tr> <tr><td>100</td><td>0.110</td><td>0.084</td><td>0.059</td></tr> <tr><td>110</td><td>0.120</td><td>0.091</td><td>0.063</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.015	0.013	0.011	20	0.034	0.027	0.021	40	0.053	0.041	0.030	60	0.072	0.055	0.040	80	0.091	0.070	0.049	100	0.110	0.084	0.059	110	0.120	0.091	0.063	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Load Ration [%]	Input Current [A]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0	0.015	0.013	0.011																																																					
20	0.034	0.027	0.021																																																					
40	0.053	0.041	0.030																																																					
60	0.072	0.055	0.040																																																					
80	0.091	0.070	0.049																																																					
100	0.110	0.084	0.059																																																					
110	0.120	0.091	0.063																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					
-	-	-	-																																																					



Model		SUW1R52415		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 18V</p> <p>- - -□- - - Input Volt. 24V</p> <p>- - -○- - - Input Volt. 36V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.27</td><td>0.31</td><td>0.41</td></tr> <tr><td>20</td><td>0.61</td><td>0.65</td><td>0.75</td></tr> <tr><td>40</td><td>0.95</td><td>0.99</td><td>1.09</td></tr> <tr><td>60</td><td>1.29</td><td>1.33</td><td>1.42</td></tr> <tr><td>80</td><td>1.64</td><td>1.67</td><td>1.76</td></tr> <tr><td>100</td><td>1.99</td><td>2.01</td><td>2.10</td></tr> <tr><td>110</td><td>2.17</td><td>2.19</td><td>2.27</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ration [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.27	0.31	0.41	20	0.61	0.65	0.75	40	0.95	0.99	1.09	60	1.29	1.33	1.42	80	1.64	1.67	1.76	100	1.99	2.01	2.10	110	2.17	2.19	2.27	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0	0.27	0.31	0.41																																																					
20	0.61	0.65	0.75																																																					
40	0.95	0.99	1.09																																																					
60	1.29	1.33	1.42																																																					
80	1.64	1.67	1.76																																																					
100	1.99	2.01	2.10																																																					
110	2.17	2.19	2.27																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		SUW1R52415		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object		_____																																			
1. Graph			2. Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>69.1</td><td>76.8</td></tr> <tr><td>18</td><td>68.6</td><td>76.7</td></tr> <tr><td>20</td><td>67.8</td><td>76.6</td></tr> <tr><td>24</td><td>66.5</td><td>75.9</td></tr> <tr><td>30</td><td>64.1</td><td>74.5</td></tr> <tr><td>36</td><td>61.3</td><td>72.6</td></tr> <tr><td>40</td><td>58.9</td><td>71.0</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	69.1	76.8	18	68.6	76.7	20	67.8	76.6	24	66.5	75.9	30	64.1	74.5	36	61.3	72.6	40	58.9	71.0	—	—	—	—	—	—
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
16	69.1	76.8																																			
18	68.6	76.7																																			
20	67.8	76.6																																			
24	66.5	75.9																																			
30	64.1	74.5																																			
36	61.3	72.6																																			
40	58.9	71.0																																			
—	—	—																																			
—	—	—																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					




Model		SUW1R52415		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 18V - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>51.2</td> <td>48.3</td> <td>42.1</td> </tr> <tr> <td>40</td> <td>64.9</td> <td>62.6</td> <td>56.9</td> </tr> <tr> <td>60</td> <td>71.2</td> <td>69.4</td> <td>64.7</td> </tr> <tr> <td>80</td> <td>74.5</td> <td>73.4</td> <td>69.4</td> </tr> <tr> <td>100</td> <td>76.7</td> <td>75.9</td> <td>72.6</td> </tr> <tr> <td>110</td> <td>77.5</td> <td>76.7</td> <td>73.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	51.2	48.3	42.1	40	64.9	62.6	56.9	60	71.2	69.4	64.7	80	74.5	73.4	69.4	100	76.7	75.9	72.6	110	77.5	76.7	73.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0	-	-	-																																																					
20	51.2	48.3	42.1																																																					
40	64.9	62.6	56.9																																																					
60	71.2	69.4	64.7																																																					
80	74.5	73.4	69.4																																																					
100	76.7	75.9	72.6																																																					
110	77.5	76.7	73.8																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model	SUW1R52415
Item	Line Regulation
Object	+15V0.05A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	15.252	15.141
18	15.244	15.142
20	15.239	15.142
24	15.232	15.142
30	15.227	15.142
36	15.224	15.142
40	15.222	15.142
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-15.269	-15.161
18	-15.261	-15.160
20	-15.254	-15.159
24	-15.247	-15.159
30	-15.242	-15.158
36	-15.238	-15.157
40	-15.237	-15.158
-	-	-
-	-	-




Model		SUW1R52415		Temperature 25°C Testing Circuitry Figure A																																																				
Item		Load Regulation																																																						
Object		+15V0.05A																																																						
1.Graph		—△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.457</td><td>15.458</td><td>15.459</td></tr> <tr><td>0.008</td><td>15.327</td><td>15.315</td><td>15.305</td></tr> <tr><td>0.016</td><td>15.283</td><td>15.270</td><td>15.259</td></tr> <tr><td>0.024</td><td>15.247</td><td>15.235</td><td>15.226</td></tr> <tr><td>0.032</td><td>15.214</td><td>15.204</td><td>15.198</td></tr> <tr><td>0.040</td><td>15.182</td><td>15.176</td><td>15.171</td></tr> <tr><td>0.048</td><td>15.149</td><td>15.148</td><td>15.147</td></tr> <tr><td>0.050</td><td>15.141</td><td>15.141</td><td>15.141</td></tr> <tr><td>0.055</td><td>15.120</td><td>15.123</td><td>15.126</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	15.457	15.458	15.459	0.008	15.327	15.315	15.305	0.016	15.283	15.270	15.259	0.024	15.247	15.235	15.226	0.032	15.214	15.204	15.198	0.040	15.182	15.176	15.171	0.048	15.149	15.148	15.147	0.050	15.141	15.141	15.141	0.055	15.120	15.123	15.126	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.000	15.457	15.458	15.459																																																					
0.008	15.327	15.315	15.305																																																					
0.016	15.283	15.270	15.259																																																					
0.024	15.247	15.235	15.226																																																					
0.032	15.214	15.204	15.198																																																					
0.040	15.182	15.176	15.171																																																					
0.048	15.149	15.148	15.147																																																					
0.050	15.141	15.141	15.141																																																					
0.055	15.120	15.123	15.126																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Object		-15V0.05A		2.Values																																																				
1.Graph		—△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.482</td><td>-15.483</td><td>-15.483</td></tr> <tr><td>0.008</td><td>-15.343</td><td>-15.330</td><td>-15.320</td></tr> <tr><td>0.016</td><td>-15.298</td><td>-15.283</td><td>-15.273</td></tr> <tr><td>0.024</td><td>-15.262</td><td>-15.249</td><td>-15.240</td></tr> <tr><td>0.032</td><td>-15.230</td><td>-15.219</td><td>-15.212</td></tr> <tr><td>0.040</td><td>-15.198</td><td>-15.191</td><td>-15.186</td></tr> <tr><td>0.048</td><td>-15.166</td><td>-15.163</td><td>-15.161</td></tr> <tr><td>0.050</td><td>-15.159</td><td>-15.157</td><td>-15.156</td></tr> <tr><td>0.055</td><td>-15.138</td><td>-15.140</td><td>-15.141</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-15.482	-15.483	-15.483	0.008	-15.343	-15.330	-15.320	0.016	-15.298	-15.283	-15.273	0.024	-15.262	-15.249	-15.240	0.032	-15.230	-15.219	-15.212	0.040	-15.198	-15.191	-15.186	0.048	-15.166	-15.163	-15.161	0.050	-15.159	-15.157	-15.156	0.055	-15.138	-15.140	-15.141	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.000	-15.482	-15.483	-15.483																																																					
0.008	-15.343	-15.330	-15.320																																																					
0.016	-15.298	-15.283	-15.273																																																					
0.024	-15.262	-15.249	-15.240																																																					
0.032	-15.230	-15.219	-15.212																																																					
0.040	-15.198	-15.191	-15.186																																																					
0.048	-15.166	-15.163	-15.161																																																					
0.050	-15.159	-15.157	-15.156																																																					
0.055	-15.138	-15.140	-15.141																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model SUW1R52415		Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V0.05A	

Input Volt. 24 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.05A)

200mV/div




2ms/div




2ms/div

Min. Load (0A) ←→
Load 50% (0.025A)

200mV/div



2ms/div




2ms/div

Load 50% (0.025A) ←→
Load 100% (0.05A)

200mV/div



2ms/div



2ms/div



Model SUW1R52415		Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	-15V0.05A	

Input Volt. 24 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.05A)

200mV/div




2ms/div




2ms/div

Min. Load (0A) ←→
Load 50% (0.025A)

200mV/div




2ms/div




2ms/div

Load 50% (0.025A) ←→
Load 100% (0.05A)

200mV/div



2ms/div



2ms/div



Model SUW1R52415		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+15V0.05A																																							
1. Graph <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>- - -○- - - Input Volt. 36V</p> </div> <div style="text-align: center;"> </div> </div>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1</td><td>2</td></tr> <tr><td>20</td><td>1</td><td>2</td></tr> <tr><td>40</td><td>2</td><td>2</td></tr> <tr><td>60</td><td>2</td><td>2</td></tr> <tr><td>80</td><td>2</td><td>2</td></tr> <tr><td>100</td><td>3</td><td>2</td></tr> <tr><td>110</td><td>4</td><td>2</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	1	2	20	1	2	40	2	2	60	2	2	80	2	2	100	3	2	110	4	2	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	1	2																																						
20	1	2																																						
40	2	2																																						
60	2	2																																						
80	2	2																																						
100	3	2																																						
110	4	2																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p>																																								
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;">Ripple [mVp-p]</div> </div> <p>Fig. Complex Ripple Wave Form</p>																																								



Model		SUW1R52415		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		-15V0.05A																																									
<p>1. Graph</p> <p>—△— Input Volt. 18V - - -○- - - Input Volt. 36V</p> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p>				<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>3</td></tr> <tr><td>20</td><td>2</td><td>3</td></tr> <tr><td>40</td><td>2</td><td>3</td></tr> <tr><td>60</td><td>2</td><td>3</td></tr> <tr><td>80</td><td>2</td><td>3</td></tr> <tr><td>100</td><td>3</td><td>3</td></tr> <tr><td>110</td><td>3</td><td>3</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	2	3	20	2	3	40	2	3	60	2	3	80	2	3	100	3	3	110	3	3	-	-	-	-	-	-	-	-	-	--	-	-
Load Ration [%]	Ripple Voltage [mV]																																										
	Input Volt. 18 [V]	Input Volt. 36 [V]																																									
0	2	3																																									
20	2	3																																									
40	2	3																																									
60	2	3																																									
80	2	3																																									
100	3	3																																									
110	3	3																																									
-	-	-																																									
-	-	-																																									
-	-	-																																									
--	-	-																																									
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																											




Model SUW1R52415		Temperature 25°C Testing Circuitry Figure B																																						
Item	Ripple-Noise																																							
Object	+15V0.05A																																							
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 18V</p> <p>-·-○-·- Input Volt. 36V</p> </div> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>4</td></tr> <tr><td>20</td><td>5</td><td>4</td></tr> <tr><td>40</td><td>5</td><td>4</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>80</td><td>5</td><td>6</td></tr> <tr><td>100</td><td>5</td><td>6</td></tr> <tr><td>110</td><td>6</td><td>6</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0	5	4	20	5	4	40	5	4	60	5	5	80	5	6	100	5	6	110	6	6	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0	5	4																																						
20	5	4																																						
40	5	4																																						
60	5	5																																						
80	5	6																																						
100	5	6																																						
110	6	6																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						



Model	SUW1R52415
Item	Ripple-Noise
Object	-15V0.05A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	4	5
20	4	5
40	4	5
60	5	6
80	5	5
100	5	5
110	5	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.





Fig.Complex Ripple Noise Wave Form



Model	SUW1R52415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.05A

Testing Circuitry Figure B

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	4
-40	2	4
-20	2	4
0	2	3
25	2	2
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	3
-40	3	3
-20	3	3
0	2	2
25	2	2
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	15.073	15.075	15.075
-40	15.101	15.102	15.102
-20	15.121	15.122	15.122
0	15.133	15.134	15.133
25	15.140	15.141	15.140
55	15.139	15.138	15.138
60	15.137	15.136	15.136
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-15.092	-15.092	-15.091
-40	-15.120	-15.118	-15.118
-20	-15.138	-15.138	-15.138
0	-15.151	-15.150	-15.149
25	-15.158	-15.157	-15.156
55	-15.156	-15.155	-15.154
60	-15.154	-15.154	-15.153
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



COSEL		Testing Circuitry Figure A
Model	SUW1R52415	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.05A (AVR 2): 0 - 0.05A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	24	0	15.456	±178	±1.2
Minimum Voltage	-40	18	0.05	15.101		

Object		-15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	24	0	-15.480	±181	±1.2
Minimum Voltage	-40	36	0.05	-15.118		




COSEL																								
Model	SUW1R52415	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V0.05A																							
1.Graph  Input Volt. 24V Load 100%		2.Values <table border="1" data-bbox="933 492 1307 1030"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.141</td></tr> <tr><td>0.5</td><td>15.142</td></tr> <tr><td>1.0</td><td>15.142</td></tr> <tr><td>2.0</td><td>15.143</td></tr> <tr><td>3.0</td><td>15.143</td></tr> <tr><td>4.0</td><td>15.144</td></tr> <tr><td>5.0</td><td>15.143</td></tr> <tr><td>6.0</td><td>15.142</td></tr> <tr><td>7.0</td><td>15.141</td></tr> <tr><td>8.0</td><td>15.140</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.141	0.5	15.142	1.0	15.142	2.0	15.143	3.0	15.143	4.0	15.144	5.0	15.143	6.0	15.142	7.0	15.141	8.0	15.140
Time since start [H]	Output Voltage [V]																							
0.0	15.141																							
0.5	15.142																							
1.0	15.142																							
2.0	15.143																							
3.0	15.143																							
4.0	15.144																							
5.0	15.143																							
6.0	15.142																							
7.0	15.141																							
8.0	15.140																							
Object -15V0.05A 1.Graph  Input Volt. 24V Load 100%		2.Values <table border="1" data-bbox="933 1288 1307 1825"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.161</td></tr> <tr><td>0.5</td><td>-15.164</td></tr> <tr><td>1.0</td><td>-15.165</td></tr> <tr><td>2.0</td><td>-15.165</td></tr> <tr><td>3.0</td><td>-15.166</td></tr> <tr><td>4.0</td><td>-15.166</td></tr> <tr><td>5.0</td><td>-15.166</td></tr> <tr><td>6.0</td><td>-15.165</td></tr> <tr><td>7.0</td><td>-15.164</td></tr> <tr><td>8.0</td><td>-15.162</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-15.161	0.5	-15.164	1.0	-15.165	2.0	-15.165	3.0	-15.166	4.0	-15.166	5.0	-15.166	6.0	-15.165	7.0	-15.164	8.0	-15.162
Time since start [H]	Output Voltage [V]																							
0.0	-15.161																							
0.5	-15.164																							
1.0	-15.165																							
2.0	-15.165																							
3.0	-15.166																							
4.0	-15.166																							
5.0	-15.166																							
6.0	-15.165																							
7.0	-15.164																							
8.0	-15.162																							




Model	SUW1R52415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.05A		

1. Graph



2. Values


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.1	4.6	4.7	0.2	2.0
100 %	0.1	4.9	5.0	0.1	1.0






Model	SUW1R52415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.05A		

1. Graph



2. Values

		[mS]				
Load	Time	Td	Tr	Ts	Th	Tf
	50 %	0.1	4.6	4.7	0.2	2.0
	100 %	0.1	4.9	5.0	0.1	1.0






Model	SUW1R52415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.05A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	9.3	9.7
-40	9.0	9.8
-20	8.8	9.9
0	8.6	10.1
25	8.3	10.3
55	8.1	10.7
60	8.1	10.9
-	-	-
-	-	-
-	-	-
--	-	-

Object	-15V0.05A
--------	-----------

1.Graph



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	9.1	9.6
-40	8.9	9.7
-20	8.6	9.8
0	8.5	10.1
25	8.3	10.2
55	8.0	10.6
60	7.9	10.7
-	-	-
-	-	-
-	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUW1R52415
Item	Overcurrent Protection
Object	+15V0.05A


Temperature 25°C
Testing Circuitry Figure A



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
15.0	0.05	0.05	0.05
14.3	0.11	0.11	0.10
13.5	0.12	0.12	0.10
12.0	0.14	0.13	0.12
10.5	0.16	0.15	0.13
9.0	0.18	0.17	0.15
7.5	0.20	0.18	0.17
6.0	0.22	0.20	0.18
4.5	0.24	0.21	0.20
3.0	0.25	0.22	0.21
1.5	0.26	0.22	0.22
0.0	0.28	0.24	0.25

Object	-15V0.05A
--------	-----------



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-15.00	0.05	0.05	0.05
-14.25	0.11	0.11	0.10
-13.50	0.12	0.12	0.10
-12.00	0.14	0.13	0.12
-10.50	0.16	0.15	0.13
-9.00	0.18	0.17	0.15
-7.50	0.20	0.18	0.17
-6.00	0.22	0.20	0.18
-4.50	0.24	0.21	0.20
-3.00	0.25	0.22	0.21
-1.50	0.26	0.23	0.22
0.00	0.28	0.25	0.25

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)