



TEST DATA OF SUW32415

Regulated DC Power Supply
Mar 14, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo
Hayato Nakatsubo Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUW32415	Temperature	25°C																																																																																
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																																
Object	<hr/>																																																																																		
1.Graph	<p>Graph showing Input Current [A] vs Input Voltage [V] for SUW32415 at 25°C. The graph shows three curves: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.8</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>9.2</td><td>0.033</td><td>0.225</td><td>0.005</td></tr> <tr><td>12.0</td><td>0.027</td><td>0.169</td><td>0.320</td></tr> <tr><td>16.0</td><td>0.023</td><td>0.127</td><td>0.238</td></tr> <tr><td>18.0</td><td>0.021</td><td>0.114</td><td>0.215</td></tr> <tr><td>20.0</td><td>0.020</td><td>0.103</td><td>0.190</td></tr> <tr><td>24.0</td><td>0.018</td><td>0.087</td><td>0.158</td></tr> <tr><td>28.0</td><td>0.016</td><td>0.076</td><td>0.137</td></tr> <tr><td>32.0</td><td>0.015</td><td>0.067</td><td>0.120</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.061</td><td>0.108</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.057</td><td>0.099</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	8.8	0.000	0.000	0.000	9.2	0.033	0.225	0.005	12.0	0.027	0.169	0.320	16.0	0.023	0.127	0.238	18.0	0.021	0.114	0.215	20.0	0.020	0.103	0.190	24.0	0.018	0.087	0.158	28.0	0.016	0.076	0.137	32.0	0.015	0.067	0.120	36.0	0.015	0.061	0.108	40.0	0.015	0.057	0.099	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
8.8	0.000	0.000	0.000																																																																																
9.2	0.033	0.225	0.005																																																																																
12.0	0.027	0.169	0.320																																																																																
16.0	0.023	0.127	0.238																																																																																
18.0	0.021	0.114	0.215																																																																																
20.0	0.020	0.103	0.190																																																																																
24.0	0.018	0.087	0.158																																																																																
28.0	0.016	0.076	0.137																																																																																
32.0	0.015	0.067	0.120																																																																																
36.0	0.015	0.061	0.108																																																																																
40.0	0.015	0.057	0.099																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.8</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>9.2</td><td>0.033</td><td>0.225</td><td>0.005</td></tr> <tr><td>12.0</td><td>0.027</td><td>0.169</td><td>0.320</td></tr> <tr><td>16.0</td><td>0.023</td><td>0.127</td><td>0.238</td></tr> <tr><td>18.0</td><td>0.021</td><td>0.114</td><td>0.215</td></tr> <tr><td>20.0</td><td>0.020</td><td>0.103</td><td>0.190</td></tr> <tr><td>24.0</td><td>0.018</td><td>0.087</td><td>0.158</td></tr> <tr><td>28.0</td><td>0.016</td><td>0.076</td><td>0.137</td></tr> <tr><td>32.0</td><td>0.015</td><td>0.067</td><td>0.120</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.061</td><td>0.108</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.057</td><td>0.099</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	8.8	0.000	0.000	0.000	9.2	0.033	0.225	0.005	12.0	0.027	0.169	0.320	16.0	0.023	0.127	0.238	18.0	0.021	0.114	0.215	20.0	0.020	0.103	0.190	24.0	0.018	0.087	0.158	28.0	0.016	0.076	0.137	32.0	0.015	0.067	0.120	36.0	0.015	0.061	0.108	40.0	0.015	0.057	0.099	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
8.8	0.000	0.000	0.000																																																																																
9.2	0.033	0.225	0.005																																																																																
12.0	0.027	0.169	0.320																																																																																
16.0	0.023	0.127	0.238																																																																																
18.0	0.021	0.114	0.215																																																																																
20.0	0.020	0.103	0.190																																																																																
24.0	0.018	0.087	0.158																																																																																
28.0	0.016	0.076	0.137																																																																																
32.0	0.015	0.067	0.120																																																																																
36.0	0.015	0.061	0.108																																																																																
40.0	0.015	0.057	0.099																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUW32415																																																	
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																
Object	—	—																																																
1.Graph																																																		
—△— Input Volt. 18V - -□--- Input Volt. 24V - -○--- Input Volt. 36V		2.Values																																																
<table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V] [A]</th> <th>24[V] [A]</th> <th>36[V] [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.021</td><td>0.018</td><td>0.015</td></tr> <tr><td>20</td><td>0.059</td><td>0.046</td><td>0.034</td></tr> <tr><td>40</td><td>0.096</td><td>0.074</td><td>0.053</td></tr> <tr><td>60</td><td>0.134</td><td>0.102</td><td>0.071</td></tr> <tr><td>80</td><td>0.173</td><td>0.130</td><td>0.090</td></tr> <tr><td>100</td><td>0.212</td><td>0.159</td><td>0.109</td></tr> <tr><td>110</td><td>0.231</td><td>0.173</td><td>0.118</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	18[V] [A]	24[V] [A]	36[V] [A]	0	0.021	0.018	0.015	20	0.059	0.046	0.034	40	0.096	0.074	0.053	60	0.134	0.102	0.071	80	0.173	0.130	0.090	100	0.212	0.159	0.109	110	0.231	0.173	0.118	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	18[V] [A]	24[V] [A]	36[V] [A]																																															
0	0.021	0.018	0.015																																															
20	0.059	0.046	0.034																																															
40	0.096	0.074	0.053																																															
60	0.134	0.102	0.071																																															
80	0.173	0.130	0.090																																															
100	0.212	0.159	0.109																																															
110	0.231	0.173	0.118																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															

COSEL

Model	SUW32415
Item	Input Power (by Load Current)
Object	_____

1.Graph

Legend:

- ▲ — Input Volt. 18V
- - □ - - Input Volt. 24V
- - ○ - - Input Volt. 36V

Load Ration [%]	18[V]	24[V]	36[V]
0	0.38	0.43	0.54
20	1.05	1.10	1.22
40	1.73	1.77	1.89
60	2.41	2.44	2.56
80	3.09	3.12	3.23
100	3.79	3.81	3.90
110	4.15	4.15	4.24
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ration [%]	Input Power [W]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	0.38	0.43	0.54
20	1.05	1.10	1.22
40	1.73	1.77	1.89
60	2.41	2.44	2.56
80	3.09	3.12	3.23
100	3.79	3.81	3.90
110	4.15	4.15	4.24
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SUW32415	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1. Graph																																			
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (10 to 50). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency decreasing as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% [%]</th> <th>Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>73.6</td><td>79.3</td></tr> <tr><td>18</td><td>73.2</td><td>79.5</td></tr> <tr><td>20</td><td>72.9</td><td>79.6</td></tr> <tr><td>24</td><td>71.9</td><td>79.3</td></tr> <tr><td>30</td><td>70.3</td><td>78.6</td></tr> <tr><td>36</td><td>68.0</td><td>77.3</td></tr> <tr><td>40</td><td>66.1</td><td>76.1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Load 50% [%]	Load 100% [%]	16	73.6	79.3	18	73.2	79.5	20	72.9	79.6	24	71.9	79.3	30	70.3	78.6	36	68.0	77.3	40	66.1	76.1	--	-	-	--	-	-		
Input Voltage [V]	Load 50% [%]	Load 100% [%]																																	
16	73.6	79.3																																	
18	73.2	79.5																																	
20	72.9	79.6																																	
24	71.9	79.3																																	
30	70.3	78.6																																	
36	68.0	77.3																																	
40	66.1	76.1																																	
--	-	-																																	
--	-	-																																	
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>73.6</td><td>79.3</td></tr> <tr><td>18</td><td>73.2</td><td>79.5</td></tr> <tr><td>20</td><td>72.9</td><td>79.6</td></tr> <tr><td>24</td><td>71.9</td><td>79.3</td></tr> <tr><td>30</td><td>70.3</td><td>78.6</td></tr> <tr><td>36</td><td>68.0</td><td>77.3</td></tr> <tr><td>40</td><td>66.1</td><td>76.1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	73.6	79.3	18	73.2	79.5	20	72.9	79.6	24	71.9	79.3	30	70.3	78.6	36	68.0	77.3	40	66.1	76.1	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
16	73.6	79.3																																	
18	73.2	79.5																																	
20	72.9	79.6																																	
24	71.9	79.3																																	
30	70.3	78.6																																	
36	68.0	77.3																																	
40	66.1	76.1																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	SUW32415	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V] (%)</th> <th>24[V] (%)</th> <th>36[V] (%)</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>55</td> <td>54</td> <td>49</td> </tr> <tr> <td>40</td> <td>68</td> <td>65</td> <td>62</td> </tr> <tr> <td>60</td> <td>75</td> <td>72</td> <td>68</td> </tr> <tr> <td>80</td> <td>78</td> <td>76</td> <td>72</td> </tr> <tr> <td>100</td> <td>79</td> <td>78</td> <td>75</td> </tr> <tr> <td>120</td> <td>80</td> <td>79</td> <td>76</td> </tr> </tbody> </table>			Load Ration [%]	18[V] (%)	24[V] (%)	36[V] (%)	20	55	54	49	40	68	65	62	60	75	72	68	80	78	76	72	100	79	78	75	120	80	79	76																							
Load Ration [%]	18[V] (%)	24[V] (%)	36[V] (%)																																																			
20	55	54	49																																																			
40	68	65	62																																																			
60	75	72	68																																																			
80	78	76	72																																																			
100	79	78	75																																																			
120	80	79	76																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>58.1</td> <td>55.7</td> <td>50.3</td> </tr> <tr> <td>40</td> <td>70.4</td> <td>68.6</td> <td>64.4</td> </tr> <tr> <td>60</td> <td>75.4</td> <td>74.3</td> <td>70.9</td> </tr> <tr> <td>80</td> <td>78.1</td> <td>77.5</td> <td>74.8</td> </tr> <tr> <td>100</td> <td>79.5</td> <td>79.2</td> <td>77.3</td> </tr> <tr> <td>110</td> <td>80.0</td> <td>80.0</td> <td>78.2</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			18[V]	24[V]	36[V]	0	-	-	-	20	58.1	55.7	50.3	40	70.4	68.6	64.4	60	75.4	74.3	70.9	80	78.1	77.5	74.8	100	79.5	79.2	77.3	110	80.0	80.0	78.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	18[V]	24[V]	36[V]																																																			
0	-	-	-																																																			
20	58.1	55.7	50.3																																																			
40	70.4	68.6	64.4																																																			
60	75.4	74.3	70.9																																																			
80	78.1	77.5	74.8																																																			
100	79.5	79.2	77.3																																																			
110	80.0	80.0	78.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	SUW32415
-------	----------

Item	Line Regulation
------	-----------------

Object	+15V0.1A
--------	----------

1.Graph

---□--- Load 50%
 —△— Load 100%



Temperature 25°C
Testing Circuitry Figure A


2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	15.087	15.013
18	15.084	15.014
20	15.081	15.014
24	15.077	15.014
30	15.074	15.014
36	15.073	15.014
40	15.072	15.014
--	-	-
--	-	-

Object	-15V0.1A
--------	----------

1.Graph

---□--- Load 50%
 —△— Load 100%




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-15.093	-15.020
18	-15.089	-15.019
20	-15.087	-15.019
24	-15.082	-15.019
30	-15.079	-15.018
36	-15.079	-15.019
40	-15.076	-15.019
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	SUW32415
Item	Load Regulation
Object	+15V0.1A



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.00	15.246	15.237	15.227
0.02	15.145	15.137	15.131
0.04	15.101	15.093	15.088
0.06	15.067	15.062	15.059
0.08	15.039	15.036	15.034
0.10	15.012	15.013	15.012
0.11	15.000	15.001	15.003
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-





2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.00	-15.259	-15.248	-15.237
0.02	-15.150	-15.142	-15.135
0.04	-15.106	-15.098	-15.094
0.06	-15.073	-15.067	-15.064
0.08	-15.044	-15.040	-15.039
0.10	-15.019	-15.017	-15.018
0.11	-15.006	-15.007	-15.008
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




COSEL

COSEL

Model	SUW32415
Item	Ripple Voltage (by Load Current)
Object	+15V0.1A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	1	1
0.02	1	1
0.04	1	1
0.06	2	1
0.08	4	1
0.10	6	1
0.11	7	2
--	-	-
--	-	-
--	-	-
--	-	-


COSEL

Model	SUW32415																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.1A																																							
1.Graph																																								
<p>—△— Input Volt. 18V -○- Input Volt. 36V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1</td><td>1</td></tr> <tr><td>0.02</td><td>1</td><td>1</td></tr> <tr><td>0.04</td><td>1</td><td>1</td></tr> <tr><td>0.06</td><td>2</td><td>1</td></tr> <tr><td>0.08</td><td>3</td><td>1</td></tr> <tr><td>0.10</td><td>5</td><td>1</td></tr> <tr><td>0.11</td><td>6</td><td>1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	1	1	0.02	1	1	0.04	1	1	0.06	2	1	0.08	3	1	0.10	5	1	0.11	6	1	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.00	1	1																																						
0.02	1	1																																						
0.04	1	1																																						
0.06	2	1																																						
0.08	3	1																																						
0.10	5	1																																						
0.11	6	1																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

COSEL

Model	SUW32415
Item	Ripple-Noise
Object	+15V0.1A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2.Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	3	4
0.02	4	4
0.04	4	4
0.06	3	4
0.08	4	4
0.10	9	4
0.11	11	4
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	SUW32415
Item	Ripple-Noise
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B


1.Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	11	13
0.02	12	14
0.04	14	15
0.06	14	16
0.08	14	16
0.10	14	16
0.11	13	16
--	-	-
--	-	-
--	-	-
--	-	-




COSEL

Model	SUW32415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.1A

1.Graph

---□--- Load 50%
—△— Load 100%




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	15
-40	3	11
-20	3	9
0	3	7
25	2	4
55	2	2
60	2	2
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	11
-40	3	10
-20	3	8
0	3	7
25	2	4
55	2	3
60	2	3
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	SUW32415
Item	Ambient Temperature Drift
Object	+15V0.1A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	14.923	14.925	14.926
-40	14.957	14.958	14.958
-20	14.982	14.983	14.983
0	15.001	15.001	15.001
25	15.014	15.014	15.014
55	15.018	15.018	15.017
60	15.018	15.017	15.017
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-14.929	-14.930	-14.932
-40	-14.962	-14.962	-14.963
-20	-14.986	-14.987	-14.988
0	-15.004	-15.005	-15.005
25	-15.018	-15.017	-15.018
55	-15.021	-15.020	-15.020
60	-15.020	-15.019	-15.019
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUW32415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.1A			Output		Output Voltage Accuracy	
	Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage		55	18	0	15.258	±151	±1.0
Minimum Voltage		-40	18	0.1	14.957		

Object	-15V0.1A			Output		Output Voltage Accuracy	
	Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage		55	18	0	-15.266	±152	±1.0
Minimum Voltage		-40	18	0.1	-14.962		

COSEL

Model	SUW32415	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.1A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>15.012</td></tr> <tr><td>0.5</td><td>15.015</td></tr> <tr><td>1.0</td><td>15.015</td></tr> <tr><td>2.0</td><td>15.015</td></tr> <tr><td>3.0</td><td>15.015</td></tr> <tr><td>4.0</td><td>15.015</td></tr> <tr><td>5.0</td><td>15.015</td></tr> <tr><td>6.0</td><td>15.015</td></tr> <tr><td>7.0</td><td>15.015</td></tr> <tr><td>8.0</td><td>15.015</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	15.012	0.5	15.015	1.0	15.015	2.0	15.015	3.0	15.015	4.0	15.015	5.0	15.015	6.0	15.015	7.0	15.015	8.0	15.015
Time since start [H]	Output Voltage [V]																								
0.0	15.012																								
0.5	15.015																								
1.0	15.015																								
2.0	15.015																								
3.0	15.015																								
4.0	15.015																								
5.0	15.015																								
6.0	15.015																								
7.0	15.015																								
8.0	15.015																								
Object -15V0.1A		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-15.017</td></tr> <tr><td>0.5</td><td>-15.018</td></tr> <tr><td>1.0</td><td>-15.018</td></tr> <tr><td>2.0</td><td>-15.018</td></tr> <tr><td>3.0</td><td>-15.018</td></tr> <tr><td>4.0</td><td>-15.018</td></tr> <tr><td>5.0</td><td>-15.018</td></tr> <tr><td>6.0</td><td>-15.018</td></tr> <tr><td>7.0</td><td>-15.018</td></tr> <tr><td>8.0</td><td>-15.018</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-15.017	0.5	-15.018	1.0	-15.018	2.0	-15.018	3.0	-15.018	4.0	-15.018	5.0	-15.018	6.0	-15.018	7.0	-15.018	8.0	-15.018
Time since start [H]	Output Voltage [V]																								
0.0	-15.017																								
0.5	-15.018																								
1.0	-15.018																								
2.0	-15.018																								
3.0	-15.018																								
4.0	-15.018																								
5.0	-15.018																								
6.0	-15.018																								
7.0	-15.018																								
8.0	-15.018																								

COSEL


Model SUW32415

Item Rise and Fall Time

Object +15V0.1A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[mS]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.0	3.1	0.1	1.5
100 %		0.1	3.2	3.3	0.1	0.7



COSEL


Model	SUW32415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.1A		

1.Graph



2.Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	3.1	3.2	0.1	2.1	
100 %		0.1	3.2	3.3	0.1	1.0	




COSEL

Model	SUW32415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.1A

Testing Circuitry Figure A

1.Graph

---□--- Load 50%
—△— Load 100%




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.9	9.8
-40	6.9	9.8
-20	6.9	9.8
0	6.9	10.0
25	6.8	10.0
55	6.9	10.0
60	6.9	10.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.1A
--------	----------

1.Graph

---□--- Load 50%
—△— Load 100%




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	6.8	9.8
-40	6.8	9.8
-20	6.8	9.8
0	6.8	9.8
25	6.8	9.9
55	6.8	9.9
60	6.8	9.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model	SUW32415
Item	Overcurrent Protection
Object	+15V0.1A



Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	18[V]	24[V]	36[V]
15.0	0.10	0.10	0.10
14.3	0.27	0.27	0.27
13.5	0.29	0.28	0.28
12.0	0.32	0.32	0.31
10.5	0.36	0.35	0.34
9.0	0.40	0.38	0.37
7.5	0.43	0.41	0.39
6.0	0.47	0.44	0.42
4.5	0.50	0.46	0.43
3.0	0.52	0.46	0.44
1.5	0.50	0.44	0.43
0.0	0.50	0.44	0.47



2.Values

Output Voltage [V]	Load Current [A]		
	18[V]	24[V]	36[V]
-15.0	0.10	0.10	0.10
-14.3	0.27	0.27	0.27
-13.5	0.28	0.28	0.28
-12.0	0.32	0.32	0.31
-10.5	0.36	0.35	0.34
-9.0	0.39	0.38	0.37
-7.5	0.43	0.41	0.39
-6.0	0.47	0.44	0.41
-4.5	0.50	0.46	0.43
-3.0	0.52	0.46	0.44
-1.5	0.50	0.44	0.43
0.0	0.49	0.44	0.47

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)