

TEST DATA OF SUW60515 SUCW60515

Regulated DC Power Supply
Feb 24, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshikazu Mizuno
Yoshikazu Mizuno Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Figure of Testing Circuitry	22

(Final Page 22)



Model		SUW60515/SUCW60515		Temperature	25°C																																																																							
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																							
Object																																																																												
1.Graph			2.Values																																																																									
<p>—△— Load 100% - - □ - - Load 50% - - ○ - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.001</td><td>0.003</td><td>0.001</td></tr> <tr><td>2.00</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>3.00</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>3.83</td><td>0.138</td><td>0.352</td><td>0.966</td></tr> <tr><td>4.00</td><td>0.133</td><td>0.630</td><td>1.277</td></tr> <tr><td>4.16</td><td>0.130</td><td>0.772</td><td>1.837</td></tr> <tr><td>4.33</td><td>0.126</td><td>0.898</td><td>1.788</td></tr> <tr><td>4.50</td><td>0.122</td><td>0.855</td><td>1.684</td></tr> <tr><td>5.00</td><td>0.115</td><td>0.782</td><td>1.479</td></tr> <tr><td>6.00</td><td>0.102</td><td>0.646</td><td>1.232</td></tr> <tr><td>7.00</td><td>0.095</td><td>0.557</td><td>1.043</td></tr> <tr><td>8.00</td><td>0.090</td><td>0.493</td><td>0.915</td></tr> <tr><td>9.00</td><td>0.088</td><td>0.447</td><td>0.816</td></tr> <tr><td>10.00</td><td>0.088</td><td>0.410</td><td>0.740</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.001	0.003	0.001	2.00	0.002	0.002	0.002	3.00	0.003	0.003	0.003	3.83	0.138	0.352	0.966	4.00	0.133	0.630	1.277	4.16	0.130	0.772	1.837	4.33	0.126	0.898	1.788	4.50	0.122	0.855	1.684	5.00	0.115	0.782	1.479	6.00	0.102	0.646	1.232	7.00	0.095	0.557	1.043	8.00	0.090	0.493	0.915	9.00	0.088	0.447	0.816	10.00	0.088	0.410	0.740	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																											
	Load 0%	Load 50%	Load 100%																																																																									
0.00	0.000	0.000	0.000																																																																									
1.70	0.001	0.003	0.001																																																																									
2.00	0.002	0.002	0.002																																																																									
3.00	0.003	0.003	0.003																																																																									
3.83	0.138	0.352	0.966																																																																									
4.00	0.133	0.630	1.277																																																																									
4.16	0.130	0.772	1.837																																																																									
4.33	0.126	0.898	1.788																																																																									
4.50	0.122	0.855	1.684																																																																									
5.00	0.115	0.782	1.479																																																																									
6.00	0.102	0.646	1.232																																																																									
7.00	0.095	0.557	1.043																																																																									
8.00	0.090	0.493	0.915																																																																									
9.00	0.088	0.447	0.816																																																																									
10.00	0.088	0.410	0.740																																																																									
--	-	-	-																																																																									
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																												



Model		SUW60515/SUCW60515		Temperature 25°C Testing Circuitry Figure A																																																			
Item		Input Current (by Load Current)																																																					
Object		_____																																																					
1.Graph <div style="float: right; margin-left: 20px;"> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - - - ○ - - - Input Volt. 9V </div>			2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.121</td><td>0.112</td><td>0.088</td></tr> <tr><td>20</td><td>0.416</td><td>0.372</td><td>0.234</td></tr> <tr><td>40</td><td>0.709</td><td>0.639</td><td>0.379</td></tr> <tr><td>60</td><td>1.030</td><td>0.925</td><td>0.520</td></tr> <tr><td>80</td><td>1.338</td><td>1.216</td><td>0.668</td></tr> <tr><td>100</td><td>1.701</td><td>1.493</td><td>0.818</td></tr> <tr><td>110</td><td>1.892</td><td>1.655</td><td>0.894</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.121	0.112	0.088	20	0.416	0.372	0.234	40	0.709	0.639	0.379	60	1.030	0.925	0.520	80	1.338	1.216	0.668	100	1.701	1.493	0.818	110	1.892	1.655	0.894	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																				
0	0.121	0.112	0.088																																																				
20	0.416	0.372	0.234																																																				
40	0.709	0.639	0.379																																																				
60	1.030	0.925	0.520																																																				
80	1.338	1.216	0.668																																																				
100	1.701	1.493	0.818																																																				
110	1.892	1.655	0.894																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				



Model		SUW60515/SUCW60515		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			—△— Input Volt. 4.5V	2.Values																																																				
			- - -□- - - Input Volt. 5V																																																					
			- · - ○ - · - Input Volt. 9V																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.54</td><td>0.57</td><td>0.79</td></tr> <tr><td>20</td><td>1.84</td><td>1.86</td><td>2.09</td></tr> <tr><td>40</td><td>3.18</td><td>3.18</td><td>3.37</td></tr> <tr><td>60</td><td>4.57</td><td>4.54</td><td>4.68</td></tr> <tr><td>80</td><td>6.01</td><td>5.97</td><td>5.98</td></tr> <tr><td>100</td><td>7.55</td><td>7.42</td><td>7.30</td></tr> <tr><td>110</td><td>8.34</td><td>8.18</td><td>7.97</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.54	0.57	0.79	20	1.84	1.86	2.09	40	3.18	3.18	3.37	60	4.57	4.54	4.68	80	6.01	5.97	5.98	100	7.55	7.42	7.30	110	8.34	8.18	7.97	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.54	0.57	0.79																																																					
20	1.84	1.86	2.09																																																					
40	3.18	3.18	3.37																																																					
60	4.57	4.54	4.68																																																					
80	6.01	5.97	5.98																																																					
100	7.55	7.42	7.30																																																					
110	8.34	8.18	7.97																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		SUW60515/SUCW60515		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object		_____																																			
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>77.7</td><td>78.4</td></tr> <tr><td>4.5</td><td>78.4</td><td>80.1</td></tr> <tr><td>5.0</td><td>78.6</td><td>81.2</td></tr> <tr><td>6.0</td><td>78.3</td><td>82.6</td></tr> <tr><td>7.0</td><td>77.7</td><td>83.3</td></tr> <tr><td>8.0</td><td>76.4</td><td>83.1</td></tr> <tr><td>9.0</td><td>75.0</td><td>82.7</td></tr> <tr><td>9.5</td><td>74.2</td><td>82.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	77.7	78.4	4.5	78.4	80.1	5.0	78.6	81.2	6.0	78.3	82.6	7.0	77.7	83.3	8.0	76.4	83.1	9.0	75.0	82.7	9.5	74.2	82.3	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
4.0	77.7	78.4																																			
4.5	78.4	80.1																																			
5.0	78.6	81.2																																			
6.0	78.3	82.6																																			
7.0	77.7	83.3																																			
8.0	76.4	83.1																																			
9.0	75.0	82.7																																			
9.5	74.2	82.3																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model SUW60515/SUCW60515		Temperature 25°C Testing Circuitry Figure A																																																		
Item Efficiency (by Load Current)																																																				
Object _____																																																				
1.Graph <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div style="width: 60%;"> </div> <div style="width: 35%;"> <p>—△— Input Volt. 4.5V</p> <p>- - -□- - - Input Volt. 5V</p> <p>...○... Input Volt. 9V</p> </div> </div>																																																				
2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>65.9</td><td>65.1</td><td>58.0</td></tr> <tr><td>40</td><td>76.1</td><td>76.1</td><td>71.7</td></tr> <tr><td>60</td><td>79.2</td><td>79.8</td><td>77.5</td></tr> <tr><td>80</td><td>80.4</td><td>80.9</td><td>80.7</td></tr> <tr><td>100</td><td>79.9</td><td>81.3</td><td>82.6</td></tr> <tr><td>110</td><td>79.5</td><td>81.2</td><td>83.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	65.9	65.1	58.0	40	76.1	76.1	71.7	60	79.2	79.8	77.5	80	80.4	80.9	80.7	100	79.9	81.3	82.6	110	79.5	81.2	83.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																			
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																	
0	-	-	-																																																	
20	65.9	65.1	58.0																																																	
40	76.1	76.1	71.7																																																	
60	79.2	79.8	77.5																																																	
80	80.4	80.9	80.7																																																	
100	79.9	81.3	82.6																																																	
110	79.5	81.2	83.3																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	



<p>Model SUW60512/SUCW60512</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Line Regulation</p>																																		
<p>Object +12V0.25A</p>																																		
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.178</td><td>12.116</td></tr> <tr><td>4.5</td><td>12.178</td><td>12.116</td></tr> <tr><td>5.0</td><td>12.176</td><td>12.116</td></tr> <tr><td>6.0</td><td>12.173</td><td>12.117</td></tr> <tr><td>7.0</td><td>12.171</td><td>12.117</td></tr> <tr><td>8.0</td><td>12.171</td><td>12.117</td></tr> <tr><td>9.0</td><td>12.168</td><td>12.116</td></tr> <tr><td>9.5</td><td>12.168</td><td>12.116</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	12.178	12.116	4.5	12.178	12.116	5.0	12.176	12.116	6.0	12.173	12.117	7.0	12.171	12.117	8.0	12.171	12.117	9.0	12.168	12.116	9.5	12.168	12.116	-	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	12.178	12.116																																
4.5	12.178	12.116																																
5.0	12.176	12.116																																
6.0	12.173	12.117																																
7.0	12.171	12.117																																
8.0	12.171	12.117																																
9.0	12.168	12.116																																
9.5	12.168	12.116																																
-	-	-																																
<p>Object -12V0.25A</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>																																		
<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.179</td><td>-12.117</td></tr> <tr><td>4.5</td><td>-12.179</td><td>-12.117</td></tr> <tr><td>5.0</td><td>-12.179</td><td>-12.117</td></tr> <tr><td>6.0</td><td>-12.176</td><td>-12.117</td></tr> <tr><td>7.0</td><td>-12.174</td><td>-12.118</td></tr> <tr><td>8.0</td><td>-12.172</td><td>-12.117</td></tr> <tr><td>9.0</td><td>-12.172</td><td>-12.117</td></tr> <tr><td>9.5</td><td>-12.172</td><td>-12.118</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-12.179	-12.117	4.5	-12.179	-12.117	5.0	-12.179	-12.117	6.0	-12.176	-12.117	7.0	-12.174	-12.118	8.0	-12.172	-12.117	9.0	-12.172	-12.117	9.5	-12.172	-12.118	-	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	-12.179	-12.117																																
4.5	-12.179	-12.117																																
5.0	-12.179	-12.117																																
6.0	-12.176	-12.117																																
7.0	-12.174	-12.118																																
8.0	-12.172	-12.117																																
9.0	-12.172	-12.117																																
9.5	-12.172	-12.118																																
-	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		




<p>Model SUW60515/SUCW60515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																				
<p>Item Load Regulation</p>																																																						
<p>Object +15V0.2A</p>																																																						
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - Input Volt. 9V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.275</td><td>15.275</td><td>15.247</td></tr> <tr><td>0.04</td><td>15.164</td><td>15.161</td><td>15.151</td></tr> <tr><td>0.08</td><td>15.125</td><td>15.122</td><td>15.115</td></tr> <tr><td>0.12</td><td>15.098</td><td>15.096</td><td>15.091</td></tr> <tr><td>0.16</td><td>15.074</td><td>15.073</td><td>15.071</td></tr> <tr><td>0.20</td><td>15.053</td><td>15.053</td><td>15.054</td></tr> <tr><td>0.22</td><td>15.041</td><td>15.043</td><td>15.046</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	15.275	15.275	15.247	0.04	15.164	15.161	15.151	0.08	15.125	15.122	15.115	0.12	15.098	15.096	15.091	0.16	15.074	15.073	15.071	0.20	15.053	15.053	15.054	0.22	15.041	15.043	15.046	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	15.275	15.275	15.247																																																			
0.04	15.164	15.161	15.151																																																			
0.08	15.125	15.122	15.115																																																			
0.12	15.098	15.096	15.091																																																			
0.16	15.074	15.073	15.071																																																			
0.20	15.053	15.053	15.054																																																			
0.22	15.041	15.043	15.046																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Object -15V0.2A</p>																																																						
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - Input Volt. 9V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.291</td><td>-15.287</td><td>-15.260</td></tr> <tr><td>0.04</td><td>-15.163</td><td>-15.160</td><td>-15.153</td></tr> <tr><td>0.08</td><td>-15.119</td><td>-15.117</td><td>-15.111</td></tr> <tr><td>0.12</td><td>-15.093</td><td>-15.090</td><td>-15.083</td></tr> <tr><td>0.16</td><td>-15.069</td><td>-15.068</td><td>-15.063</td></tr> <tr><td>0.20</td><td>-15.047</td><td>-15.047</td><td>-15.045</td></tr> <tr><td>0.22</td><td>-15.037</td><td>-15.037</td><td>-15.037</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	-15.291	-15.287	-15.260	0.04	-15.163	-15.160	-15.153	0.08	-15.119	-15.117	-15.111	0.12	-15.093	-15.090	-15.083	0.16	-15.069	-15.068	-15.063	0.20	-15.047	-15.047	-15.045	0.22	-15.037	-15.037	-15.037	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	-15.291	-15.287	-15.260																																																			
0.04	-15.163	-15.160	-15.153																																																			
0.08	-15.119	-15.117	-15.111																																																			
0.12	-15.093	-15.090	-15.083																																																			
0.16	-15.069	-15.068	-15.063																																																			
0.20	-15.047	-15.047	-15.045																																																			
0.22	-15.037	-15.037	-15.037																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						





Model SUW60515/SUCW60515		Temperature 25°C Testing Circuitry Figure A
Item Dynamic Load Response		
Object +15V0.2A		



Input Volt. 5 V
Cycle 100 mS





Min. Load (0A) \longleftrightarrow
Load 100% (0.2A)



Min. Load (0A) \longleftrightarrow
Load 50% (0.1A)




Load 50% (0.1A) \longleftrightarrow
Load 100% (0.2A)






Model	SUW60515/SUCW60515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V0.2A		

Input Volt. 5 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.2A)

200mV/div




2ms/div




2ms/div

Min. Load (0A) ←→
Load 50% (0.1A)

200mV/div




2ms/div




2ms/div

Load 50% (0.1A) ←→
Load 100% (0.2A)

200mV/div



2ms/div



2ms/div



Model		SUW60515/SUCW60515																																							
Item		Ripple Voltage (by Load Current)																																							
Object		+15V0.2A																																							
		Temperature	25°C																																						
		Testing Circuitry	Figure B																																						
<p>1.Graph</p> <div style="text-align: center;"> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.04</td><td>2</td><td>2</td></tr> <tr><td>0.08</td><td>2</td><td>2</td></tr> <tr><td>0.12</td><td>2</td><td>3</td></tr> <tr><td>0.16</td><td>3</td><td>4</td></tr> <tr><td>0.20</td><td>6</td><td>4</td></tr> <tr><td>0.22</td><td>8</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	2	2	0.04	2	2	0.08	2	2	0.12	2	3	0.16	3	4	0.20	6	4	0.22	8	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																							
0.00	2	2																																							
0.04	2	2																																							
0.08	2	2																																							
0.12	2	3																																							
0.16	3	4																																							
0.20	6	4																																							
0.22	8	4																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p> <div style="text-align: center;"> </div> <p>Fig.Complex Ripple Wave Form</p>																																									



COSEL																																									
Model	SUW60515/SUCW60515	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	-15V0.2A																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.04</td><td>2</td><td>2</td></tr> <tr><td>0.08</td><td>2</td><td>2</td></tr> <tr><td>0.12</td><td>2</td><td>3</td></tr> <tr><td>0.16</td><td>2</td><td>3</td></tr> <tr><td>0.20</td><td>5</td><td>3</td></tr> <tr><td>0.22</td><td>7</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	2	2	0.04	2	2	0.08	2	2	0.12	2	3	0.16	2	3	0.20	5	3	0.22	7	3	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																							
0.00	2	2																																							
0.04	2	2																																							
0.08	2	2																																							
0.12	2	3																																							
0.16	2	3																																							
0.20	5	3																																							
0.22	7	3																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									



<p>Model SUW60515/SUCW60515</p> <p>Item Ripple-Noise</p> <p>Object +15V0.2A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>—△— Input Volt. 4.5V - - ○ - - Input Volt. 9V</p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>3</td></tr> <tr><td>0.04</td><td>2</td><td>3</td></tr> <tr><td>0.08</td><td>2</td><td>3</td></tr> <tr><td>0.12</td><td>3</td><td>3</td></tr> <tr><td>0.16</td><td>4</td><td>4</td></tr> <tr><td>0.20</td><td>6</td><td>4</td></tr> <tr><td>0.22</td><td>8</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	2	3	0.04	2	3	0.08	2	3	0.12	3	3	0.16	4	4	0.20	6	4	0.22	8	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.00	2	3																																						
0.04	2	3																																						
0.08	2	3																																						
0.12	3	3																																						
0.16	4	4																																						
0.20	6	4																																						
0.22	8	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




<p>Model SUW60515/SUCW60515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object -15V0.2A</p>																																								
<p>1.Graph</p> <div style="text-align: center;"> <p>—△— Input Volt. 4.5V - -○- - Input Volt. 9V</p> </div> <p style="text-align: center;">Ripple-Noise [mV]</p> <p style="text-align: center;">Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p style="text-align: center;">Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>3</td></tr> <tr><td>0.04</td><td>2</td><td>3</td></tr> <tr><td>0.08</td><td>2</td><td>3</td></tr> <tr><td>0.12</td><td>3</td><td>3</td></tr> <tr><td>0.16</td><td>3</td><td>3</td></tr> <tr><td>0.20</td><td>5</td><td>3</td></tr> <tr><td>0.22</td><td>7</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	2	3	0.04	2	3	0.08	2	3	0.12	3	3	0.16	3	3	0.20	5	3	0.22	7	3	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.00	2	3																																						
0.04	2	3																																						
0.08	2	3																																						
0.12	3	3																																						
0.16	3	3																																						
0.20	5	3																																						
0.22	7	3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



Model	SUW60515/SUCW60515
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A


Testing Circuitry Figure B



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	8
-40	4	7
-20	4	7
0	3	6
25	2	4
55	1	3
60	1	3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	4
-40	3	4
-20	3	4
0	2	3
25	2	3
55	1	2
60	1	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



<p>Model SUW60515/SUCW60515</p>																																																						
<p>Item Ambient Temperature Drift</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object +15V0.2A</p>																																																						
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.985</td><td>14.986</td><td>14.987</td></tr> <tr><td>-40</td><td>15.013</td><td>15.014</td><td>15.014</td></tr> <tr><td>-20</td><td>15.034</td><td>15.034</td><td>15.034</td></tr> <tr><td>0</td><td>15.047</td><td>15.048</td><td>15.048</td></tr> <tr><td>25</td><td>15.053</td><td>15.054</td><td>15.054</td></tr> <tr><td>55</td><td>15.048</td><td>15.049</td><td>15.049</td></tr> <tr><td>60</td><td>15.046</td><td>15.047</td><td>15.047</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	14.985	14.986	14.987	-40	15.013	15.014	15.014	-20	15.034	15.034	15.034	0	15.047	15.048	15.048	25	15.053	15.054	15.054	55	15.048	15.049	15.049	60	15.046	15.047	15.047	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	14.985	14.986	14.987																																																			
-40	15.013	15.014	15.014																																																			
-20	15.034	15.034	15.034																																																			
0	15.047	15.048	15.048																																																			
25	15.053	15.054	15.054																																																			
55	15.048	15.049	15.049																																																			
60	15.046	15.047	15.047																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Object -15V0.2A</p>																																																						
<p>1.Graph</p> <p> —△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.977</td><td>-14.978</td><td>-14.977</td></tr> <tr><td>-40</td><td>-15.006</td><td>-15.007</td><td>-15.005</td></tr> <tr><td>-20</td><td>-15.027</td><td>-15.027</td><td>-15.026</td></tr> <tr><td>0</td><td>-15.041</td><td>-15.041</td><td>-15.039</td></tr> <tr><td>25</td><td>-15.047</td><td>-15.047</td><td>-15.046</td></tr> <tr><td>55</td><td>-15.044</td><td>-15.044</td><td>-15.042</td></tr> <tr><td>60</td><td>-15.042</td><td>-15.042</td><td>-15.040</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-14.977	-14.978	-14.977	-40	-15.006	-15.007	-15.005	-20	-15.027	-15.027	-15.026	0	-15.041	-15.041	-15.039	25	-15.047	-15.047	-15.046	55	-15.044	-15.044	-15.042	60	-15.042	-15.042	-15.040	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
-60	-14.977	-14.978	-14.977																																																			
-40	-15.006	-15.007	-15.005																																																			
-20	-15.027	-15.027	-15.026																																																			
0	-15.041	-15.041	-15.039																																																			
25	-15.047	-15.047	-15.046																																																			
55	-15.044	-15.044	-15.042																																																			
60	-15.042	-15.042	-15.040																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		Testing Circuitry Figure A
Model	SUW60515/SUCW60515	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.2A (AVR 2): 0 - 0.2A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	55	4.5	0	15.280	±134	±0.9	
Minimum Voltage	-40	4.5	0.2	15.013			

Object		-15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ration [%]	
Maximum Voltage	55	4.5	0	-15.296	±145	±1.0	
Minimum Voltage	-40	5	0.2	-15.006			




COSEL																									
Model	SUW60515/SUCW60515	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.2A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.056</td></tr> <tr><td>0.5</td><td>15.054</td></tr> <tr><td>1.0</td><td>15.053</td></tr> <tr><td>2.0</td><td>15.053</td></tr> <tr><td>3.0</td><td>15.053</td></tr> <tr><td>4.0</td><td>15.053</td></tr> <tr><td>5.0</td><td>15.053</td></tr> <tr><td>6.0</td><td>15.053</td></tr> <tr><td>7.0</td><td>15.053</td></tr> <tr><td>8.0</td><td>15.053</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	15.056	0.5	15.054	1.0	15.053	2.0	15.053	3.0	15.053	4.0	15.053	5.0	15.053	6.0	15.053	7.0	15.053	8.0	15.053
Time since start [H]	Output Voltage [V]																								
0.0	15.056																								
0.5	15.054																								
1.0	15.053																								
2.0	15.053																								
3.0	15.053																								
4.0	15.053																								
5.0	15.053																								
6.0	15.053																								
7.0	15.053																								
8.0	15.053																								
Object	-15V0.2A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.050</td></tr> <tr><td>0.5</td><td>-15.049</td></tr> <tr><td>1.0</td><td>-15.048</td></tr> <tr><td>2.0</td><td>-15.047</td></tr> <tr><td>3.0</td><td>-15.047</td></tr> <tr><td>4.0</td><td>-15.047</td></tr> <tr><td>5.0</td><td>-15.047</td></tr> <tr><td>6.0</td><td>-15.047</td></tr> <tr><td>7.0</td><td>-15.047</td></tr> <tr><td>8.0</td><td>-15.047</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-15.050	0.5	-15.049	1.0	-15.048	2.0	-15.047	3.0	-15.047	4.0	-15.047	5.0	-15.047	6.0	-15.047	7.0	-15.047	8.0	-15.047
Time since start [H]	Output Voltage [V]																								
0.0	-15.050																								
0.5	-15.049																								
1.0	-15.048																								
2.0	-15.047																								
3.0	-15.047																								
4.0	-15.047																								
5.0	-15.047																								
6.0	-15.047																								
7.0	-15.047																								
8.0	-15.047																								




Model	SUW60515/SUCW60515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.2A		

1. Graph



2. Values


Load	Time	[ms]				
		Td	Tr	Ts	Th	Tf
50 %		0.2	3.8	4.0	0.1	2.6
100 %		0.2	4.0	4.2	0.1	1.3






Model	SUW60515/SUCW60515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.2A		

1. Graph



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	3.9	4.1	0.1	2.9
100 %		0.2	4.0	4.2	0.1	1.5






Model	SUW60515/SUCW60515
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.8	3.9
-40	3.7	3.8
-20	3.6	3.6
0	3.4	3.5
25	3.4	3.4
55	3.3	3.4
60	3.2	3.3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.8	3.9
-40	3.7	3.8
-20	3.6	3.6
0	3.4	3.5
25	3.4	3.4
55	3.3	3.4
60	3.2	3.3
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model		SUW60515/SUCW60515		Temperature 25°C Testing Circuitry Figure A																																																								
Item		Overcurrent Protection																																																										
Object		+15V0.2A																																																										
1.Graph		<p> <input type="checkbox"/> Input Volt. 4.5V <input type="checkbox"/> Input Volt. 5V <input type="checkbox"/> Input Volt. 9V </p>		2.Values																																																								
				<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>14.3</td><td>0.34</td><td>0.37</td><td>0.37</td></tr> <tr><td>13.5</td><td>0.36</td><td>0.39</td><td>0.39</td></tr> <tr><td>12.0</td><td>0.40</td><td>0.42</td><td>0.41</td></tr> <tr><td>10.5</td><td>0.44</td><td>0.47</td><td>0.44</td></tr> <tr><td>9.0</td><td>0.48</td><td>0.51</td><td>0.47</td></tr> <tr><td>7.5</td><td>0.53</td><td>0.55</td><td>0.49</td></tr> <tr><td>6.0</td><td>0.56</td><td>0.58</td><td>0.52</td></tr> <tr><td>4.5</td><td>0.59</td><td>0.60</td><td>0.53</td></tr> <tr><td>3.0</td><td>0.59</td><td>0.60</td><td>0.54</td></tr> <tr><td>1.5</td><td>0.56</td><td>0.56</td><td>0.51</td></tr> <tr><td>0.0</td><td>0.61</td><td>0.65</td><td>0.67</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	15.0	0.20	0.20	0.20	14.3	0.34	0.37	0.37	13.5	0.36	0.39	0.39	12.0	0.40	0.42	0.41	10.5	0.44	0.47	0.44	9.0	0.48	0.51	0.47	7.5	0.53	0.55	0.49	6.0	0.56	0.58	0.52	4.5	0.59	0.60	0.53	3.0	0.59	0.60	0.54	1.5	0.56	0.56	0.51	0.0	0.61	0.65	0.67
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																									
15.0	0.20	0.20	0.20																																																									
14.3	0.34	0.37	0.37																																																									
13.5	0.36	0.39	0.39																																																									
12.0	0.40	0.42	0.41																																																									
10.5	0.44	0.47	0.44																																																									
9.0	0.48	0.51	0.47																																																									
7.5	0.53	0.55	0.49																																																									
6.0	0.56	0.58	0.52																																																									
4.5	0.59	0.60	0.53																																																									
3.0	0.59	0.60	0.54																																																									
1.5	0.56	0.56	0.51																																																									
0.0	0.61	0.65	0.67																																																									
Object		-15V0.2A		2.Values																																																								
1.Graph		<p> <input type="checkbox"/> Input Volt. 4.5V <input type="checkbox"/> Input Volt. 5V <input type="checkbox"/> Input Volt. 9V </p>																																																										
		<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>-14.25</td><td>0.34</td><td>0.36</td><td>0.37</td></tr> <tr><td>-13.50</td><td>0.36</td><td>0.39</td><td>0.39</td></tr> <tr><td>-12.00</td><td>0.40</td><td>0.42</td><td>0.41</td></tr> <tr><td>-10.50</td><td>0.44</td><td>0.47</td><td>0.44</td></tr> <tr><td>-9.00</td><td>0.49</td><td>0.51</td><td>0.47</td></tr> <tr><td>-7.50</td><td>0.53</td><td>0.55</td><td>0.49</td></tr> <tr><td>-6.00</td><td>0.57</td><td>0.58</td><td>0.52</td></tr> <tr><td>-4.50</td><td>0.59</td><td>0.60</td><td>0.53</td></tr> <tr><td>-3.00</td><td>0.60</td><td>0.60</td><td>0.54</td></tr> <tr><td>-1.50</td><td>0.56</td><td>0.57</td><td>0.51</td></tr> <tr><td>0.00</td><td>0.59</td><td>0.62</td><td>0.63</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-15.00	0.20	0.20	0.20	-14.25	0.34	0.36	0.37	-13.50	0.36	0.39	0.39	-12.00	0.40	0.42	0.41	-10.50	0.44	0.47	0.44	-9.00	0.49	0.51	0.47	-7.50	0.53	0.55	0.49	-6.00	0.57	0.58	0.52	-4.50	0.59	0.60	0.53	-3.00	0.60	0.60	0.54	-1.50	0.56	0.57	0.51	0.00	0.59	0.62	0.63
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																									
-15.00	0.20	0.20	0.20																																																									
-14.25	0.34	0.36	0.37																																																									
-13.50	0.36	0.39	0.39																																																									
-12.00	0.40	0.42	0.41																																																									
-10.50	0.44	0.47	0.44																																																									
-9.00	0.49	0.51	0.47																																																									
-7.50	0.53	0.55	0.49																																																									
-6.00	0.57	0.58	0.52																																																									
-4.50	0.59	0.60	0.53																																																									
-3.00	0.60	0.60	0.54																																																									
-1.50	0.56	0.57	0.51																																																									
0.00	0.59	0.62	0.63																																																									




Figure A




Figure B (Ripple and Ripple noise Characteristic)