

TEST DATA OF SUW61212 SUCW61212

Regulated DC Power Supply
Feb 24, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Yoshikazu Mizuno
Yoshikazu Mizuno Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1
 2.Input Current (by Load Current) 2
 3.Input Power (by Load Current) 3
 4.Efficiency (by Input Voltage) 4
 5.Efficiency (by Load Current) 5
 6.Line Regulation 6
 7.Load Regulation 7
 8.Dynamic Load Response 8
 9.Ripple Voltage (by Load Current) 10
 10.Ripple-Noise 12
 11.Ripple Voltage (by Ambient Temperature) 14
 12.Ambient Temperature Drift 15
 13.Output Voltage Accuracy 16
 14.Time Lapse Drift 17
 15.Rise and Fall Time 18
 16.Minimum Input Voltage for Regulated Output Voltage 20
 17.Overcurrent Protection 21
 18.Figure of Testing Circuitry 22

(Final Page 22)




<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C</p>																																																																								
<p>Item Input Current (by Input Voltage)</p>		<p>Testing Circuitry Figure A</p>																																																																								
<p>Object _____</p>																																																																										
<p>1.Graph</p> <p> —△— Load 100% - - □ - - Load 50% - - ○ - - Load 0% </p> <p> Input Current [A] Input Voltage [V] </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>4.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>7.6</td><td>0.059</td><td>0.499</td><td>0.808</td></tr> <tr><td>8.0</td><td>0.057</td><td>0.471</td><td>0.931</td></tr> <tr><td>9.0</td><td>0.053</td><td>0.415</td><td>0.815</td></tr> <tr><td>10.0</td><td>0.050</td><td>0.378</td><td>0.727</td></tr> <tr><td>12.0</td><td>0.046</td><td>0.317</td><td>0.603</td></tr> <tr><td>14.0</td><td>0.044</td><td>0.275</td><td>0.519</td></tr> <tr><td>16.0</td><td>0.043</td><td>0.247</td><td>0.457</td></tr> <tr><td>18.0</td><td>0.044</td><td>0.224</td><td>0.411</td></tr> <tr><td>20.0</td><td>0.045</td><td>0.208</td><td>0.375</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.001	0.001	0.001	4.0	0.001	0.001	0.001	6.0	0.002	0.002	0.002	7.6	0.059	0.499	0.808	8.0	0.057	0.471	0.931	9.0	0.053	0.415	0.815	10.0	0.050	0.378	0.727	12.0	0.046	0.317	0.603	14.0	0.044	0.275	0.519	16.0	0.043	0.247	0.457	18.0	0.044	0.224	0.411	20.0	0.045	0.208	0.375	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0.0	0.000	0.000	0.000																																																																							
2.0	0.001	0.001	0.001																																																																							
4.0	0.001	0.001	0.001																																																																							
6.0	0.002	0.002	0.002																																																																							
7.6	0.059	0.499	0.808																																																																							
8.0	0.057	0.471	0.931																																																																							
9.0	0.053	0.415	0.815																																																																							
10.0	0.050	0.378	0.727																																																																							
12.0	0.046	0.317	0.603																																																																							
14.0	0.044	0.275	0.519																																																																							
16.0	0.043	0.247	0.457																																																																							
18.0	0.044	0.224	0.411																																																																							
20.0	0.045	0.208	0.375																																																																							
--	-	-	-																																																																							
--	-	-	-																																																																							
--	-	-	-																																																																							



Model	SUW61212/SUCW61212
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



2.Values

Load Ration [%]	Input Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0	0.053	0.045	0.044
20	0.197	0.153	0.117
40	0.346	0.261	0.189
60	0.492	0.372	0.261
80	0.649	0.484	0.334
100	0.810	0.600	0.408
110	0.879	0.657	0.446
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model SUW61212/SUCW61212		Temperature 25°C Testing Circuitry Figure A																																																			
Item	Input Power (by Load Current)																																																				
Object	_____																																																				
1.Graph		2.Values																																																			
<p> —△— Input Volt. 9V - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V </p>																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.48</td><td>0.55</td><td>0.78</td></tr> <tr><td>20</td><td>1.77</td><td>1.85</td><td>2.12</td></tr> <tr><td>40</td><td>3.08</td><td>3.14</td><td>3.41</td></tr> <tr><td>60</td><td>4.42</td><td>4.46</td><td>4.70</td></tr> <tr><td>80</td><td>5.81</td><td>5.80</td><td>6.01</td></tr> <tr><td>100</td><td>7.22</td><td>7.16</td><td>7.35</td></tr> <tr><td>110</td><td>7.92</td><td>7.85</td><td>8.01</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.48	0.55	0.78	20	1.77	1.85	2.12	40	3.08	3.14	3.41	60	4.42	4.46	4.70	80	5.81	5.80	6.01	100	7.22	7.16	7.35	110	7.92	7.85	8.01	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Ration [%]	Input Power [W]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0	0.48	0.55	0.78																																																		
20	1.77	1.85	2.12																																																		
40	3.08	3.14	3.41																																																		
60	4.42	4.46	4.70																																																		
80	5.81	5.80	6.01																																																		
100	7.22	7.16	7.35																																																		
110	7.92	7.85	8.01																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL																																			
Model	SUW61212/SUCW61212	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p> <p style="text-align: center;">Input Voltage [V]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8</td><td>80.6</td><td>83.0</td></tr> <tr><td>9</td><td>80.8</td><td>83.8</td></tr> <tr><td>10</td><td>80.6</td><td>84.3</td></tr> <tr><td>12</td><td>79.7</td><td>84.5</td></tr> <tr><td>15</td><td>77.6</td><td>83.8</td></tr> <tr><td>18</td><td>74.8</td><td>82.5</td></tr> <tr><td>20</td><td>72.5</td><td>81.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8	80.6	83.0	9	80.8	83.8	10	80.6	84.3	12	79.7	84.5	15	77.6	83.8	18	74.8	82.5	20	72.5	81.3	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
8	80.6	83.0																																	
9	80.8	83.8																																	
10	80.6	84.3																																	
12	79.7	84.5																																	
15	77.6	83.8																																	
18	74.8	82.5																																	
20	72.5	81.3																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Efficiency (by Load Current)</p>																																																					
<p>Object _____</p>																																																					
<p>1.Graph</p> <p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - - - ○ - - - Input Volt. 18V </p> <p>Efficiency [%]</p> <p>Load Ratio [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>68.8</td><td>65.7</td><td>57.4</td></tr> <tr><td>40</td><td>78.8</td><td>77.0</td><td>71.1</td></tr> <tr><td>60</td><td>82.1</td><td>81.4</td><td>77.2</td></tr> <tr><td>80</td><td>83.4</td><td>83.5</td><td>80.5</td></tr> <tr><td>100</td><td>83.8</td><td>84.5</td><td>82.4</td></tr> <tr><td>110</td><td>84.0</td><td>84.8</td><td>83.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	68.8	65.7	57.4	40	78.8	77.0	71.1	60	82.1	81.4	77.2	80	83.4	83.5	80.5	100	83.8	84.5	82.4	110	84.0	84.8	83.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0	-	-	-																																																		
20	68.8	65.7	57.4																																																		
40	78.8	77.0	71.1																																																		
60	82.1	81.4	77.2																																																		
80	83.4	83.5	80.5																																																		
100	83.8	84.5	82.4																																																		
110	84.0	84.8	83.1																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




Model		SUW61212/SUCW61212		Temperature		25°C																																	
Item		Line Regulation		Testing Circuitry		Figure A																																	
Object		+12V0.25A		2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8</td><td>12.155</td><td>12.089</td></tr> <tr><td>9</td><td>12.153</td><td>12.090</td></tr> <tr><td>10</td><td>12.152</td><td>12.090</td></tr> <tr><td>12</td><td>12.149</td><td>12.091</td></tr> <tr><td>15</td><td>12.147</td><td>12.091</td></tr> <tr><td>18</td><td>12.145</td><td>12.091</td></tr> <tr><td>20</td><td>12.145</td><td>12.092</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8	12.155	12.089	9	12.153	12.090	10	12.152	12.090	12	12.149	12.091	15	12.147	12.091	18	12.145	12.091	20	12.145	12.092	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																						
	Load 50%	Load 100%																																					
8	12.155	12.089																																					
9	12.153	12.090																																					
10	12.152	12.090																																					
12	12.149	12.091																																					
15	12.147	12.091																																					
18	12.145	12.091																																					
20	12.145	12.092																																					
--	-	-																																					
--	-	-																																					
1.Graph 																																							
Object		-12V0.25A		2.Values <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8</td><td>-12.164</td><td>-12.098</td></tr> <tr><td>9</td><td>-12.161</td><td>-12.098</td></tr> <tr><td>10</td><td>-12.159</td><td>-12.098</td></tr> <tr><td>12</td><td>-12.155</td><td>-12.098</td></tr> <tr><td>15</td><td>-12.152</td><td>-12.096</td></tr> <tr><td>18</td><td>-12.149</td><td>-12.096</td></tr> <tr><td>20</td><td>-12.148</td><td>-12.096</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8	-12.164	-12.098	9	-12.161	-12.098	10	-12.159	-12.098	12	-12.155	-12.098	15	-12.152	-12.096	18	-12.149	-12.096	20	-12.148	-12.096	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																						
	Load 50%	Load 100%																																					
8	-12.164	-12.098																																					
9	-12.161	-12.098																																					
10	-12.159	-12.098																																					
12	-12.155	-12.098																																					
15	-12.152	-12.096																																					
18	-12.149	-12.096																																					
20	-12.148	-12.096																																					
--	-	-																																					
--	-	-																																					
1.Graph <p>Note: Slanted line shows the range of the rated input voltage.</p>																																							



Model	SUW61212/SUCW61212
Item	Load Regulation
Object	+12V0.25A


Temperature 25°C
Testing Circuitry Figure A



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.000	12.361	12.350	12.326
0.050	12.212	12.208	12.203
0.100	12.168	12.164	12.160
0.150	12.138	12.135	12.132
0.200	12.113	12.112	12.110
0.250	12.089	12.090	12.091
0.275	12.078	12.080	12.082
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Object	-12V0.25A
--------	-----------



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.000	-12.378	-12.364	-12.341
0.050	-12.220	-12.215	-12.212
0.100	-12.175	-12.169	-12.163
0.150	-12.145	-12.141	-12.136
0.200	-12.121	-12.118	-12.114
0.250	-12.098	-12.097	-12.095
0.275	-12.086	-12.087	-12.086
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.





Model		SUW61212/SUCW61212	
Item		Dynamic Load Response	
Object		+12V0.25A	
		Temperature	25°C
		Testing Circuitry	Figure A



Input Volt. 12 V
Cycle 100 mS





Min. Load (0A) ←→
Load 100% (0.25A)



Min. Load (0A) ←→
Load 50% (0.125A)



Load 50% (0.125A) ←→
Load 100% (0.25A)






Model		SUW61212/SUCW61212	Temperature 25°C Testing Circuitry Figure A
Item		Dynamic Load Response	
Object		-12V0.25A	

Input Volt. 12 V
Cycle 100 mS



Min. Load (0A) ←→
Load 100% (0.25A)

200mV/div




2ms/div




2ms/div

Min. Load (0A) ←→
Load 50% (0.125A)

200mV/div




2ms/div




2ms/div

Load 50% (0.125A) ←→
Load 100% (0.25A)

200mV/div



2ms/div



2ms/div



COSEL																																									
Model	SUW61212/SUCW61212	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+12V0.25A																																								
<p>1.Graph</p> <div style="text-align: center;"> <p>—△— Input Volt. 9V</p> <p>- -○- - Input Volt. 18V</p> </div> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>2</td></tr> <tr><td>0.050</td><td>2</td><td>3</td></tr> <tr><td>0.100</td><td>3</td><td>3</td></tr> <tr><td>0.150</td><td>4</td><td>3</td></tr> <tr><td>0.200</td><td>5</td><td>4</td></tr> <tr><td>0.250</td><td>8</td><td>5</td></tr> <tr><td>0.275</td><td>9</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	2	2	0.050	2	3	0.100	3	3	0.150	4	3	0.200	5	4	0.250	8	5	0.275	9	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.000	2	2																																							
0.050	2	3																																							
0.100	3	3																																							
0.150	4	3																																							
0.200	5	4																																							
0.250	8	5																																							
0.275	9	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p> <p style="text-align: center;">Fig.Complex Ripple Wave Form</p>																																									



<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object -12V0.25A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 9V - - ○ - - Input Volt. 18V</p> </div> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>2</td></tr> <tr><td>0.050</td><td>2</td><td>2</td></tr> <tr><td>0.100</td><td>2</td><td>2</td></tr> <tr><td>0.150</td><td>2</td><td>2</td></tr> <tr><td>0.200</td><td>3</td><td>2</td></tr> <tr><td>0.250</td><td>5</td><td>2</td></tr> <tr><td>0.275</td><td>7</td><td>2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	2	2	0.050	2	2	0.100	2	2	0.150	2	2	0.200	3	2	0.250	5	2	0.275	7	2	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	2	2																																						
0.050	2	2																																						
0.100	2	2																																						
0.150	2	2																																						
0.200	3	2																																						
0.250	5	2																																						
0.275	7	2																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p style="text-align: center;">Fig.Complex Ripple Wave Form</p>																																								



<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +12V0.25A</p>																																								
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 9V</p> <p>-·-○-·- Input Volt. 18V</p> </div> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>3</td><td>3</td></tr> <tr><td>0.050</td><td>4</td><td>4</td></tr> <tr><td>0.100</td><td>4</td><td>4</td></tr> <tr><td>0.150</td><td>5</td><td>5</td></tr> <tr><td>0.200</td><td>6</td><td>5</td></tr> <tr><td>0.250</td><td>9</td><td>5</td></tr> <tr><td>0.275</td><td>11</td><td>6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	3	3	0.050	4	4	0.100	4	4	0.150	5	5	0.200	6	5	0.250	9	5	0.275	11	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	3	3																																						
0.050	4	4																																						
0.100	4	4																																						
0.150	5	5																																						
0.200	6	5																																						
0.250	9	5																																						
0.275	11	6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object -12V0.25A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 9V -·-○-·- Input Volt. 18V</p> </div> <p style="text-align: center;">Ripple-Noise [mV]</p> <p style="text-align: center;">Load Current [A]</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>3</td></tr> <tr><td>0.050</td><td>3</td><td>3</td></tr> <tr><td>0.100</td><td>3</td><td>4</td></tr> <tr><td>0.150</td><td>4</td><td>4</td></tr> <tr><td>0.200</td><td>5</td><td>4</td></tr> <tr><td>0.250</td><td>6</td><td>5</td></tr> <tr><td>0.275</td><td>8</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	2	3	0.050	3	3	0.100	3	4	0.150	4	4	0.200	5	4	0.250	6	5	0.275	8	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	2	3																																						
0.050	3	3																																						
0.100	3	4																																						
0.150	4	4																																						
0.200	5	4																																						
0.250	6	5																																						
0.275	8	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Noise[mVp-p]</p> <p style="text-align: center;">Fig.Complex Ripple Noise Wave Form</p>																																								



Model	SUW61212/SUCW61212
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A


Testing Circuitry Figure B



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	7
-40	5	6
-20	4	6
0	4	6
25	3	5
55	2	3
60	2	3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	2	3
-40	2	3
-20	2	3
0	2	2
25	2	2
55	1	2
60	1	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Model		SUW61212/SUCW61212		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+12V0.25A																																																						
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - - ○ - - - Input Volt. 18V </p>		2.Values																																																				
<p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.024</td><td>12.026</td><td>12.027</td></tr> <tr><td>-40</td><td>12.049</td><td>12.050</td><td>12.051</td></tr> <tr><td>-20</td><td>12.067</td><td>12.068</td><td>12.069</td></tr> <tr><td>0</td><td>12.080</td><td>12.081</td><td>12.082</td></tr> <tr><td>25</td><td>12.090</td><td>12.091</td><td>12.091</td></tr> <tr><td>55</td><td>12.092</td><td>12.093</td><td>12.093</td></tr> <tr><td>60</td><td>12.092</td><td>12.092</td><td>12.093</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-60	12.024	12.026	12.027	-40	12.049	12.050	12.051	-20	12.067	12.068	12.069	0	12.080	12.081	12.082	25	12.090	12.091	12.091	55	12.092	12.093	12.093	60	12.092	12.092	12.093	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																					
-60	12.024	12.026	12.027																																																					
-40	12.049	12.050	12.051																																																					
-20	12.067	12.068	12.069																																																					
0	12.080	12.081	12.082																																																					
25	12.090	12.091	12.091																																																					
55	12.092	12.093	12.093																																																					
60	12.092	12.092	12.093																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Object		-12V0.25A		2.Values																																																				
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - - ○ - - - Input Volt. 18V </p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.030</td><td>-12.030</td><td>-12.030</td></tr> <tr><td>-40</td><td>-12.055</td><td>-12.054</td><td>-12.054</td></tr> <tr><td>-20</td><td>-12.074</td><td>-12.073</td><td>-12.072</td></tr> <tr><td>0</td><td>-12.087</td><td>-12.087</td><td>-12.086</td></tr> <tr><td>25</td><td>-12.097</td><td>-12.097</td><td>-12.096</td></tr> <tr><td>55</td><td>-12.101</td><td>-12.100</td><td>-12.098</td></tr> <tr><td>60</td><td>-12.100</td><td>-12.099</td><td>-12.098</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-60	-12.030	-12.030	-12.030	-40	-12.055	-12.054	-12.054	-20	-12.074	-12.073	-12.072	0	-12.087	-12.087	-12.086	25	-12.097	-12.097	-12.096	55	-12.101	-12.100	-12.098	60	-12.100	-12.099	-12.098	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																					
-60	-12.030	-12.030	-12.030																																																					
-40	-12.055	-12.054	-12.054																																																					
-20	-12.074	-12.073	-12.072																																																					
0	-12.087	-12.087	-12.086																																																					
25	-12.097	-12.097	-12.096																																																					
55	-12.101	-12.100	-12.098																																																					
60	-12.100	-12.099	-12.098																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>		<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		Testing Circuitry Figure A
Model	SUW61212/SUCW61212	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.25A (AVR 2): 0 - 0.25A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	9	0	12.373	±162	±1.4	
Minimum Voltage	-40	9	0.25	12.049			

Object		-12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	9	0	-12.390	±168	±1.4	
Minimum Voltage	-40	18	0.25	-12.054			




COSEL																									
Model	SUW61212/SUCW61212	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 12V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.093</td></tr> <tr><td>0.5</td><td>12.092</td></tr> <tr><td>1.0</td><td>12.091</td></tr> <tr><td>2.0</td><td>12.090</td></tr> <tr><td>3.0</td><td>12.090</td></tr> <tr><td>4.0</td><td>12.090</td></tr> <tr><td>5.0</td><td>12.090</td></tr> <tr><td>6.0</td><td>12.090</td></tr> <tr><td>7.0</td><td>12.090</td></tr> <tr><td>8.0</td><td>12.090</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.093	0.5	12.092	1.0	12.091	2.0	12.090	3.0	12.090	4.0	12.090	5.0	12.090	6.0	12.090	7.0	12.090	8.0	12.090
Time since start [H]	Output Voltage [V]																								
0.0	12.093																								
0.5	12.092																								
1.0	12.091																								
2.0	12.090																								
3.0	12.090																								
4.0	12.090																								
5.0	12.090																								
6.0	12.090																								
7.0	12.090																								
8.0	12.090																								
Object	-12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 12V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.099</td></tr> <tr><td>0.5</td><td>-12.098</td></tr> <tr><td>1.0</td><td>-12.098</td></tr> <tr><td>2.0</td><td>-12.097</td></tr> <tr><td>3.0</td><td>-12.097</td></tr> <tr><td>4.0</td><td>-12.097</td></tr> <tr><td>5.0</td><td>-12.097</td></tr> <tr><td>6.0</td><td>-12.097</td></tr> <tr><td>7.0</td><td>-12.097</td></tr> <tr><td>8.0</td><td>-12.097</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.099	0.5	-12.098	1.0	-12.098	2.0	-12.097	3.0	-12.097	4.0	-12.097	5.0	-12.097	6.0	-12.097	7.0	-12.097	8.0	-12.097
Time since start [H]	Output Voltage [V]																								
0.0	-12.099																								
0.5	-12.098																								
1.0	-12.098																								
2.0	-12.097																								
3.0	-12.097																								
4.0	-12.097																								
5.0	-12.097																								
6.0	-12.097																								
7.0	-12.097																								
8.0	-12.097																								



Model		SUW61212/SUCW61212	
Item		Rise and Fall Time	
Object		+12V0.25A	
		Temperature 25°C Testing Circuitry Figure A	


1. Graph

Input Volt. 12 V



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	2.3	2.5	0.1	1.8
100 %		0.2	2.5	2.7	0.1	0.9






Model		SUW61212/SUCW61212	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		-12V0.25A		


1. Graph

Input Volt. 12 V



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	2.4	2.6	0.1	2.0
100 %		0.2	2.5	2.7	0.1	1.0






Model	SUW61212/SUCW61212
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.2	8.2
-40	8.0	8.0
-20	7.9	8.0
0	7.7	7.8
25	7.7	7.6
55	7.5	7.4
60	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.1	8.1
-40	7.9	7.9
-20	7.8	7.9
0	7.8	7.8
25	7.6	7.6
55	7.5	7.4
60	7.5	7.4
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<p>Model SUW61212/SUCW61212</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																								
<p>Item Overcurrent Protection</p>																																																										
<p>Object +12V0.25A</p>																																																										
<p>1.Graph</p> <p> Input Volt. 9V Input Volt. 12V Input Volt. 18V </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.25</td><td>0.25</td><td>0.25</td></tr> <tr><td>11.4</td><td>0.44</td><td>0.49</td><td>0.49</td></tr> <tr><td>10.8</td><td>0.47</td><td>0.52</td><td>0.51</td></tr> <tr><td>9.6</td><td>0.53</td><td>0.58</td><td>0.55</td></tr> <tr><td>8.4</td><td>0.59</td><td>0.64</td><td>0.64</td></tr> <tr><td>7.2</td><td>0.65</td><td>0.69</td><td>0.68</td></tr> <tr><td>6.0</td><td>0.71</td><td>0.75</td><td>0.73</td></tr> <tr><td>4.8</td><td>0.77</td><td>0.79</td><td>0.76</td></tr> <tr><td>3.6</td><td>0.81</td><td>0.82</td><td>0.79</td></tr> <tr><td>2.4</td><td>0.83</td><td>0.82</td><td>0.79</td></tr> <tr><td>1.2</td><td>0.80</td><td>0.78</td><td>0.76</td></tr> <tr><td>0.0</td><td>1.09</td><td>1.06</td><td>1.06</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	12.0	0.25	0.25	0.25	11.4	0.44	0.49	0.49	10.8	0.47	0.52	0.51	9.6	0.53	0.58	0.55	8.4	0.59	0.64	0.64	7.2	0.65	0.69	0.68	6.0	0.71	0.75	0.73	4.8	0.77	0.79	0.76	3.6	0.81	0.82	0.79	2.4	0.83	0.82	0.79	1.2	0.80	0.78	0.76	0.0	1.09	1.06	1.06
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																							
12.0	0.25	0.25	0.25																																																							
11.4	0.44	0.49	0.49																																																							
10.8	0.47	0.52	0.51																																																							
9.6	0.53	0.58	0.55																																																							
8.4	0.59	0.64	0.64																																																							
7.2	0.65	0.69	0.68																																																							
6.0	0.71	0.75	0.73																																																							
4.8	0.77	0.79	0.76																																																							
3.6	0.81	0.82	0.79																																																							
2.4	0.83	0.82	0.79																																																							
1.2	0.80	0.78	0.76																																																							
0.0	1.09	1.06	1.06																																																							
<p>Object -12V0.25A</p>																																																										
<p>1.Graph</p> <p> Input Volt. 9V Input Volt. 12V Input Volt. 18V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.25</td><td>0.25</td><td>0.25</td></tr> <tr><td>-11.4</td><td>0.44</td><td>0.50</td><td>0.50</td></tr> <tr><td>-10.8</td><td>0.47</td><td>0.52</td><td>0.51</td></tr> <tr><td>-9.6</td><td>0.53</td><td>0.58</td><td>0.56</td></tr> <tr><td>-8.4</td><td>0.59</td><td>0.64</td><td>0.64</td></tr> <tr><td>-7.2</td><td>0.65</td><td>0.70</td><td>0.69</td></tr> <tr><td>-6.0</td><td>0.72</td><td>0.75</td><td>0.73</td></tr> <tr><td>-4.8</td><td>0.77</td><td>0.79</td><td>0.77</td></tr> <tr><td>-3.6</td><td>0.82</td><td>0.82</td><td>0.79</td></tr> <tr><td>-2.4</td><td>0.83</td><td>0.82</td><td>0.79</td></tr> <tr><td>-1.2</td><td>0.80</td><td>0.78</td><td>0.76</td></tr> <tr><td>0.0</td><td>1.04</td><td>1.03</td><td>1.03</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-12.0	0.25	0.25	0.25	-11.4	0.44	0.50	0.50	-10.8	0.47	0.52	0.51	-9.6	0.53	0.58	0.56	-8.4	0.59	0.64	0.64	-7.2	0.65	0.70	0.69	-6.0	0.72	0.75	0.73	-4.8	0.77	0.79	0.77	-3.6	0.82	0.82	0.79	-2.4	0.83	0.82	0.79	-1.2	0.80	0.78	0.76	0.0	1.04	1.03	1.03
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																							
-12.0	0.25	0.25	0.25																																																							
-11.4	0.44	0.50	0.50																																																							
-10.8	0.47	0.52	0.51																																																							
-9.6	0.53	0.58	0.56																																																							
-8.4	0.59	0.64	0.64																																																							
-7.2	0.65	0.70	0.69																																																							
-6.0	0.72	0.75	0.73																																																							
-4.8	0.77	0.79	0.77																																																							
-3.6	0.82	0.82	0.79																																																							
-2.4	0.83	0.82	0.79																																																							
-1.2	0.80	0.78	0.76																																																							
0.0	1.04	1.03	1.03																																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)