

# TEST DATA OF SUW64812 SUCW64812

Regulated DC Power Supply  
Feb 22, 2005

Approved by : Tetsuo Sugimori  
Tetsuo Sugimori Design Manager

Prepared by : Yoshikazu Mizuno  
Yoshikazu Mizuno Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	10
10. Ripple-Noise . . . . .	12
11. Ripple Voltage (by Ambient Temperature) . . . . .	14
12. Ambient Temperature Drift . . . . .	15
13. Output Voltage Accuracy . . . . .	16
14. Time Lapse Drift . . . . .	17
15. Rise and Fall Time . . . . .	18
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17. Overcurrent Protection . . . . .	21
18. Figure of Testing Circuitry . . . . .	22

(Final Page 22)

COSEL

Model	SUW64812/SUCW64812	Temperature	25°C																																																																							
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																							
Object	_____																																																																									
1.Graph		2.Values																																																																								
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>31.4</td><td>0.014</td><td>0.117</td><td>0.227</td></tr> <tr><td>33.0</td><td>0.013</td><td>0.111</td><td>0.216</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.102</td><td>0.198</td></tr> <tr><td>40.0</td><td>0.012</td><td>0.093</td><td>0.177</td></tr> <tr><td>48.0</td><td>0.010</td><td>0.078</td><td>0.148</td></tr> <tr><td>60.0</td><td>0.010</td><td>0.064</td><td>0.120</td></tr> <tr><td>70.0</td><td>0.010</td><td>0.056</td><td>0.104</td></tr> <tr><td>76.0</td><td>0.010</td><td>0.053</td><td>0.097</td></tr> <tr><td>80.0</td><td>0.010</td><td>0.051</td><td>0.093</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.001	0.001	0.001	31.4	0.014	0.117	0.227	33.0	0.013	0.111	0.216	36.0	0.012	0.102	0.198	40.0	0.012	0.093	0.177	48.0	0.010	0.078	0.148	60.0	0.010	0.064	0.120	70.0	0.010	0.056	0.104	76.0	0.010	0.053	0.097	80.0	0.010	0.051	0.093	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0.0	0.000	0.000	0.000																																																																							
8.0	0.000	0.000	0.000																																																																							
16.0	0.000	0.000	0.000																																																																							
24.0	0.001	0.001	0.001																																																																							
31.4	0.014	0.117	0.227																																																																							
33.0	0.013	0.111	0.216																																																																							
36.0	0.012	0.102	0.198																																																																							
40.0	0.012	0.093	0.177																																																																							
48.0	0.010	0.078	0.148																																																																							
60.0	0.010	0.064	0.120																																																																							
70.0	0.010	0.056	0.104																																																																							
76.0	0.010	0.053	0.097																																																																							
80.0	0.010	0.051	0.093																																																																							
--	-	-	-																																																																							
--	-	-	-																																																																							
--	-	-	-																																																																							

**COSEL**

Model	SUW64812/SUCW64812																																																				
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
1.Graph	Input Volt. 36V Input Volt. 48V Input Volt. 76V																																																				
	<p>The graph plots Input Current [A] on the Y-axis (0.00 to 0.30) against Load Ration [%] on the X-axis (0 to 120). Three linear data series are shown for different input voltages:</p> <ul style="list-style-type: none"> <li>Input Volt. 36V (solid line with open triangle markers)</li> <li>Input Volt. 48V (dashed line with open square markers)</li> <li>Input Volt. 76V (dash-dot line with open circle markers)</li> </ul> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.012</td><td>0.010</td><td>0.010</td></tr> <tr><td>20</td><td>0.048</td><td>0.037</td><td>0.028</td></tr> <tr><td>40</td><td>0.084</td><td>0.064</td><td>0.045</td></tr> <tr><td>60</td><td>0.121</td><td>0.091</td><td>0.062</td></tr> <tr><td>80</td><td>0.158</td><td>0.119</td><td>0.079</td></tr> <tr><td>100</td><td>0.196</td><td>0.147</td><td>0.096</td></tr> <tr><td>110</td><td>0.215</td><td>0.161</td><td>0.105</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0	0.012	0.010	0.010	20	0.048	0.037	0.028	40	0.084	0.064	0.045	60	0.121	0.091	0.062	80	0.158	0.119	0.079	100	0.196	0.147	0.096	110	0.215	0.161	0.105																				
Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																		
0	0.012	0.010	0.010																																																		
20	0.048	0.037	0.028																																																		
40	0.084	0.064	0.045																																																		
60	0.121	0.091	0.062																																																		
80	0.158	0.119	0.079																																																		
100	0.196	0.147	0.096																																																		
110	0.215	0.161	0.105																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.012</td><td>0.010</td><td>0.010</td></tr> <tr><td>20</td><td>0.048</td><td>0.037</td><td>0.028</td></tr> <tr><td>40</td><td>0.084</td><td>0.064</td><td>0.045</td></tr> <tr><td>60</td><td>0.121</td><td>0.091</td><td>0.062</td></tr> <tr><td>80</td><td>0.158</td><td>0.119</td><td>0.079</td></tr> <tr><td>100</td><td>0.196</td><td>0.147</td><td>0.096</td></tr> <tr><td>110</td><td>0.215</td><td>0.161</td><td>0.105</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.012	0.010	0.010	20	0.048	0.037	0.028	40	0.084	0.064	0.045	60	0.121	0.091	0.062	80	0.158	0.119	0.079	100	0.196	0.147	0.096	110	0.215	0.161	0.105	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Ration [%]	Input Current [A]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	0.012	0.010	0.010																																																		
20	0.048	0.037	0.028																																																		
40	0.084	0.064	0.045																																																		
60	0.121	0.091	0.062																																																		
80	0.158	0.119	0.079																																																		
100	0.196	0.147	0.096																																																		
110	0.215	0.161	0.105																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

**coSEL**

Model	SUW64812/SUCW64812																																																				
Item	Input Power (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object	_____	_____																																																			
1. Graph																																																					
<p style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; border: 1px solid black; border-radius: 50%; margin-right: 5px;"></span> Input Volt. 36V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%; margin-right: 5px;"></span> Input Volt. 48V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%; border: 1px solid black; margin-right: 5px;"></span> Input Volt. 76V         </p>																																																					
<p>2. Values</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.45</td><td>0.50</td><td>0.75</td></tr> <tr><td>20</td><td>1.74</td><td>1.79</td><td>2.10</td></tr> <tr><td>40</td><td>3.04</td><td>3.09</td><td>3.39</td></tr> <tr><td>60</td><td>4.36</td><td>4.40</td><td>4.68</td></tr> <tr><td>80</td><td>5.70</td><td>5.71</td><td>5.99</td></tr> <tr><td>100</td><td>7.05</td><td>7.05</td><td>7.30</td></tr> <tr><td>110</td><td>7.74</td><td>7.72</td><td>7.96</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.45	0.50	0.75	20	1.74	1.79	2.10	40	3.04	3.09	3.39	60	4.36	4.40	4.68	80	5.70	5.71	5.99	100	7.05	7.05	7.30	110	7.74	7.72	7.96	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	0.45	0.50	0.75																																																		
20	1.74	1.79	2.10																																																		
40	3.04	3.09	3.39																																																		
60	4.36	4.40	4.68																																																		
80	5.70	5.71	5.99																																																		
100	7.05	7.05	7.30																																																		
110	7.74	7.72	7.96																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

**COSEL**

Model	SUW64812/SUCW64812	Temperature Testing Circuitry	25°C Figure A																													
Item	Efficiency (by Input Voltage)																															
Object	_____																															
1. Graph			2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>82.2</td><td>85.6</td></tr> <tr><td>36</td><td>82.0</td><td>85.9</td></tr> <tr><td>40</td><td>81.8</td><td>86.1</td></tr> <tr><td>48</td><td>81.1</td><td>86.0</td></tr> <tr><td>55</td><td>80.1</td><td>85.6</td></tr> <tr><td>60</td><td>79.1</td><td>85.2</td></tr> <tr><td>70</td><td>76.8</td><td>83.9</td></tr> <tr><td>76</td><td>75.1</td><td>83.0</td></tr> <tr><td>80</td><td>73.9</td><td>82.3</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	82.2	85.6	36	82.0	85.9	40	81.8	86.1	48	81.1	86.0	55	80.1	85.6	60	79.1	85.2	70	76.8	83.9	76	75.1	83.0	80	73.9	82.3
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																														
33	82.2	85.6																														
36	82.0	85.9																														
40	81.8	86.1																														
48	81.1	86.0																														
55	80.1	85.6																														
60	79.1	85.2																														
70	76.8	83.9																														
76	75.1	83.0																														
80	73.9	82.3																														
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																

**COSEL**


Model	SUW64812/SUCW64812																																																				
Item	Efficiency (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object	<hr/>																																																				
1.Graph																																																					
<p style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: black; border-radius: 50%; border: 1px solid black;"></span> Input Volt. 36V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%;"></span> Input Volt. 48V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black; border-radius: 50%; background-color: white;"></span> Input Volt. 76V     </p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Load Ration [%]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>20</td><td>69.8</td><td>67.8</td><td>58.1</td></tr> <tr><td>40</td><td>79.8</td><td>78.6</td><td>71.7</td></tr> <tr><td>60</td><td>83.4</td><td>82.7</td><td>77.6</td></tr> <tr><td>80</td><td>85.1</td><td>84.8</td><td>80.9</td></tr> <tr><td>100</td><td>85.9</td><td>85.9</td><td>82.9</td></tr> <tr><td>110</td><td>86.1</td><td>86.3</td><td>83.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	36[V]	48[V]	76[V]	20	69.8	67.8	58.1	40	79.8	78.6	71.7	60	83.4	82.7	77.6	80	85.1	84.8	80.9	100	85.9	85.9	82.9	110	86.1	86.3	83.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-									
Load Ration [%]	36[V]	48[V]	76[V]																																																		
20	69.8	67.8	58.1																																																		
40	79.8	78.6	71.7																																																		
60	83.4	82.7	77.6																																																		
80	85.1	84.8	80.9																																																		
100	85.9	85.9	82.9																																																		
110	86.1	86.3	83.7																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
2.Values																																																					
<table border="1" style="width: 100%;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>69.8</td><td>67.8</td><td>58.1</td></tr> <tr><td>40</td><td>79.8</td><td>78.6</td><td>71.7</td></tr> <tr><td>60</td><td>83.4</td><td>82.7</td><td>77.6</td></tr> <tr><td>80</td><td>85.1</td><td>84.8</td><td>80.9</td></tr> <tr><td>100</td><td>85.9</td><td>85.9</td><td>82.9</td></tr> <tr><td>110</td><td>86.1</td><td>86.3</td><td>83.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	69.8	67.8	58.1	40	79.8	78.6	71.7	60	83.4	82.7	77.6	80	85.1	84.8	80.9	100	85.9	85.9	82.9	110	86.1	86.3	83.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	69.8	67.8	58.1																																																		
40	79.8	78.6	71.7																																																		
60	83.4	82.7	77.6																																																		
80	85.1	84.8	80.9																																																		
100	85.9	85.9	82.9																																																		
110	86.1	86.3	83.7																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

**COSEL**

Model	SUW64812/SUCW64812
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	12.171	12.100
36	12.170	12.101
40	12.168	12.102
48	12.166	12.102
55	12.164	12.103
60	12.163	12.103
70	12.162	12.103
76	12.162	12.104
80	12.162	12.104

Object	-12V0.25A
--------	-----------

## 1.Graph



## 2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	-12.179	-12.109
36	-12.176	-12.108
40	-12.174	-12.108
48	-12.171	-12.108
55	-12.169	-12.107
60	-12.167	-12.107
70	-12.166	-12.107
76	-12.165	-12.107
80	-12.164	-12.106

Note: Slanted line shows the range of the rated input voltage.


**COSEL**

Model	SUW64812/SUCW64812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.25A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 36V</li> <li>- -□-- Input Volt. 48V</li> <li>- -○-- Input Volt. 76V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.400</td><td>12.379</td><td>12.367</td></tr> <tr><td>0.050</td><td>12.233</td><td>12.230</td><td>12.225</td></tr> <tr><td>0.100</td><td>12.186</td><td>12.181</td><td>12.177</td></tr> <tr><td>0.150</td><td>12.154</td><td>12.150</td><td>12.148</td></tr> <tr><td>0.200</td><td>12.126</td><td>12.124</td><td>12.124</td></tr> <tr><td>0.250</td><td>12.100</td><td>12.101</td><td>12.102</td></tr> <tr><td>0.275</td><td>12.088</td><td>12.091</td><td>12.093</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.400	12.379	12.367	0.050	12.233	12.230	12.225	0.100	12.186	12.181	12.177	0.150	12.154	12.150	12.148	0.200	12.126	12.124	12.124	0.250	12.100	12.101	12.102	0.275	12.088	12.091	12.093	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	12.400	12.379	12.367																																																			
0.050	12.233	12.230	12.225																																																			
0.100	12.186	12.181	12.177																																																			
0.150	12.154	12.150	12.148																																																			
0.200	12.126	12.124	12.124																																																			
0.250	12.100	12.101	12.102																																																			
0.275	12.088	12.091	12.093																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.25A	2.Values																																																				
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 36V</li> <li>- -□-- Input Volt. 48V</li> <li>- -○-- Input Volt. 76V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.408</td><td>-12.386</td><td>-12.369</td></tr> <tr><td>0.050</td><td>-12.240</td><td>-12.234</td><td>-12.228</td></tr> <tr><td>0.100</td><td>-12.191</td><td>-12.185</td><td>-12.180</td></tr> <tr><td>0.150</td><td>-12.160</td><td>-12.155</td><td>-12.150</td></tr> <tr><td>0.200</td><td>-12.133</td><td>-12.129</td><td>-12.126</td></tr> <tr><td>0.250</td><td>-12.108</td><td>-12.107</td><td>-12.105</td></tr> <tr><td>0.275</td><td>-12.095</td><td>-12.096</td><td>-12.095</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.408	-12.386	-12.369	0.050	-12.240	-12.234	-12.228	0.100	-12.191	-12.185	-12.180	0.150	-12.160	-12.155	-12.150	0.200	-12.133	-12.129	-12.126	0.250	-12.108	-12.107	-12.105	0.275	-12.095	-12.096	-12.095	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	-12.408	-12.386	-12.369																																																			
0.050	-12.240	-12.234	-12.228																																																			
0.100	-12.191	-12.185	-12.180																																																			
0.150	-12.160	-12.155	-12.150																																																			
0.200	-12.133	-12.129	-12.126																																																			
0.250	-12.108	-12.107	-12.105																																																			
0.275	-12.095	-12.096	-12.095																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**



**COSEL**




# COSEL

Model	SUW64812/SUCW64812
Item	Ripple Voltage (by Load Current)
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	4	3
0.050	4	4
0.100	4	4
0.150	5	5
0.200	7	6
0.250	9	6
0.275	11	6
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form


# COSEL

Model	SUW64812/SUCW64812
Item	Ripple Voltage (by Load Current)
Object	-12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph

—△— Input Volt. 36V  
—○— Input Volt. 76V



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	3	5
0.050	4	5
0.100	5	5
0.150	5	5
0.200	5	5
0.250	7	5
0.275	8	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model SUW64812/SUCW64812

Item Ripple-Noise

Object +12V0.25A

## 1.Graph

—△— Input Volt. 36V  
 - - -○- - Input Volt. 76V



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure B

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	4	3
0.050	6	6
0.100	8	8
0.150	10	10
0.200	11	11
0.250	11	11
0.275	13	13
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SUW64812/SUCW64812
Item	Ripple-Noise
Object	-12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	8	6
0.050	13	13
0.100	13	13
0.150	14	16
0.200	15	16
0.250	17	18
0.275	17	18
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	SUW64812/SUCW64812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A

## 1.Graph




## Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	8
-40	5	8
-20	4	7
0	4	7
25	3	7
55	3	5
60	3	5
--	-	-
--	-	-
--	-	-
--	-	-

## 1.Graph



## 2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	8	8
-40	7	8
-20	6	7
0	5	6
25	4	5
55	3	4
60	3	3
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**


Model	SUW64812/SUCW64812
Item	Ambient Temperature Drift
Object	+12V0.25A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	12.017	12.019	12.019
-40	12.046	12.047	12.048
-20	12.068	12.069	12.071
0	12.086	12.087	12.088
25	12.101	12.102	12.103
55	12.108	12.109	12.110
60	12.108	12.110	12.110
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-12.021	-12.021	-12.020
-40	-12.050	-12.050	-12.050
-20	-12.073	-12.073	-12.073
0	-12.092	-12.091	-12.090
25	-12.107	-12.107	-12.105
55	-12.115	-12.114	-12.113
60	-12.116	-12.114	-12.113
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUW64812/SUCW64812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.25A (AVR 2) : 0 - 0.25A

\* Other Output : Rated Load

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36	0	12.418	±186	±1.6
Minimum Voltage	-40	36	0.25	12.046		

Object	-12V0.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36	0	-12.427	±189	±1.6
Minimum Voltage	-40	36	0.25	-12.050		

**COSEL**

Model	SUW64812/SUCW64812	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>12.103</td></tr> <tr><td>0.5</td><td>12.101</td></tr> <tr><td>1.0</td><td>12.101</td></tr> <tr><td>2.0</td><td>12.101</td></tr> <tr><td>3.0</td><td>12.101</td></tr> <tr><td>4.0</td><td>12.101</td></tr> <tr><td>5.0</td><td>12.101</td></tr> <tr><td>6.0</td><td>12.101</td></tr> <tr><td>7.0</td><td>12.101</td></tr> <tr><td>8.0</td><td>12.101</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.103	0.5	12.101	1.0	12.101	2.0	12.101	3.0	12.101	4.0	12.101	5.0	12.101	6.0	12.101	7.0	12.101	8.0	12.101
Time since start [H]	Output Voltage [V]																								
0.0	12.103																								
0.5	12.101																								
1.0	12.101																								
2.0	12.101																								
3.0	12.101																								
4.0	12.101																								
5.0	12.101																								
6.0	12.101																								
7.0	12.101																								
8.0	12.101																								
Object -12V0.25A		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-12.109</td></tr> <tr><td>0.5</td><td>-12.107</td></tr> <tr><td>1.0</td><td>-12.107</td></tr> <tr><td>2.0</td><td>-12.107</td></tr> <tr><td>3.0</td><td>-12.107</td></tr> <tr><td>4.0</td><td>-12.107</td></tr> <tr><td>5.0</td><td>-12.107</td></tr> <tr><td>6.0</td><td>-12.107</td></tr> <tr><td>7.0</td><td>-12.107</td></tr> <tr><td>8.0</td><td>-12.107</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.109	0.5	-12.107	1.0	-12.107	2.0	-12.107	3.0	-12.107	4.0	-12.107	5.0	-12.107	6.0	-12.107	7.0	-12.107	8.0	-12.107
Time since start [H]	Output Voltage [V]																								
0.0	-12.109																								
0.5	-12.107																								
1.0	-12.107																								
2.0	-12.107																								
3.0	-12.107																								
4.0	-12.107																								
5.0	-12.107																								
6.0	-12.107																								
7.0	-12.107																								
8.0	-12.107																								

**COSEL**


Model SUW64812/SUCW64812

Item Rise and Fall Time

Object +12V0.25A

Temperature 25°C  
Testing Circuitry Figure A


## 1. Graph



## 2. Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.3	2.5	2.8	0.1	1.8
100 %		0.3	2.6	2.9	0.1	0.9




**COSEL**

Model	SUW64812/SUCW64812
Item	Rise and Fall Time
Object	-12V0.25A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.3	2.5	2.8	0.1	2.0	
100 %		0.3	2.5	2.8	0.1	1.0	






Model	SUW64812/SUCW64812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

## 1.Graph

---□--- Load 50%  
—△— Load 100%



Testing Circuitry Figure A


## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.8	30.8
-40	30.4	30.5
-20	30.2	30.3
0	30.0	30.1
25	29.9	29.9
55	29.7	29.8
60	29.7	29.8
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------

## 1.Graph

---□--- Load 50%  
—△— Load 100%



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.8	30.8
-40	30.5	30.5
-20	30.2	30.3
0	30.1	30.2
25	29.9	30.0
55	29.8	29.8
60	29.8	29.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**


Model SUW64812/SUCW64812

Item Overcurrent Protection

Object +12V0.25A

## 1.Graph

— Input Volt. 36V  
 — Input Volt. 48V  
 — Input Volt. 76V

Temperature 25°C  
Testing Circuitry Figure A


## 2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
12.0	0.25	0.25	0.25
11.4	0.46	0.49	0.46
10.8	0.49	0.51	0.48
9.6	0.58	0.61	0.53
8.4	0.68	0.71	0.66
7.2	0.75	0.77	0.72
6.0	0.82	0.83	0.77
4.8	0.88	0.87	0.82
3.6	0.93	0.91	0.86
2.4	0.95	0.91	0.87
1.2	0.91	0.87	0.85
0.0	1.27	1.25	1.26

Object -12V0.25A

## 1.Graph

— Input Volt. 36V  
 — Input Volt. 48V  
 — Input Volt. 76V



## 2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-12.0	0.25	0.25	0.25
-11.4	0.46	0.49	0.46
-10.8	0.49	0.51	0.48
-9.6	0.58	0.61	0.54
-8.4	0.68	0.71	0.66
-7.2	0.76	0.77	0.72
-6.0	0.82	0.83	0.78
-4.8	0.88	0.88	0.82
-3.6	0.93	0.91	0.86
-2.4	0.95	0.92	0.88
-1.2	0.92	0.88	0.86
0.0	1.25	1.23	1.24

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)