

# TEST DATA OF TEPS45F05

Regulated DC Power Supply  
October.3. 2023

Approved by : Satoshi Uetani  
Design Manager

Prepared by : Riku Nishimura  
Design Engineer

**COSEL CO.,LTD.**



CONTENTS


- 1.Input Current (by Load Current) . . . . . 1
- 2.Efficiency (by Load Current) . . . . . 2
- 3.Power Factor (by Load Current) . . . . . 3
- 4.Inrush Current . . . . . 4
- 5.Leakage Current . . . . . 5
- 6.Line Regulation . . . . . 6
- 7.Load Regulation . . . . . 7
- 8.Ripple-Noise . . . . . 7
- 9.Dynamic Load Response . . . . . 8
- 10.Rise and Fall Time . . . . . 9
- 11.Hold-Up Time . . . . . 10
- 12.Instantaneous Interruption Compensation . . . . . 11
- 13.Overcurrent Protection . . . . . 12
- 14.Ambient Temperature Drift . . . . . 13
- 15.Minimum Input Voltage for Regulated Output Voltage . . . . . 13
- 16.Overvoltage Protection . . . . . 13
- 17.Figure of Testing Circuitry . . . . . 14

(Final Page 15)



Model	TEPS45F05
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A



2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	0.005	0.008	0.009
0.8	0.110	0.071	0.064
1.6	0.191	0.122	0.111
2.4	0.268	0.170	0.154
3.2	0.350	0.221	0.202
4.0	0.413	0.261	0.238
4.8	0.483	0.305	0.278
6.4	0.622	0.389	0.355
8.0	0.759	0.471	0.430
8.8	0.830	0.512	0.468
--	-	-	-

Note: Slanted line shows the range of the rated load current.






<p>Model      TEPS45F05</p>		<p>Temperature      25°C Testing Circuitry      Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> <span style="margin-left: 20px;">—△—</span>    Input Volt.    100V  <span style="margin-left: 20px;">- - -□- - -</span>    Input Volt.    200V  <span style="margin-left: 20px;">- · - ○ - · -</span>    Input Volt.    230V                 </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.8</td><td>88.6</td><td>85.8</td><td>84.3</td></tr> <tr><td>1.6</td><td>89.8</td><td>88.3</td><td>87.4</td></tr> <tr><td>2.4</td><td>89.6</td><td>89.4</td><td>88.7</td></tr> <tr><td>3.2</td><td>90.1</td><td>89.6</td><td>89.1</td></tr> <tr><td>4.0</td><td>90.3</td><td>89.7</td><td>89.2</td></tr> <tr><td>4.8</td><td>90.4</td><td>90.2</td><td>89.2</td></tr> <tr><td>6.4</td><td>90.2</td><td>90.6</td><td>90.0</td></tr> <tr><td>8.0</td><td>90.2</td><td>90.8</td><td>90.4</td></tr> <tr><td>8.8</td><td>89.9</td><td>90.9</td><td>90.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.8	88.6	85.8	84.3	1.6	89.8	88.3	87.4	2.4	89.6	89.4	88.7	3.2	90.1	89.6	89.1	4.0	90.3	89.7	89.2	4.8	90.4	90.2	89.2	6.4	90.2	90.6	90.0	8.0	90.2	90.8	90.4	8.8	89.9	90.9	90.5	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
0.8	88.6	85.8	84.3																																																		
1.6	89.8	88.3	87.4																																																		
2.4	89.6	89.4	88.7																																																		
3.2	90.1	89.6	89.1																																																		
4.0	90.3	89.7	89.2																																																		
4.8	90.4	90.2	89.2																																																		
6.4	90.2	90.6	90.0																																																		
8.0	90.2	90.8	90.4																																																		
8.8	89.9	90.9	90.5																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model		TEPS45F05		Temperature 25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			—△— Input Volt. 100V - - - □ - - - Input Volt. 200V ···○··· Input Volt. 230V																																																					
			2.Values																																																					
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.107</td><td>0.045</td><td>0.039</td></tr> <tr><td>0.8</td><td>0.418</td><td>0.335</td><td>0.330</td></tr> <tr><td>1.6</td><td>0.473</td><td>0.378</td><td>0.364</td></tr> <tr><td>2.4</td><td>0.506</td><td>0.403</td><td>0.388</td></tr> <tr><td>3.2</td><td>0.529</td><td>0.423</td><td>0.406</td></tr> <tr><td>4.0</td><td>0.544</td><td>0.434</td><td>0.417</td></tr> <tr><td>4.8</td><td>0.557</td><td>0.444</td><td>0.426</td></tr> <tr><td>6.4</td><td>0.578</td><td>0.461</td><td>0.441</td></tr> <tr><td>8.0</td><td>0.593</td><td>0.475</td><td>0.454</td></tr> <tr><td>8.8</td><td>0.598</td><td>0.480</td><td>0.459</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.107	0.045	0.039	0.8	0.418	0.335	0.330	1.6	0.473	0.378	0.364	2.4	0.506	0.403	0.388	3.2	0.529	0.423	0.406	4.0	0.544	0.434	0.417	4.8	0.557	0.444	0.426	6.4	0.578	0.461	0.441	8.0	0.593	0.475	0.454	8.8	0.598	0.480	0.459	--	-	-	-
Load Current [A]	Power Factor																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.107	0.045	0.039																																																					
0.8	0.418	0.335	0.330																																																					
1.6	0.473	0.378	0.364																																																					
2.4	0.506	0.403	0.388																																																					
3.2	0.529	0.423	0.406																																																					
4.0	0.544	0.434	0.417																																																					
4.8	0.557	0.444	0.426																																																					
6.4	0.578	0.461	0.441																																																					
8.0	0.593	0.475	0.454																																																					
8.8	0.598	0.480	0.459																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		TEPS45F05	
Item		Inrush Current	
Object		_____	
		Temperature	25°C
		Testing Circuitry	Figure A





<b>COSEL</b>		
Model	TEPS45F05	
Item	Leakage Current	Temperature 25°C Testing Circuitry Figure C
Object	_____	

## 1.Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	264 [V]	
DEN-AN	Figure C-1	Both phases	0.04	0.08	0.09	Operation
		One of phases	0.05	0.12	0.14	Stand by
IEC62368-1	Figure C-2	Both phases	0.03	0.08	0.09	Operation
		One of phases	0.05	0.12	0.14	Stand by
	Figure C-3	Both phases	0.03	0.08	0.09	Operation
		One of phases	0.05	0.12	0.13	Stand by

The value for "One of phases" is the reference value only.

## 2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



<b>COSEL</b>																																		
Model	TEPS45F05																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+5V8A																																	
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>5.063</td> <td>-</td> </tr> <tr> <td>100</td> <td>5.063</td> <td>5.063</td> </tr> <tr> <td>115</td> <td>5.063</td> <td>5.063</td> </tr> <tr> <td>200</td> <td>5.063</td> <td>5.063</td> </tr> <tr> <td>230</td> <td>5.063</td> <td>5.063</td> </tr> <tr> <td>264</td> <td>5.063</td> <td>5.062</td> </tr> <tr> <td>280</td> <td>5.063</td> <td>5.062</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	5.063	-	100	5.063	5.063	115	5.063	5.063	200	5.063	5.063	230	5.063	5.063	264	5.063	5.062	280	5.063	5.062	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	5.063	-																																
100	5.063	5.063																																
115	5.063	5.063																																
200	5.063	5.063																																
230	5.063	5.063																																
264	5.063	5.062																																
280	5.063	5.062																																
--	-	-																																
--	-	-																																



<b>COSEL</b>																																																					
Model	TEPS45F05																																																				
Item	Load Regulation	Temperature 25°C Testing Circuitry Figure A																																																			
Object	+5V8A																																																				
<p>1.Graph</p> <p> <span style="margin-right: 20px;">—△—</span> Input Volt. 100V  <span style="margin-right: 20px;">- - - □ - - -</span> Input Volt. 200V  <span style="margin-right: 20px;">- · - ○ - · - -</span> Input Volt. 230V                 </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.068</td><td>5.067</td><td>5.068</td></tr> <tr><td>0.8</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>1.6</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>2.4</td><td>5.068</td><td>5.067</td><td>5.067</td></tr> <tr><td>3.2</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>4.0</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>4.8</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>6.4</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>8.0</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>8.8</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	5.068	5.067	5.068	0.8	5.067	5.067	5.067	1.6	5.067	5.067	5.067	2.4	5.068	5.067	5.067	3.2	5.067	5.067	5.067	4.0	5.067	5.067	5.067	4.8	5.067	5.067	5.067	6.4	5.067	5.067	5.067	8.0	5.067	5.067	5.067	8.8	5.067	5.067	5.067	--	--	--	--
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	5.068	5.067	5.068																																																		
0.8	5.067	5.067	5.067																																																		
1.6	5.067	5.067	5.067																																																		
2.4	5.068	5.067	5.067																																																		
3.2	5.067	5.067	5.067																																																		
4.0	5.067	5.067	5.067																																																		
4.8	5.067	5.067	5.067																																																		
6.4	5.067	5.067	5.067																																																		
8.0	5.067	5.067	5.067																																																		
8.8	5.067	5.067	5.067																																																		
--	--	--	--																																																		
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																																			
Object	+5V8A																																																				
<p>1.Graph</p> <p>Input Voltage 230V Load 100%</p> <p style="text-align: center;">100[μs/div]</p>																																																					





Model		TEPS45F05	
Item		Dynamic Load Response	
Object		+5V8A	
		Temperature	25°C
		Testing Circuitry	Figure A



Input Volt. 230 V      Response.  $t_1=t_2=50\mu\text{s}$ . Typ  
 Cycle 1000 ms





Load 0%(0A) ←→  
 Load 100%(8A)



Load 50%(4A) ←→  
 Load 100%(8A)




Load 0%(0A) ←→  
 Load 50%(4A)






Model	TEPS45F05	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V8A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		177.8	2.5	180.3	8.9	1.3
230 V		174.5	2.5	177.0	69.8	1.1





<b>COSEL</b>																																			
Model	TEPS45F05	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+5V8A																																		
<p>1.Graph</p> <p style="text-align: center;"> <span style="margin-right: 20px;">---□---</span> Load 50%  <span>—△—</span> Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>14</td><td>-</td></tr> <tr><td>100</td><td>21</td><td>8</td></tr> <tr><td>115</td><td>30</td><td>12</td></tr> <tr><td>200</td><td>105</td><td>49</td></tr> <tr><td>230</td><td>142</td><td>67</td></tr> <tr><td>264</td><td>188</td><td>91</td></tr> <tr><td>280</td><td>215</td><td>105</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	14	-	100	21	8	115	30	12	200	105	49	230	142	67	264	188	91	280	215	105	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	14	-																																	
100	21	8																																	
115	30	12																																	
200	105	49																																	
230	142	67																																	
264	188	91																																	
280	215	105																																	
--	-	-																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.            Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model      TEPS45F05</p>		<p>Temperature      25°C Testing Circuitry      Figure A</p>																																																			
<p>Item</p>	<p>Instantaneous Interruption Compensation</p>																																																				
<p>Object</p>	<p>+5V8A</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.8</td><td>128</td><td>537</td><td>714</td></tr> <tr><td>1.6</td><td>64</td><td>270</td><td>361</td></tr> <tr><td>2.4</td><td>40</td><td>181</td><td>241</td></tr> <tr><td>3.3</td><td>27</td><td>131</td><td>174</td></tr> <tr><td>4.0</td><td>23</td><td>107</td><td>144</td></tr> <tr><td>4.8</td><td>19</td><td>89</td><td>120</td></tr> <tr><td>6.4</td><td>13</td><td>65</td><td>88</td></tr> <tr><td>8.0</td><td>9</td><td>51</td><td>70</td></tr> <tr><td>8.8</td><td>7</td><td>45</td><td>62</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.8	128	537	714	1.6	64	270	361	2.4	40	181	241	3.3	27	131	174	4.0	23	107	144	4.8	19	89	120	6.4	13	65	88	8.0	9	51	70	8.8	7	45	62	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
0.8	128	537	714																																																		
1.6	64	270	361																																																		
2.4	40	181	241																																																		
3.3	27	131	174																																																		
4.0	23	107	144																																																		
4.8	19	89	120																																																		
6.4	13	65	88																																																		
8.0	9	51	70																																																		
8.8	7	45	62																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> <span style="margin-right: 20px;">—△—</span> Input Volt. 100V  <span style="margin-right: 20px;">- - □ - -</span> Input Volt. 200V  <span style="margin-right: 20px;">- · · ○ · · -</span> Input Volt. 230V                 </p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																					



<b>COSEL</b>																																												
Model	TEPS45F05	Temperature	25°C																																									
Item	Overcurrent Protection	Testing Circuitry	Figure A																																									
Object	+5V8A																																											
<p>1.Graph</p> <div style="text-align: right;"> <p>— Input Volt. 100V</p> <p>— Input Volt. 230V</p> </div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>10.80</td><td>15.49</td></tr> <tr><td>4.75</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	5.00	10.80	15.49	4.75	-	-	4.50	-	-	4.00	-	-	3.50	-	-	3.00	-	-	2.50	-	-	2.00	-	-	1.50	-	-	1.00	-	-	0.50	-	-	0.00	-	-
Output Voltage [V]	Load Current [A]																																											
	Input Volt. 100[V]	Input Volt. 230[V]																																										
5.00	10.80	15.49																																										
4.75	-	-																																										
4.50	-	-																																										
4.00	-	-																																										
3.50	-	-																																										
3.00	-	-																																										
2.50	-	-																																										
2.00	-	-																																										
1.50	-	-																																										
1.00	-	-																																										
0.50	-	-																																										
0.00	-	-																																										

# COSEL

<b>COSEL</b>		
Model	TEPS45F05	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+5V8A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	5.081	5.081	5.081
25	5.068	5.067	5.067
50	5.055	5.055	5.054

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V8A	

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	61	62
25	62	62
50	61	62

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+5V8A	

## 1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-10	5.71	5.71
25	5.71	5.71
50	5.71	5.71




Figure A




Figure B




Figure C-1 ( DEN-AN )




Figure C-2 ( IEC62368-1 refer to IEC60990 Fig.4 )




Figure C-3 ( IEC62368-1 refer to IEC60990 Fig.5 )